

**44100113: COMPUTER NETWORKS**  
**HOMEWORK 1: CHAPTER 2 Application Layer**

**Submission Due: 23:59 P.M., Oct 4, 2022**

*Notes: All exercises are in accordance with the 6<sup>th</sup> edition (International Edition). We change data values in some problems, which are **highlighted**.*

**Exercise 1 (R5)**

What information is used by a process running on one host to identify a process running on another host?

**Exercise 2 (R6)**

Suppose you wanted to do a transaction from a remote client to a server as fast as possible. Would you use UDP or TCP? Why?

**Exercise 3 (R23)**

What is an overlay network? Does it include routers? What are the edges in the overlay network?

**Exercise 4 (P1)**

Answer true or false to the following questions and briefly justify your answer:

- a. A user requests a Web page that consists of some text and three images. For this page, the client will send one request message and receive four response messages.
- b.** Two distinct Web pages (for example, `www.mit.edu/research.html` and `www.mit.edu/students.html`) can be sent over the same persistent connection.
- c. With nonpersistent connections between browser and origin server, it is possible for a single TCP segment to carry two distinct HTTP request messages.
- d. The `Date:` header in the HTTP response message indicates when the object in the response was last modified.
- e. HTTP response messages never have an empty message body.

**Exercise 5 (P4)**

Consider the following string of ASCII characters that were captured by Wireshark when the browser sent an HTTP GET message (i.e., this is the actual content of an HTTP GET message). The characters `<cr><lf>` are carriage return and line-feed characters (that is, the italicized character string `<cr>` in the text below represents the single carriage-return character that was contained at that point in the HTTP header). Answer the following questions, indicating where in the HTTP GET message below you find the answer.

```
GET /cs453/index.html HTTP/1.1<cr><lf>Host: gai
a.cs.umass.edu<cr><lf>User-Agent: Mozilla/5.0 (
Windows;U; Windows NT 5.1; en-US; rv:1.7.2) Gec
ko/20040804 Netscape/7.2 (ax) <cr><lf>Accept:ex
t/xml, application/xml, application/xhtml+xml, text
/html;q=0.9, text/plain;q=0.8,image/png,*/*;q=0.5

<cr><lf>Accept-Language: en-us,en;q=0.5<cr><lf>Accept-
Encoding: zip,deflate<cr><lf>Accept-Charset: ISO
-8859-1,utf-8;q=0.7,*;q=0.7<cr><lf>Keep-Alive: 300<cr>
<lf>Connection:keep-alive<cr><lf><cr><lf>
```

- What is the URL of the document requested by the browser?
- What version of HTTP is the browser running?
- Does the browser request a non-persistent or a persistent connection?
- What is the IP address of the host on which the browser is running?
- What type of browser initiates this message? Why is the browser type needed in an HTTP request message?

### Exercise 6 (P5)

The text below shows the reply sent from the server in response to the HTTP GET message in the question above. Answer the following questions, indicating where in the message below you find the answer.

```
HTTP/1.1 200 OK<cr><lf>Date: Tue, 07 Mar 2008
12:39:45GMT<cr><lf>Server: Apache/2.0.52 (Fedora)
<cr><lf>Last-Modified: Sat, 10 Dec2005 18:27:46
GMT<cr><lf>ETag: "526c3-f22-a88a4c80"<cr><lf>Accept-
Ranges: bytes<cr><lf>Content-Length: 3874<cr><lf>
Keep-Alive: timeout=max=100<cr><lf>Connection:
Keep-Alive<cr><lf>Content-Type: text/html; charset=
ISO-8859-1<cr><lf><cr><lf><!doctype html public "-
//w3c//dtd html 4.0transitional//en"><lf><html><lf>
<head><lf> <meta http-equiv="Content-Type"
content="text/html; charset=iso-8859-1"><lf> <meta
name="GENERATOR" content="Mozilla/4.79 [en] (Windows NT
5.0; U) Netscape]"><lf> <title>CMPSCI 453 / 591 /
NTU-ST550ASpring 2005 homepage</title><lf></head><lf>
<much more document text following here (not shown)>
```

- Was the server able to successfully find the document or not? What time was the document reply provided?
- When was the document last modified?
- How many bytes are there in the document being returned?
- What are the first 5 bytes of the document being returned? Did the server agree to a persistent connection?

**Exercise 7 (P7)**

Suppose within your Web browser you click on a link to obtain a Web page. The IP address for the associated URL is not cached in your local host, so a DNS lookup is necessary to obtain the IP address. Suppose that  $n$  DNS servers are visited before your host receives the IP address from DNS; the successive visits incur an RTT of  $RTT_1, \dots, RTT_n$ . Further suppose that the Web page associated with the link contains exactly one object, consisting of a small amount of HTML text. Let  $RTT_0$  denote the RTT between the local host and the server containing the object. Assuming zero transmission time of the object, how much time elapses from when the client clicks on the link until the client receives the object?