SOFTWARE SPECIFICATIONS

Painkiller System

Group 16 Author: 王书悦

Table of Contents

System Architecture	3
T1: Unit Test	3
T1.1: SystemProcessor Unit Test	3
T1.1.1: Test updateInjectionSpeed ()	3
T1.1.2: Test refresh()	4
T1.1.3: Test getCurTime()	5
T1.1.4: Test getCurSpeed ()	5
T1.1.5: Test setSpeed()	6
T1.1.6: Test setSwitch()	6
T1.1.7: Test setPainkillerFull ()	7
T1.1.8: Test bolusPressed()	7
T1.2: SystemDB Unit Test	8
T1.2.1: Test createNormalData()	8
T1.2.2: Test getPainkillerBetween()	8
T1.2.3: Test getRecentBolusDataList()	9
T1.2.4: Test getRecentNormalDataList()	10
T1.2.5: Test getPainkillerLast1h()	11
T1.2.6: Test getPainkillerLast24h()	11
T1.2.7: Test getPainkillerRemaining()	12
T1.2.8: Test getPossibleBolus()	12
T1.2.9: Test getLastInjectionTime()	13
T1.2.10: Test checkPassword()	14
T1.2.11: Test getParameters()	14
T1.2.12: Test getBaseline()	15
T1.2.13: Test getDailyLimit()	16
T1.2.14: Test getHourlyLimit()	16
T1.2.15: Test getInterval()	17
T1.2.16: Test addPainkiller()	17
T1.2.17: Test updateInjectionSpeed()	18
T1.2.18: Test makeBolus()	19
T1.2.19: Test setParameters()	20
T1 3: MainBoardIII Unit Test	20

T1.3.1: Test show()2	.0
T2: Integration Test2	2
T2.1: SystemProcessor+SystemDB+mainBoardUI Integration2	2
T2.2: SystemProcessor+SystemDB+mainBoardUI+PasswordUI+SettingUI Integration2	3
T3: Functional Test2	4
T3.1: Use Case "Get basic information"2	4
T3.1.1: Test 'Get default information'2	4
T3.1.2: Test 'Get changed information'2	.4
T3.2: Use Case "Get static data"2	.5
T3.2.1: Test 'Get normal static data'2	.5
T3.2.2: Test 'Get special static data'2	.5
T3.3: Use Case "Set parameters"2	.5
T3.3.1: Test 'Set parameters'2	.5
T3.4: Use Case "Inject bolus"2	6
T3.4.1: Test 'Inject bolus'2	6
T4: Model Checking2	6
Full PainKiller Model2	6
Physician2	7
Patient2	7
Processor2	8
Check Properties2	.8
P4.12	.8
P4.22	9
P4.32	9
P4.4	9

System Architecture

The system architecture is shown below:

Since MatLab is not able to test private functions, so I change all private functions to public functions in a new folder for the convenience of testing.

T1: Unit Test

T1.1: SystemProcessor Unit Test

T1.1.1: Test updateInjectionSpeed ()

```
function injectionSpeed = updateInjectionSpeed(pro, time)
      % Check if normal injection should be on or off.
     % Also update the database about the decision.
        Input: time [datetime]
                   current time
     %
        Return: injectionSpeed [float]
                   the speed of the injection
     db = pro.sysDB;
     % Check if the switch is on.
     if pro.isOn && db.getPainkillerRemaining(pro.time) > 0
     % Branch - Tcover1.1.1.1
         injectionSpeed = db.getBaseline();
     else % Branch - Tcover1.1.1.2
         injectionSpeed = 0;
     end
      % Check 1 hour limit
     last1h = db.getPainkillerLast1h(time);
     % Check 24 hour limit
     last24h = db.getPainkillerLast24h(time);
     if (last24h >= db.getDailyLimit()) || (last1h >=
            db.getHourlyLimit())
                                 % Branch - Tcover1.1.1.3
          injectionSpeed = 0;
      end
     db.updateInjectionSpeed(time, injectionSpeed);
 end
```

- Coverage Criteria: Branch coverage
- Test case

	Test Case T1.1.1.1	Test Case T1.1.1.2	Test Case T1.1.1.3
Coverage Item	Tcover1.1.1.1	Tcover1.1.1.2	Tcover1.1.1.3
Input	time = pro.time;	time = pro.time;	time = pro.time;
State	pro = SystemProcessor;	pro = SystemProcessor;	db = SystemDB
	pro.isOn = 0;	db.baseline = 0.02;	db.baseline = 0.1;
		pro.isOn = 1;	pro.speed = 3600;
			pro.isOn = 1; pause(1);

Expected	injectionSpeed==0	injectionSpeed==0.02	injectionSpeed==0
Output			

• Test coverage: 3/3=100%

Test result: 3 passed

```
T1.1.2: Test refresh()
```

```
function refresh(pro,~,~)
            % The timer update function. This function will be called every
            % 0.1 second once functino 'run' is called.
            % This function will be invisible from outside, and will never
            % be called by objects except proTimer.
            db = pro.sysDB;
            % Update current time.
            currectTime = datetime();
            pro.time = pro.time + pro.speed*(currectTime - pro.tickTimeTag);
            pro.tickTimeTag = currectTime;
            % Update current injection speed.
            injectionSpeed = pro.updateInjectionSpeed(pro.time);
            % Gathering information...
            % Info for last 1 h
            last1h = db.getPainkillerLast1h(pro.time);
            limit1h = db.getHourlyLimit();
            last1h = sprintf('%0.2fml / %0.2fml',min([last1h, limit1h]),
limit1h);
            % Info for last 24 h
            last24h = db.getPainkillerLast24h(pro.time);
            limit24h = db.getDailyLimit();
            last24h = sprintf('%0.2fml / %0.2fml',min([last24h, limit24h]),
limit24h);
            % Info about bolus
            possibleBolus = db.getPossibleBolus(pro.time);
            interval = db.getInterval();
            lastTime = db.getLastInjectionTime();
            % Info about painkiller left
            painkillerLeft = db.getPainkillerRemaining(pro.time);
            % Show the result
            pro.mainApp.show(pro.time, injectionSpeed, last1h, last24h,...
                possibleBolus, interval, lastTime, painkillerLeft);
            % Control the bolus button
            if possibleBolus == 0 || ~pro.isOn % Branch - Tcover1.1.2.1
                pro.bolusApp.BolusButton.Enable = 'off';
            else % Branch - Tcover1.1.2.2
                pro.bolusApp.BolusButton.Enable = 'on';
            end
        end
    end
```

• Coverage Criteria: Branch coverage

Test case

	Test Case T1.1.2.1	Test Case T1.1.2.2	
Coverage Item	Tcover1.1.2.1	Tcover1.1.2.2	
Input			
State	Pro = SystemProcessor;	Pro = SystemProcessor;	
	pro.isOn = 0;	pro.isOn = 1;	
Expected Output	injectionSpeed==0	injectionSpeed==0.02	

Test coverage: 2/2=100%Test result: 2 passed

T1.1.3: Test getCurTime()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.1.3.1
Coverage Item	Tcover1.1.3.1
Input	
State	Pro = SystemProcessor;
	y1 = datetime();pause(1);
	x = pro.getCurTime();pause(1);
	y2 = datetime();
Expected Output	Time is between y1 and y2

Test coverage: 1/1=100%Test result: 1 passed

T1.1.4: Test getCurSpeed ()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.1.4.1
Coverage Item	Tcover1.1.4.1
Input	

State	Pro = SystemProcessor;	
	pro.speed = 3600;	
Expected Output	3600	

Test coverage: 1/1=100%Test result: 1 passed

T1.1.5: Test setSpeed()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.1.5.1
Coverage Item	Tcover1.1.5.1
Input	2
State	Pro = SystemProcessor;
Expected Output	pro.speed = 3600

• Test coverage: 1/1=100%

• Test result: 1 passed

T1.1.6: Test setSwitch()

```
function setSwitch(pro, switchValue)
    % Set the switch to be consistent with the machine switch.
      Caller: MainBoardUI.Switch - callback
                SwitchValueChanged(event)
       Input: switchValue [string]
    %
    %
                  'On' is the machine is on, 'Off' if the machine
    %
                  is off.
      Return: None
   if strcmp(switchValue, 'On') % Branch - Tcover1.1.6.1
       pro.isOn = 1;
    else % Branch - Tcover1.1.6.2
       pro.isOn = 0;
    end
end
```

- Coverage Criteria: Branch coverage
- Test case

	Test Case T1.1.6.1	Test Case T1.1.6.2
Coverage Item	Tcover1.1.6.1	Tcover1.1.6.2
Input	'On'	'Off'
State	Pro = SystemProcessor;	Pro = SystemProcessor;

Expected Output pro.isOn == 1 pro.isOn == 0

Test coverage: 2/2=100%Test result: 2 passed

T1.1.7: Test setPainkillerFull ()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.1.7.1
Coverage Item	Tcover1.1.7.1
Input	
State	Pro = SystemProcessor; db = SystemDB;
Expected Output	Db. painkillerRemaining = 10

Test coverage: 1/1=100%Test result: 1 passed

T1.1.8: Test bolusPressed()

- Coverage Criteria: Branch coverage
- Test case

	Test Case T1.1.8.1	Test Case T1.1.8.2
Coverage Item	Tcover1.1.8.1	Tcover1.1.8.1
Input		
State	Pro = SystemProcessor; db = SystemDB;	Pro = SystemProcessor; db =
	tc.pro.isOn = 1;	SystemDB; tc.pro.isOn = 1;
Expected Output	db.bolusDataList(end).amount == tc.db.bolus	db.bolusDataList is empty

Test coverage: 2/2=100%Test result: 2 passed

T1.2: SystemDB Unit Test

T1.2.1: Test createNormalData()

```
function createNormalData(DB, time, speed)
         % Add a data line in normal data.
         % Only accessible inside database.
            Caller: SystemDB.updateInjectionSpeed(time, injectionSpeed)
            Input: time [datatime]
                       current time of processor. used as start time
                      point of inserted injection data.
                     speed [float]
                       injection speed of the inserted data.
           Return: None
        nd = NormalData; % Statement - Tcover1.2.1.1
        nd.startTime = time;
        nd.speed = speed;
        nd.endTime = DB.DUMMYTIME;
        DB.normalDataList = [DB.normalDataList; nd];
    end
end
```

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.1.1	
Coverage Item	Tcover1.2.1.1	
Input	datetime(), 1	
State	Pro = SystemProcessor; db = SystemDB;	
Expected Output	db. normalDataList (end).startTime == datetime();	
	db. normalDataList (end).speed == 1;	

- Test coverage: 1/1=100%
- Test result: 1 passed

T1.2.2: Test getPainkillerBetween()

```
function amount = getPainkillerBetween(DB, startTime, endTime)
    % Get the amount of painkiller injected
   % between start time and end time.
      Input: startTime [datetime]
   %
                  start time point of the query.
   %
               endTime [datetime]
                 end time point of the query.
      Return: amount [float]
                 total injection (include normal and bolus) made
                  between start time point and end time point.
   amount = 0;
   % Check bolus data
   for data = DB.bolusDataList'
        if startTime < data.injectTime && data.injectTime <= endTime</pre>
            amount = amount + data.amount;
          % Branch - Tcover1.2.2.1
        end
   end
```

```
% Check normal data
for data = DB.normalDataList'
   if data.endTime == DB.DUMMYTIME && endTime > data.startTime
        du = endTime - max(startTime, data.startTime);
   % Branch - Tcover1.2.2.2
        amount = amount + data.speed * minutes(du);
   elseif data.endTime > startTime && data.startTime < endTime
        % Branch - Tcover1.2.2.3
        du = min(endTime, data.endTime) - max(startTime,
        data.startTime);
        amount = amount + data.speed * minutes(du);
        end
   end
end</pre>
```

- Coverage Criteria: Branch coverage
- Test case

	Test Case T1.2.2.1
Coverage Item	Tcover1.2.2.1, Tcover1.2.2.2, Tcover1.2.2.3
Input	pro.time -duration(24,0,0), pro.time
State	Pro = SystemProcessor;
	db = SystemDB;
	Make the system on, let time speed to 3600x, press
	bolusButton, pause 5 seconds;
Expected Output	3

Test coverage: 1/1=100%Test result: 1 passed

T1.2.3: Test getRecentBolusDataList()

```
function bolusDataList = getRecentBolusDataList(DB)
            % Get the most recent 10 records in bolus data list.
               Input: None
               Return: bolusDataList [array[string](size=[[0,10], 2])]
                          most recent 10 records in bolus data list.
                          each row contains 2 data, first is the injection
                          time, second is the injection amount.
                          all data in string format.
            bolusDataList = repmat(["NULL",
0],min(10,length(DB.bolusDataList)),1); % Statement - Tcover1.2.3.1
            for i=1:min(10,length(DB.bolusDataList))
                bolusDataList(i,1) =
string(datetime(DB.bolusDataList(length(DB.bolusDataList)+1-
i).injectTime,'Format','yyyy-MM-dd HH:mm:ss'));
                bolusDataList(i,2) =
round(DB.bolusDataList(length(DB.bolusDataList)+1-i).amount, 2);
            end
        end
```

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.3.1
Coverage Item	Tcover1.2.3.1

Input	
State	Pro = SystemProcessor;
	db = SystemDB;
	Make the system on, press bolusButton;
Expected Output	bolusDataList(1,2) == 0.3

• Test coverage: 1/1=100%

• Test result: 1 passed

T1.2.4: Test getRecentNormalDataList()

```
function normalDataList = getRecentNormalDataList(DB)
            % Get the most recent 10 records in normal data list.
               Input: None
               Return: normalDataList [array[string](size=[[0,10], 3])]
                          most recent 10 records in bolus data list.
                          each row contains 3 data, first is the starting
                          injection time, second is the ending injection
                          time, third is the injection speed.
                          all data in string format.
            normalDataList =
repmat(["start", "end", 0], min(10, length(DB.normalDataList)), 1);
            for i=1:min(10,length(DB.normalDataList))
                normalDataList(i,1) =
                  string(datetime(DB.normalDataList(length(DB.normalDataList)
                  +1-i).startTime,'Format','yyyy-MM-dd HH:mm:ss'));
                if DB.normalDataList(length(DB.normalDataList)+1-i).endTime
                  ~= DB.DUMMYTIME % Branch - Tcover1.2.4.1
                    normalDataList(i,2) =
                        string(datetime(DB.normalDataList(length(DB.normalDat
                  aList)+1-i).endTime,'Format','yyyy-MM-dd HH:mm:ss'));
                else
                        % Branch - Tcover1.2.4.2
                    normalDataList(i,2) = "--(now)--";
                normalDataList(i,3) =
round(DB.normalDataList(length(DB.normalDataList)+1-i).speed, 2);
            end
        end
    end
```

- Coverage Criteria: Branch coverage
- Test case

	Test Case T1.2.4.1
Coverage Item	Tcover1.2.4.1, Tcover1.2.4.2
Input	
State	Pro = SystemProcessor; db = SystemDB;
	Set baseline = 0.2, speed = 60x, make the system on, pause 1
	second; Set baseline = 0.2, pause 1 second;
Expected Output	NormalDataList (2,3) == 0.2, NormalDataList (1,2) == "(now)"

• Test coverage: 1/1=100%

T1.2.5: Test getPainkillerLast1h()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.5.1
Coverage Item	Tcover1.2.5.1
Input	detetime()
State	Pro = SystemProcessor; db = SystemDB;
	Set baseline = 0, make a bolus;
Expected Output	amount == db.bolus

Test coverage: 1/1=100%Test result: 1 passed

T1.2.6: Test getPainkillerLast24h()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.6.1
Coverage Item	Tcover1.2.6.1
Input	detetime()
State	Pro = SystemProcessor; db = SystemDB;
	Set baseline = 0, make a bolus;
Expected Output	amount == db.bolus

Test coverage: 1/1=100%Test result: 1 passed

T1.2.7: Test getPainkillerRemaining()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.7.1
Coverage Item	Tcover1.2.7.1
Input	detetime()
State	Pro = SystemProcessor; db = SystemDB;
	Set baseline = 0, add painkiller to full (10 ml), make a bolus;
Expected Output	amount == 10 - db.bolus

- Test coverage: 1/1=100%
- Test result: 1 passed

T1.2.8: Test getPossibleBolus()

```
function amount = getPossibleBolus(DB, time)
    % Return the amount of the possible maximum bolus currently.
   % Input: time [datetime]
   %
                 current time in processor
    용
       Return: amount [float]
                 the maximum amount of painkiller possible if make
                 a bolus at this time.
   last1h = DB.getPainkillerLast1h(time);
   last24h = DB.getPainkillerLast24h(time);
   amount = max([0, min([...]
                    DB.bolus,...
                    DB.hourlyLimit - last1h,...
                    DB.dailyLimit - last24h,...
                    DB.getPainkillerRemaining(time)]);
   if ~isempty(DB.bolusDataList) &&...
           DB.bolusDataList(end).injectTime + ...
            duration(0, DB.interval, 0) > time
    % Branch - Tcover1.2.8.1
       amount = 0;
   end
```

- end
- Coverage Criteria: Branch coverage
- Test case

		Test Case T1.2.8.1	Test Case T1.2.8.2
--	--	--------------------	--------------------

Coverage	Tcover1.2.8.1	Tcover1.2.8.1
Item		
Input	detetime()	detetime()
State	Pro = SystemProcessor; db = SystemDB;	Pro = SystemProcessor; db =
	Set baseline = 0, turn on the system;	SystemDB;
		Set baseline = 0, turn on the
		system, make a bolus;
Expected	amount == db.bolus	amount == 0
Output		

Test coverage: 2/2=100%Test result: 2 passed

T1.2.9: Test getLastInjectionTime()

```
function lastTime = getLastInjectionTime(DB)
            % Return a string representing the last time injecting a bolus.
            % Input: None
              Return: lastTime [string]
                          string representing the last time injecting a
                         bolus. Format should be 'yyyy-MM-dd HH:mm'. If no
            %
                         bolus has been made, return 'No record...'.
            if isempty(DB.bolusDataList) % Branch - Tcover1.2.9.1
                lastTime = 'No record...';
            else % Branch - Tcover1.2.9.2
                lastTime = DB.bolusDataList(end).injectTime;
                lastTime = string(datetime(lastTime,'Format','yyyy-MM-dd
HH:mm'));
            end
        end
```

• Coverage Criteria: Branch coverage

• Test case

	Test Case T1.2.9.1	Test Case T1.2.9.2
Coverage	Tcover1.2.9.1	Tcover1.2.9.2
Item		
Input		
State	Pro = SystemProcessor; db = SystemDB;	Pro = SystemProcessor; db =
	Set baseline = 0, turn on the system;	SystemDB;
		Set baseline = 0, turn on the
		system, make a bolus;
Expected	lastTime == 'No record'	lastTime ~= 'No record'
Output		

Test coverage: 2/2=100%Test result: 2 passed

T1.2.10: Test checkPassword()

- Coverage Criteria: Branch coverage
- Test case

	Test Case T1.2.10.1	Test Case T1.2.10.2
Coverage	Tcover1.2.10.1	Tcover1.2.10.2
Item		
Input	DB.password	123
State	Pro = SystemProcessor;	Pro = SystemProcessor;
	db = SystemDB;	db = SystemDB;
Expected	true	false
Output		

Test coverage: 2/2=100%Test result: 2 passed

T1.2.11: Test getParameters()

```
function [baseline,dailyLimit,...
       hourlyLimit,bolus,...
       interval,password] = getParameters(DB, password)
   % Get all the parameters from database, used for setting.
       Caller: SettingUI.startupFcn()
       Input: password [string]
                 the password user inputs, waiting to check.
   %
   % Return: baseline [float]
               dailyLimit [float]
   %
               hourlyLimit [float]
               bolus [float]
   %
               interval [float]
               password [string]
                 parameters from database.
   passed = DB.checkPassword(password);
   if passed % Branch - Tcover1.2.11.1
       baseline = DB.baseline;
       dailyLimit = DB.dailyLimit;
       hourlyLimit = DB.hourlyLimit;
                  = DB.bolus;
       bolus
       interval = DB.interval;
       password = DB.password;
              % Branch - Tcover1.2.11.2
   else
       baseline = 0;
```

```
dailyLimit = 0;
hourlyLimit = 0;
bolus = 0;
interval = 0;
password = 'Invalid password!';
end
end
```

- Coverage Criteria: Branch coverage
- Test case

	Test Case T1.2.11.1	Test Case T1.2.11.2
Coverage	Tcover1.2.11.1	Tcover1.2.11.2
Item		
Input	DB.password	123
State	Pro = SystemProcessor;	Pro = SystemProcessor;
	db = SystemDB;	db = SystemDB;
Expected	[db.baseline, db.dailyLimit,	[0,0,0,0,0,'Invalid password!']
Output	db.hourlyLimit, db.bolus, db.interval,	
	db.password]	

• Test coverage: 2/2=100%

• Test result: 2 passed

T1.2.12: Test getBaseline()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.12.1
Coverage	Tcover1.2.12.1
Item	
Input	
State	Pro = SystemProcessor;
	db = SystemDB;
	Set db.baseline = 0.03
Expected	0.03
Output	

• Test coverage: 1/1=100%

T1.2.13: Test getDailyLimit()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.13.1
Coverage	Tcover1.2.13.1
Item	
Input	
State	Pro = SystemProcessor;
	db = SystemDB;
	Set db. dailyLimit = 4
Expected	4
Output	

• Test coverage: 1/1=100%

• Test result: 1 passed

T1.2.14: Test getHourlyLimit()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.14.1	
Coverage	Tcover1.2.14.1	
Item		
Input		
State	Pro = SystemProcessor;	
	db = SystemDB;	
	Set db. hourlyLimit = 4	
Expected	4	
Output		

• Test coverage: 1/1=100%

T1.2.15: Test getInterval()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.15.1	
Coverage	Tcover1.2.15.1	
Item		
Input		
State	Pro = SystemProcessor;	
	db = SystemDB;	
	Set db. interval = 4	
Expected	4	
Output		

• Test coverage: 1/1=100%

Test result: 1 passed

T1.2.16: Test addPainkiller()

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.16.1
Coverage	Tcover1.2.16.1
Item	
Input	datetime(),1
State	Pro = SystemProcessor;
	db = SystemDB;
Expected	db.painkillerRemaining == 1;
Output	db.painkillerCheckpoint == datetime()

• Test coverage: 1/1=100%

T1.2.17: Test updateInjectionSpeed()

```
function updateInjectionSpeed(DB, time, injectionSpeed)
    % If injectionSpeed differs from current, update the database
   % normal injection status.
       Input: time [datetime]
                  current time in processor.
                injectionSpeed [float]
    %
                  the injection speed at current time that the
    o<sub>c</sub>
                  processor want to set.
   %
       Return: None
   % First data line
   if isempty(DB.normalDataList) % Branch - Tcover1.2.17.1
        if injectionSpeed ~= 0 % Branch - Tcover1.2.17.2
            DB.createNormalData(time, injectionSpeed);
        end
    % Already have data, currently not 0
   elseif DB.normalDataList(end).endTime == DB.DUMMYTIME &&...
           DB.normalDataList(end).speed ~= injectionSpeed
          % Branch - Tcover1.2.17.3
        DB.normalDataList(end).endTime = time;
        if injectionSpeed ~= 0 % Branch - Tcover1.2.17.4
            DB.createNormalData(time, injectionSpeed);
        end
    % Already have data, currently 0
   elseif DB.normalDataList(end).endTime ~= DB.DUMMYTIME &&...
            injectionSpeed ~= 0 % Branch - Tcover1.2.17.5
        DB.createNormalData(time, injectionSpeed);
   end
end
```

- Coverage Criteria: Branch coverage
- Test case

		,	1
	Test Case T1.2.17.1	Test Case T1.2.17.2	Test Case T1.2.17.3
Coverag	Tcover1.2.17.1,	Tcover1.2.17.1,	Tcover1.2.17.1,
e Item	Tcover1.2.17.2	Tcover1.2.17.2	Tcover1.2.17.3,
			Tcover1.2.17.4
Input	datetime(), 0	datetime(), 0.02	datetime(), 0.02
State	Pro=SystemProcessor;	Pro=SystemProcessor;	Pro=SystemProcessor;
	db=SystemDB;	db=SystemDB;	db=SystemDB;
			nd=NormalData;
			nd.startTime=datetime();
			nd.endTime
			=db.DUMMYTIME;
			nd.speed=0.03;
			db.normalDataList=[nd];
Expecte	db.normalDataList is	db.normalDataList(end).s	db.normalDataList(end).speed
d	empty	peed=0.02	= 0.02
Output			
	Test Case T1.2.17.4	Test Case T1.2.17.5	Test Case T1.2.17.6

			•
Coverag	Tcover1.2.17.1,	Tcover1.2.17.1,	Tcover1.2.17.1,
e Item	Tcover1.2.17.3,	Tcover1.2.17.3,	Tcover1.2.17.3,
	Tcover1.2.17.4	Tcover1.2.17.5	Tcover1.2.17.5
Input	datetime(), 0	datetime(), 0.02	datetime(), 0
State	Pro=SystemProcessor;	Pro=SystemProcessor;	Pro=SystemProcessor;
	db=SystemDB;	db=SystemDB;	db=SystemDB;
	nd=NormalData;	nd=NormalData;	nd=NormalData;
	nd.startTime=datetime	nd.startTime=datetime();	nd.startTime=datetime();
	(); nd.endTime	nd.endTime =datetime();	nd.endTime =datetime();
	=db.DUMMYTIME;	nd.speed=0.03;	nd.speed=0.03;
	nd.speed=0.03;	db.normalDataList=[nd];	db.normalDataList=[nd];
	db.normalDataList=[nd		
];		
Expecte	db.normalDataList(end	db.normalDataList(end).s	db.normalDataList(end).speed
d).speed = 0.03	peed = 0.02	= 0.03
Output			

• Test coverage: 16/16=100%

• Test result: 6 passed

T1.2.18: Test makeBolus()

```
function makeBolus(DB, time)
    % Make a bolus. Write into database.
    % Input: time [datetime]
    % current time in processor.
    % Return: None

bo = BolusData; % Statement - Tcover1.2.18.1
    bo.injectTime = time;
    bo.amount = DB.getPossibleBolus(time);
    DB.bolusDataList = [DB.bolusDataList; bo];
end
```

- Coverage Criteria: Statement coverage
- Test case

	Test Case T1.2.18.1
Coverage	Tcover1.2.18.1
Item	
Input	datetime()
State	Pro = SystemProcessor;
	db = SystemDB;
Expected	Length of db.bolusDataList is 1;
Output	db.bolusDataList(end).amount == db.bolus;

• Test coverage: 1/1=100%

T1.2.19: Test setParameters()

```
function setParameters(DB, baseline,dailyLimit,...
       hourlyLimit,bolus,...
        interval,password,originPassword)
    % Set the database parameters.
       Caller: SettingUI.ConfirmButtonPushed()
       Input: baseline [float]
               dailyLimit [float]
    %
               hourlyLimit [float]
               bolus [float]
               interval [float]
    %
               password [string]
                 the parameters to set.
    %
               originPassword [string]
   %
                 the original password UI gives, waiting to check.
       Return: None
   passed = DB.checkPassword(originPassword);
    if passed % Branch - Tcover1.2.19.1
       DB.baseline
                    = baseline;
       DB.dailyLimit = dailyLimit;
       DB.hourlyLimit = hourlyLimit;
        DB.bolus
                     = bolus;
       DB.interval = interval;
        DB.password = password;
    end
end
```

- Coverage Criteria: Branch coverage
- Test case

	Test Case T1.2.19.1	Test Case T1.2.19.2
Coverage	Tcover1.2.19.1	Tcover1.2.19.1
Item		
Input	[db.baseline, db.dailyLimit, db.hourlyLimit,	[db.baseline, db.dailyLimit,
	db.bolus, db.interval, '2333', db.password]	db.hourlyLimit, db.bolus, db.interval,
		'2333', '2333']
State	Pro = SystemProcessor;	Pro = SystemProcessor;
	db = SystemDB;	db = SystemDB;
Expected	db.password == '2333'	db.password ~= '2333'
Output		

Test coverage: 2/2=100%Test result: 2 passed

T1.3: MainBoardUI Unit Test

T1.3.1: Test show()

```
app.last24h.Text = last24h;
            app.bolus.Text = sprintf('%0.2f', possibleBolus);
            if possibleBolus == 0 || strcmp(app.Switch.Value, 'Off')
            % Branch - Tcover1.3.1.1
                app.Lamp.Color = [1,0,0];
            else % Branch - Tcover1.3.1.2
                app.Lamp.Color = [0,1,0];
            end
            app.intervalTime.Text = sprintf('%0.0f min', interval);
            app.lastTime.Text = lastTime;
            app.PainKillerLeftGauge.Value = painkillerLeft;
            if painkillerLeft == 0 % Branch - Tcover1.3.1.3
                app.PainkillerWarning.Visible = 'on';
                app.PainkillerWarning.Text = "Warning: No painkiller left.";
                app.PainkillerWarning.FontColor = [1.00,0,0];
            elseif painkillerLeft < 1 % Branch - Tcover1.3.1.4</pre>
                app.PainkillerWarning.Visible = 'on';
                app.PainkillerWarning.Text = "Warning: Painkiller running
out.";
                app.PainkillerWarning.FontColor = [1.00,0.41,0.16];
            else % Branch - Tcover1.3.1.5
                app.PainkillerWarning.Visible = 'off';
            end
            if painkillerLeft == 10 % Branch - Tcover1.3.1.6
                app.AddPainkillerButton.Enable = 'off';
            else % Branch - Tcover1.3.1.7
                app.AddPainkillerButton.Enable = 'on';
            end
            app.SpeedLabel.Text = app.processor.getCurSpeed() + "x";
        end
```

- Coverage Criteria: Branch coverage
- Test case

	Test Case T1.3.1.1	Test Case T1.3.1.2	Test Case T1.3.1.3
Coverag	Tcover1.3.1.1,	Tcover1.3.1.2,	Tcover1.3.1.2,
e Item	Tcover1.3.1.3,	Tcover1.3.1.4,	Tcover1.3.1.5,
	Tcover1.3.1.7	Tcover1.3.1.7	Tcover1.3.1.6
Input	datetime(), 0.02, '0.80ml	datetime(), 0.02, '0.80ml	datetime(), 0.02, '0.80ml /
	/ 1.00ml', '1.20ml	/ 1.00ml', '1.20ml	1.00ml', '1.20ml
	/1.00ml',1,1,string(dateti	/1.00ml',1,1,string(dateti	/1.00ml',1,1,string(datetim
	me()), 0	me()), 0.5	e()), 10
State	Pro = SystemProcessor;	Pro = SystemProcessor;	Pro = SystemProcessor;
	db = SystemDB;	db = SystemDB;	db = SystemDB;
	mainApp = MainBoardUI;	mainApp = MainBoardUI;	mainApp = MainBoardUI;
		mainApp.Switch.Value =	mainApp.Switch.Value =
		"On";	"On";
Expecte	mainApp.Lamp.Color ==	mainApp.Lamp.Color ==	mainApp.Lamp.Color ==
d	[1,0,0];	[0,1,0];	[0,1,0];
Output			

mainApp.PainkillerWarni	mainApp.PainkillerWarni	mainApp.PainkillerWarning
ng.FontColor==[1.00,0,0]	ng.FontColor[1.00,0.41,0.	.Visible=='off';
;	16];	mainApp.AddPainkillerButt
mainApp.AddPainkillerBu	mainApp.AddPainkillerBu	on.Enable=='off'
tton.Enable == 'on'	tton.Enable == 'on'	

Test coverage: 9/9=100%Test result: 3 passed

T2: Integration Test

Since the painkiller system is so sensitive to time that there may be some deviation between the actual value and the theoretical value.

T2.1: SystemProcessor+SystemDB+mainBoardUI Integration

```
function injection_test(tc)
 % ----- START INJECTION -----
    tc.choose(tc.mainApp.Switch, 'On');
    pause(15);
    tc.press(tc.bolusApp.BolusButton);
    pause(1);
    tc.press(tc.bolusApp.BolusButton);
    pause(1);
    tc.press(tc.bolusApp.BolusButton);
    pause(6);
    tc.press(tc.bolusApp.BolusButton);
    tc.press(tc.mainApp.AddPainkillerButton); pause(5);
     % speed up to go through the 24h
    tc.drag(tc.mainApp.TimeElapseSpeedSlider, 1.56239, 2);
     % from 600x to 3600x
    pause(18);
```

end

Test case

	Test Case T2.1
Coverage Item	Tcover 1.1.1.1.1.3
	Tcover 1.1.2.1-1.1.2.2
	Tcover 1.1.3.1-1.1.5.1
	Tcover 1.1.6.1-1.1.6.2
	Tcover 1.1.7.1-1.1.8.1
	Tcover 1.2.1.1
	Tcover 1.2.2.1-1.2.2.3
	Tcover 1.2.5.1-1.2.8.1
	Tcover 1.2.9.1-1.2.9.2
	Tcover 1.2.12.1-1.2.16.1
	Tcover 1.2.17.1-1.2.17.5
	Tcover 1.2.18.1
	Tcover1.3.1.1-1.3.1.7
Input	Press switch button to turn on the system.

	After 15s (150min), press bolus button.
	After 1s (10min), press bolus button again.
	After 1s (10min), press bolus button again.
	After 6s (60min), press bolus button again.
	After 8s (80min), press addPainkiller button.
	After 5s (50min), set the speed to 3600.
	Wait 18s (180min).
State	Speed is initially 600x, then set to 3600x to cross 24h.
	baseline = 0.01; dailyLimit = 3; hourlyLimit = 1; bolus = 0.3; interval = 15;
Expected Output	The last 1h amount will increase at beginning and stop at 0.60/1.00 for
	a while.
	After first bolus, it will increase again to 0.90/1.00.
	The second bolus press is invalid because it is within the interval.
	The third bolus will change last 1h amount to 0.99/1.00;
	The 4 th bolus will accelerate the last 24h amount to 3.00/3.00, then the
	system stop injecting;
	After press addpainKiller button, the painkiller remaining will be set to
	full.
	After waiting enough time, the system continuous to inject.

Test coverage: 40/40=100%

Test result: 1 passed

T2.2: SystemProcessor+SystemDB+mainBoardUI+PasswordUI+SettingUI Integration

```
function setting_test(tc)
                           %T2.2
   tc.press(tc.mainApp.SettingButton);
   % Wrong password
   tc.type(tc.mainApp.passwordDialog.InputPassword, '1234');
   tc.press(tc.mainApp.passwordDialog.ConfirmButton);
   % Correct password
   tc.type(tc.mainApp.passwordDialog.InputPassword, '123456');
   tc.press(tc.mainApp.passwordDialog.ConfirmButton);
   ----- SETTING ------
   tc.drag(tc.mainApp.settingDialog.BaseLineSlider, 0.01, 0.025);
   tc.drag(tc.mainApp.settingDialog.BolusSlider, 0.3, 0.23);
   tc.type(tc.mainApp.settingDialog.LimitperdaySpinner, 10);
   tc.type(tc.mainApp.settingDialog.LimitperhourSpinner, 2);
   tc.type(tc.mainApp.settingDialog.IntervaltimeSpinner, 20);
   tc.type(tc.mainApp.settingDialog.PasswordEditField, 'qwqqqq');
   tc.press(tc.mainApp.settingDialog.ConfirmButton);
   tc.press(tc.mainApp.settingDialog.closeButton);
   % Test changed setting
   tc.press(tc.mainApp.SettingButton);
   tc.type(tc.mainApp.passwordDialog.InputPassword, 'qwqqqq');
   tc.press(tc.mainApp.passwordDialog.ConfirmButton);
   tc.addTeardown(@delete, tc.mainApp.settingDialog);
end
```

Test case

	Test Case T2.2
Coverage Item	Tcover 1.1.1.2

Tcover 1.1.1.2, 1.1.2.1, 1.1.3.1, 1.2.10.2, 1.2.11.1, 1.2.11.2, 1.2.19.1,
1.3.1.1, 1.3.1.5, 1.3.1.7
Press setting button;
Type wrong password; Press confirm button;
Type correct password; Press confirm button;
Change baseline: $0.01 \rightarrow 0.025$, bolus: $0.3 \rightarrow 0.23$, dailyLimit $\rightarrow 10$,
hourlyLimit→2, interval→20, password→'qwqqqq'; Press confirm
button; Close setting UI;
Press setting button;
Type changed password; Press confirm button;
mainApp = MainBoardUI;
Initial setting is: baseline = 0.01; dailyLimit = 3; hourlyLimit = 1; bolus =
0.3; interval = 15;
After press setting button, password UI will pop first. After entering
wrong password, the UI will show 'Invalid password! Please try again.'.
After entering correct password, the setting UI will be opened.
After change the parameters, when press setting UI next time, the
corrcte password will become our change password 'qwqqqq', and the
parameters' value will be correctly illustrated on SettingUI.

• Test coverage: 10/10=100%

• Test result: 1 passed

T3: Functional Test

T3.1: Use Case "Get basic information"

T3.1.1: Test 'Get default information'

• Test case

	Test Case T3.1.1
State	baseline = 0.01; dailyLimit = 3; hourlyLimit = 1;
Operation	Turn on the system, pause 1 second
Expected	The MainBoardUI will show
Behavior	baseline/bolus/daily_limit/hourly_limit/lockout_interval/remaining_painkiller, and use lamp to show whether can inject bolus now: before turn on the system, the lamp
	is red, after that, the lamp becomes green.

• Test result: 1 passed

T3.1.2: Test 'Get changed information'

Test case

	Test Case T3.1.2
State	baseline = 0.01; dailyLimit = 3; hourlyLimit = 1;
Operation	Turn on the system, pause 1 second, press bolus button, pause 2 seconds
Expected	The MainBoardUI will show
Behavior	baseline/bolus/daily_limit/hourly_limit/lockout_interval/remaining_painkiller, and use lamp to show whether can inject bolus now: before turn on the system, the lamp is red, after that, the lamp becomes green.

After pressing the bolus, the lamp will become red again, and MainBoardUI will give
the time of last bolus.

• Test result: 1 passed

T3.2: Use Case "Get static data"

T3.2.1: Test 'Get normal static data'

• Test case

	Test Case T3.2.1
State	baseline = 0.01; dailyLimit = 3; hourlyLimit = 1;
Operation	Turn on the system, open MoniterUI, pause 1 second
Expected	The MainBoardUI will show amount of painkiller injected in last hour and last day,
Behavior	MonitorUI can show injection history with figure and tables.

• Test result: 1 passed

T3.2.2: Test 'Get special static data'

• Test case

	Test Case T3.2.2
State	baseline = 0.01; dailyLimit = 3; hourlyLimit = 1;
Operation	Turn on the system, open MoniterUI, pause 1 second, press bolus button, pause 3
	second, set the speed to 3600x, pause 3 second, set the accuracy number of sampled
	to 600x on MonitorUI.
Expected	The MainBoardUI will show amount of painkiller injected in last hour and last day,
Behavior	MonitorUI can show injection history with figure and tables.
	After making a bolus, there will be a spike on the dynamic figure on MoniterUI.
	After set the speed to 3600x, the axis of the figure will be compressed.
	After set the axis accuracy to 60x in MonitorUI, the figure will be stressed.

• Test result: 1 passed

T3.3: Use Case "Set parameters"

T3.3.1: Test 'Set parameters'

• Test case

	Test Case T3.3.1
State	mainApp = MainBoardUI;
	Initial setting is: baseline = 0.01; dailyLimit = 3; hourlyLimit = 1; bolus = 0.3; interval =
	15;
Operation	Press setting button; Wait until the amount injected in last 1h reached a positive
	number.
	Type wrong password; Press confirm button;
	Type correct password; Press confirm button;

	Change baseline: 0.01→0.025, bolus:0.3→0.23,dailyLimit→10, hourlyLimit→0, interval→20, password→'qwqqqq'; Press confirm button; Close setting UI; Press setting button; Type changed password; Press confirm button;
Expected	After press setting button, password UI will pop first. After entering wrong password,
Behavior	the UI will show 'Invalid password! Please try again.'.
	After entering correct password, the setting UI will be opened.
	After change the parameters, we will see the amount injected in last 1h and last 24h is
	also updated to 0 to ensure they are within limit;
	When press setting UI next time, the corrcte password will become our change
	password 'qwqqqq', and the parameters' value will be correctly illustrated on
	SettingUI.

• Test result: 1 passed

T3.4: Use Case "Inject bolus"

T3.4.1: Test 'Inject bolus'

Test case

	Test Case T3.4.1
State	baseline = 0.01; dailyLimit = 3; hourlyLimit = 1;
Operation	Turn on the system, pause 1s, press bolus button, pause 1s, pressbolus button again.
Expected	The first bolus is valid, the 2 nd bolus is invalis because it is too close to 1 st one.
Behavior	

• Test result: 1 passed

T4: Model Checking

A UPPAAL model of this PainKiller system is built for model checking.

Full PainKiller Model


As UPPAAL is weak to check 'double' type, so I multiplied all the numbers involved in the dose by 100 times: baseline $0.01 \rightarrow 10$; dailyLimit $3 \rightarrow 300$; hourlyLimit $1 \rightarrow 100$; bolus $0.03 \rightarrow 30$;

A 24*60 injectHistory array is used for recording the injection history of every minute over the past 24*60 minutes (1 day).




Physician will help to add painkiller so that our model checking can continue. As soon as the remaining painkiller == 200, physician will call 'AddPainKiller!' and painkiller will be added to 1000.

Patient



Just the same as real life, the patient can call bolus whenever he wants.



The processor will not stay at initial state more than 5s to avoid deadlock.

The injecting state will been updated every 1 second (which represents 1min in real life). The function 'addBaseLine()' will calculate the baseline can be added now and update the injectHistory array.

When processor receives 'Bolus' call, it will check if a bolus is valid under current state. If it is valid, bolus will been made and the injectHistory array will be updated at the same time. A clock 'bolusT' is specifically used to record the interval between two success bolus.

When processor receives 'AddPainKiller' call, it will immediately set the painkillerRemaing to full.

Check Properties

P4.1

Property	A[] processor.last1h() <= hourlyLimit
Description	At any time, the injection volume in the past 1 hour will not exceed the limit.
Result	Passed

P4.2

Property	A[] processor.last24h() <= dailyLimit
Description	At any time, the injection volume in the past 24 hour will not exceed the limit.
Result	Passed

P4.3

Property	A[] processor.bolus imply processor.bolusT >= interval
Description	The time between two successful bolus will always be greater than the setting interval.
Result	Passed

P4.4

Property	A[] 0 <= painKillerRemaining <= 1000
Description	The painkiller margin must always be within the limits.
Result	Passed