

Package ‘QCpipeline’

March 23, 2012

Version 0.6.0

Type Package

Title Utilities for the QC pipeline

Description Configuration and plotting code

Author Stephanie Gogarten, Sarah Nelson, Jess Shen, Leila Zelnick

Maintainer Stephanie Gogarten <sdmorris@u.washington.edu>

Depends GWASTools

Imports gplots, grid, gridBase, hexbin, Biostrings, quantsmooth

Suggests MSBVAR, GWASdata

License Artistic-2.0

LazyLoad yes

R topics documented:

bestLegendPos	2
boxplotMeanSD	2
dbgapAnnotation	3
ideogram	4
make.allele.mappings	6
plot2DwithHist	8
readConfig	9
Index	10

bestLegendPos	<i>Best legend position</i>
---------------	-----------------------------

Description

Find the section of a plot with the fewest number of points for placing a legend

Usage

```
bestLegendPos(x, y)
```

Arguments

x	Points on the x axis
y	Points on the y axis

Value

Returns one of the legend placement strings from the list "bottomright", "bottom", "bottomleft", "left", "topleft", "top", "topright", "right" and "center".

Author(s)

Stephanie Gogarten

Examples

```
x <- sample(1:100, 50, replace=TRUE)
y <- sample(1:100, 50, replace=TRUE)
plot(x,y)
legend(bestLegendPos(x,y), "points", pch=1)
```

boxplotMeanSD	<i>Boxplot with mean and SD</i>
---------------	---------------------------------

Description

Boxplot with mean and SD

Usage

```
boxplotMeanSD(x, y, data=NULL, xlab=NULL, ylab=NULL, nSD=1, ...)
```

Arguments

x	vector or character string denoting column in data
y	vector or character string denoting column in data
data	data.frame
xlab	title for x axis (defaults to x if data is not NULL)
ylab	title for y axis (defaults to y if data is not NULL)
nSD	number of standard deviations to plot
...	additional plotting arguments

Author(s)

Jess Shen

Examples

```
age <- sample(25:55, 100, replace=TRUE)
sex <- sample(c("M", "F"), 100, replace=TRUE)
boxplotMeanSD(sex, age)

data <- data.frame(age, sex)
boxplotMeanSD("sex", "age", data)
```

dbgapAnnotation

Write annotation files for dbGaP

Description

dbgapScanAnnotation and dbgapSnpAnnotation create text files appropriate for posting on db-GaP.

Usage

```
dbgapScanAnnotation(scanAnnot, dir=".",
  consentVar="consent", subjVar="subj.plink", dupVar="dup.post", omitVar="no.post",
  annotationCol="annotation", analysisCol="analysis")

dbgapSnpAnnotation(snpAnnot, dir=".",
  annotationCol="annotation", analysisCol="analysis")
```

Arguments

scanAnnot	A ScanAnnotationDataFrame .
snpAnnot	A SnpAnnotationDataFrame .
dir	A character string with the directory for file output.
consentVar	The variable in scanAnnot containing consent levels.
subjVar	The logical variable in scanAnnot indicating unique subjects to post.
dupVar	The logical variable in scanAnnot indicating duplicate scans to post.
omitVar	The logical variable in scanAnnot indicating scans to be omitted from posting.
annotationCol	The logical column in the metadata indicating which variables should be included in the annotation files.
analysisCol	The logical column in the metadata indicating which variables should be included in the analysis files.

Details

dbgapScanAnnotation writes the following files to dir:

- Sample_annotation.csv
- Sample_annotation_consent_*.csv
- Sample_annotation_duplicates.csv
- Sample_annotation_duplicates_consent_*.csv
- Sample_annotation_DD.txt
- Sample_analysis.csv
- Sample_analysis_duplicates.csv
- Sample_analysis_DD.txt

dbgapSnpAnnotation writes the following files to dir:

- SNP_annotation.csv
- SNP_annotation_DD.txt
- SNP_analysis.csv
- SNP_analysis_DD.txt

Which variables should be written to the annotation and analysis files are indicated in the metadata columns annotationCol and analysisCol.

The data dictionary files are populated from the metadata. The "type" column is automatically generated from the classes of the variables in scanAnnot and snpAnnot.

Author(s)

Stephanie Gogarten

ideogram

BAF/LRR plots with chromosome ideograms

Description

Plot BAF/LRR with chromosome ideograms at the bottom.

Usage

```
chromIntensityPlotIdeogram(intenData, scan.ids, chrom.ids,
                           main=NULL, info=NULL, ...,
                           ideo.zoom=TRUE, ideo.rect=FALSE,
                           cex.axis=1.7, cex.lab=1.7, cex.main=1.7,
                           cex.sub=1.5, cex.leg=1.5)

anomStatsPlotIdeogram(intenData, genoData, anom.stats, snp.ineligible,
                      win=5, main=NULL, info=NULL, ...,
                      ideo.zoom=FALSE, ideo.rect=TRUE,
                      cex.axis=1.7, cex.lab=1.7, cex.main=1.7,
                      cex.leg=1.5)
```

Arguments

<code>intenData</code>	IntensityData object
<code>genoData</code>	GenotypeData object
<code>scan.ids</code>	A vector containing the sample indices of the plots.
<code>chrom.ids</code>	A vector containing the chromosome indices of the plots.
<code>anom.stats</code>	data.frame of chromosome anomalies with statistics, usually the output of <code>anomSegStats</code> . Names must include "anom.id", "scanID", "chromosome", "left.index", "right.index", "method", "nmark.all", "nmark.elig", "left.base", "right.base", "nbase", "non.anom.baf.med", "non.anom.lrr.med", "anom.baf.dev.med", "anom.baf.dev.5", "anom.lrr.med", "nmark.baf", "nmark.lrr". Left and right refer to start and end, respectively, of the anomaly, in position order.
<code>snp.ineligible</code>	vector of ineligible snp ids (e.g., intensity-only, failed snps, XTR and HLA regions). See HLA and pseudoautosomal .
<code>win</code>	size of the window (a multiple of anomaly length) surrounding the anomaly to plot
<code>main</code>	Vector of plot titles. If NULL then the title will include scanID, sex, and chromosome.
<code>info</code>	A character vector containing extra information to include in the main title.
<code>...</code>	additional arguments to chromIntensityPlot or anomStatsPlot
<code>ideo.zoom</code>	logical for whether to zoom in on the ideogram to match the range of the BAF/LRR plots
<code>ideo.rect</code>	logical for whether to draw a rectangle on the ideogram indicating the range of the BAF/LRR plots
<code>cex.axis</code>	cex value for the axis
<code>cex.lab</code>	cex value for the labels
<code>cex.main</code>	cex value for the title
<code>cex.sub</code>	cex value for the subtitle
<code>cex.leg</code>	cex value for the ideogram legend

Details

`chromIntensityPlotIdeogram` is a wrapper for [chromIntensityPlot](#). `anomStatsPlotIdeogram` is a wrapper for [anomStatsPlot](#).

These functions call [paintCytobands](#) to draw ideograms.

Author(s)

Stephanie Gogarten

See Also

[chromIntensityPlot](#), [anomStatsPlot](#), [paintCytobands](#)

Examples

```
library(GWASdata)
data(illuminaScanADF)
data(illuminaSnpADF)
blfile <- system.file("extdata", "illumina_bl.nc", package="GWASdata")
blnc <- NcdfIntensityReader(blfile)
intenData <- IntensityData(blnc, scanAnnot=illuminaScanADF, snpAnnot=illuminaSnpADF)

genofile <- system.file("extdata", "illumina_genotype.nc", package="GWASdata")
genonc <- NcdfGenotypeReader(genofile)
genoData <- GenotypeData(genonc, scanAnnot=illuminaScanADF, snpAnnot=illuminaSnpADF)

# chromIntensityPlotIdeogram
scanID <- getScanID(illuminaScanADF, index=1:2)
#png("tmp_%03d.png", width=720, height=900)
main <- paste("Sample", c("A", "B"), "- Chromosome X")
chromIntensityPlotIdeogram(intenData=intenData, scan.ids=scanID,
                           chrom.ids=c(23,23), main=main,
                           colorGenotypes=TRUE, genoData=genoData)

#dev.off()

# anomStatsPlotIdeogram
scan.ids <- illuminaScanADF$scanID[1:2]
chrom.ids <- unique(illuminaSnpADF$chromosome)
snp.ids <- illuminaSnpADF$snpID[illuminaSnpADF$missing.n1 < 1]
snp.failed <- illuminaSnpADF$snpID[illuminaSnpADF$missing.n1 == 1]

# example results from anomDetectBAF
baf.anoms <- data.frame("scanID"=scan.ids[1], "chromosome"=21,
  "left.index"=100, "right.index"=200, sex="M", method="BAF",
  anom.id=1, stringsAsFactors=FALSE)

# example results from anomDetectLOH
loh.anoms <- data.frame("scanID"=scan.ids[2], "chromosome"=22,
  "left.index"=400, "right.index"=500, sex="F", method="LOH",
  anom.id=2, stringsAsFactors=FALSE)

anoms <- rbind(baf.anoms, loh.anoms)
data(centromeres.hg18)
stats <- anomSegStats(intenData, genoData, snp.ids=snp.ids, anom=anoms,
  centromere=centromeres.hg18)

#png("tmp_%03d.png", width=720, height=900)
main <- paste("Sample", c("A", "B"), "- Chromosome", stats$chromosome)
anomStatsPlotIdeogram(intenData, genoData, anom.stats=stats,
  snp.ineligible=snp.failed, centromere=centromeres.hg18, main=main)
#dev.off()

close(genoData)
close(intenData)
```

Description

Function to take Illumina build 37 SNP annotation data file and make an Allele Mappings table

Usage

```
make.allele.mappings(snp.dat)

make.allele.annotation(map, alleles=c("top", "design", "fwd", "plus"))
```

Arguments

snp.dat	a data frame made from SNP Illumina annotation file (i.e., "HumanOmni2.5-4v1_D.csv"), with following fields: "IlmnID", "Name", "IlmnStrand", "SNP", "GenomeBuild", "SourceStrand", "SourceSeq", "TopGenomicSeq", "RefStrand"
map	a data frame with allele mappings (output of make.allele.mappings), with following fields: "snp", "alle.AB", "alle.design", "alle.top", "alle.fwd", "alle.plus"
alleles	character string with type of alleles to return in the annotation table ("top", "design", "fwd", or "plus")

Details

In the case of indels, the make.allele.mappings codes A or B as "-" and the other allele with the insertion/deletion sequence. make.allele.annotation codes indels as "D" and "I" (useful for making PLINK files).

Note that "RefStrand" in build 37 annotations from Illumina is result of BLAST search of DESIGN strand. In previous strand annotations from Illumina for build 36 arrays, "BlastStrand" held +/- result of BLAST search of the SOURCE sequence.

Value

make.allele.mappings returns a data frame object with columns ("snp", "alle.AB", "alle.design", "alle.top", "alle.fwd", "alle.plus").

make.allele.annotation returns a data frame with columns "snp", "alleleA.*", "alleleB.*" where "*" = alleles.

Author(s)

Sarah Nelson

Examples

```
## Not run:
## Load in Illumina annotation
column.select <- rep("NULL", times=21)
column.select[c(1:4, 9:11, 16:18, 21)] <- NA ## only read in select columns
snp.dat <- read.csv(file="/projects/geneva/geneva_sata/SNP_annotation/Illumina/HumanOmni2.5_4v1/HumanOmni2.5_4v1_D.csv",
  skip=7, colClasses=column.select, nrows=2450000) ## last rows are for control probes
map.final <- make.allele.mappings(snp.dat)
write.csv(map.final, file="/projects/geneva/geneva_sata/SNP_annotation/Illumina/HumanOmni2.5_4v1/testfn.csv",
  row.names=FALSE, quote=FALSE)

## Create a data frame with one row per SNP, TOP alleles, and indels coded as D/I
snp.annot <- make.allele.annotation(map.final, alleles="top")
```

```
## Example allele mappings table:
#           snp alle.AB alle.design alle.top alle.fwd alle.plus
# rs1000000    A       T       A       T       A
# rs1000000    B       C       G       C       G
# rs1000002    A       A       A       A       T
# rs1000002    B       G       G       G       C
# rs10000023   A       T       A       T       T
# rs10000023   B       G       C       G       G

## With the following data dictionary:
# variable      type      description
# snp           text      rs id and other comparable identifiers for a snp
# alle.AB       text      A or B, per the Illumina genotyping system nomenclature
# alle.design    text      nucleotide(s) corresponding to A or B allele for design strand
# alle.top       text      nucleotide(s) corresponding to A or B allele for Illumina TOP strand
# alle.fwd       text      nucleotide(s) corresponding to A or B allele for FORWARD strand, with respect to dbSNP re
# alle.plus      text      nucleotide(s) corresponding to A or B allele
# for PLUS(+) strand, relative to the forward direction in the human
# reference genome sequence

## End(Not run)
```

plot2DwithHist	<i>Scatterplot with density</i>
----------------	---------------------------------

Description

plot2DwithHist produces a scatterplot of y vs x, along with histograms of the marginal distributions of x and y.

Usage

```
plot2DwithHist(x, y, xlab=NULL, ylab=NULL, xlim=NULL, ylim=NULL,
  sublab=NULL, mn=NULL, sd=NULL, ...)
```

Arguments

x	vector of x coordinates
y	vector of y coordinates
xlab	x-axis label (defaults to variable name)
ylab	y-axis label (defaults to variable name)
xlim	x-axis limits (defaults to [min,max] of X, plus a bit of space)
ylim	y-axis limits (defaults to [min,max] of Y, plus a bit of space)
sublab	sub-label (instead of main, since there's no room)
mn	2-element vector with mean of x and y
sd	2-element vector with sd of x and y
...	additional arguments to pass to points

Author(s)

Leila Zelnick

Examples

```
library(MSBVAR)
# generate some multivariate normal example data
n <- 5000
mu <- c(0, 2)
vmat <- matrix(c(1, 0.7, 0.7, 1), nrow=2)

dat <- rmultnorm(n, mu, vmat) # generates n multivariate normal obs.
x <- dat[,1]
y <- dat[,2]

plot2DwithHist(x, y, xlab="This is the X variable", ylab="This is the Y variable.",
  sub="Example Plot!")
# defining axis limits
plot2DwithHist(x, y, xlab="This is the X variable", ylab="This is the Y variable.",
  sub="Example Plot!", xlim=c(0,4), ylim=c(-2,2))
```

readConfig

Read a configuration file

Description

Read a configuration file

Usage

```
readConfig(file, ...)
```

Arguments

file	file where column 1 is parameter name and column 2 is value.
...	additional arguments to read.table

Value

Returns a named character vector of parameter values.

Author(s)

Stephanie Gogarten

Index

`anomStatsPlot`, 5
`anomStatsPlotIdeogram (ideogram)`, 4

`bestLegendPos`, 2
`boxplotMeanSD`, 2

`chromIntensityPlot`, 5
`chromIntensityPlotIdeogram (ideogram)`, 4

`dbgapAnnotation`, 3
`dbgapScanAnnotation (dbgapAnnotation)`, 3
`dbgapSnpAnnotation (dbgapAnnotation)`, 3

`GenotypeData`, 5

`HLA`, 5

`ideogram`, 4
`IntensityData`, 5

`make.allele.annotation`
 `(make.allele.mappings)`, 6
`make.allele.mappings`, 6

`paintCytobands`, 5
`plot2DwithHist`, 8
`pseudoautosomal`, 5

`readConfig`, 9

`ScanAnnotationDataFrame`, 3
`SnpAnnotationDataFrame`, 3