

Report of ESE5023_Assignments_#1

Name: HUANG Pizhu

SID:12332298

Date:Otc 25, 2023

1.Flowchart

Write a function `Print_values()` with arguments a, b, and c accoding to the flowchart with conditional statement.

```
def Print_values(a,b,c):
    if a>b:
        if b>c:
            return a,b,c
        else:
            if a>c:
                return a,c,b
            else:
                return c,a,b
    else:
        if b>c:
            return None
        else:
            return c,b,a
```

Report the output with a,b and c that can express code logic.

a	b	c	output
5	3	1	(5,3,1)
5	1	3	(5,3,1)
3	1	5	(5,3,1)
1	5	1	None
1	3	5	(5,3,1)

2.Matrix multiplication

2.1

Use `random.randint()` to generate the random numbers.
loop `for i in range()` to fill out rows and comlums.

```
import random
import numpy as np
M1 = np.random.randint(0, 50, size=(5, 10))
M2 = np.random.randint(0, 50, size=(10, 5))
```

2.2

Initialize the shape of the result matrix based on the two matrices being multiplied. Use nested loops to traverse and fill each position with value in the result matrix.

```
def Matrix_multip(M1,M2):
    result = [[0 for _ in range(len(M2[0]))] for _ in range(len(M1))]
    for i in range(len(M1)):
        for j in range(len(M2[0])):
            for k in range(len(M2)):
                result[i][j] += M1[i][k] * M2[k][j]
    return result
```

3.Pascal triangle

The i th number in the k th row is sum of the $(i-1)$ th and i th numbers in the $(k-1)$ th row. *I got the mathematical version of Pascal triangle by reading "<https://www.mathsisfun.com/pascals-triangle.html>"*

*I learned about the **recursion** of thought from this passage accessed online at*

<https://blog.csdn.net/dreamispossible/article/details/90552557>, and I use recursion in problem 3 and 4.

The function Pascal triangle(k), when $k > 1$, for k th row, the i th number is sum of the $(i-1)$ th and i th numbers in the $(k-1)$ th row. Recurse $(k-1)$ th row and append 0 in the end to conveniently calculate the k th row.

Pascal triangle(100) and Pascal triangle(200) has output as annotation in PS1_3.py

```
def Pascal_triangle(k):
    if k == 1:
        return [1]
    else:
        row = Pascal_triangle(k-1)
        row.append(0)
        new_row = []
        for i in range(len(row)-1):
            new_row.append(row[i]+row[i+1])
        new_row.insert(0,1)
    return new_row
```

4.Add or double

Considering path from number x to 1, double operation is more than add 1 operation in case of number more than 1. If x is even, one step of double and recursively call the function with $x/2$. If x is odd, one step that $x-1$ and recursively call the function with $x-1$. The function will recursively calculate the minimum number of steps reducing x to 1.

```
def Least_moves(x):
    if x == 1:
        return 0
    elif x % 2 == 0:
        return 1 + Least_moves(x // 2)
    else:
        return 1 + Least_moves(x - 1)
```

5.Dynamic programming

5.1

In the function `find_expressions(target)`, firstly define numbers' string and three state("+", "-", and " ") and initialize a list to save valid expressions. For number '12345678', per number has three state behind, so there are total 3^8 state in 8 positions between '123456789', using `itertools.product()` from itertools package to creat all arrange of operators(states). In loop, concatenate numbers '12345678' and states by `zip()` and number 9 is appended in the end; use `eval()` to decide the string expression and target. *(I got information of some python function to solve this problem, its java code accessed online at <https://blog.csdn.net/tao617/article/details/107547933>)*

```
import itertools
def find_expressions(target):
    num, ope, expressions = "123456789", ["+", "-", ""], []
    for i in itertools.product(ope, repeat=len(num) - 1):
        expression = "".join(j + k for j, k in zip(num, i)) + num[-1]
        if eval(expression) == target:
            expressions.append(f"{expression} = {target}")
    return expressions
```

5.2

Rewrite the function in 5.1 to return the lenth of different targets, which is number of expression.

```
def Total_solutions():
    def new_find_expressions(target):
        num, ope, expressions= "123456789", ["+", "-", ""], []
        for i in itertools.product(ope, repeat=len(num) - 1):
            expression = "".join(j + k for j, k in zip(num, i)) + num[-1]
            if eval(expression) == target:
                expressions.append(f"{expression} = {target}")
        return len(expressions)
    results = []
    for target in range(1, 101):
        num_of_expressions = new_find_expressions(target)
        results.append(num_of_expressions)
    return results
Total_solutions = Total_solutions()
```

Plot a bar chart of numbers and their valid expressions.

```
import matplotlib.pyplot as plt
import numpy as np
x = range(1, 101)
plt.figure(figsize=(18, 5))
plt.bar(x, Total_solutions, color='forestgreen', alpha=0.7, label='Number of Expressions')
plt.xticks(np.arange(1, 102, 2))
plt.yticks(np.arange(int(min(Total_solutions)), int(max(Total_solutions)) + 1))
plt.xlabel('Target Value', fontsize=16)
plt.ylabel('Number of Expressions', fontsize=16)
plt.title('Number of Expressions for Targets 1-100', fontsize=16)
plt.legend()
plt.show()
```

Find the max and min in the list saving number of expressions:

maximum is 26 for target numbers 1 and 45

minimum is 6 for target number 88

```
max_value = max(Total_solutions)
min_value = min(Total_solutions)

max_indices = [index + 1 for index, value in enumerate(Total_solutions) if
value == max_value]
min_indices = [index + 1 for index, value in enumerate(Total_solutions) if
value == min_value]

print(f"maximum: {max_value}, number: {max_indices}")
print(f"minimum: {min_value}, number: {min_indices}")
```