

SecureBoost: A Lossless Federated Learning Framework

Kewei Cheng, Tao Fan, Yilun Jin, Yang Liu, *Member, IEEE*, Tianjian Chen, Dimitrios Papadopoulos, Qiang Yang, *Fellow, IEEE*

Abstract—The protection of user privacy is an important concern in machine learning, as evidenced by the rolling out of the General Data Protection Regulation (GDPR) in the European Union (EU) in May 2018. The GDPR is designed to give users more control over their personal data, which motivates us to explore machine learning frameworks for data sharing that do not violate user privacy. To meet this goal, in this paper, we propose a novel lossless privacy-preserving tree-boosting system known as SecureBoost in the setting of federated learning. SecureBoost first conducts entity alignment under a privacy-preserving protocol and then **constructs boosting trees across multiple parties** with a carefully designed encryption strategy. This federated learning system allows the learning process to be jointly conducted over multiple parties with common user samples but different feature sets, which corresponds to a vertically partitioned data set. An advantage of SecureBoost is that it provides the same level of accuracy as the non privacy-preserving approach while at the same time, reveals no information of each private data provider. We show that the SecureBoost framework is as accurate as other non-federated gradient tree-boosting algorithms that require centralized data and thus it is highly scalable and practical for industrial applications such as credit risk analysis. To this end, we discuss information leakage during the protocol execution and propose ways to provably reduce it.

Index Terms—Federated Learning, Privacy, Security, Decision Tree

1 INTRODUCTION

The modern society is increasingly concerned with the unlawful use and exploitation of personal data. At the individual level, improper use of personal data may cause potential risk to user privacy. At the enterprise level, data leakage may have grave consequences on commercial interests. Actions are being taken by different societies. For example, the European Union has enacted a law known as General Data Protection Regulation (GDPR). GDPR is designed to give users more control over their personal data [1], [2], [3], [4]. Many enterprise that rely heavily on machine learning are beginning to make sweeping changes as a consequence.

Despite difficulty in meeting the goal of user privacy protection, the need for different organizations to collaborate while building machine learning models still stays strong. In reality, many data owners do not have sufficient amount of data to build high-quality models. For example, retail companies have users' purchases and transaction data, which are highly useful if provided to banks for credit rating applications. Likewise, mobile phone companies have users' usage data, but each company may only have a small amount of users which are not enough to train high-quality user preference models. Such companies have strong motivation to collaboratively exploit the joint data value.

So far, it is still a challenge to allow different data owners to collaboratively build high-quality machine learning models while at the same time protecting user data privacy and confidentiality. In the past, several attempts have been made to address the

user privacy issue in machine learning [5], [6]. For example, Apple proposed to use *differential privacy* (DP) [7], [8] to address the privacy preservation issue. The basic idea of DP is to add properly calibrated noise to data to disambiguate the identity of any individuals when data is being exchanged and analyzed by a third party. However, DP only prevents user-data leakage to a certain degree and cannot completely rule out the identity of an individual. In addition, data exchange under DP still requires that data change hands between organizations, which may not be allowed by strict laws like GDPR. Furthermore, the DP method is *lossy* in machine learning in that models built after noise is injected may perform unsatisfactorily in prediction accuracy.

More recently, Google introduced a *federated learning* (FL) framework [9] and deployed it on Android cloud. The basic idea is to allow individual clients to upload only model updates but not raw data to a central server where the models are aggregated. A secure aggregation protocol was further introduced [10] to ensure the model parameters do not leak user information to the server. This framework is also referred to as horizontal FL [11] or data-partition FL where each partition corresponds to a subset of data samples collected from one or multiple users.

In this paper, we consider another setting of multiple parties collaboratively build their machine learning models while protecting user privacy and data confidentiality. Our setting is shown in Figure 2 and is typically referred as vertical FL [11] because data are partitioned by features among different parties. This setting has a wide range of real-world applications. For example, financial institutes can leverage alternative data from a third party to enhance users' and small and medium enterprises' credit ratings [12]. Patents' record from multiple hospitals can be used together for diagnoses [13], [14]. We can regard the data located at different parties as a subsection of a virtual big data table obtained by taking the union of all data at different parties.

Yang Liu and Qiang Yang are the corresponding authors. Email: yangliu@webank.com, qyang@cse.ust.hk

Kewei Cheng is with the University of California, Los Angeles, Los Angeles, USA. Tao Fan, Yang Liu, Tianjian Chen are with Department of Artificial Intelligence, Webank, Shenzhen, China. Yilun Jin, Dimitrios Papadopoulos are with Hong Kong University of Science and Technology. Qiang Yang is with both Webank and Hong Kong University of Science and Technology.




Fig. 1: Illustration of the proposed SecureBoost framework




Fig. 2: Vertically partitioned data set

Then the data at each party has the following property:

- 1) The big data table is vertically split, such that the data are split in the feature dimension among parties;
- 2) Only one data provider has the label information;
- 3) Parties share a common set of users.

Our goal is then to allow parties to build a prediction model jointly while protecting all parties from leaking data information to other parties. In contrast with most existing work on privacy-preserving data mining and machine learning, the complexity in our setting is significantly increased. Unlike sample-partitioned/horizontal FL, the vertical FL setting requires a more complex mechanism to decompose the loss function at each party [5], [15], [16]. In addition, since only one data provider owns the label information, we need to propose a secure protocol to guide the learning process instead of sharing label information explicitly among all parties. Finally, data confidentiality and privacy concerns prevent parties from exposing their own users. Hence, entity alignment should also be conducted in a sufficiently secure manner.

Tree boosting is a highly effective and widely used machine learning method, which excels in many machine learning tasks due to its high efficiency as well as strong interpretability. For example, XGBoost [17] has been widely used in various applications including credit risk analysis and user behavior studies. In this paper, we propose a novel end-to-end privacy-preserving tree-boosting algorithm and framework known as SecureBoost to enable machine learning in a federated setting. Secureboost has been implemented in an open-sourced FL project, FATE¹ to enable industrial applications. Our federated learning framework operates in two steps. First, we find the common users among the parties

under a privacy-preserving constraint. Then, we collaboratively learn a shared classification or regression model without leaking any user information to each other. We summarize our main contributions as follows:

- We formally define a novel problem of privacy-preserving machine learning over vertically partitioned data in the setting of federated learning.
- We present an approach to train a high-quality tree boosting model collaboratively while keeping the training data local over multiple parties. Our protocol does not need the participation of a trusted third party.
- Finally and importantly, we prove that our approach is *lossless* in the sense that it is as accurate as any centralized non-privacy-preserving methods that bring all data to a central location.
- In addition, along with a proof of security, we discuss what would be required to make the protocols completely secure.

2 PRELIMINARIES AND RELATED WORK

To protect the privacy of the data used for learning a model, the authors in [18] proposed to take advantage of differential privacy (DP) for learning a deep learning model. Recently, Google introduced a federated learning framework to prevent the data from being transmitted by bringing the model training to each mobile terminal [9], [10], [19]. Its basic idea is that each local mobile terminal trains the local model using its local data with the same model architecture. The global model can simply be updated by averaging all the local models. Following the same idea, several attempts have been made to reinvent different machine learning models to the federated setting, including decision tree [20], [21], linear/logistic regression [22], [23], [24] and neural network [25], [26].

All the above methods are designed for horizontally partitioned data. Unlike sample-partitioned/horizontal FL, the vertical FL setting requires a more complex mechanism to decompose the loss function at each party. The concept of vertical FL is first proposed in [5], [11] and protocols are proposed for linear models [5], [13] and neural networks [27]. Some previous works have been proposed for privacy-preserving decision trees over vertically partitioned data [16], [28]. However, their proposed

1. <https://github.com/FederatedAI/FATE>

methods have to reveal class distribution over given attributes, which will cause potential security risks. In addition, they can only handle discrete data, which is less practical for real-life scenarios. In contrast, our method guarantees better protection to the data and can be easily applied to continuous data. Another work proposed in [29] jointly performs logistic regression over the encrypted vertically-partitioned data by approximating a non-linear logistic loss by a Taylor expansion, which will inevitably compromise the performance of the model. In contrast to these works, we propose a novel approach that is *lossless* in nature.

3 PROBLEM STATEMENT

Let $\{\mathbf{X}^k \in \mathbb{R}^{n_k \times d_k}\}_{k=1}^m$ be the data matrix distributed on m private parties with each row $\mathbf{X}_{i*}^k \in \mathbb{R}^{1 \times d_k}$ being a data instance. We use $\mathcal{F}^k = \{f_1, \dots, f_{d_k}\}$ to denote the feature set of corresponding data matrix \mathbf{X}^k . Two parties p and q have different sets of features, denoted as $\mathcal{F}^p \cap \mathcal{F}^q = \emptyset, \forall p \neq q \in \{1 \dots m\}$. Different parties may hold different sets of users as well, allowing some degree of overlap. Only one of the parties holds the class labels \mathbf{y} .

Definition 1. Active Party:

We define the active party as the data provider who holds both a data matrix and the class label. Since the class label information is indispensable for supervised learning, the active party naturally takes the responsibility as a dominating *server* in federated learning.

Definition 2. Passive Party:

We define the data provider which has only the data matrix as a passive party. Passive parties play the role of clients in the federated learning setting.

The problem of privacy-preserving machine learning over vertically split data in federated learning can be stated as:

Given: a vertically partitioned data matrix $\{\mathbf{X}^k\}_{k=1}^m$ distributed on m private parties and the class labels \mathbf{y} distributed on active party.

Learn: a machine learning model M without giving information of the data matrix of any party to others in the process. The model M is a function that has a projection M_i at each party i , such that M_i takes input of its own features X_i .

Lossless Constraint: We require that the model M is lossless, which means that the loss of M under federated learning over the training data is the same as the loss of M' when M' is built on the union of all data.

4 FEDERATED LEARNING WITH SECUREBOOST

As one of the most popular machine learning algorithms, the gradient-tree boosting excels in many machine learning tasks, such as fraud detection, feature selection and product recommendation. In this section, we propose a novel gradient-tree boosting algorithm called SecureBoost in the federated learning setting. It consists of two major steps. First, it aligns the data under the privacy constraint. Second, it collaboratively learns a shared gradient-tree boosting model while keeping all the training data secret over multiple private parties. We explain each step below.

Our first goal is to find a common set of data samples at all participating parties so as to build a joint model M . When the data is vertically partitioned among parties, different parties hold different but partially overlapping users, which can be identified

using their IDs. The problem is how to find the common data samples across the parties without revealing the non-shared parts. To achieve this goal, we align the data samples under a privacy-preserving protocol for inter-database intersections [30].

After aligning the data across different parties under the privacy constraint, we now consider the problem of jointly building tree ensemble models over multiple parties without violating privacy. Before further discussing the detail of the algorithm, we first introduce the general framework of federated learning. In federated learning, a typical iteration consists of four steps. First, each client downloads the current global model from server. Second, each client computes an updated model based on its local data and the current global model, which resides within the active party. Third, each client sends the model update back to the server under encryption. Finally, the server aggregates these model updates and construct the updated global model.

Following the general framework of federated learning, we see that to design a privacy-preserving tree boosting framework in the setting of federated learning, essentially we have to answer the following three questions: (1) How can each client (i.e., a passive party) compute an updated model based on its local data without reference to class label? (2) How can the server (i.e., the active party) aggregate all the updated model and obtain a new global model? (3) How to share the updated global model among all parties without leaking any information at inference time? To answer these three questions, we start by reviewing a tree ensemble model, XGBoost [31], in a non-federated setting.

Given a data set $\mathbf{X} \in \mathbb{R}^{n \times d}$ with n samples and d features, XGBoost predicts the output by using K regression trees.

$$\hat{y}_i = \sum_{k=1}^K f_k(\mathbf{x}_i) \quad (1)$$

To learn the set of regression tree models used in Eq.(1), it greedily adds a tree f_t at the t -th iteration to minimize the following loss.

$$\mathcal{L}^{(t)} \simeq \sum_{i=1}^n \left[l(y_i, \hat{y}_i^{(t-1)}) + g_i f_t(\mathbf{x}_i) + \frac{1}{2} h_i f_t^2(\mathbf{x}_i) \right] + \Omega(f_t) \quad (2)$$

where $\Omega(f_t) = \gamma T + \frac{1}{2} \lambda \|w\|^2$, $g_i = \partial_{\hat{y}_i^{(t-1)}} l(y_i, \hat{y}_i^{(t-1)})$ and $h_i = \partial_{\hat{y}_i^{(t-1)}}^2 l(y_i, \hat{y}_i^{(t-1)})$.

When constructing the regression tree in the t -th iteration, it starts from the tree with depth of 0 and add a split for each leaf node until reaching the maximum depth. In particular, it maximizes the following equation to determine the best split, where I_L and I_R are the instance spaces of left and right tree nodes after the split.

$$\mathcal{L}_{sp} = \frac{1}{2} \left[\frac{(\sum_{i \in I_L} g_i)^2}{\sum_{i \in I_L} h_i + \lambda} + \frac{(\sum_{i \in I_R} g_i)^2}{\sum_{i \in I_R} h_i + \lambda} - \frac{(\sum_{i \in I} g_i)^2}{\sum_{i \in I} h_i + \lambda} \right] - \gamma \quad (3)$$

After it obtains an optimal tree structure, the optimal weight w_j^* of leaf j can be computed by the following equation, where I_j is the instance space of leaf j .

$$w_j^* = - \frac{\sum_{i \in I_j} g_i}{\sum_{i \in I_j} h_i + \lambda} \quad (4)$$

From the above review, we make following observations:

Algorithm 1 Aggregate Encrypted Gradient Statistics

Input: I , instance space of current node
Input: d , feature dimension
Input: $\{\langle g_i \rangle, \langle h_i \rangle\}_{i \in I}$
Output: $\mathbf{G} \in \mathbb{R}^{d \times l}$, $\mathbf{H} \in \mathbb{R}^{d \times l}$

- 1: **for** $k = 0 \rightarrow d$ **do**
- 2: Propose $S_k = \{s_{k1}, s_{k2}, \dots, s_{kl}\}$ by percentiles on feature k
- 3: **end for**
- 4: **for** $k = 0 \rightarrow d$ **do**
- 5: $\mathbf{G}_{kv} = \sum_{i \in \{i | s_{k,v} \geq x_{i,k} > s_{k,v-1}\}} \langle g_i \rangle$
- 6: $\mathbf{H}_{kv} = \sum_{i \in \{i | s_{k,v} \geq x_{i,k} > s_{k,v-1}\}} \langle h_i \rangle$
- 7: **end for**

(1) The evaluation of split candidates and the calculation of the optimal weight of leaf only depends on the g_i and h_i , which makes it easily adapted to the setting of federated learning.

(2) The class label can be inferred from g_i and h_i . For instance, when we take the square loss as the loss function, we have $g_i = \hat{y}_i^{(t-1)} - y_i$.

With the above observations, we now introduce our federated gradient tree boosting algorithm. Following observation (1), we can see that **passive parties can determine their locally optimal split with only its local data and g_i, h_i** , which motivates us to follow such method to decompose learning task at each party. However, according to observation (2), g_i and h_i should be regarded as sensitive data, since they are able to disclose class label information to passive parties. Therefore, in order to keep g_i and h_i confidential, the active party is required to encrypt g_i and h_i before sending them to passive parties. The remaining challenge is how to determine the locally optimal split with encrypted g_i and h_i for each passive party.

According to Eq.(3), the optimal split can be found if $g_l = \sum_{i \in I_L} g_i$ and $h_l = \sum_{i \in I_L} h_i$ are calculated for every possible split. So next, we show how to obtain g_l and h_l with encrypted g_i and h_i using additive homomorphic encryption scheme [32]. The Paillier encryption scheme is taken as our encryption scheme.

Denoting the encryption of a number u under the Paillier cryptosystem as $\langle u \rangle$, the main property of the Paillier cryptosystem ensures that for arbitrary numbers u and v , we have $\langle u \rangle \cdot \langle v \rangle = \langle u + v \rangle$. Therefore, $\langle h_l \rangle = \prod_{i \in I_L} \langle h_i \rangle$ and $\langle g_l \rangle = \prod_{i \in I_L} \langle g_i \rangle$. Consequently, the best split can be found in the following way. First, each passive party computes $\langle g_l \rangle$ and $\langle h_l \rangle$ for all possible splits locally, which are then sent back to the active party. The active party deciphers all $\langle g_l \rangle$ and $\langle h_l \rangle$ and calculates the global optimal split according to Eq.(3). We adopt the approximation scheme used by [31], so as to alleviate the need of enumerating all possible split candidates and communicating their $\langle g_i \rangle$ and $\langle h_i \rangle$. The details of our secure gradient aggregation algorithm are shown in Algorithm 1.

Following the observation (1), the split finding algorithm remains largely the same as XGBoost except for minor adjustments to fit the federated learning framework. Due to separation in features, SecureBoost requires different parties to store certain information for each split, so as to perform prediction for new samples. Passive parties should keep a lookup table as shown in Figure 3. It contains split thresholds [feature id k , threshold value v] and a unique record id r used to index the table, in order to look up split conditions during inference. In the meantime,

Algorithm 2 Split Finding

Input: I , instance space of current node
Input: $\{\mathbf{G}^i, \mathbf{H}^i\}_{i=1}^m$, aggregated encrypted gradient statistics from m parties
Output: Partition current instance space according to the selected attribute's value

- 1: /*Conduct on Active Party*/
- 2: $g \leftarrow \sum_{i \in I} g_i, h \leftarrow \sum_{i \in I} h_i$
- 3: **for** $i = 0$ to m **do**
- 4: **for** $k = 0$ to d_i **do**
- 5: $g_l \leftarrow 0, h_l \leftarrow 0$
- 6: //enumerate all threshold value
- 7: **for** $v = 0$ to l_k **do**
- 8: get decrypted values $D(\mathbf{G}_{kv}^i)$ and $D(\mathbf{H}_{kv}^i)$
- 9: $g_l \leftarrow g_l + D(\mathbf{G}_{kv}^i), h_l \leftarrow h_l + D(\mathbf{H}_{kv}^i)$
- 10: $g_r \leftarrow g - g_l, h_r \leftarrow h - h_l$
- 11: $score \leftarrow \max(score, \frac{g_l^2}{h_l + \lambda} + \frac{g_r^2}{h_r + \lambda} - \frac{g^2}{h + \lambda})$
- 12: **end for**
- 13: **end for**
- 14: **end for**
- 15: Return k_{opt} and v_{opt} to the passive party i_{opt} when we obtain the max score.
- 16: /*Conduct on Passive Party i_{opt} */
- 17: Determine the selected attribute's value according to k_{opt} and v_{opt} and partition current instance space.
- 18: Record the selected attribute's value and return [record id, I_L] back to the active party.
- 19: /*Conduct on Active Party*/
- 20: Split current node according to I_L and associate current node with [party id, record id].

because the active party does not have features located in passive parties, for the active party to know which passive party to deliver an instance to, as well as instructing the passive party which split condition to use at inference time, it associates every tree node with a pair (party id i , record id r). Specific details about the split finding algorithm for SecureBoost is summarized in Algorithm 2. The problem remaining is the computation of optimal leaf weights. According to Equation 4, the optimal weight of leaf j only depends on $\sum_{i \in I_j} g_i$ and $\sum_{i \in I_j} h_i$. Consequently, it follows similar procedures as split finding. When a leaf node is reached, the passive party sends $\langle \sum_{i \in I_j} g_i \rangle$ and $\langle \sum_{i \in I_j} h_i \rangle$ to the active party, which are then deciphered to compute corresponding weights through Equation 4.

5 FEDERATED INFERENCE

In this section, we describe how the learned model (distributed among parties) can be used to classify a new instance even though the features of the instance to be classified are private and distributed among parties. Since each party knows its own features but nothing of the others, we need a secure distributed inference protocol to control passes from one party to another, based on the decision made. To illustrate the inference process, we consider a system with three parties as depicted in Figure 3. Specifically, party 1 is the active party, which collects information including user's *monthly bill payment*, *education*, as well as the *label*, whether the user X made the payment on time. Party 2 and party 3 are passive parties, holding features *age*, *gender*, *marriage status* and *amount of given credit* respectively. Suppose we wish to




Fig. 3: An illustration of Federated Inference

predict whether a user X_6 would make payment on time, then all sites would have to collaborate to make the prediction. The whole process is coordinated by the active party. Starting from the root, by referring to the record [party id:1, record id:1], the active party knows party 1 holds the root node, thereby requiring party 1 to retrieve the corresponding attribute, *Bill Payment*, from its lookup table based on the record id 1. Since the classifying attribute is *bill payment* and party 1 knows the bill payment for user X_6 is 4367, which is less than the threshold 5000, it makes the decision that it should move down to its left child, node 1. Then, active party refers to the record [party id:3, record id:1] associated with node 1 and requires party 3 to conduct the same operations. This process continues until a leaf is reached.

6 THEORETICAL ANALYSIS FOR LOSSLESS PROPERTY

Theorem 1. *SecureBoost is lossless, i.e. SecureBoost model M and XGBoost model M' would behave identically provided that the models M and M' are identically initialized and hyper-parameterized.*

Proof. According to Eq.(3), g_l and h_l are the only information needed for the calculation of the best split, which can be obtained with encrypted g_i and h_i using Paillier cryptosystem in SecureBoost. In the Paillier cryptosystem, the encryption of a message m is $\langle m \rangle = g^m r^n \mod n^2$, for some random $r \in \{0, \dots, n-1\}$. Given the definition of encrypted message, we have $\langle m_1 \rangle \cdot \langle m_2 \rangle = \langle m_1 + m_2 \rangle$ for arbitrary message m_1 and m_2 under Paillier cryptosystem, which can be proved as follows:

$$\begin{aligned} \langle m_1 \rangle \cdot \langle m_2 \rangle &= (g^{m_1} r_1^c) (g^{m_2} r_2^c) \mod n \\ &= g^{m_1+m_2} (r_1 r_2)^c \mod n \\ &= \langle m_1 + m_2 \rangle \end{aligned} \quad (5)$$

Therefore, we have $\langle h_l \rangle = \prod_{i \in I_L} \langle h_i \rangle$ and $\langle g_l \rangle = \prod_{i \in I_L} \langle g_i \rangle$. Provided that with the same initialization, an instance i will have the same value of g_i and h_i under either setting. Thus, model M and M' can always achieve the same best split

throughout the construction of the tree and result in identical M and M' , which ensures the property of lossless. \square

7 SECURITY DISCUSSION

SecureBoost avoids revealing data records held by each of the parties to others during training and inference thus protecting the privacy of individual parties' data. However, we stress that there is some leakage that can be inferred during the protocol execution which is quite different for passive vs. active parties.

The **active party** is in an advantageous position with SecureBoost as it learns the instance space for each split and which party is responsible for the decision at each node. Also, it learns all the possible values of g_l, g_r and h_l, h_r , during learning. The former seems unavoidable in this setting, unless one is willing to severely increase the overhead during the inference phase. However, the latter can be avoided using secure multi-party computation techniques for comparison of encrypted values (e.g., [33], [34]). In this way, the active party learns only the optimal g_l, g_r, h_l, h_r per party; on the other hand, this significantly affects the efficiency during learning.

Note that the instances that are associated with the same leaf strongly indicates they belong to the same class. We denote the proportion of samples which belong to the majority class as **leaf purity**. The information leakage with respect to **passive parties** is directly related with **leaf purity** of the first tree of SecureBoost. Moreover, the first tree's **leaf purity** can be inferred from the weight of the leaves.

Theorem 2. *Given a learned SecureBoost model, its first tree's leaf purity can be inferred from the weight of the leaves.*

Proof. The loss function for binary classification problem is given as follows.

$$L = y_i \log(1 + e^{-\hat{y}_i}) + (1 - y_i) \log(1 + e^{\hat{y}_i}) \quad (6)$$

Based on the loss function, we have $g_i = \hat{y}_i^{(0)} - y_i$ and $h_i = \hat{y}_i^{(0)} * (1 - \hat{y}_i^{(0)})$ during the construction of the decision tree at first iteration. Specifically, $\hat{y}_i^{(0)}$ is given as initialized value. Suppose

we initialize all $\hat{y}_i^{(0)}$ as a where $0 < a < 1$. According to Eq.(4), for the instances associated with the specific leaf j , $\hat{y}_i^{(1)} = S(w_j^*) = S(-\frac{\sum_{i \in I_j} g_i}{\sum_{i \in I_j} h_i + \lambda})$ where $S(x)$ is the sigmoid function. Suppose the number of instances associated with the leaf j is n_j and the percentage of positive samples is θ_j . When n_j is relatively big, we can ignore λ in $-\frac{\sum_{i \in I_j} g_i}{\sum_{i \in I_j} h_i + \lambda}$ and rewrite the weight of leaf j as $w_j^* = -\frac{\sum_{i \in I_j} g_i}{\sum_{i \in I_j} h_i} = -\frac{\theta_j * n_j * (a-1) + (1-\theta_j) * n_j * a}{n_j * a * (1-a)} = -\frac{\theta_j * n_j * (a-1) + (1-\theta_j) * n_j * a}{n_j * a * (1-a)} = \frac{a-\theta_j}{a(1-a)}$. By reformulating the equation, we have $\theta_j = a - a(a-1)w_j^*$. θ_j depends on a and w_j^* and a is given as initialization. Thus, w_j^* is the key to determine θ_j . Note that θ_j can be used to represent the leaf purity of leaf j (i.e., purity of leaf j can be formally written as $\max(\theta_j, 1 - \theta_j)$), leaf purity of the first tree can be inferred from the weight of the leaves (w_j^*) given a learned SecureBoost model. \square

According to Theorem 2, given a SecureBoost model, the weight of the leaves of its first tree can reveal sensitive information. In order to reduce information leakage with respect to **passive parties**, we opt to store decision tree leaves at the active party and propose a modified version of our framework, called *Reduced-Leakage SecureBoost (RL-SecureBoost)*. With *RL-SecureBoost*, the active party learns the first tree independently based only on its own features which fully protects the instance space of its leaves. Hence, all the information that passive parties learn is based on residuals. Although the residuals may also reveal information, we prove that as the purity in the first tree increases, this residual information decreased.

Theorem 3. *As the purity in the first tree increases, the residual information decreased.*

Proof. As mentioned before, for binary classification problem, we have $g_i = \hat{y}_i^{(t-1)} - y_i$ and $h_i = \hat{y}_i^{(t-1)} * (1 - \hat{y}_i^{(t-1)})$, where $g_i \in [-1, 1]$. Hence,

$$\begin{cases} h_i = g_i(1 - g_i), & \text{if } y_i = 0 \\ h_i = -g_i(g_i + 1), & \text{if } y_i = 1 \end{cases} \quad (7)$$

When we construct the decision tree at the t -th iteration with k leaves to fit the residuals of the previous tree, in essential, we split the data into k clusters to minimize the following loss.

$$\begin{aligned} L &= -\sum_{j=1}^k \frac{(\sum_{i \in I_j} g_i)^2}{\sum_{i \in I_j} h_i} \\ &= -\sum_{j=1}^k \frac{(\sum_{i \in I_j} g_i)^2}{\sum_{i \in I_j^N} g_i(1 - g_i) + \sum_{i \in I_j^P} -g_i(1 + g_i)} \end{aligned} \quad (8)$$

We know $\hat{y}_i^{(t-1)} \in [0, 1]$ and $g_i = \hat{y}_i^{(t-1)} - y_i$. Thus, we have $g_i \in [-1, 0]$ for positive samples and $g_i \in [0, 1]$ for negative samples. Taking the range of g_i into consideration, we can rewrite the above equation as follows.

$$\sum_{j=1}^k \frac{(\sum_{i \in I_j^N} |g_i| - \sum_{i \in I_j^P} |g_i|)^2}{\sum_{i \in I_j^N} |g_i|(|g_i| - 1) + \sum_{i \in I_j^P} |g_i|(|g_i| + 1)} \quad (9)$$

Where I_j^N and I_j^P denote the set of negative samples and positive samples associated with leaf j respectively. We denote the expectation of $|g_i|$ for positive samples as μ_p and the expectation

of $|g_i|$ for negative samples as μ_n . When we have a large amount of samples but small number of leave nodes k , we can use the following equation to approximate Eq.(9).

$$\sum_{j=1}^k \frac{(n_j^n \mu_n - n_j^p \mu_p)^2}{n_j^n \mu_n (\mu_n - 1) + n_j^p \mu_p (\mu_p - 1)} \quad (10)$$

Where n_j^n and n_j^p represent the number of negative samples and positive samples associated with leaf j . Since $\mu_n \in [0, 1]$ and $\mu_p \in [0, 1]$, we know the numerator has to be positive and the denominator has to be negative. Thus, the whole equation has to be negative. To minimize Eq.(10) is equal to maximizing the numerator while minimizing the denominator. Note that the denominator is $\sum x^2$ and the numerator is $(\sum x)^2$ where $x \in [0, 1]$. The equation is dominated by numerator. Thereby, minimizing Eq.(10) can be regarded as maximizing the numerator $(n_j^n \mu_n - n_j^p \mu_p)^2$. Ideally, we require $n_j^n = n_j^p$ in order to prevent label information from divulging. When $|\mu_n - \mu_p|$ is bigger, more possible we can achieve the goal. And we know $|g_i| = |\hat{y}_i^{(t-1)} - y_i| = \hat{y}_i^{(t-1)}$ for negative samples and $|g_i| = |\hat{y}_i^{(t-1)} - y_i| = 1 - \hat{y}_i^{(t-1)}$ for positive samples. Thereby, $\mu_n = \frac{1}{N_n} \sum_{j=1}^k (1 - \theta_j) n_j \hat{y}_i^{(t-1)}$ and $\mu_p = \frac{1}{N_p} \sum_{j=1}^k \theta_j n_j (1 - \hat{y}_i^{(t-1)})$. $|\mu_n - \mu_p|$ can be calculated as follows.

$$\begin{aligned} &|\mu_n - \mu_p| \\ &= \left| \frac{1}{N_n} \sum_{j=1}^k (1 - \theta_j) n_j \hat{y}_i^{(t-1)} - \frac{1}{N_p} \sum_{j=1}^k \theta_j n_j (1 - \hat{y}_i^{(t-1)}) \right| \end{aligned} \quad (11)$$

Where N_n and N_p correspond to the number of negative samples and positive samples in total. θ_j is the percentage of positive samples associated with leaf j for decision tree at $(t-1)$ -th iteration (previous decision tree). n_j denote the number of instances associated with leaf j for previous decision tree. $\hat{y}_i^{(t-1)} = S(w_j)$ where w_j represents the weight of j -th leave of previous decision tree. When the positive samples and negative samples are balanced, $N_n = N_p$, we have

$$\begin{aligned} &|\mu_n - \mu_p| \\ &= \frac{1}{N_n} \left| \sum_{j=1}^k ((1 - \theta_j) n_j S(w_j) - \theta_j n_j (1 - S(w_j))) \right| \\ &= \frac{1}{N_n} \sum_{j=1}^k n_j |(S(w_j) - \theta_j)| \\ &= \frac{1}{N_n} \sum_{j=1}^k n_j \left| S\left(\frac{a - \theta_j}{a(a-1)}\right) - \theta_j \right| \end{aligned} \quad (12)$$

As observed from Eq.(12), it achieves the minimum value when $S(\frac{a - \theta_j}{a(a-1)}) = a$. By solving the equation, we have the optimal solution of θ_j as $\theta_j^* = a(1 + (1 - a) \ln(\frac{a}{1-a}))$. In order to achieve bigger $\mu_n - \mu_p$, we want the deviation from θ_j to θ_j^* to be as big as possible. When we have proper initialization of a , for instance $a = 0.5$, $\theta_j^* = 0.5$. In this case, maximizing $|\theta_j - \theta_j^*|$ is the same as maximizing $\max(\theta_j, 1 - \theta_j)$, which exactly is the leaf purity. Therefore, we have proved that high leaf purity will guarantee big difference between μ_n and μ_p , which finally results in less information leakage. We complete our proof. \square




Fig. 4: Loss convergence

TABLE 1: First Tree vs. Second Tree in terms of Leaf Purity

Mean Purity	Credit 1	Credit 2
1st Tree	0.8058	0.7159
2nd Tree	0.66663	0.638

Given Theorem 3, we prove that *RL-SecureBoost* is secure as long as its first tree learns enough information to mask the actual label with residuals. Moreover, as we experimentally demonstrate in Section 8, *RL-SecureBoost* performs identically as *SecureBoost* in terms of prediction accuracy.

8 EXPERIMENTS

We conduct experiments on two public datasets.

Credit 1²: It involves the problem of classifying whether a user would suffer from serious financial problems. It contains a total of 150000 instances and 10 attributes.

Credit 2³: It is also a credit scoring dataset, correlated to the task of predicting whether a user would make payment on time. It consist of 30000 instances and 25 attributes in all.

In our experiment, we use 2/3 of each dataset for training and the remaining for testing. We split the data vertically into two halves and distribute them to two parties. To fairly compare different methods, we set the maximum depth of each tree as 3, the fraction of samples used to fit individual regression trees as 0.8, and learning rate as 0.3 for all methods. The Paillier encryption scheme is taken as our encryption scheme with a key size of 512 bits. All experiments are conducted on a machine with 8GB RAM and Intel Core i5-7200u CPU.

8.1 Scalability

Note that the efficiency of *SecureBoost* may be reflected by rate of convergence and runtime, which may be influenced by (1) maximum depth of individual regression trees; (2) the size of the datasets. In this subsection, we conduct convergence analysis as well as study the impact of all the variables on the runtime of learning. All experiments are conducted on dataset Credit2.

First, we are interested in the convergence rate of our proposed system. We compare the convergence behavior of *SecureBoost* with non-federated tree boosting counterparts, including GBDT⁴ and XGBoost⁵. As can be observed from Figure 4, *SecureBoost* shows a similar learning curve with other non-federated methods on the training dataset and even performs slightly better than others on the test dataset. In addition, the convergence behavior of

training and test loss of *SecureBoost* are very much alike GBDT and XGBoost.

Next, to investigate how maximum depth of individual trees affects the runtime of learning, we vary the maximum depth of individual tree among {3, 4, 5, 6, 7, 8} and report the runtime of one boosting stage. As depicted in Figure 5 (a), the runtime increases almost linearly with the maximum depth of individual trees, which indicates that we can train deep trees with relatively little additional time, which is very appealing in practice, especially in scenarios like big data.

Finally we study the impact of data size on the runtime of our proposed system. We augment the feature sets by feature products. We fix the maximum depth of individual regression trees to 3 and vary the feature number in {50, 500, 1000, 5000} and the sample number in {5000, 10000, 30000}. We compare the runtime of one boosting stage to investigate how each variant affects the efficiency of the algorithm. We make similar observations on both Figure 5 (b) and Figure 5 (c), which imply that sample and feature numbers contribute equally to running time. In addition, we can see that our proposed framework scales well even with relatively big data.

8.2 Performance of RL-SecureBoost

To investigate the performance of *RL-SecureBoost* in both security and prediction accuracy, we aim to answer the following questions: (1) Does the first tree, built upon only features held by active party, learns enough information to reduce information leakage? (2) Does *RL-SecureBoost* suffer from a loss of accuracy compared with *SecureBoost*?

First, we study the performance of *RL-SecureBoost* in security. Following the analysis in Section 7, we evaluate information leakage in terms of leaf purity. Also, we know that as the leaf purity in the first tree increases, leaked information is reduced. Thereby, to verify the security of *RL-SecureBoost*, we have to illustrate that the first tree of *RL-SecureBoost* perform well enough to reduce the information leaked from the second tree. As shown in Table 1, we compare the mean leaf purity of the first tree with the second tree. In particular, the mean leaf purity is the weighted average, which is calculated by $\sum_{i=0}^k \frac{n_i}{n} p_i$. Here, k and n represents number of leaves and number of instances in total. p_i and n_i are defined as leaf purity and number of instances associated with leaf i . According to Table 1, the mean leaf purity decreases significantly from the first to the second tree on both datasets, which reflects a great reduction in information leakage. Moreover, the mean leaf purity of the second tree is just over 0.6 on both datasets, which is good enough to ensure a safe protocol.

Next, to investigate the prediction performance of *RL-SecureBoost*, we compare *RL-SecureBoost* with *SecureBoost* with respect to the the first tree's performance and the overall performance. We consider commonly used metrics including accuracy, Area under ROC curve (AUC) and f1-score. The results are presented in Table 2. As observed, *RL-SecureBoost* performs equally well compared to *SecureBoost* in almost all cases. We also conduct a pairwise Wilcoxon signed-rank test between *RL-SecureBoost* and *SecureBoost*. The comparison results indicate that *RL-SecureBoost* is as accurate as *SecureBoost*, with a significance level of 0.05. The property of lossless is still guaranteed for *RL-SecureBoost*.

9 CONCLUSION

In this paper, we proposed a lossless privacy-preserving tree boosting algorithm, *SecureBoost*, to train a high-quality tree

2. <https://www.kaggle.com/c/GiveMeSomeCredit/data>
3. <https://www.kaggle.com/uciml/default-of-credit-card-clients-dataset>
4. <http://scikit-learn.org/stable/modules/generated/sklearn.ensemble.GradientBoostingClassifier.html>
5. <https://github.com/dmlc/xgboost>




Fig. 5: Scalability Analysis of SecureBoost

TABLE 2: Classification Performance for RL-SecureBoost vs. SecureBoost

Model	Credit 1			Credit 2		
	ACC	F1-score	AUC	ACC	F1-score	AUC
1st Tree, SecureBoost	0.9298	0.012	0.7002	0.7806	0	0.6381
1st Tree, RL-SecureBoost	0.9186	0	0.6912	0.7793	0	0.6320
Overall, SecureBoost	0.9345	0.2576	0.8461	0.8180	0.4634	0.7701
Overall, RL-SecureBoost	0.9331	0.2549	0.8423	0.8179	0.4650	0.7682

boosting model with private data split across multiple parties. We theoretically prove that our proposed framework is as accurate as non-federated gradient tree boosting counterparts. In addition, we analyze information leakage during the protocol execution and propose provable ways to reduce it.

ACKNOWLEDGMENT

This work was partially supported by the National Key Research and Development Program of China under Grant No. 2018AAA0101100.

REFERENCES

- [1] P. Regulation, "The general data protection regulation," *European Commission*. Available at: <https://eur-lex.europa.eu/legal-content/EN/TXT>, 2016.
- [2] J. P. Albrecht, "How the gdpr will change the world," *Eur. Data Prot. L. Rev.*, vol. 2, p. 287, 2016.
- [3] V. Mayer-Schonberger and Y. Padova, "Regime change: Enabling big data through europe's new data protection regulation," *Colum. Sci. & Tech. L. Rev.*, vol. 17, p. 315, 2015.
- [4] B. Goodman and S. Flaxman, "European union regulations on algorithmic decision-making and a" right to explanation", *arXiv preprint arXiv:1606.08813*, 2016.
- [5] S. Hardy, W. Henecka, H. Ivey-Law, R. Nock, G. Patrini, G. Smith, and B. Thorne, "Private federated learning on vertically partitioned data via entity resolution and additively homomorphic encryption," *arXiv preprint arXiv:1711.10677*, 2017.
- [6] P. Mohassel and Y. Zhang, "Secureml: A system for scalable privacy-preserving machine learning," in *2017 38th IEEE Symposium on Security and Privacy (SP)*. IEEE, 2017, pp. 19–38.
- [7] C. Dwork, A. Roth et al., "The algorithmic foundations of differential privacy," *Foundations and Trends® in Theoretical Computer Science*, vol. 9, no. 3–4, pp. 211–407, 2014.
- [8] C. Dwork, "Differential privacy: A survey of results," in *International Conference on Theory and Applications of Models of Computation*. Springer, 2008, pp. 1–19.
- [9] J. Konečný, H. B. McMahan, F. X. Yu, P. Richtárik, A. T. Suresh, and D. Bacon, "Federated learning: Strategies for improving communication efficiency," *arXiv preprint arXiv:1610.05492*, 2016.
- [10] K. Bonawitz, V. Ivanov, B. Kreuter, A. Marcedone, H. B. McMahan, S. Patel, D. Ramage, A. Segal, and K. Seth, "Practical secure aggregation for privacy-preserving machine learning," in *CCS*, 2017, pp. 1175–1191.
- [11] Q. Yang, Y. Liu, T. Chen, and Y. Tong, "Federated machine learning: Concept and applications," *ACM Transactions on Intelligent Systems and Technology*, vol. 10, no. 2, pp. 12:1–12:19, 2019.
- [12] Y. C. Y. K. T. C. Qiang Yang, Yang Liu and H. Yu, *Federated Learning*. Morgan Claypool, 2019.
- [13] Y. Liu, Y. Kang, X. Zhang, L. Li, Y. Cheng, T. Chen, M. Hong, and Q. Yang, "A communication efficient vertical federated learning framework," *CoRR*, vol. abs/1912.11187, 2019. [Online]. Available: <http://arxiv.org/abs/1912.11187>
- [14] X. Liang, Y. Liu, J. Luo, Y. He, T. Chen, and Q. Yang, "Self-supervised cross-silo federated neural architecture search," 2021.
- [15] J. Vaidya, "A survey of privacy-preserving methods across vertically partitioned data," in *Privacy-preserving data mining*. Springer, 2008, pp. 337–358.
- [16] J. Vaidya and C. Clifton, "Privacy-preserving decision trees over vertically partitioned data," in *IFIP Annual Conference on Data and Applications Security and Privacy*. Springer, 2005, pp. 139–152.
- [17] *KDD '16: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. New York, NY, USA: Association for Computing Machinery, 2016.
- [18] R. Shokri and V. Shmatikov, "Privacy-preserving deep learning," in *Proceedings of the 22nd ACM SIGSAC conference on computer and communications security*. ACM, 2015, pp. 1310–1321.
- [19] P. Kairouz, H. B. McMahan, B. Avent, A. Bellet, M. Bennis, A. N. Bhagoji, K. Bonawitz, Z. Charles, G. Cormode, R. Cummings, R. G. L. D'Oliveira, S. E. Rouayheb, D. Evans, J. Gardner, Z. Garrett, A. Gascón, B. Ghazi, P. B. Gibbons, M. Gruteser, Z. Harchaoui, C. He, L. He, Z. Huo, B. Hutchinson, J. Hsu, M. Jaggi, T. Javidi, G. Joshi, M. Khodak, J. Konečný, A. Korolova, F. Koushanfar, S. Koyejo, T. Lepoint, Y. Liu, P. Mittal, M. Mohri, R. Nock, A. Özgür, R. Pagh, M. Raykova, H. Qi, D. Ramage, R. Raskar, D. Song, W. Song, S. U. Stich, Z. Sun, A. T. Suresh, F. Tramèr, P. Vepakomma, J. Wang, L. Xiong, Z. Xu, Q. Yang, F. X. Yu, H. Yu, and S. Zhao, "Advances and open problems in federated learning," *CoRR*, vol. abs/1912.04977, 2019. [Online]. Available: <http://arxiv.org/abs/1912.04977>
- [20] L. Zhao, L. Ni, S. Hu, Y. Chen, P. Zhou, F. Xiao, and L. Wu, "Inprivate digging: Enabling tree-based distributed data mining with differential privacy," in *IEEE INFOCOM 2018-IEEE Conference on Computer Communications*. IEEE, 2018, pp. 2087–2095.
- [21] Q. Li, Z. Wen, and B. He, "Practical federated gradient boosting decision trees," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 34, no. 04, 2020, pp. 4642–4649.
- [22] T. Li, A. K. Sahu, M. Zaheer, M. Sanjabi, A. Talwalkar, and V. Smith, "Federated optimization in heterogeneous networks," *arXiv preprint arXiv:1812.06127*, 2018.
- [23] F. Hanzely, S. Hanzely, S. Horváth, and P. Richtárik, "Lower bounds and optimal algorithms for personalized federated learning," *arXiv preprint arXiv:2010.02372*, 2020.
- [24] M. Mohri, G. Sivek, and A. T. Suresh, "Agnostic federated learning," in *International Conference on Machine Learning*. PMLR, 2019, pp. 4615–4625.
- [25] M. Yurochkin, M. Agarwal, S. Ghosh, K. Greenewald, N. Hoang,

- and Y. Khazaeni, "Bayesian nonparametric federated learning of neural networks," in *International Conference on Machine Learning*. PMLR, 2019, pp. 7252–7261.
- [26] H. Wang, M. Yurochkin, Y. Sun, D. Papailiopoulos, and Y. Khazaeni, "Federated learning with matched averaging," *arXiv preprint arXiv:2002.06440*, 2020.
- [27] Y. Liu, Y. Kang, C. Xing, T. Chen, and Q. Yang, "A secure federated transfer learning framework," *IEEE Intelligent Systems*, vol. 35, no. 4, pp. 70–82, 2020.
- [28] J. Vaidya, C. Clifton, M. Kantarcioglu, and A. S. Patterson, "Privacy-preserving decision trees over vertically partitioned data," *ACM Transactions on Knowledge Discovery from Data (TKDD)*, vol. 2, no. 3, p. 14, 2008.
- [29] M. Djatmiko, S. Hardy, W. Henecka, H. Ivey-Law, M. Ott, G. Patrini, G. Smith, B. Thorne, and D. Wu, "Privacy-preserving entity resolution and logistic regression on encrypted data," *Private and Secure Machine Learning (PSML)*, 2017.
- [30] G. Liang and S. S. Chawathe, "Privacy-preserving inter-database operations," in *International Conference on Intelligence and Security Informatics*. Springer, 2004, pp. 66–82.
- [31] T. Chen and C. Guestrin, "Xgboost: A scalable tree boosting system," in *Proceedings of the 22nd acm sigkdd international conference on knowledge discovery and data mining*. ACM, 2016, pp. 785–794.
- [32] P. Paillier, "Public-key cryptosystems based on composite degree residuosity classes," in *International Conference on the Theory and Applications of Cryptographic Techniques*. Springer, 1999, pp. 223–238.
- [33] R. Bost, R. A. Popa, S. Tu, and S. Goldwasser, "Machine learning classification over encrypted data," in *22nd Annual Network and Distributed System Security Symposium, NDSS*, 2015.
- [34] F. Baldimtsi, D. Papadopoulos, S. Papadopoulos, A. Scafuro, and N. Triandopoulos, "Server-aided secure computation with off-line parties," in *Computer Security - ESORICS 2017 - 22nd European Symposium on Research in Computer Security, Proceedings, Part I*, 2017, pp. 103–123.

Kewei Cheng is a PhD student at the University of California, Los Angeles since September 2018. Prior to that, she obtained her M.Sc. degree in Computer Science at Arizona State University in 2017, and B.Eng. degree in Software Engineering at Sichuan University in 2015. Her research interests mainly focus on in knowledge graph reasoning, machine learning, and federated learning. Contact her at kewei-cheng@g.ucla.edu.

Tao Fan is a Principal Researcher in the AI Department of WeBank, Shenzhen, China. He is now responsible for FATE, an industrial level federated learning open source project. Before joining WeBank, he worked at Baidu, Tencent. He has more than 8 years of experience in large-scale machine learning system and big data application fields. He received his Master degree from University of Science and Technology of China in 2013 and his Bachelor's degree from Shandong University of Science and Technology in 2010. Contact him at dylan-fan@webank.com.

Yilun Jin is a PhD student at the Hong Kong University of Science and Technology. He obtained his Bachelor's degrees in Computer Science and Economics from Peking University in 2019. His has published in multiple top conferences including AAAI, KDD, WWW and IJCAI. His research interest lies in machine learning and data mining, including federated learning, transfer learning, and learning on graph data. Contact him at yilun.jin@connect.ust.hk.

Yang Liu is currently a Principal Researcher with the AI Department of WeBank, Shenzhen, China. Her research interests include federated learning, transfer learning, multiagent systems, statistical mechanics, and applications of these technologies in the industry. She received the Ph.D. degree from Princeton University, Princeton, NJ, USA, in 2012 and the Bachelor's degree from Tsinghua University, Beijing, China, in 2007. She holds multiple patents. Her research has been published in leading scientific journals such as ACM TIST and Nature. Contact her at liuyang.princeton@gmail.com.

Tianjian Chen is currently the Deputy General Manager with the AI Department of WeBank, Shenzhen, China. He is now responsible for building the Banking Intelligence Ecosystem based on Federated Learning Technology. Before joining WeBank, he was the Chief Architect of Baidu Finance, Principal Architect of Baidu. He has more than 12 years of experience in large-scale distributed system design and enabling technology innovations in various application fields. Contact him at tobychen@webank.com.

Dimitrios Papadopoulos is an Assistant Professor at the Computer Science and Engineering Department of the Hong Kong University of Science and Technology. He received his PhD in Computer Science from Boston University. His research focus is the development of novel cryptographic protocols for a variety of application scenarios and problems related to cloud data privacy, distributed machine learning, and blockchain settings. Contact him at dipapado@cse.ust.hk.

Qiang Yang is currently the Head of AI at WeBank, Shenzhen, China, (Chief AI Officer) and Chair Professor with the Computer Science and Engineering Department of the Hong Kong University of Science and Technology. His research interests include transfer learning, automated planning, federated learning, and case-based reasoning. He is a Fellow of several international societies, including ACM, AAAI, IEEE, IAPR, and AAAS. He received the B.Sc. degree in astrophysics from Peking University, Beijing, China, in 1982, and the Ph.D. degree from the Computer Science Department in 1989 and the M. Sc. degree in astrophysics in 1985, both from the University of Maryland, College Park, MD, USA. He is a Fellow of the IEEE. Contact him at qyang@cse.ust.hk.