

Segmentation and Clustering (Part 3)

This Lecture

- Segmentation and grouping
 - Gestalt principles
 - Image segmentation
- Segmentation as clustering
 - k-Means
 - Feature spaces
- Probabilistic clustering
 - Mixture of Gaussians, EM
- **Model-free clustering**
 - Mean-Shift clustering
- Graph theoretic segmentation
 - Normalised cuts

Mean-Shift Segmentation

- An advanced and versatile technique for clustering-based segmentation

Segmented "landscape 1"




Segmented "landscape 2"



D. Comaniciu and P. Meer, [Mean Shift: A Robust Approach toward Feature Space Analysis](#), PAMI 2002.


Finding Modes in a Histogram



● How many modes are there?

- *Mode* = local maximum of the density of a given distribution
- Easy to see, hard to compute


Finding Modes in a Histogram



● How many modes are there?

- *Mode* = local maximum of the density of a given distribution
- Easy to see, hard to compute


Mean-Shift Algorithm



● Iterative Mode Search

1. Initialise random seed, and window W
2. Calculate centre of gravity (the “mean”) of W : $\sum_{x \in W} xH(x)$
3. Shift the search window to the “mean”
4. Repeat Step 2 until convergence

Mean-Shift and mode finding




One-dimensional visualization of **kernel density estimate**, its derivative, and a mean shift.

Further details:


- Parzen window or kernel approach to probability density estimation:
 - Duda, Hart, and stork 2001, section 4.3
 - Bishop 2006, section 2.5.1
- D. Comaniciu and P. Meer, [Mean Shift: A Robust Approach toward Feature Space Analysis](#), PAMI 2002 (*copy on blackboard*)

Mean-Shift




Mean-Shift


Region of
interest




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift




Mean-Shift



Real Modality Analysis




Real Modality Analysis




Run the procedure in parallel

Real Modality Analysis




Run the procedure in parallel

Real Modality Analysis



The blue data points were traversed by the windows towards the mode.


Real Modality Analysis



The blue data points were traversed by the windows towards the mode.


Mean-Shift Clustering

- **Cluster:** all data points in the attraction basin of a mode
- **Attraction basin:** the region for which all trajectories lead to the same mode 轨迹




Mean-Shift Clustering/Segmentation


- Find **features** (colour, gradients, texture, etc)
- Initialize windows at individual pixel locations
- Perform **mean shift** for each window until convergence
- Merge windows that end up near the same “peak” or mode




(a)



(b)



Mean-Shift Segmentation Results



D. Comaniciu and P. Meer, [Mean Shift: A Robust Approach toward Feature Space Analysis](#), PAMI 2002.

Summary Mean-Shift

● Pros

- General, application-independent tool
- **Model-free**, does not assume any prior shape (spherical, elliptical, etc.) on data clusters

Summary Mean-Shift

● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size h)

Summary Mean-Shift

● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size h)
- Finds variable number of modes

Summary Mean-Shift

● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size h)
- Finds variable number of modes
- Robust to outliers

Summary Mean-Shift

● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size h)
- Finds variable number of modes
- Robust to outliers

● Cons

Summary Mean-Shift

● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size h)
- Finds variable number of modes
- Robust to outliers

● Cons

- Output depends on window size

Summary Mean-Shift

● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size h)
- Finds variable number of modes
- Robust to outliers

● Cons

- Output depends on window size
- Window size (bandwidth) selection is not trivial

Summary Mean-Shift

● Pros

- General, application-independent tool
- Model-free, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (window size h)
- Finds variable number of modes
- Robust to outliers

● Cons

- Output depends on window size
- Window size (bandwidth) selection is not trivial
- Computationally (relatively) expensive ($\sim 2s/\text{image}$)

Summary Mean-Shift

● Pros

- General, application-independent tool
- **Model-free**, does not assume any prior shape (spherical, elliptical, etc.) on data clusters
- Just a single parameter (**window size h**)
- Finds variable number of modes
- **Robust to outliers**

● Cons

- Output depends on window size
- **Window size (bandwidth) selection** is not trivial
- Computationally (relatively) **expensive** (~2s/image)
- Does not scale well with dimension of feature space

Today's Lecture

- Segmentation and grouping
 - Gestalt principles
 - Image segmentation
- Segmentation as clustering
 - k-Means
 - Feature spaces
- Probabilistic clustering
 - Mixture of Gaussians, EM
- Model-free clustering
 - Mean-Shift clustering
- Graph theoretic segmentation
 - Normalised cuts

Reading

Reading

- **Forsyth, Ponce: Chapter 14**

Reading

- Forsyth, Ponce: Chapter 14
- D. Comaniciu and P. Meer, Mean Shift: A Robust Approach toward Feature Space Analysis, PAMI 2002 (copy on blackboard)