ERIBench: A Comprehensive Benchmark for Embodied Reference Interaction in Human-Robot Scenarios

Huayu Gu*‡, Menghan Xia†, Shaoli Huang‡, Wenjie Xuan*, Juhua Liu*§, Bo Du*
*School of Computer Science, Wuhan University, Wuhan, China
†Huazhong University of Science and Technology, Wuhan, China
‡AgiBot, China

***Abstract*—With the remarkable advancements in Multimodal Large Language Models (MLLMs) in perception and generation, utilizing them as the central "brain" for embodied agents has emerged as a promising paradigm toward General Artificial Intelligence. While existing evaluation frameworks demonstrate the robust performance of MLLMs across non-interactive embodied tasks, they overlook the critical scenario of Embodied Reference Interaction (ERI). In real-world interactions, users naturally and efficiently combine linguistic and non-linguistic cues (*e.g.*, pointing gestures) to specify target objects and assign tasks. To bridge this gap, we introduce ERIBench, a comprehensive benchmark designed to systematically evaluate the performance of MLLMs in ERI. ERIBench defines five essential dimensions, *i.e.*, Visual Perception, Visual Reasoning, Intent Inference, Safety and Task Planning, covering 10 distinct tasks and 6,535 high-quality question-answer pairs. Extensive experiments conducted on 14 state-of-the-art (SOTA) MLLMs reveal several critical bottlenecks: insufficient capabilities in complex multimodal reference grounding, inadequate understanding of spatial relationships, and significantly struggle with distance-aware boundary safety judgment. While targeted fine-tuning yields certain improvements, it has not yet reached the satisfactory level required for reliable and safe deployment. In conclusion, ERIBench not only serves as a rigorous diagnostic tool for evaluating MLLMs in complex ERI environments, but also provides valuable directions and insights for the development of future safe and precise embodied AI systems. Our code and data are publicly available at https://github.com/HuayuGu/ERIBench**

***Index Terms*—Multimodal Large Language Models, Benchmark, Embodied AI, Embodied Reference Interaction**

I. Introduction

Developing embodied agents capable of solving complex real-world tasks remains a formidable challenge [1], [2]. Recently, Multimodal Large Language Models (MLLMs) have demonstrated extraordinary capability in instruction following, visual understanding, reasoning, and task planning [3]–[7]. These advancements have prompted researchers to adopt MLLMs as the "embodied brain", a central controller that leverages foundational models to interact with environments for complex problem-solving [8]–[11].

Given this paradigm, it is crucial to conduct a systematic evaluation of the MLLMs as the embodied controller.

§Corresponding authors: Juhua Liuliujuhua@whu.edu.cn).




Fig. 1. An example of an embodied reference interaction scenario, where a user conveys their intentions using natural language and pointing gestures.

While existing embodied benchmarks comprehensively evaluate MLLM capabilities in perception, reasoning, planning, and safety within non-interactive embodied scenarios, such as MMRo [19], RoboBench [20] and EmbodiedBench [18], among others [16], [17], [21]. They overlook a more prevalent real-world scenario: a human user within the robot's line of sight providing pointing gestures in the context of natural language instructions [22]–[29]. We refer to this as Embodied Reference Interaction (ERI), a typical ERI scenario is shown in Figure 1. Compared to non-interactive scenarios, the complexity of ERI is twofold:

- **Face-to-face Interaction**: Unlike human-free environments, the agent must explicitly account for user safety during the task.
- **Natural Multimodal instructions**: Users give instructions through natural language and pointing gestures, which places higher demands on the agent's multimodal alignment capabilities.

Existing ERI datasets remain insufficient for a comprehensive evaluation. YouRefIt [12] and Refer360 [15] focus exclusively on the Visual Grounding. SIGAR [14] introduced intent-based grounding but failed to move beyond the grounding paradigm. Although EQA-MX [13] covers perception and reasoning data in multi-view simulations environment, it lacks safety awareness and task planning data, which are

TABLE I
COMPARISON OF ERIBENCH WITH EXISTING BENCHMARKS ACROSS KEY EVALUATION DIMENSIONS, THE ABBREVIATIONS FOR THE SCENARIOS ARE: REAL(REALITY), SIM(SIMULATION), ERI(EMBODIED REFERENCE INTERACTION), NIE(NON-INTERACTIVE EMBODIED).

Benchmarks	Scenarios		Visual Perception	Visual Reasoning	Intent Inference	Task Planning	Safety	Dataset Scale
YouRefIt [12]	real	ERI	✓	✗	✗	✗	✗	4,195
EQA-MX [13]	sim	ERI	✓	✓	✗	✗	✗	8, 243, 893
SIGAR [14]	real	ERI	✓	✗	✓	✗	✗	20,193
Refer360 [15]	real	ERI	✓	✗	✗	✗	✗	13,935
Visual Agent Bench [16]	sim	NIE	✗	✗	✗	✓	✗	181
Embodied Agent Interface [17]	sim	NIE	✗	✗	✗	✓	✗	438
EmbodiedBench [18]	sim	NIE	✓	✓	✗	✓	✗	1,128
MMRo [19]	real	NIE	✓	✓	✗	✓	✓	26,175
RoboBench [20]	real	NIE	✓	✓	✗	✓	✗	6,092
ERIBench(**Ours**)	real	ERI	✓	✓	✓	✓	✓	6,535

indispensable for embodied agents. As summarized in Table I, existing benchmarks are insufficient to comprehensively evaluate MLLM capabilities in ERI scenarios.

To bridge this gap, we introduce ERIBench, a comprehensive benchmark designed to systematically evaluate the performance of MLLMs in ERI scenarios. ERIBench evaluates perception and reasoning tasks in ERI scenarios that overlap with non-interactive scenarios. Furthermore, it redefines and evaluates intent inference, safety, and task planning tasks that are absent in existing ERI datasets and are specifically tailored to ERI scenarios. Specifically, ERIBench evaluate MLLMs across five critical dimensions: Visual Perception, Visual Reasoning, Intent Inference, Safety and Task Planning, encompassing a total of 10 sub-tasks. These dimensions comprehensively cover the capabilities required for embodied agents to perform tasks in ERI scenario: perceiving relevant information about target objects, reasoning about the relationship between objects and the environment, inferring user intent, assessing task safety, and ultimately formulating a secure high-level task plan. ERIBench utilizes images curated from real-world ERI datasets (YouRefIt [12] and Refer360 [15]), comprising 573 test images and 2,278 training images. We leverage the state-of-the-art MLLM, Gemini 3 [7], for automated data generation from the test images, followed by rigorous human verification to guarantee high data quality, resulting in 6,535 test datas.

Evaluations conducted on 14 state-of-the-art MLLMs yield three key findings: (1) MLLMs exhibit limitations in complex multimodal alignment, leading to poor embodied reference grounding capabilities. (2) MLLMs perform poorly in perceiving 3D depth information from images, leading to confusion between compound and primary directions in spatial relationship reasoning (*e.g.*, confusing "Front-Left" with "Left"). (3) MLLMs significantly struggle with distance-aware safety judgment. Further analysis experiments reveal that while targeted fine-tuning improves the performance of open-source MLLMs on three challenging ERI tasks, they did not yet reach the standards for reliable and safe deployment. These findings underscore that while MLLMs hold immense promise as "embodied brains", they still struggle with complex multimodal alignment and spatial distance reasoning. Currently, MLLMs are still insufficient for the demands of complex and safe embodied interactions. In summary, our main contributions are three-fold:

- We introduce ERIBench, the first comprehensive benchmark for Embodied Reference Interaction (ERI). It systematically evaluates the performance of MLLMs as 'embodied brains' across five key dimensions, covering 10 distinct tasks and 6,535 curated question-answer pairs.
- We conduct large-scale systematic evaluation of both closed-source and open-source SOTA MLLMs, establishing a leaderboard that offers actionable insights for the evolution of brains in embodied agent.
- We conduct analysis and fine-tuning experiments to address the shortcoming of MLLMs in complex multimodal reference grounding and spatial distance reasoning, providing insights for the future development of precise and safe embodied agent.

II. RELATED WORKS

A. MLLMs in Embodied AI

The evolution of Multimodal Large Language Models (MLLMs) represents a pivotal paradigm shift in the field of AI [3], [5], [30], [31], effectively synergizing the cognitive reasoning of Large Language Models (LLMs) [32]–[34] with the advanced perceptual capabilities of vision models [35], [36]. State-of-the-art models, ranging from closed-source leaders like GPT-5 [6] and Gemini 3 pro [7] to prominent open-source counterparts such as Qwen3-VL [5], InternVL 3.5 [37], and LLaVA [4], [38], have demonstrated extraordinary proficiency in instruction following, multimodal understanding, reasoning, and strategic task planning. The rapid maturation of these models has catalyzed a surge in Embodied AI research [10]. In Vision-Language-Action (VLA) models, MLLMs are utilized as the foundation backbone and fine-tuned to directly output low-level control tokens for multimodal inputs (*e.g.*, π_0 [39], OpenVLA [40], $\pi_{0.5}$ [41]). Alternatively, in modular embodied agent frameworks, MLLMs function as the "embodied brain," orchestrating high-level task planning, navigation, and environmental reasoning (*e.g.*, VoxPoser [8], ReKep [42], SayCan [43], SayPlan [44], SayTap [45], PaLM-E [9], and RoboBrain [46]).




Fig. 2. The example illustration of ten tasks in ERIBench, which are categorized into five distinct dimensions.

B. Embodied Benchmark for MLLMs

Recent research has introduced various benchmarks to evaluate the performance of MLLMs in embodied AI tasks. In non-interactive embodied scenarios, Visual Agent Bench [16] and Embodied Agent Interface [17] focus on assessing task planning and action execution in simulated environments, while EmbodiedBench [18] and EmbodiedEval [21] incorporate additional dimensions of visual perception and reasoning. Moving toward real-world applications, MMRo [19] and RoboBench [20] provide comprehensive evaluations covering perception, reasoning, intent inference, task planning, safety, and error analysis. Regarding Embodied Reference Interaction (ERI), YouRefIt [12] pioneered the concept and defined the foundational interaction scenarios, while Refer360 [15] subsequently scaled up it in terms of data and scenario complexity. However, these benchmarks remain primarily restricted to the single task of visual grounding. Although SIGAR [14] proposes locating target objects based on user intent rather than literal descriptions, it remains confined to the grounding paradigm. More recently, EQA-MX [13] introduces a multi-view simulation dataset (ego, exo, and top views) focusing on perception and reasoning tasks, such as object grounding, attribute querying, and relational understanding. Nevertheless, it lacks the high-level reasoning and task planning capabilities indispensable for autonomous agents. As summarized in Table I, existing benchmarks fall short of providing a holistic evaluation of MLLMs as "embodied brains" within the complex landscape of ERI tasks.

III. ERIBench

In this section, we present ERIBench, a systematic evaluation framework designed to quantify the embodied physical-world perception and spatial reasoning capabilities of existing MLLMs in Human-Robot Interaction (HRI) contexts. Specifically, this benchmark focuses on Embodied Reference Interaction (ERI), where the model is expected to interpret a single egocentric or third-person image featuring a human user providing pointing gestures in the context of natural language commands. The evaluation is conducted by designing a suite of tasks covering perception, intent inference, and high-level task planning, and employ various models to solve these tasks with multimodal referential cues. These tasks inherently require MLLMs to decipher complex 3D spatial relationships and draw upon embodied commonsense knowledge to generate safe and actionable plans. To this end, we curate a high-quality dataset and establish a multi-dimensional evaluation

framework with rigorously designed tasks, detailed in the following sections.

A. Task Definition

Compared to other embodied benchmarks that evaluate agents in human-free scenarios, ERIBench evaluates MLLM capabilities in ERI contexts, where human user serves as a pivotal factor in the evaluation tasks. ERIBench adopts the evaluation dimensions of existing embodied benchmarks but redefines the sub-tasks to align with ERI scenarios involving deep human involvement. As showcased in Figure 2, we curated 10 tasks across five key dimensions, which are described below:

- **Visual Perception:** Including four sub-tasks: Visual Grounding, Object Color, Object Shape, and Object Material. While adhering to the task definitions of general embodied benchmarks, we augment the instructions by incorporating user gestures as a novel component. These tasks evaluate the MLLM's capabilities in object grounding under multimodal reference conditions, as well as its capabilities to recognize object attributes, including color, shape, and material.
- **Visual Reasoning:** Including two sub-tasks: Object Function and Spatial Relationship. While adhering to the task definitions of general embodied benchmarks, we incorporate user gestures as a novel component of the instructions. These tasks evaluate the MLLM's reasoning capabilities regarding the target object's function in its environment and its spatial orientation relative to surrounding entities.
- **Intent Inference:** Including only Intent Inference task. Diverging from RoboBench [20], which relies on implicit instruction comprehension and planning without explicit target objects or user confirmation, leading to highly ambiguous and suboptimal interaction experience, ERIBench redefines Intent Inference task. In our framework, MLLM must synthesize the user's referred target and their underlying intent to infer the specific task that the user requires the agent to perform.
- **Safety:** Including two sub-tasks: Task Safety and Boundary Safety, which are newly defined to pivot the safety focus toward human user. These tasks evaluate the MLLM's capabilities to identify two specific hazardous scenarios: (1) whether executing the task would cause physical harm to the user, and (2) whether it would violate safety boundaries by getting too close to the user.
- **Task Planning:** Including only Task Planning task. We redefine this task by incorporating the user's variable states (*e.g.*, position and pose) into task planning to ensure collision avoidance during execution. We evaluate the MLLM's capability to decompose user instructions into a sequence of logically coherent, high-level, and safe executable steps.

To facilitate automated evaluation, the data for visual grounding and task planning are formulated as open-ended questions, while task safety and boundary safety judgment are presented as binary judgment tasks. Object Color, Object Shape, Object Material, Object Function, Spatial Relationship and Intent Inference are all formulated as multiple-choice questions.

B. Benchmark Construction

We present the detailed construction pipeline in Figure 3. We first curate images from real-world dataset, filtering test samples under a strict scene-level split to prevent data overlap. Then we leverage Gemini-3-flash to generate task metadata and answers. To mitigate potential biases introduced by MLLM annotation, final test queries are constructed using standardized templates populated with the extracted metadata. Finally, the entire dataset undergoes rigorous manual verification to guarantee benchmark accuracy and reliability.

a) Data Collection: The image resources for ERIBench are curated from two real-world Embodied Reference Interaction (ERI) datasets: YouRefIt [12] and Refer360 [15]. To establish a high-quality evaluation benchmark, we implemented a rigorous filtering pipeline to exclude blurred frames, non-robot-centric perspectives (*e.g.*, proximal selfies), and redundant images with high scene similarity. From the initially filtered pool of 2,851 images, we further selected 573 high-quality samples to serve as the test set. The selection criteria strictly adhere to the practical requirements of embodied intelligence: ensuring salient visibility of both the user and the target object, while adopting an eye-level orientation that mimics a robot's perspective. Furthermore, we ensured strict scene-level split, guaranteeing no overlap between the test set and the remaining images in physical environments. The average resolution of all images is 1800×1200.

b) Data Annotation: We use Gemini-3-flash-preview to generate data for the 10 distinct task categories mentioned above for each image. For each task, specialized prompts are utilized to concurrently generate questions, relevant metadata, and answers, ensuring at least one Q&A pair per task per scene. To ensure evaluation fairness and mitigate question bias, we do not use the question generated by Gemini 3 as the test data. Instead, we extract key information from metadata and populate pre-designed, standardized templates to construct the final test data. Regarding ground-truth labels, Visual Grounding task utilizes the original bounding boxes from the source dataset, while the remaining tasks rely on answers generated by Gemini 3. To ensure data quality and difficulty, we explicitly defined the distractors logic within the data construction prompts for some multiple-choice tasks.

This approach enhances the interference of the options, preventing incorrect choices from being easily eliminated. For instance, in the task "What color is the cup I am pointing at?", distractors are designed to include colors of other cups in the image, common cup colors, or the colors of nearby objects. Finally, we performed rigorous manual review and refinement of the template-based test data, ultimately building ERIBench.

c) Human Check and Refinement: All 6,535 test question-answer pairs are manually reviewed and refined by three annotators against the images and user instructions. For




Fig. 3. **Dataset Construction Pipeline.** The prompt and metadata depicted here are synthesized summaries of the content structures across the 10 tasks and are intended for illustrative purposes; they do not represent the actual full-length instances used in the study. The template shown is a representative example from the intent inference task.




Fig. 4. Sample statistics of various evaluation dimensions and tasks in ERIBench.

tasks with determinate correct answers, they verify answer correctness and correct erroneous answers or inappropriate distractors. Disagreements are resolved by majority vote. For Task Planning, each annotator proposes revisions to the candidate reference plan based on task completeness, logical coherence of the steps, and user safety, and the final reference answer is determined through discussion among all three annotators.


d) Evaluation Metric: For visual grounding questions, we adopt the widely-used Accuracy@0.5 metric, which represents the proportion of samples where the Intersection over Union (IoU) between the ground-truth and predicted bounding box exceeds 0.5. For multiple-choice and binary judgment questions, we calculate the Accuracy by matching the MLLM's predictions directly with the ground-truth labels. To evaluate Task Planning, which is an open-ended generation task, we employ the MLLM-as-a-Judge paradigm. To ensure evaluation fairness and mitigate potential self-bias, we utilize Doubao-seed-1.8 [47] as an independent scoring model, as it is not included in the ERIBench evaluation pool. The judge model assesses the quality of candidate responses based on expert-refined reference answers, evaluating task completion, logic, and safety.

C. Dataset Statistics

The detailed distribution and data statistics for subtasks across different dimensions is shown in Figure 4. ERIBench consists of 573 high-quality images and 6,535 unique questions, covering 5 primary dimensions and 10 subtasks to ensure a comprehensive and challenging evaluation for MLLMs. Regarding the diversity of evaluation scenarios, as shown in Figure 5a, ERIBench covers 12 different indoor scenarios with varying conditions (*e.g.*, lighting, tidiness, *etc.*) and 221 unique interactive objects. Each major scenario category includes a modifier to highlight detailed diversity. Figures 5b and 5c display word clouds for manipulation objects and task actions. For Spatial Relationship tasks (Figure 5d), ERIBench provides questions in 10 directions with a balanced distribution. Regarding task and boundary safety, ERIBench offers questions with safe/unsafe answers in a balanced manner, as shown in Figure 5e.

D. Discussion


a) Fairness of questions: Many existing benchmarks evaluate closed-source MLLMs on data constructed by those models themselves. The fairness of this paradigm is concerning, as model may construct questions that are easier for itself




(a) ERIBench scenarios statistics




(b) Object label word cloud



(c) Task action word cloud



(d) Spatial Relationship direction distribution



(e) Safe and Unsafe statistics

Fig. 5. ERIBench Data Statistics

to answer, thus introducing implicit bias. To mitigate this bias, ERIBench avoids directly generating questions. Instead, we generate question metadata and employ a template-filling strategy to construct test question. We analyze the fairness of this construction method in detail in Section IV-E.

b) Plausibility of options: When constructing data for the four multiple-choice tasks, *i.e.*, Object Color, Shape, Material, and Function, we incorporated a prioritized distractor logic into generation prompts. Specifically, we implement a hierarchical strategy: distractors primarily source from the attributes of other objects within same label in the image, followed by common-sense attributes associated with that label, and finally from the attributes of surrounding objects. This setup ensures that all options are highly relevant to the target, thereby preventing trivial elimination of incorrect options. Furthermore, these three distractors represent the potential absence of gesture, visual, and language modalities, respectively, thus testing the complex multimodal alignment capabilities of MLLMs.

IV. Experiments and Analysis

In this section, we systematically evaluate 14 state-of-the-art (SOTA) models on ERIBench. We detail the experiment setup in Section IV-A and report evaluation results in Section IV-B. We further provide an in-depth analysis of strategies to enhance MLLMs performance on three challenging ERI tasks in Section IV-C. Finally we analyze human-MLLM evaluation agreement and errors statistics in Task Planning in Section IV-D and assess the fairness of our benchmark construction in Section IV-E.

A. Experiment Setups

We evaluate 7 open-source general models: Qwen3-VL (2B, 30B-A3B, 32B) [5], LLaVA-OneVision-1.5 (4B, 8B) [4], and InternVL3.5 (1B, 14B) [37], 2 open-source embodied models: RynnBrain-8B [48], RoboBrain2.5-4B [49] and 5 closed-source models: Qwen3-VL-flash, Qwen3-VL-plus [5], GPT-5.1 [6], Claude-sonnet-4.5 [50], and Gemini-3-flash-preview [7]. To ensure rigorous and standardized evaluation, we employed a unified prompt template to organize image inputs and textual queries. For multiple-choice questions, an explicit instruction is appended to the prompt, requiring the models to provide the correct option in structured JSON format. All inference experiments are conducted using greedy decoding and temperature set to 0 to ensure deterministic results and reproducibility. After obtaining the MLLM outputs, for visual grounding, multiple-choice and true or false safety tasks, we employ regular expressions to extract the predicted answers, which are then compared against the ground truth to calculate accuracy. For the Task Planning, we utilize Doubao-seed-1.8 to score the outputs *w.r.t* the benchmark answers on a scale of 0 to 10.

B. Benchmark Results

Table II presents the evaluation results of all models on ERIBench. Gemini-3-flash-preview achieves the highest performance in Visual Perception, Visual Reasoning, and Intent Inference, whereas GPT-5.1 excels in Safety and Task

TABLE II

EVALUATION RESULTS ON ERIBENCH. THE EVALUATION RESULTS FOR THE **VISUAL GROUNDING** TASK FOR GPT-5.1, CLAUDE-SONNET-4.5, AND LLAVA ARE NOT PROVIDED DUE TO THEIR INABILITY TO GENERATE VALID COORDINATE RESULTS (THEIR OFFICIAL DOCUMENTATION DOES NOT PROVIDE A COORDINATE FORMAT THAT PRODUCES USABLE RESULTS FOR THESE MODELS).

Model	Visual Perception				Visual Reasoning		Intent Inference	Safety		Task Planning
	Visual Grounding	Object Color	Object Shape	Object Material	Object Function	Spatial Relationship	Intent Inference	Task Safety	Boundary Safety	Task Planning
Closed-Source MLLMs										
Gemini-3-flash-preview	**72.8**	**82.4**	**95.5**	**92.7**	92.1	**43.4**	**93.4**	87.9	58.3	6.7
Claude-sonnet-4.5	-	67.9	89.7	84.6	89.2	26.6	92.8	86.9	54.3	6.7
GPT-5.1	-	77.1	91.6	88.8	90.9	18.7	91.6	**90.0**	**61.4**	**9.0**
Qwen3-VL-plus	68.4	78.0	90.9	88.7	91.6	31.0	90.1	89.5	60.4	7.9
Qwen3-VL-flash	66.8	78.4	88.7	89.2	90.6	27.6	84.3	85.9	54.3	6.7
Open-Source general MLLMs										
InternVL3.5-14B	42.4	70.9	83.2	84.1	88.5	22.8	83.6	84.3	54.1	5.7
InternVL3.5-1B	25.1	56.2	67.5	66.7	82.2	15.9	59.5	45.6	48.9	1.9
LLaVA-1.5-8B-Ins	-	51.5	84.6	78.2	87.3	16.4	86.2	82.8	49.7	4.8
LLaVA-1.5-4B-Ins	-	52.9	80.1	76.1	87.1	13.8	81.7	76.5	46.4	3.8
Qwen3-VL-32B-Ins	66.3	77.7	90.8	88.5	**92.3**	29.5	89.4	81.9	56.9	6.8
Qwen3-VL-30B-A3B-Ins	67.0	75.7	87.6	88.5	89.9	28.0	86.6	87.3	53.8	6.1
Qwen3-VL-2B-Ins	55.2	71.2	79.6	77.1	87.4	20.5	71.9	63.3	48.2	2.4
Open-Source embodied MLLMs										
RynnBrain-8B	58.8	74.3	88.3	84.3	90.9	10.0	81.0	65.5	52.7	1.8
RoboBrain2.5-4B	60.9	71.7	85.9	82.2	90.4	26.0	84.6	65.4	52.2	3.0

Planning. Although closed-source models outperform open-source models across all five dimensions, the margin is generally marginal, with performance gaps typically remaining below 10%. A pronounced disparity (exceeding 30%) is observed only in Spatial Relationship reasoning and Task Planning. Embodied models marginally outperform similarly sized general MLLMs in visual understanding and reasoning tasks. However, they fall short of general MLLMs in intent, safety judgment, and comprehensive task planning. Notably, RynnBrain-8B achieves a very low score in task planning due to its reasoning paradigm, which is restricted to outputting only the next-step action. Evaluation results further indicate substantial variance both across different dimensions and among specific tasks within the same dimension. While accuracy in foundational perception and reasoning is relatively high, persistent bottlenecks remain in spatial and distance-based reasoning, as well as safety distance judgment.

In the Visual Perception dimension, MLLMs demonstrate high accuracy in identifying the attributes of referred objects (*e.g.*, color, shape, and material), yet struggle with precise spatial localization. Unlike conventional visual grounding tasks, the ERI scenario necessitates a more complex multimodal alignment between linguistic instructions, pointing gestures, and visual targets. The evaluation results indicate that existing MLLMs have limitations in complex multimodal alignment.

In the Visual Reasoning dimension, MLLMs demonstrate a robust capacity for accurately inferring the functional properties of referred targets by integrating common-sense knowledge with contextual cues. Conversely, their performance declines significantly in Spatial Relationship tasks that require rigorous spatial reasoning. Even the most advanced proprietary model Gemini-3-flash achieves only 43.4% accuracy.

In the Intent Inference dimension, MLLMs exhibit outstanding performance. Specifically, the leading proprietary model, Gemini-3-flash-preview, and the state-of-the-art open-source model, Qwen3-VL-32B-Ins, achieve accuracies of 93.4% and 89.4%, respectively. These results demonstrate that in ERI contexts, MLLMs can leverage their sophisticated comprehension and reasoning capabilities to decode human intentions and infer actionable tasks for embodied agents with a high degree of reliability.

In the safety dimension, MLLMs demonstrate proficiency in assessing task-level safety by leveraging the visual scenes and the semantic of instructions. However, they struggle significantly with distance-aware safety judgment, which necessitates an analysis of spatial distance factors. While the performance gap between models is minimal in this task, the overall accuracy remains generally low.

In the Task Planning dimension, MLLMs performance exhibits a pronounced scaling effect: while large-scale closed-source models demonstrate robust planning capabilities, small-scale open-source models struggle significantly. The latter frequently exhibit critical failures, such as omitting key execution steps, failing to complete assigned tasks, and violating safety distance requirements.

C. Analysis on Challenging ERI Tasks

In this section, we analyze the causes of the performance bottlenecks in current MLLMs across three challenging ERI tasks: Visual Grounding, Spatial Relationship, and Safety Boundary, and explore potential improvements through fine-tuning. From the 2,851 high-quality images filtered in Section III-B, we utilized 2,278 images for fine-tuning after excluding the 573 images reserved for the test set (ensuring zero overlap). Following our established data construction pipeline, we leveraged Gemini-3-flash-preview to generate the Supervised Fine-Tuning (SFT) and Group Relative Policy

TABLE III
POINTING GESTURE RECOGNITION ACCURACY ON THE FULL TEST SET AND THE FAILED GROUNDING SUBSET.

Model	Pointing Gesture Recognition Acc.	
	Full Set	FG Subset
Qwen3-VL-32B-Ins	95.8	97.9
Qwen3-VL-2B-Ins	93.9	94.9

TABLE IV
EVALUATION RESULTS ON THE ERI VISUAL GROUNDING TASK AFTER FINE-TUNING.


Model	Visual Grounding Acc@0.5
Closed-Source MLLMs	
Qwen3-VL-plus	68.4
Qwen3-VL-flash	66.8
Open-Source MLLMs	
Qwen3-VL-32B-Ins	66.3
+SFT	71.4(+5.1)
+GRPO	68.9(+2.6)
Qwen3-VL-2B-Ins	55.2
+SFT	68.6(+13.4)
+GRPO	68.2(+13.0)

Optimization (GRPO) [51] data. Detailed results are presented in the following subsections.

1) Can MLLMs Comprehend Pointing Gestures?: While existing MLLMs have achieved remarkable performance on existing visual grounding benchmarks, they struggle in ERI contexts. We hypothesize two primary reasons for this discrepancy: (1) MLLMs may fail to comprehend the visual cues of pointing gestures, and (2) the scarcity of large-scale ERI-specific data prevents MLLMs from effectively aligning gestures with linguistic and visual inputs.

We first investigate whether MLLMs can comprehend user pointing gestures through an observational experiment. We employ a straightforward methodology: images are presented to the MLLM with the prompt, "What is the person in the picture doing?" We then perform keyword matching on the model's outputs to identify terms semantically associated with pointing (*e.g.*, "pointing", "hand reaching", or "hand extended toward"). Table III presents the accuracy of MLLMs in interpreting these gestures across both the entire dataset and the subset of samples where visual grounding localization failed. The results indicate that MLLMs are generally capable of perceiving and understanding the visual information of pointing gestures.

We further investigate whether fine-tuning on ERI-specific data can enhance the grounding capabilities of MLLMs. The training set consists of 2,278 samples, with a one-to-one mapping between images and samples. We conduct SFT and GRPO with SFT cold start on Qwen3-VL. The evaluation results on the ERI Visual Grounding task after fine-tuning are presented in Table IV. Our analysis yields two primary insights: (1) Fine-tuning on the limited ERI dataset leads to substantial improvements for smaller MLLMs, whereas larger models encounter performance bottleneck. Nevertheless, both scales achieve performance comparable to or even exceeding that of closed-source models. (2) The GRPO training paradigm



(a) Qwen3-VL-2B-Instruct (b) Gemini-3-flash-preview

Fig. 6. Examples of confusion matrices for Spatial Relationship.

TABLE V
COMPARISON OF EVALUATION RESULTS ON THE SPATIAL RELATIONSHIP TASK AFTER DIRECT INTEGRATION OF DEPTH MAPS.

Model	Spatial Relationship Acc.	
	w/o depth map	w depth map
Closed-Source MLLMs		
Gemini-3-flash-preview	43.4	43.9(+0.5)
GPT-5.1	18.7	20.4(+1.7)
Qwen3-VL-plus	31.0	29.1(-1.9)
Open-Source MLLMs		
InternVL3.5-14B	22.8	22.5(-0.3)
LLaVA-1.5-8B-Ins	16.4	9.0(-7.4)
Qwen3-VL-32B-Ins	29.5	25.8(-3.7)

performs less effective on the ERI Visual Grounding task, with performance gains trailing behind those achieved through SFT.

2) Error Analysis of Spatial Relationship Reasoning: We employ confusion matrices to scrutinize the performance falters significantly of MLLMs in Spatial Relationship reasoning. Our observations reveal that these failures are not stochastically distributed. Instead, as shown in the representative examples in Figure 6, they are predominantly concentrated between compound and primary directions (*e.g.*, confusing "Left" with "Front-Left"). Notably, this challenge persists even for the most advanced models, such as Gemini-3-flash-preview. We hypothesize that this stems from the inherent difficulty MLLMs face in extracting precise depth information from 2D visual representations. Consequently, we utilized Depth-Anything-3 [52] to generate depth maps for ERI scenarios, which were then provided along with the original images as input. However, experiment results in Table V indicate that the direct integration of depth maps does not effectively bolster performance and, in most cases, is even detrimental to overall accuracy.

SpatialVLM [53] achieves robust spatial reasoning capabilities by leveraging massive data scaling. Inspired by this, we construct a training set comprising 10,811 samples from 2,278 images, with each image associated with at most 5 questions and ensure a balanced answer distribution. We then conduct SFT on Qwen3-VL. The evaluation results on the Spatial Relationship task after SFT are presented in Table VI. Our evaluation results demonstrate that training on specialized datasets significantly improves the spatial relationship reasoning capabilities of MLLMs.

TABLE VI
EVALUATION RESULTS ON THE SPATIAL RELATIONSHIP TASK AFTER SFT.

Model	Spatial Relationship Acc.
Closed-Source MLLMs	
Gemini-3-flash-preview	43.4
Claude-sonnet-4.5	26.6
GPT-5.1	18.7
Qwen3-VL-plus	31.0
Qwen3-VL-flash	27.6
Open-Source MLLMs	
Qwen3-VL-32B-Ins	29.5
+SFT	69.4(+39.9)
Qwen3-VL-2B-Ins	20.5
+SFT	66.3(+45.8)

TABLE VII
COMPARISON OF MODEL PERFORMANCE ON THE SAFETY BOUNDARY TASK POST-SFT AND POST-GRPO.

Model	Safety Boundary Acc.
Closed-Source MLLMs	
Gemini-3-flash-preview	58.3
Claude-sonnet-4.5	54.3
GPT-5.1	61.4
Qwen3-VL-plus	60.4
Qwen3-VL-flash	54.3
Open-Source MLLMs	
Qwen3-VL-32B-Ins	56.9
+SFT	62.3(+5.4)
+GRPO	73.6(+16.7)
Qwen3-VL-2B-Ins	48.2
+SFT	57.6(+9.4)
+GRPO	71.4(+23.2)

3) RL effectively enhances the Boundary Safety capabilities of MLLMs.: Safety Boundary necessitates sophisticated spatial-distance reasoning and requires a synergy of understanding and planning. Consequently, we hypothesize that Reinforcement Learning (RL) is more efficacious for enhancing safety boundary capabilities. We construct a training set comprising 4,556 samples from 2,278 images, with each image associated with 2 questions and ensure a balanced answer distribution. We conduct SFT and GRPO with SFT cold start on Qwen3-VL. The evaluation results on the Safety Boundary task after fine-tuning are presented in Table VII. Our results demonstrate that GRPO is significantly more effective than SFT in bolstering the safety boundary capabilities of MLLMs.

D. Human-MLLM evaluation agreement and errors statistics for Task Planning

We sample 100 instances and manually score the Task Planning responses generated by each of the five models—GPT-5.1, Gemini-3-flash, Qwen3-VL-32B-Ins, LLaVA-OV1.5-8B-Ins, and InternVL3.5-1B—yielding 500 evaluated responses in total. Each response is scored by three annotators, and the mean of their scores is used as the human score. The Pearson correlation between human and MLLM scores across all responses is 0.929, indicating a high level of consistency, and supporting our MLLM-as-judge paradigm is a reliable alternative to human evaluation. Table VIII reports the error distributions of GPT-5.1 and InternVL3.5-1B, the highest and lowest scoring general models, respectively. GPT-5.1 primarily struggles with safety and logic, while InternVL3.5-1B suffers from severe logical flaws, missing steps, and safety violations (over 50%). These results highlight the need to improve logical coherence and user safety awareness in MLLM-generated plans for ERI human–robot collaboration.

TABLE VIII
TASK PLANNING ERROR RATES.

Model	Logic Error	Missing Steps	Safety Issue	Task Incomplete	Role Confusion	Object Error
GPT-5.1	14%	7%	17%	5%	0%	2%
InternVL3.5-1B	85%	85%	60%	46%	18%	9%

TABLE IX
COMPARISON OF EVALUATION RESULTS USING DIFFERENT MODEL ANNOTATIONS. THE ABBREVIATIONS ARE: G (GEMINI-3-FLASH-PREVIEW ANNOTATION), Q (QWEN3-VL-PLUS ANNOTATION).

Model	Object Color		Intent Inference	
	G	Q	G	Q
Closed-Source MLLMs				
Gemini-3-flash-preview	82.4	82.4	93.4	95.6
Claude-sonnet-4.5	67.9	70.0	92.8	93.7
GPT-5.1	77.1	77.1	91.6	92.5
Qwen3-VL-plus	78.0	79.9	90.1	90.9
Qwen3-VL-flash	78.4	78.9	84.3	87.3
Open-Source General MLLMs				
InternVL3.5-14B	70.9	73.5	83.6	87.3
InternVL3.5-1B	56.2	59.5	59.5	63.9
LLaVA-1.5-8B-Ins	51.5	55.7	86.2	86.6
LLaVA-1.5-4B-Ins	52.9	51.3	81.7	85.2
Qwen3-VL-32B-Ins	77.7	77.8	89.4	91.4
Qwen3-VL-30B-A3B-Ins	75.7	77.3	86.6	88.8
Qwen3-VL-2B-Ins	71.2	72.8	71.9	77.8

E. Fairness of ERIBench Construction

To investigate whether the questions generated by Gemini-3-flash-preview introduce a self-preference bias, where the model might find its own questions easier to answer, thus compromising the fairness of our benchmark. To solve this issue, following the same data curation pipeline as above, we used Qwen3-vl-plus as the generator and reconstructed the Object Color and Intent Inference data. As shown in Table IX, the evaluation results of the 12 general MLLMs demonstrate that our benchmark construction paradigm is insensitive to annotator-model selection. It shows that the same method yields very marginal score differences on a given task annotated by different models, proving that using different models for annotation has a minimal impact on the benchmark.

V. CONCLUSION

In this paper, we introduce ERIBench, a comprehensive benchmark designed to systematically evaluate the performance of Multimodal Large Language Models (MLLMs) in Embodied Reference Interaction (ERI) scenarios. ERIBench establishes an evaluation framework across five dimensions, *i.e.*, Visual Perception, Visual Reasoning, Intent Inference, Safety, and Task Planning, comprising 10 distinct tasks and 6,535 Q&A pairs. This framework provides an end-to-end coverage of the interaction pipeline in ERI scenarios. Our extensive evaluation of 14 state-of-the-art MLLMs reveals that

existing models exhibit robust capabilities in attribute understanding, user intent inference, and task safety assessment. However, in the dimension of task planning, performance demonstrates a pronounced scaling effect: while closed-source models display superior proficiency, smaller-scale open-source models struggle significantly. Furthermore, our evaluation results indicate that even top-tier models such as Gemini-3-flash, GPT-5.1, and Qwen3-VL exhibit significant performance bottlenecks, particularly in complex multimodal reference grounding, spatial reasoning, and distance-based safety judgment. While targeted Supervised Fine-Tuning (SFT) and Reinforcement Learning (RL) yield certain improvements, they have yet to reach satisfactory levels for reliable deployment. We believe ERIBench serves as a key evaluation benchmark for the community, propelling MLLMs toward more reliable and safe human-robot collaboration. Future work will focus on scaling data for complex multimodal reference grounding, spatial reasoning, and distance-based safety judgment, and extending the benchmark to encompass dynamic video-based interactions and real-world robotic deployments.

REFERENCES

[1] Z. Durante, Q. Huang, N. Wake, R. Gong, J. S. Park, B. Sarkar, R. Taori, Y. Noda, D. Terzopoulos, Y. Choi *et al.*, "Agent ai: Surveying the horizons of multimodal interaction," *arXiv preprint arXiv:2401.03568*, 2024.

[2] F. Sun, R. Chen, T. Ji, Y. Luo, H. Zhou, and H. Liu, "A comprehensive survey on embodied intelligence: Advancements, challenges, and future perspectives," *CAAI Artificial Intelligence Research*, vol. 3, no. 9150042, p. 1, 2024.

[3] Z. Wu, X. Chen, Z. Pan, X. Liu, W. Liu, D. Dai, H. Gao, Y. Ma, C. Wu, B. Wang *et al.*, "Deepseek-vl2: Mixture-of-experts vision-language models for advanced multimodal understanding," *arXiv preprint arXiv:2412.10302*, 2024.

[4] X. An, Y. Xie, K. Yang, W. Zhang, X. Zhao, Z. Cheng, Y. Wang, S. Xu, C. Chen, D. Zhu *et al.*, "Llava-onevision-1.5: Fully open framework for democratized multimodal training," *arXiv preprint arXiv:2509.23661*, 2025.

[5] S. Bai, Y. Cai, R. Chen, K. Chen, X. Chen, Z. Cheng, L. Deng, W. Ding, C. Gao, C. Ge *et al.*, "Qwen3-vl technical report," *arXiv preprint arXiv:2511.21631*, 2025.

[6] A. Singh, A. Fry, A. Perelman, A. Tart, A. Ganesh, A. El-Kishky, A. McLaughlin, A. Low, A. Ostrow, A. Ananthram *et al.*, "Openai gpt-5 system card," *arXiv preprint arXiv:2601.03267*, 2025.

[7] Google DeepMind, "Gemini 3 pro technical report," https://deepmind.google/models/gemini/pro/, 2025.

[8] W. Huang, C. Wang, R. Zhang, Y. Li, J. Wu, and L. Fei-Fei, "Voxposer: Composable 3d value maps for robotic manipulation with language models," in *Conference on Robot Learning*. PMLR, 2023, pp. 540–562.

[9] D. Driess, F. Xia, M. S. Sajjadi, C. Lynch, A. Chowdhery, B. Ichter, A. Wahid, J. Tompson, Q. Vuong, T. Yu *et al.*, "Palm-e: an embodied multimodal language model," in *Proceedings of the 40th International Conference on Machine Learning*, 2023, pp. 8469–8488.

[10] S. Chen, Z. Wu, K. Zhang, C. Li, B. Zhang, F. Ma, F. R. Yu, and Q. Li, "Exploring embodied multimodal large models: Development, datasets, and future directions," *Information Fusion*, vol. 122, p. 103198, 2025.

[11] Y. Liu, W. Chen, Y. Bai, X. Liang, G. Li, W. Gao, and L. Lin, "Aligning cyber space with physical world: A comprehensive survey on embodied ai," *IEEE/ASME Transactions on Mechatronics*, 2025.

[12] Y. Chen, Q. Li, D. Kong, Y. L. Kei, S.-C. Zhu, T. Gao, Y. Zhu, and S. Huang, "Yourefit: Embodied reference understanding with language and gesture," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021, pp. 1385–1395.

[13] M. M. Islam, A. Gladstone, R. Islam, and T. Iqbal, "Eqa-mx: Embodied question answering using multimodal expression," in *The Twelfth International Conference on Learning Representations*, 2024.

[14] H. Guo, J. Zhu, W. Fan, C. Yi, and F. Jiang, "Beyond object categories: Multi-attribute reference understanding for visual grounding," *arXiv preprint arXiv:2503.19240*, 2025.

[15] M. M. Islam, A. Gladstone, S. Sarker, G. Nanduru, M. Fahim, K. Du, A. Chadha, and T. Iqbal, "Embodied referring expression comprehension in human-robot interaction," *arXiv preprint arXiv:2512.06558*, 2025.

[16] X. Liu, T. Zhang, Y. Gu, I. L. Iong, S. XiXuan, Y. Xu, S. Zhang, H. Lai, J. Sun, X. Yang *et al.*, "Visualagentbench: Towards large multimodal models as visual foundation agents," in *The Thirteenth International Conference on Learning Representations*, 2025.

[17] M. Li, S. Zhao, Q. Wang, K. Wang, Y. Zhou, S. Srivastava, C. Gokmen, T. Lee, E. L. Li, R. Zhang *et al.*, "Embodied agent interface: Benchmarking llms for embodied decision making," *Advances in Neural Information Processing Systems*, vol. 37, pp. 100 428–100 534, 2024.

[18] R. Yang, H. Chen, J. Zhang, M. Zhao, C. Qian, K. Wang, Q. Wang, T. V. Koripella, M. Movahedi, M. Li *et al.*, "Embodiedbench: Comprehensive benchmarking multi-modal large language models for vision-driven embodied agents," in *International Conference on Machine Learning*. PMLR, 2025, pp. 70 576–70 631.

[19] J. Li, Y. Zhu, Z. Xu, J. Gu, M. Zhu, X. Liu, N. Liu, Y. Peng, F. Feng, and J. Tang, "Mmro: Are multimodal llms eligible as the brain for in-home robotics?" *arXiv preprint arXiv:2406.19693*, 2024.

[20] Y. Luo, C.-K. Fan, M. Dong, J. Shi, M. Zhao, B.-W. Zhang, C. Chi, J. Liu, G. Dai, R. Zhang *et al.*, "Robobench: A comprehensive evaluation benchmark for multimodal large language models as embodied brain," *arXiv preprint arXiv:2510.17801*, 2025.

[21] Z. Cheng, Y. Tu, R. Li, S. Dai, J. Hu, S. Hu, J. Li, Y. Shi, T. Yu, W. Chen *et al.*, "Embodiedeval: Evaluate multimodal llms as embodied agents," *arXiv preprint arXiv:2501.11858*, 2025.

[22] N. Kotani and A. Kanezaki, "Point anywhere: Directed object estimation from omnidirectional images," in *ACM SIGGRAPH 2023 Posters*, 2023, pp. 1–2.

[23] Y. Li, X. Chen, H. Zhao, J. Gong, G. Zhou, F. Rossano, and Y. Zhu, "Understanding embodied reference with touch-line transformer," in *The Eleventh International Conference on Learning Representations*, 2023.

[24] H. Guo, W. Fan, B. Wei, J. Zhu, J. Tian, C. Yi, and F. Jiang, "Addino: Attention-dynamic dino for distance-aware embodied reference understanding," *IEEE Transactions on Circuits and Systems for Video Technology*, 2025.

[25] F. I. Eyiokur, D. Yaman, H. K. Ekenel, and A. Waibel, "A multimodal depth-aware method for embodied reference understanding," *arXiv preprint arXiv:2510.08278*, 2025.

[26] F. I. Eyiokur, D. Yaman, H. K. Ekenel, and A. Waibel, "Cape: A clip-aware pointing ensemble of complementary heatmap cues for embodied reference understanding," in *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 2026, pp. 3939–3950.

[27] S. Constantin, F. I. Eyiokur, D. Yaman, L. Bärmann, and A. Waibel, "Interactive multimodal robot dialog using pointing gesture recognition," in *European conference on computer vision*. Springer, 2022, pp. 640–657.

[28] A. Oyama, S. Hasegawa, Y. Hagiwara, A. Taniguchi, and T. Taniguchi, "Ecrap: Exophora resolution and classifying user commands for robot action planning by large language models," in *2024 Eighth IEEE International Conference on Robotic Computing (IRC)*. IEEE, 2024, pp. 1–8.

[29] Y. Lai, S. Yuan, Y. Nassar, M. Fan, A. Gopal, A. Yorita, N. Kubota, and M. Rätsch, "Natural multimodal fusion-based human–robot interaction: Application with voice and deictic posture via large language model," *IEEE robotics & automation magazine*, 2025.

[30] H. Liu, C. Li, Q. Wu, and Y. J. Lee, "Visual instruction tuning," *Advances in Neural Information Processing Systems*, vol. 36, pp. 34 892–34 916, 2023.

[31] D. Zhu, J. Chen, X. Shen, X. Li, and M. Elhoseiny, "Minigpt-4: Enhancing vision-language understanding with advanced large language models," in *The Twelfth International Conference on Learning Representations*, 2024.

[32] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar *et al.*, "Llama: Open and efficient foundation language models," *arXiv preprint arXiv:2302.13971*, 2023.

[33] A. Yang, A. Li, B. Yang, B. Zhang, B. Hui, B. Zheng, B. Yu, C. Gao, C. Huang, C. Lv *et al.*, "Qwen3 technical report," *arXiv preprint arXiv:2505.09388*, 2025.

[34] D. Guo, D. Yang, H. Zhang, J. Song, P. Wang, Q. Zhu, R. Xu, R. Zhang, S. Ma, X. Bi *et al.*, "Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning," *arXiv preprint arXiv:2501.12948*, 2025.

[35] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark *et al.*, "Learning transferable visual models from natural language supervision," in *International conference on machine learning*. PmLR, 2021, pp. 8748–8763.

[36] A. Dosovitskiy, L. Beyer, A. Kolesnikov, D. Weissenborn, X. Zhai, T. Unterthiner, M. Dehghani, M. Minderer, G. Heigold, S. Gelly *et al.*, "An image is worth 16x16 words: Transformers for image recognition at scale," in *The ninth International Conference on Learning Representations*, 2021.

[37] W. Wang, Z. Gao, L. Gu, H. Pu, L. Cui, X. Wei, Z. Liu, L. Jing, S. Ye, J. Shao *et al.*, "Internvl3. 5: Advancing open-source multimodal models in versatility, reasoning, and efficiency," *arXiv preprint arXiv:2508.18265*, 2025.

[38] B. Li, Y. Zhang, D. Guo, R. Zhang, F. Li, H. Zhang, K. Zhang, P. Zhang, Y. Li, Z. Liu *et al.*, "Llava-onevision: Easy visual task transfer," *Transactions on Machine Learning Research*, 2025.

[39] K. Black, N. Brown, D. Driess, A. Esmail, M. Equi, C. Finn, N. Fusai, L. Groom, K. Hausman, B. Ichter *et al.*, "π_0: A vision-language-action flow model for general robot control," *arXiv preprint arXiv:2410.24164*, 2024.

[40] M. J. Kim, K. Pertsch, S. Karamcheti, T. Xiao, A. Balakrishna, S. Nair, R. Rafailov, E. P. Foster, P. R. Sanketi, Q. Vuong *et al.*, "Openvla: An open-source vision-language-action model," in *Conference on Robot Learning*. PMLR, 2025, pp. 2679–2713.

[41] K. Black, N. Brown, J. Darpinian, K. Dhabalia, D. Driess, A. Esmail, M. R. Equi, C. Finn, N. Fusai, M. Y. Galliker *et al.*, "$\pi_{0.5}$: a vision-language-action model with open-world generalization," in *Conference on Robot Learning*. PMLR, 2025, pp. 17–40.

[42] W. Huang, C. Wang, Y. Li, R. Zhang, and L. Fei-Fei, "Rekep: Spatio-temporal reasoning of relational keypoint constraints for robotic manipulation," in *Conference on Robot Learning*. PMLR, 2025, pp. 4573–4602.

[43] A. Brohan, Y. Chebotar, C. Finn, K. Hausman, A. Herzog, D. Ho, J. Ibarz, A. Irpan, E. Jang, R. Julian *et al.*, "Do as i can, not as i say: Grounding language in robotic affordances," in *Conference on robot learning*. PMLR, 2023, pp. 287–318.

[44] K. Rana, J. Haviland, S. Garg, J. Abou-Chakra, I. Reid, and N. Suenderhauf, "Sayplan: Grounding large language models using 3d scene graphs for scalable robot task planning," in *Conference on Robot Learning*. PMLR, 2023, pp. 23–72.

[45] Y. Tang, W. Yu, J. Tan, H. Zen, A. Faust, and T. Harada, "Saytap: Language to quadrupedal locomotion," in *Conference on Robot Learning*. PMLR, 2023, pp. 3556–3570.

[46] Y. Ji, H. Tan, J. Shi, X. Hao, Y. Zhang, H. Zhang, P. Wang, M. Zhao, Y. Mu, P. An *et al.*, "Robobrain: A unified brain model for robotic manipulation from abstract to concrete," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2025, pp. 1724–1734.

[47] B. Seed, "Seed1. 8 model card: Towards generalized real-world agency," *arXiv preprint arXiv:2603.20633*, 2026.

[48] R. Dang, J. Guo, B. Hou, S. Leng, K. Li, X. Li, J. Liu, Y. Mao, Z. Wang, Y. Yuan *et al.*, "Rynnbrain: Open embodied foundation models," *arXiv preprint arXiv:2602.14979*, 2026.

[49] H. Tan, E. Zhou, Z. Li, Y. Xu, Y. Ji, X. Chen, C. Chi, P. Wang, H. Jia, Y. Ao *et al.*, "Robobrain 2.5: Depth in sight, time in mind," *arXiv preprint arXiv:2601.14352*, 2026.

[50] Anthropic, "System card: Claude sonnet 4.5," https://assets.anthropic.com/m/12f214efcc2f457a/original/ClaudeSonnet-4-5-System-Card.pdf, Tech. Rep., 2025.

[51] Z. Shao, P. Wang, Q. Zhu, R. Xu, J. Song, X. Bi, H. Zhang, M. Zhang, Y. Li, Y. Wu *et al.*, "Deepseekmath: Pushing the limits of mathematical reasoning in open language models," *arXiv preprint arXiv:2402.03300*, 2024.

[52] H. Lin, S. Chen, J. Liew, D. Y. Chen, Z. Li, G. Shi, J. Feng, and B. Kang, "Depth anything 3: Recovering the visual space from any views," in *The Fourteenth International Conference on Learning Representations*, 2026.

[53] B. Chen, Z. Xu, S. Kirmani, B. Ichter, D. Sadigh, L. Guibas, and F. Xia, "Spatialvlm: Endowing vision-language models with spatial reasoning capabilities," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024, pp. 14 455–14 465.