



OpenL Tablets Demo Project Guide

OpenL Tablets 5.12

OpenL Tablets BRMS

Document number: **TP_OpenL_Demo_2.4_LSh**
Revised: 01-18-2014



OpenL Tablets Documentation is licensed under a [Creative Commons Attribution 3.0 United States License](https://creativecommons.org/licenses/by/3.0/us/).

OpenL Tablets Demo Project

This section describes complete OpenL Tablets Demo package which contains configured and ready to demonstrate infrastructure for OpenL Tablets product. The Demo enables a user to develop business rules and manage business rules sets in OpenL Tablets WebStudio, and then execute these rules as Web Services ready to be used by user applications.

In order to make work with WebStudio more comfortable and quick to start, several projects are already loaded in user workspace. As a result, a user can work on projects already created from OpenL Tablets Templates or in case of necessity create their own projects via Repository in WebStudio. In addition to demonstrate usage of rules in applications, the user can also invoke rules of the preloaded project via Web Services Client application deployed in Demo package by default.

Demo package is a .zip file which the user can download from [OpenL Tablets website](#). After unzipping this file you will see that Demo package consists of web server Apache Tomcat (version 7.0.40) with 4 web applications which are located in `\apache-tomcat-7.0.40\webapps\` folder.

These applications are:

- webstudio.war
- webservice.war
- webservice-client.war
- production-repository-server.war

Note! As production-repository-server we use Jackrabbit Web Application version 2.4.4.

To start [OpenL Tablets Demo](#), locate `<unzipped Demo package folder>\apache-tomcat-7.0.40\bin\startup.bat` file and run it by double-click (or via console window commands).

It is actual for Windows. But there are some specifics of launching OpenL Tablets Demo under Linux. A working directory for OpenL Tablets Demo is located `<unzipped demo package folder>\apache-tomcat-7.0.40\bin\openl-demo\.` That is why after unzipping OpenL Tablets Demo zip file user should change access rights to this folder:

```
sudo chmod 775 -R /<unzipped demo package folder>
```

To get more information refer to section “Deploying OpenL Tablets WebStudio” of Installation Guide document.

After successful launching you can use the following links to the applications:

Demo application	Url
Webstudio	→ http://localhost:8080/webstudio
Webservice	→ http://localhost:8080/webservice
Webservice-client	→ http://localhost:8080/webservice-client

Note! After starting Demo, WebStudio installation wizard doesn't appear. WebStudio is preconfigured in single user mode. The user sees WebStudio welcome page at start.

The following sections provides more details on Demo Project work.

WebStudio in Demo Project

Note! WebStudio is preconfigured in single user mode. The user will be automatically signed in WebStudio and will see welcome page at start.

Rules Editor

Several Examples and Tutorials are already in Editing status, therefore available in Rules Editor by default. For information how to manage rules in Rules Editor, please refer to chapter [“Using Rules Editor” of WebStudio User Guide](#)).




Figure 1: Projects in Rules Editor available for editing

Repository Editor

For details how to manage projects in Repository, see chapter “Using Repository Editor” of WebStudio User Guide.

The user can work with projects loaded in Repository in Demo package as well as create a new projects on his own.

There is one “Example 3 - Auto Policy Calculation” project already deployed using Deploy configuration “Example 3 - Auto Policy Calculation” to use it via [Web Services](#) in [Web Services Client](#).

As WebStudio is preconfigured in single user mode, all projects in Repository are created/modified by 'DEFAULT' user.





















Projects					
Name	Revision	Status	Modified By	Modified At	Actions
Example 1 - Bank Rating	0	Editing	DEFAULT	10/10/2013	 
Example 2 - Corporate Rating	0	Editing	DEFAULT	10/10/2013	 
Example 3 - Auto Policy Calculation	2	Closed	DEFAULT	10/15/2013	 
Tutorial 1 - Introduction to Decision Tables	0	Editing	DEFAULT	10/10/2013	 
Tutorial 2 - Introduction to Data Tables	0	Editing	DEFAULT	10/10/2013	 
Tutorial 3 - More Advanced Decision and Data Tables	0	Editing	DEFAULT	10/10/2013	 
Tutorial 4 - Introduction to Column Match Tables	0	Editing	DEFAULT	10/10/2013	 
Tutorial 5 - Introduction to TBasic Tables	1	Closed	DEFAULT	10/10/2013	 
Tutorial 6 - Introduction to Spreadsheet Tables	1	Closed	DEFAULT	10/10/2013	 
Tutorial 7 - Introduction to Table Properties	1	Closed	DEFAULT	10/10/2013	 


Figure 1: The whole list of rules projects in Repository of Demo Project

Administration


By default User Workspace, History and Design Repository are configured as local and located in `openl-demo` folder of directory `<unzipped demo package folder>\apache-tomcat-7.0.40\bin\`. This setting is made in order to simplify configuration and usage of Demo package. It should be noted that the user can change default directory to another one (How to do it, read in [WebStudio User Guide "Managing system settings"](#)).

WebStudio

System Settings



Common



Repository

User Workspace

Workspace Directory:

History

History Directory:

Figure 3: Common system settings in Administration

Production Repository is set to use Remote – RMI connection. An appropriate URL (`//localhost:1099/production-repository`) is configured by default and defined in

WebStudio rules-production.properties file in folder <unzipped demo package folder>\apache-tomcat-7.0.40\webapps\webstudio\WEB-INF\conf\.

Design Repository	
Name:	Design
Type:	Local
Directory:	c:\openl-demo\design-repository
Secure connection	<input type="checkbox"/>

Production Repositories	
Name:	Production
Type:	Remote - RMI
URL:	//localhost:1099/production-repository

Figure 4: Settings of Design and Production repositories in Administration

Web Services in Demo Project

By default project from Template - “Example 3 – Auto Policy Calculation” is deployed to Production Repository.

In order to use this project as illustrative example of project deployments in [Web Services Client](#), several settings are defined in Rules Configuration of the project. It is set up that only *DriverRisk*, *DriverAgeType*, *AccidentPremium* (draw your attention that here are wildcards) rules are included and can be used from Web Services Client application.

Available SOAP services:	
VirtualModule\$RuntimeContextDecoratedPortType	Endpoint address: http://localhost:8080/webService/Example 3 - Auto Policy Calculation/Example 3 - Auto Policy Calculation
<ul style="list-style-type: none"> • DriverAgeType • AccidentPremium • DriverRiskScore • DriverRisk • DriverRiskPremium 	WSDL : {http://DefaultNamespace}VirtualModule\$RuntimeContextDecorated Target namespace: http://DefaultNamespace

Figure 5: Web Services main page and deployed project on it.

The demo doesn't restrict any deployments of other projects or has any other limitations so the user can deploy his own projects in Demo setup. If users deploys anything else the full list of deployed projects will appear on this page including the user's ones.

Web Services Client in Demo Package

Web Services Client application is an application specially created to demonstrate usage of OpenL Tablets rules via Web Services application. Web Services Client is very simple application and should be used just to check that rules are easily accessible from other applications via web services.

Note! This Client invokes only several methods of particular pre deployed project “Example 3 – Auto Policy Calculation”. It means that other projects deployed by the user can not be used from within Web Services Client application.

Web Services Client application allows the user to define driver type by his age and gender, get Premium per accident or determine how risky a driver is according to Business Rules specified in the project (“Example 3 - Auto Policy Calculation”).

The screenshot displays a web application interface for the Web Services Client. It is divided into two main sections. The top section, titled "Methods to call", lists three methods: "DriverAgeType" (Returns a type of driver by age and gender), "AccidentPremium" (Returns auto accident premium), and "DriverRisk" (Returns a type of driver risk by number of incidents). Each method has input fields for its parameters. For "DriverAgeType", the "Age" field is set to "20" and the "Gender" field is set to "Male". To the right of each method's input fields is an orange "Execute" button. A large red arrow originates from the "Execute" button for "DriverAgeType" and points down to the result section. The bottom section, titled "Result of calling DriverAgeType method", displays the result "Young Driver".

Methods to call	
DriverAgeType Returns a type of driver by age and gender	
Age	<input type="text" value="20"/>
Gender	<input type="text" value="Male"/>
AccidentPremium Returns auto accident premium	
DriverRisk Returns a type of driver risk by number of incidents	
DUI	<input type="text" value="0"/>
Accidents	<input type="text" value="0"/>
Moving Violations	<input type="text" value="0"/>

Result of calling DriverAgeType method

Young Driver

Figure 6: Executing DriverAgeType rule and getting result via Web Services Client.

The user can change the values of input parameters in fields and click the **Execute** button. The corresponding result will be displayed right below the list of rules to call.

OpenL Tablets Demo as common deployment pattern

The easiest way to get introduced how to use OpenL Tablets rules as Web Services in your application is to explore OpenL Tablets Demo package. This Demo configuration represents general usage scenario of OpenL Tablets product.

In short, common deployment scenario is:

- deploy Web Services application, WebStudio application and Rules Repository application (jackrabbit JCR) into web server;
- make proper configurations for JCR (jackrabbit settings), repository configurations in WebStudio and Web Services application (insure 'production' repository is configured the same way in both applications; see configurations in Demo);
- put preinitialized rules repository on your file system (jackrabbit repository according to settings for JCR);
- run web server (insure JCR application starts first).

Note! Preinitialized jackrabbit repository is required because jackrabbit cannot initialize repository in remote mode. As option, you can run WebStudio with jackrabbit configured as local and take fresh repository it creates.