

Assignment_02

November 13, 2023

1 Authors

- Raphael Wäspi (18-918-938)
- Nicolas Huber (16-936-205)

```
[1]: import math
      # Imports
      import numpy as np
      import matplotlib.pyplot as plt
      import networkx as nx
      import os
      import glob
      import re
      import random
      from statistics import mean

      import scipy.special
      from tqdm import tqdm
      import shutil
      from joblib import Parallel, delayed
      from scipy.special import factorial
      import powerlaw
```

```
[2]: # Define colors with reduced opacity from a colormap
      COLOR_BLUE = 'dodgerblue'
      COLOR_RED = 'lightcoral'
      COLOR_GREY = 'slategrey'
      COLOR_BLACK = 'black'
      COLOR_LIGHT_GRAY = 'lightgray'
      COLOR_DARK_GRAY = 'darkgray'

      # Define the main data directory
      OUTPUT_PATH = "./output"
```

```
[3]: # Prepare output folder

      # Delete the entire 'output' directory and its contents
      if os.path.exists(OUTPUT_PATH):
```

```

shutil.rmtree(OUTPUT_PATH)

# Create the 'output' directory
os.makedirs(OUTPUT_PATH)

# Define subdirectories
OUTPUT_PATH_ER = os.path.join(OUTPUT_PATH, "erdos_renyi_avg_clustering")
OUTPUT_PATH_WS = os.path.join(OUTPUT_PATH, "watts_strogatz_model")
OUTPUT_PATH_COMMUNITIES = os.path.join(OUTPUT_PATH, "communities")
OUTPUT_PATH_POWER_LAWS = os.path.join(OUTPUT_PATH, "power_laws")

# Recreate the subdirectories
os.makedirs(OUTPUT_PATH_ER)
os.makedirs(OUTPUT_PATH_WS)
os.makedirs(OUTPUT_PATH_COMMUNITIES)
os.makedirs(OUTPUT_PATH_POWER_LAWS)

```

```

[4]: # Define the directory containing the .gml files
directory = 'assignment_02_data'

# Use glob to get a list of all .gml files in the directory
gml_files = glob.glob(os.path.join(directory, '*.gml'))

# Init an empty dictionary for all graphs - the key is the actual name, and the
↳ value is the graph data
graphs = {}

# Use tqdm to show a progress bar in Jupyter Notebook
with tqdm(total=len(gml_files), desc="Loading GML Files") as pbar:
    # Loop through the list of .gml files and load them
    for file_path in gml_files:
        with open(file_path, 'r') as file:
            content = file.read()

            # Use regex to extract the desired part
            match = re.search(r'/(~/+).gml$', file_path)
            if match:
                graph_name = match.group(1)

                # Add to the graph dictionary
                graph = nx.read_gml(file_path)
                graphs[graph_name] = graph

                # Print the graph name when each part is finished
                print(f"Finished loading {graph_name}")

pbar.update(1) # Update the progress bar

```

```
Loading GML Files: 43%|          | 3/7 [00:07<00:07, 1.88s/it]
```

```
Finished loading graph_internet  
Finished loading graph_Korea  
Finished loading graph_eu_airlines  
Finished loading graph_macaque
```

```
Loading GML Files: 100%|         | 7/7 [00:35<00:00, 5.11s/it]
```

```
Finished loading graph_hep-th  
Finished loading graph_starwars  
Finished loading graph_madrid
```

2 I Erdos-Renyi Model

```
[5]: graphs
```

```
[5]: {'graph_internet': <networkx.classes.graph.Graph at 0x12275bfd0>,  
      'graph_Korea': <networkx.classes.graph.Graph at 0x1200d3710>,  
      'graph_eu_airlines': <networkx.classes.graph.Graph at 0x120457cd0>,  
      'graph_macaque': <networkx.classes.graph.Graph at 0x1201fcfd0>,  
      'graph_hep-th': <networkx.classes.graph.Graph at 0x12a5cbfd0>,  
      'graph_starwars': <networkx.classes.graph.Graph at 0x1220cbd50>,  
      'graph_madrid': <networkx.classes.graph.Graph at 0x1222d3d50>}
```

2.1 1. Write a function to generate an Erdős-Rényi undirected graph $G(N, p)$.

It should take in two input parameters: - N : the number of nodes of the network, - p : the probability of an edge existing between two nodes,

and it should output a network (the data structure to represent the network is left to your choice, in the hint a suggestion is provided).

```
[6]: random.seed(a=42)
```

```
[7]: def generate_custom_erdos_renyi_graph(N, p):  
      # Precondition  
      if p < 0 or p > 1:  
          raise ValueError("Probability p must be in the range [0, 1]")  
  
      # Create a graph object  
      G = nx.Graph()  
  
      # Init N nodes  
      G.add_nodes_from(range(N))  
  
      # Model: each pair of nodes is connected with edge creation probability
```

```

for i in range(N):
    for j in range(i + 1, N):
        # In total: N (N-1) * 0.5 possible links
        if random.random() < p: # Select node with probability p
            G.add_edge(i, j)

return G

```

2.2 2. Using the function you wrote at point (1), generate three Erdős-Rényi networks with $N = 100$ nodes and link probability

- (a) $p = 0.001$,
- (b) $p = 0.01$,
- (c) $p = 0.1$, and
- (d) $p = 0.5$.

Provide a visualisation of these networks, in order to emphasize the existence of connected components.

```

[8]: SEED = 42
     N = 100
     PROBABILITIES = [0.001, 0.01, 0.1, 0.5]

```

```

[9]: generated_networks = []

```


```

[10]: for p in PROBABILITIES:
        g = generate_custom_erdos_renyi_graph(N, p)
        generated_networks.append({"graph":g, "N": N, "p": p})
        pos = nx.spring_layout(G=g, seed=SEED) # Layout algorithm for node_
        ↪positions
        plt.figure(figsize=(12, 8))
        nx.draw(g, pos, with_labels=True, node_size=200, node_color=COLOR_BLUE,
        ↪edge_color=COLOR_GREY, width=2, font_size=10)
        plt.title(fr"Generated Erdős-Rényi Graph ( $N$={N}$ ,  $p$={p}$ )")
        plt.axis('off')


        file_name = f"sample_network_N{N}_p{p}.png"
        complete_plot_filename = os.path.join(OUTPUT_PATH_ER, file_name)
        plt.savefig(complete_plot_filename)
        plt.show()

```


Generated Erdős-Rényi Graph ($N=100$, $p=0.001$)




Generated Erdős-Rényi Graph ($N=100$, $p=0.01$)



Generated Erdős-Rényi Graph ($N=100$, $p=0.1$)



Generated Erdős-Rényi Graph ($N=100$, $p=0.5$)



2.3 3. Generate ER graphs with $N = 100$ nodes for different edge creation probabilities $p \in [0, 1]$ and plot the probability that a node belongs to the largest connected component N_G/N as a function of p and mark with a vertical line the critical probability $p_C = 1/N$.

```
[11]: N = 100
sample_size = 100
probabilities_log_range = np.logspace(-5, 0, 200)

[12]: # Clustering for 1.4 (handed in the same loop)

ratios_avg = {}
clusters_average = {}
for p in probabilities_log_range:
    ratios = []
    clusters = []
    for n in range(sample_size):
        # Generate ER graph samples for each p
        g = generate_custom_erdos_renyi_graph(N,p)

        # Get all components
        # https://networkx.org/documentation/stable/reference/algorithms/
        # generated/networkx.algorithms.components.connected_components.html
        connected_components = sorted(nx.connected_components(g), key=len,
        ↪reverse=True)

        # Get largest connected component (LCC)
        largest_connected_component = g.subgraph(connected_components[0])

        # Find size of lcc
        nodes_lcc = largest_connected_component.number_of_nodes()

        # Calculate ration  $N_G / N$ 
        ratio = float(nodes_lcc / len(g))

        # Append to ratio sample list
        ratios.append(ratio)

        # Add cluster for each graph
        clusters.append(nx.average_clustering(g))

    # Average all results in ratios to get value for a specific p
    ratios_avg[f"{p}"] = mean(ratios)
```


```
# Average in the clusters
clusters_average[f"{p}"] = mean(clusters)
```

```
[13]: fig = plt.figure(figsize=(9,7))
ax = fig.add_subplot(111)

ax.plot(probabilities_log_range, np.array(list(ratios_avg.values()))), "x", ms=5, color=COLOR_RED, label=r"$N_G / N$") # Regular values ### Converted ratios_avg.values to array because before they were dict_values and plottign was not possible
plt.axvline(x=1/(N-1), linestyle="--", lw="1.8", color=COLOR_BLUE, label=f'$p_c = \frac{1}{N}$') # Horizontal line p_c = 1 / N

# Formatting
plt.title(r"$\frac{N_G}{N}$ vs. edge creation probability $p$ during ER-model creation")
ax.set_xlabel(r"Edge creation probability $p$", fontsize=20)
ax.set_ylabel(r"$\frac{N_G}{N}$", fontsize=20)
ax.tick_params(which = "major", axis='both', width=1.5, length = 10, labelsiz=20, direction="in")
ax.tick_params(which = "minor", axis='both', width=1.5, length = 5, labelsiz=20, direction="in")
plt.yticks(fontsize = 20)
plt.xticks(fontsize = 20)
ax.set_ylim(0,1.0)
ax.set_xscale("log")
plt.legend()

file_name = "average_ng_vs_n_ratio_for_different_probabilities.png"
complete_plot_filename = os.path.join(OUTPUT_PATH_ER, file_name)
plt.savefig(complete_plot_filename)
plt.show()
```



2.4 4. Plot the average clustering c as a function of p and give an interpretation of the result.

```
[14]: fig = plt.figure(figsize=(9,7))
ax = fig.add_subplot(111)
ax.plot(probabilities_log_range, np.array(list(clusters_average.values())),'x', ms=5,color=COLOR_RED) # Regular values ### Converted clusters_average.
# values to array because before they were dict_values and plottign was not possible


# Formatting
plt.title(r"Average cluster coefficient  $\langle c \rangle$  vs edge creation probability  $p$ ")
ax.set_xlabel(r"Edge creation probability  $p$ ", fontsize=20)
ax.set_ylabel(r"Average cluster coefficient  $\langle c \rangle$ ", fontsize=20)
ax.tick_params(which = "major", axis='both', width=1.5, length = 10, labels=20,direction="in")
```

```

ax.tick_params(which = "minor", axis='both', width=1.5, length = 5,
               ↳labels=20,direction="in")
plt.yticks(fontsize = 20)
plt.xticks(fontsize = 20)
ax.set_ylim(0,1.0)
ax.set_xscale("log")

file_name = "average_cluster_vs_p_for_different_probabilities.png"
complete_plot_filename = os.path.join(OUTPUT_PATH_ER, file_name)
plt.savefig(complete_plot_filename)
plt.show()

```



Interpretation: As p increases, so does the clustering within the network. This aligns with our expectations because a higher p implies a greater number of edges between nodes. With this the network gets denser and the clustering coefficient indicates a denser network.

3 II Watts-Strogatz Model

3.1 1. Write a function to generate a one-dimensional lattice with periodic boundary conditions and coordination

number k , defined as we saw in the class and assignment 1. The function should take in input two parameters: - N : the number of nodes of the lattice, - k : the coordination number,

and it should output a network (the data structure to represent the network is left to your choice, in the hint a suggestion is provided). You have to implement the algorithm yourself and cannot rely on modules' functions. Finally, produce a visualisation of a network generated using such function, with $N = 21$ and $k = 5$.

```
[15]: random.seed(42)
```

```
[16]: def generate_one_dim_lattice(N, k):
    # Precondition
    if k >= N:
        raise ValueError("Coordination number k must not be larger or equal
        to than the number of nodes in the lattice N.")

    # Create a graph object
    G = nx.Graph()

    # Init N nodes
    G.add_nodes_from(range(1, N+1, 1))

    # Connect the nodes
    for i in range(1, N+1, 1):
        current_node = i

        # Forward edges
        for j in range(i + 1, i + k + 1, 1):
            G.add_edge(current_node, j if j <= N else j % N) # else case
            handles the overflow

        # Backward edges
        for j in range(i - 1, i - k - 1, -1):
            G.add_edge(current_node, j if j > 0 else N - (abs(j) % N)) # else
            case handles the overflow


    return G
```

```
[17]: N = 21
      k = 5
```

```
[18]: g = generate_one_dim_lattice(N=N, k=k)
      pos = nx.circular_layout(G=g) # Layout algorithm for node positions
```

```
plt.figure(figsize=(12, 8))
nx.draw(g, pos, with_labels=True, node_size=200, node_color=COLOR_BLUE,
        edge_color=COLOR_GREY, width=2, font_size=10)
plt.axis("off")
plt.title(fr"One-dimensional lattice with ( $N={N}$ ,  $k={k}$ )")
file_name = f"one_dim_lattice_N{N}_k{k}.png"
complete_plot_filename = os.path.join(OUTPUT_PATH_WS, file_name)
plt.savefig(complete_plot_filename)
plt.show()
```

One-dimensional lattice with ($N=21$, $k=5$)



3.2 2. Produce a plot of the average distance of each graph in a sequence of one-dimensional periodic lattices generated using the function you wrote at point 1,

where $k = 10$ is fixed and on the x-axis N ranges between 50 and 1000. What is the relation between the average distance and the number of nodes? Does it meet your expectations? Provide an interpretation of the plot.

```
[19]: k = 10
      N = range(50, 1001, 1)
```

```
[20]: avg_shortest_paths = []
```

```
[21]: for n in tqdm(N, desc="Calculating Average Shortest Paths"):
        lattice = generate_one_dim_lattice(N=n, k=k)


        # Calculate the average shortest path
        avg_shortest_path = nx.average_shortest_path_length(G=lattice)
        avg_shortest_paths.append(avg_shortest_path)
```

Calculating Average Shortest Paths: 100% | 951/951 [08:44<00:00, 1.81it/s]

```
[22]: # Calculate the values with the formula from assignment 1
        calculated_avg_nodes = []
        calculated_avg_distances = []

        for i, avg_shortest_path in enumerate(avg_shortest_paths):
            n = i+50
            if (n % 2 != 0) and ((n - 1) / (2 * k)).is_integer():
                d = (n-1 + 2*k) / (4*k)
                calculated_avg_nodes.append(n)
                calculated_avg_distances.append(d)
```

```
[23]: plt.figure(figsize=(10, 6))
        plt.plot(N, avg_shortest_paths, marker="o", linestyle="-", color=COLOR_BLUE,
            label='Observed Data', alpha=0.1)
        plt.plot(calculated_avg_nodes, calculated_avg_distances, marker='x',
            linestyle='-', color=COLOR_RED, label='Calculated Data', alpha=1.0)
        plt.title("Average Shortest Path Length in one-dimensional Lattices")
        plt.xlabel(r"Number of Nodes ($N$)")
        plt.ylabel(r"Average Shortest Path Length \langle d_{i,j} \rangle")
        plt.legend()
        plt.grid(True)
        file_name = f"average_shortest_path_one_dim_lattice.png"
        complete_plot_filename = os.path.join(OUTPUT_PATH_WS, file_name)
        plt.savefig(complete_plot_filename)
        plt.show()
```



Does it meet your expectations?

Yes, the observed data, that was generated with the `generate_one_dim_lattice()` function is clearly aligned with the calculated values from the formula in Assignment 1.

Provide an interpretation of the plot. We have observed a linear dependency, specifically a positive correlation, between the number of nodes N and the average shortest path length $\langle d_{i,j} \rangle$. This correlation is governed by the following formula:

When N is odd and $\frac{N-1}{2k}$ is an integer:

$$\langle d_{i,j} \rangle = \frac{N - 1 + 2k}{4k}$$

The formula demonstrates that when N satisfies the given conditions, the average shortest path length is determined by the expression $\frac{N-1+2k}{4k}$. In cases where N falls between integer values, the plot shows a clear interpolation between data points.

3.3 3. Implement the original Watts-Strogatz Watts and Strogatz [1998] model, following the example we saw in the slides. It should take in input three parameters:

- N : the number of nodes of the network,
- k : the coordination number of the $1 - d$ original lattice with periodic condition,
- p : the rewiring probability,

and it should output a network (the data structure to represent the network is left to your choice, in the hint a useful suggestion is provided). Implement the algorithm yourself and do not rely on networkx/third parties module functions. Finally, plot the network generated using such a function, for $N = 21$, $p = 0.1$, $k = 5$, using a circular layout.

You want to make sure no self-loops and multi-edges (multiple edges between the same two nodes) happen.

```
[24]: N = 21
      p = 0.1
      k = 5
```

```
[25]: def generate_custom_watts_strogatz_graph(N, k, p, debug=False):
      # Precondition
      if p < 0 or p > 1:
          raise ValueError("Probability p must be in the range [0, 1]")

      g = generate_one_dim_lattice(N=N, k=k)

      if debug:
          plt.figure(figsize=(12, 8))
          nx.draw(g, pos, with_labels=True, node_size=200,
          ↪ node_color=COLOR_BLUE, edge_color=COLOR_GREY, width=2, font_size=10)
          plt.axis("off")
          plt.title(fr"Watts-Strogatz model of a one-dimensional lattice_
          ↪ with (N$={N}, $k$={k}, $p$={p})")
          plt.show()

      nodes = list(g.nodes())
      first_node = nodes[0]
      last_node = nodes[-1]
      #print(first_node, last_node)

      # TODO: can we use g.edges?
      for node in nodes:
          edges = list(g.edges(node))
          #print(f"Edges connected to node {node}: {edges}")

          # Initialize potential_targets for this node
          # no self-loops and multi-edges (multiple edges between the same two_
          ↪ nodes)
          potential_targets = list(set(g.nodes()) - set([node]) - set(g.
          ↪ neighbors(node)))

          for edge in edges:
              source_node, old_target_node = edge
```

```

        # no self-loops and multi-edges (multiple edges between the same
↪two nodes)
        # very slow
        # potential_targets = list(set(g.nodes()) - set([source_node]) -
↪set(g.neighbors(source_node)))
        #print(potential_targets)

    if random.random() < p: # Change edge with probability p
        #print("Change")
        new_target_node = random.choice(potential_targets)
        #print(new_target_node)

        # Rewire
        g.remove_edge(source_node, old_target_node)
        g.add_edge(source_node, new_target_node)

        # Update potential_targets after rewiring
        potential_targets.remove(new_target_node)
        potential_targets.append(old_target_node)

        if debug:
            print(f"changed {source_node} -> {old_target_node} to
↪{source_node} -> {new_target_node}")

    else:
        if debug:
            print("did not change anything")
        else:
            pass

    #print(f"Edges connected to node {node}: {edges}")

    if debug:
        plt.figure(figsize=(12, 8))
        nx.draw(g, pos, with_labels=True, node_size=200,
↪node_color=COLOR_BLUE, edge_color=COLOR_GREY, width=2, font_size=10)
        plt.axis("off")
        plt.title(fr"Watts-Strogatz model of a one-dimensional lattice
↪with (N$={N}, k$={k}, p$={p})")
        plt.show()

    return g


```

[26]: `ws_graph = generate_custom_watts_strogatz_graph(N=N, k=k, p=p, debug=False)`

```
[27]: pos = nx.circular_layout(G=ws_graph) # Layout algorithm for node positions
plt.figure(figsize=(12, 8))
nx.draw(ws_graph, pos, with_labels=True, node_size=200, node_color=COLOR_BLUE,
        edge_color=COLOR_GREY, width=2, font_size=10)

plt.axis("off")
plt.title(fr"Watts-Strogatz model of a one-dimensional lattice with ( $N={N}$ ,  $k={k}$ ,  $p={p}$ )")
file_name = f"watts_strogatz_model_example_one_dim_lattice_N{N}_k{k}_p{p}.png"
complete_plot_filename = os.path.join(OUTPUT_PATH_WS, file_name)
plt.savefig(complete_plot_filename)
plt.show()
```

Watts-Strogatz model of a one-dimensional lattice with ($N=21$, $k=5$, $p=0.1$)



- 3.4 4. Compute and plot L , the average distance (we are painfully aware that the same measure was denoted as Copy code $\langle d_{i,j} \rangle$ in the previous assignment nonetheless we opted for the use of L in this exercise to be faithful to the original notation used in Watts and Strogatz [1998]), and c , the global clustering coefficient on a sample of networks generated from the Watts-Strogatz model (using the python function you wrote in the previous point), as a function of $p \in [0, 1]$ (the rewiring parameter), keeping $N = 1000$ and $k = 10$ fixed.

```
[28]: N = 1000
      k = 10
      sample_size = 100
      probabilities_log_range = np.logspace(-5, 0, 50)
```

```
[29]: avg_shortest_path_averages = {}
      avg_clustering_coefficients = {}
      def compute_metrics(p):
          avg_shortest_paths = []
          clustering_coefficients = []

          for n in range(sample_size):
              # Generate custom WS graph samples for each p
              g = generate_custom_watts_strogatz_graph(N=N, k=k, p=p, debug=False)

              if nx.is_connected(g):
                  # Calculate the shortest path length
                  avg_shortest_path = nx.average_shortest_path_length(g)
                  avg_shortest_paths.append(avg_shortest_path)

                  # Calculate clustering coefficient
                  clustering_coefficient = nx.average_clustering(g)
                  clustering_coefficients.append(clustering_coefficient)

          avg_shortest_path_avg = mean(avg_shortest_paths)
          avg_clustering_coefficient = mean(clustering_coefficients)

          return p, avg_shortest_path_avg, avg_clustering_coefficient

      results = Parallel(n_jobs=-1)(delayed(compute_metrics)(p) for p in_
      ↪ tqdm(probabilities_log_range, desc="Processing p values"))

      for p, avg_shortest_path_avg, avg_clustering_coefficient in results:
          avg_shortest_path_averages[f"{p}"] = avg_shortest_path_avg
          avg_clustering_coefficients[f"{p}"] = avg_clustering_coefficient
```

Processing p values: 100%| | 50/50 [31:14<00:00, 37.49s/it]

```
[30]: print(avg_shortest_path_averages)
      print(avg_clustering_coefficients)
```

```
{'1e-05': 25.076192632632633, '1.2648552168552958e-05': 24.302342882882883,
'1.5998587196060572e-05': 24.246943263263265, '2.0235896477251556e-05':
24.054023863863865, '2.559547922699533e-05': 23.8606982982983,
'3.237457542817647e-05': 23.31334990990991, '4.094915062380427e-05':
22.732173673673675, '5.1794746792312125e-05': 22.11395793793794,
'6.55128556859551e-05': 21.489159099099098, '8.286427728546843e-05':
20.78516072072072, '0.00010481131341546853': 18.885274734734736,
'0.00013257113655901095': 18.639127267267266, '0.00016768329368110083':
16.899543243243244, '0.00021209508879201905': 15.775756736736737,
'0.0002682695795279727': 14.00987881881882, '0.000339322177189533':
12.848824624624624, '0.00042919342601287783': 11.895311631631632,
'0.0005428675439323859': 10.488722562562563, '0.0006866488450042998':
9.70587957957958, '0.000868511373751353': 8.795352292292293,
'0.0010985411419875584': 7.960076756756757, '0.0013894954943731374':
7.42214976976977, '0.001757510624854793': 6.82520042042042,
'0.0022229964825261957': 6.27560024024024, '0.002811768697974231':
5.809178698698699, '0.0035564803062231283': 5.437471911911912,
'0.004498432668969444': 5.104516756756757, '0.005689866029018299':
4.8120666666666665, '0.0071968567300115215': 4.558315415415415,
'0.009102981779915217': 4.339932552552552, '0.011513953993264481':
4.14329993993994, '0.014563484775012445': 3.949507987987988,
'0.018420699693267165': 3.785382962962963, '0.023299518105153717':
3.6314987987987988, '0.029470517025518096': 3.4894774974974974,
'0.037275937203149416': 3.362245965965966, '0.04714866363457394':
3.2523732132132133, '0.05963623316594643': 3.152344984984985,
'0.07543120063354623': 3.056417097097097, '0.09540954763499944':
2.9623976376376375, '0.1206792640639329': 2.8845401401401403,
'0.15264179671752334': 2.818004864864865, '0.19306977288832497':
2.765062782782783, '0.244205309454865': 2.7221365965965965,
'0.30888435964774846': 2.6884455455455454, '0.3906939937054621':
2.6629054654654656, '0.49417133613238384': 2.647237277272727,
'0.6250551925273976': 2.6405687087087086, '0.7906043210907702':
2.6388006206206205, '1.0': 2.6376310510510512}
{'1e-05': 0.710500815371768, '1.2648552168552958e-05': 0.7104637777777831,
'1.5998587196060572e-05': 0.7104426574770312, '2.0235896477251556e-05':
0.710442129490398, '2.559547922699533e-05': 0.7104381578947422,
'3.237457542817647e-05': 0.7104002406015091, '4.094915062380427e-05':
0.7103799665831297, '5.1794746792312125e-05': 0.7103160793650846,
'6.55128556859551e-05': 0.7102593943191363, '8.286427728546843e-05':
0.710191336675026, '0.00010481131341546853': 0.710013375104433,
'0.00013257113655901095': 0.7100157940305359, '0.00016768329368110083':
0.7098326212456326, '0.00021209508879201905': 0.7096349966583174,
'0.0002682695795279727': 0.7093129464213167, '0.000339322177189533':
0.7090774625646159, '0.00042919342601287783': 0.7086545635032367,
'0.0005428675439323859': 0.7081939693217044, '0.0006866488450042998':
```

```

0.7077123610757154, '0.000868511373751353': 0.7069093581547495,
'0.0010985411419875584': 0.7059482356783264, '0.0013894954943731374':
0.7050086237429619, '0.001757510624854793': 0.703545300801026,
'0.0022229964825261957': 0.7014043235426233, '0.002811768697974231':
0.6989057351268814, '0.0035564803062231283': 0.6958096283430262,
'0.004498432668969444': 0.6918670871105562, '0.005689866029018299':
0.6871659637284455, '0.0071968567300115215': 0.681050932114836,
'0.009102981779915217': 0.673755666981482, '0.011513953993264481':
0.6645393334404582, '0.014563484775012445': 0.6516973489893081,
'0.018420699693267165': 0.6376708119965362, '0.023299518105153717':
0.6193351210354828, '0.029470517025518096': 0.5966091876140156,
'0.037275937203149416': 0.5684268931481019, '0.04714866363457394':
0.5353281801439596, '0.05963623316594643': 0.49607163461779363,
'0.07543120063354623': 0.45045049752695954, '0.09540954763499944':
0.39549373795206305, '0.1206792640639329': 0.33713659409217045,
'0.15264179671752334': 0.27319586793929296, '0.19306977288832497':
0.20825858472527078, '0.244205309454865': 0.14582940597111044,
'0.30888435964774846': 0.0927002002078083, '0.3906939937054621':
0.053462260675063315, '0.49417133613238384': 0.030515859030321828,
'0.6250551925273976': 0.021471884120462133, '0.7906043210907702':
0.02026628380167113, '1.0': 0.020468928634418355}

```

[31]: *# This is only done to compare the results*

```

avg_shortest_path_averages_built_in = {}
avg_clustering_coefficients_built_in = {}
def compute_metrics_built_in(p):
    avg_shortest_paths_built_in = []
    clustering_coefficients_built_in = []

    for n in range(sample_size):
        # Generate ER graph samples for each p
        g = nx.watts_strogatz_graph(n=N, k=k, p=p)

        if nx.is_connected(g):
            # Calculate the shortest path length
            avg_shortest_path = nx.average_shortest_path_length(g)
            avg_shortest_paths_built_in.append(avg_shortest_path)

            # Calculate clustering coefficient
            clustering_coefficient = nx.average_clustering(g)
            clustering_coefficients_built_in.append(clustering_coefficient)

    avg_shortest_path_avg = mean(avg_shortest_paths_built_in)
    avg_clustering_coefficient = mean(clustering_coefficients_built_in)

    return p, avg_shortest_path_avg, avg_clustering_coefficient

```

```

results = Parallel(n_jobs=-1)(delayed(compute_metrics_built_in)(p) for p in tqdm(
    probabilities_log_range, desc="Processing p values"))

for p, avg_shortest_path_avg, avg_clustering_coefficient in results:
    avg_shortest_path_averages_built_in[f"{p}"] = avg_shortest_path_avg
    avg_clustering_coefficients_built_in[f"{p}"] = avg_clustering_coefficient

```

Processing p values: 100% | 50/50 [19:02<00:00, 22.86s/it]

```

[32]: print(avg_shortest_path_averages_built_in)
      print(avg_clustering_coefficients_built_in)

```

```

{'1e-05': 49.97457347347348, '1.2648552168552958e-05': 49.95307755755756,
'1.5998587196060572e-05': 49.63228570570571, '2.0235896477251556e-05':
49.39803707707708, '2.559547922699533e-05': 49.4711535935936,
'3.237457542817647e-05': 49.50168786786787, '4.094915062380427e-05':
49.461791151151154, '5.1794746792312125e-05': 48.06825597597598,
'6.55128556859551e-05': 47.39859273273274, '8.286427728546843e-05':
46.909549169169175, '0.00010481131341546853': 47.91472146146146,
'0.00013257113655901095': 45.49842514514515, '0.00016768329368110083':
44.32780460460461, '0.00021209508879201905': 43.561526006006005,
'0.0002682695795279727': 42.34417863863864, '0.000339322177189533':
38.290528168168166, '0.00042919342601287783': 36.26813401401402,
'0.0005428675439323859': 35.252444844844845, '0.0006866488450042998':
33.26667119119119, '0.000868511373751353': 28.785162182182184,
'0.0010985411419875584': 26.47550952952953, '0.0013894954943731374':
23.240005705705705, '0.001757510624854793': 20.874247667667667,
'0.0022229964825261957': 17.959555155155154, '0.002811768697974231':
16.577306126126125, '0.0035564803062231283': 14.91462, '0.004498432668969444':
12.790644824824826, '0.005689866029018299': 11.546785885885885,
'0.0071968567300115215': 10.31596960960961, '0.009102981779915217':
9.303352892892892, '0.011513953993264481': 8.545796916916917,
'0.014563484775012445': 7.780649549549549, '0.018420699693267165':
7.044985845845845, '0.023299518105153717': 6.522038938938939,
'0.029470517025518096': 6.088500700700701, '0.037275937203149416':
5.685741981981982, '0.04714866363457394': 5.30934, '0.05963623316594643':
5.00133003003003, '0.07543120063354623': 4.732453173173173,
'0.09540954763499944': 4.4815430630630635, '0.1206792640639329':
4.258272292292292, '0.15264179671752334': 4.066637577577578,
'0.19306977288832497': 3.890862982982983, '0.244205309454865':
3.732314934934935, '0.30888435964774846': 3.5931186386386385,
'0.3906939937054621': 3.479448628628629, '0.49417133613238384':
3.3863091491491493, '0.6250551925273976': 3.315160920920921,
'0.7906043210907702': 3.275646726726727, '1.0': 3.268398098098098}
{'1e-05': 0.6666448383838354, '1.2648552168552958e-05': 0.6666419494949465,
'1.5998587196060572e-05': 0.6666257121212091, '2.0235896477251556e-05':

```

```

0.6666198535353505, '2.559547922699533e-05': 0.6666165101010071,
'3.237457542817647e-05': 0.6665990959595929, '4.094915062380427e-05':
0.6666159747474717, '5.1794746792312125e-05': 0.6665633838383808,
'6.55128556859551e-05': 0.6665104292929263, '8.286427728546843e-05':
0.6664710151515121, '0.00010481131341546853': 0.6665150101010071,
'0.00013257113655901095': 0.6663928838383808, '0.00016768329368110083':
0.6663645505050475, '0.00021209508879201905': 0.6662700151515121,
'0.0002682695795279727': 0.6662084090909061, '0.000339322177189533':
0.6659561911976881, '0.00042919342601287783': 0.6657346161616131,
'0.0005428675439323859': 0.6656792727272697, '0.0006866488450042998':
0.6654320202020171, '0.000868511373751353': 0.6649158845598815,
'0.0010985411419875584': 0.6645517085137054, '0.0013894954943731374':
0.66395538311688, '0.001757510624854793': 0.6631951103896072,
'0.0022229964825261957': 0.6620909718614686, '0.002811768697974231':
0.661293315295812, '0.0035564803062231283': 0.6600217020201987,
'0.004498432668969444': 0.6577082581307547, '0.005689866029018299':
0.6557189572649538, '0.0071968567300115215': 0.6527634009878974,
'0.009102981779915217': 0.6489336470196434, '0.011513953993264481':
0.6449683165723131, '0.014563484775012445': 0.6392772253857222,
'0.018420699693267165': 0.631019681152178, '0.023299518105153717':
0.6222540097125071, '0.029470517025518096': 0.6111903961038943,
'0.037275937203149416': 0.597163658286157, '0.04714866363457394':
0.5788710563325558, '0.05963623316594643': 0.5572667286047286,
'0.07543120063354623': 0.5310087975357978, '0.09540954763499944':
0.49792310816960844, '0.1206792640639329': 0.45788924353424365,
'0.15264179671752334': 0.41168384879009895, '0.19306977288832497':
0.3573833530848238, '0.244205309454865': 0.2952851265956267,
'0.30888435964774846': 0.22745099019934328, '0.3906939937054621':
0.15828356248335457, '0.49417133613238384': 0.09364866091003979,
'0.6250551925273976': 0.04273858162451606, '0.7906043210907702':
0.01469908283598069, '1.0': 0.00909139925227851}

```

```


[33]: plt.figure(figsize=(12, 8))
plt.subplot(1, 2, 1)
plt.semilogx(probabilities_log_range, avg_shortest_path_averages.values())
plt.xlabel('Probability')
plt.ylabel('Average Distance')
plt.title('Average Distance vs. Rewiring Probability')

plt.subplot(1, 2, 2)
plt.semilogx(probabilities_log_range, avg_clustering_coefficients.values())
plt.xlabel('Probability')
plt.ylabel('Clustering Coefficient')
plt.title('Clustering Coefficient vs. Rewiring Probability')
plt.tight_layout()

file_name = f"watts_strogatz_model_average_paths_and_communities.png"

```

```
complete_plot_filename = os.path.join(OUTPUT_PATH_WS, file_name)
plt.savefig(complete_plot_filename)
plt.show()
```




```
[34]: plt.figure(figsize=(12, 8))
plt.subplot(1, 2, 1)
plt.semilogx(probabilities_log_range, avg_shortest_path_averages_built_in.
    ↪values())
plt.xlabel('Probability')
plt.ylabel('Average Distance')
plt.title('Average Distance vs. Rewiring Probability (built-in function)')

plt.subplot(1, 2, 2)
plt.semilogx(probabilities_log_range, avg_clustering_coefficients_built_in.
    ↪values())
plt.xlabel('Probability')
plt.ylabel('Clustering Coefficient')
plt.title('Clustering Coefficient vs. Rewiring Probability (built-in function)')
plt.tight_layout()

file_name = f"watts_strogatz_model_built_in_average_paths_and_communities.png"
complete_plot_filename = os.path.join(OUTPUT_PATH_WS, file_name)
plt.savefig(complete_plot_filename)
```

```
plt.show()
```



4 III Community Detection

4.1 1. For the provided network datasets find the communities using

- (a) the greedy modularity maximization by Clauset Newman and Moore Clauset et al. [2004] and
- (b) the label propagation algorithm.

Assign to each community a color and draw the resulting graph, where each node is colored after the community it belongs to, while community internal links and inter-communities links are clearly recognizable.

```
[35]: graphs
```

```
[35]: {'graph_internet': <networkx.classes.graph.Graph at 0x12275bfd0>,  
      'graph_Korea': <networkx.classes.graph.Graph at 0x1200d3710>,  
      'graph_eu_airlines': <networkx.classes.graph.Graph at 0x120457cd0>,  
      'graph_macaque': <networkx.classes.graph.Graph at 0x1201fcfd0>,  
      'graph_hep-th': <networkx.classes.graph.Graph at 0x12a5cbfd0>,  
      'graph_starwars': <networkx.classes.graph.Graph at 0x1220cbd50>,  
      'graph_madrid': <networkx.classes.graph.Graph at 0x1222d3d50>}
```

```
[36]: CONSIDERED_GRAPHS = ['graph_madrid', 'graph_starwars', 'graph_Korea']
```

```
[37]: for graph_name, graph in graphs.items():

    if graph_name in CONSIDERED_GRAPHS:
        # Find communities using the greedy modularity maximization algorithm
        # https://networkx.org/documentation/stable/reference/algorithms/
        ↪generated/networkx.algorithms.community.modularity_max.
        ↪greedy_modularity_communities.html
        communities = list(nx.community.greedy_modularity_communities(graph))

        # Create a dictionary to map nodes to their respective community
        community_dict = {}
        for i, community in enumerate(communities):
            for node in community:
                community_dict[node] = i

        # Create a list of colors for nodes based on their community
        node_colors = [community_dict[node] for node in graph.nodes]

        plt.figure(figsize=(12, 8))

        # Create a color map for inter-community edges
        cmap = plt.get_cmap('Set1', len(communities))

        # Create a list of edge colors based on community assignments
        # Inner edge: community color (cmap)
        # Outside edge: grey
        edge_colors = [cmap(community_dict[u]) if community_dict[u] ==
        ↪community_dict[v] else COLOR_LIGHT_GRAY for u, v in graph.edges]

        # Visualize the graph with community colors and distinguish internal
        ↪and inter-community links
        pos = nx.spring_layout(graph, seed=42) # Layout for visualization
        nx.draw_networkx_nodes(graph, pos, node_color=node_colors, cmap=cmap,
        ↪node_size=200)
        nx.draw_networkx_labels(graph, pos, font_size=10)
        nx.draw_networkx_edges(graph, pos, edge_color=edge_colors, alpha=0.5)
        plt.title(f"Graph {graph_name} with Greedy Modularity Communities
        ↪visualizing different Communities")

        # Create a legend for communities with the corresponding colors and
        ↪node counts
        legend_labels = [f"Community {i+1} ({len(community)})" for i, community
        ↪in enumerate(communities)]
```

```

        legend_handles = [plt.Line2D([0], [0], marker='o', color='w',
↪label=label, markerfacecolor=cmap(i)) for i, label in
↪enumerate(legend_labels)]

        # Set the bbox_to_anchor to place the legend outside the plotting area
↪at the bottom in a straight line
        plt.legend(handles=legend_handles, title="Communities", loc='upper
↪center', bbox_to_anchor=(0.5, -0.05), ncol=len(legend_labels))

        file_name = f"greedy_modularity_communities_{graph_name}.png"
        complete_plot_filename = os.path.join(OUTPUT_PATH_COMMUNITIES,
↪file_name)
        plt.savefig(complete_plot_filename)
        plt.show()
    else:
        pass


```

```


/var/folders/ck/vgxn_9f907d122j56f3203gm0000gn/T/ipykernel_71014/3636630277.py:3
1: DeprecationWarning: `alltrue` is deprecated as of NumPy 1.25.0, and will be
removed in NumPy 2.0. Please use `all` instead.
    nx.draw_networkx_edges(graph, pos, edge_color=edge_colors, alpha=0.5)

```


Graph graph_Korea with Greedy Modularity Communities visualizing different Communities



Graph graph_starwars with Greedy Modularity Communities visualizing different Communities



Graph graph_madrid with Greedy Modularity Communities visualizing different Communities



```

[38]: for graph_name, graph in graphs.items():

    if graph_name in CONSIDERED_GRAPHS:
        # Find communities using the greedy modularity maximization algorithm
        # https://networkx.org/documentation/stable/reference/algorithms/
        ↪generated/networkx.algorithms.community.label_propagation.
        ↪label_propagation_communities.html
        communities = list(nx.community.label_propagation_communities(graph))

        # Create a dictionary to map nodes to their respective community
        community_dict = {}
        for i, community in enumerate(communities):
            for node in community:
                community_dict[node] = i

        # Create a list of colors for nodes based on their community
        node_colors = [community_dict[node] for node in graph.nodes]

        plt.figure(figsize=(12, 8))

        # Create a color map for inter-community edges
        cmap = plt.get_cmap('Set1', len(communities))

        # Create a list of edge colors based on community assignments
        # Inner edge: community color (cmap)
        # Outside edge: grey
        edge_colors = [cmap(community_dict[u]) if community_dict[u] ==
        ↪community_dict[v] else COLOR_LIGHT_GRAY for u, v in graph.edges]

        # Visualize the graph with community colors and distinguish internal
        ↪and inter-community links
        pos = nx.spring_layout(graph, seed=42) # Layout for visualization
        nx.draw_networkx_nodes(graph, pos, node_color=node_colors, cmap=cmap,
        ↪node_size=200)
        nx.draw_networkx_labels(graph, pos, font_size=10)
        nx.draw_networkx_edges(graph, pos, edge_color=edge_colors, alpha=0.5)
        plt.title(f"Graph {graph_name} with Label Propagation Communities
        ↪visualizing different Communities")

        # Create a legend for communities with the corresponding colors and
        ↪node counts
        legend_labels = [f"Community {i+1} ({len(community)})" for i, community
        ↪in enumerate(communities)]

```

```

        legend_handles = [plt.Line2D([0], [0], marker='o', color='w',
↪label=label, markerfacecolor=cmap(i)) for i, label in
↪enumerate(legend_labels)]

        # Set the bbox_to_anchor to place the legend outside the plotting area
↪at the bottom in a straight line
        plt.legend(handles=legend_handles, title="Communities", loc='upper
↪center', bbox_to_anchor=(0.5, -0.05), ncol=len(legend_labels))

        file_name = f"label_propagation_communities_{graph_name}.png"
        complete_plot_filename = os.path.join(OUTPUT_PATH_COMMUNITIES,
↪file_name)
        plt.savefig(complete_plot_filename)
        plt.show()
    else:
        pass


```

```


/var/folders/ck/vgxn_9f907d122j56f3203gm0000gn/T/ipykernel_71014/3615388165.py:3
1: DeprecationWarning: `alltrue` is deprecated as of NumPy 1.25.0, and will be
removed in NumPy 2.0. Please use `all` instead.
    nx.draw_networkx_edges(graph, pos, edge_color=edge_colors, alpha=0.5)

```


Graph graph_Korea with Label Propagation Communities visualizing different Communities



Graph graph_starwars with Label Propagation Communities visualizing different Communities



Graph graph_madrid with Label Propagation Communities visualizing different Communities



```
[39]: # Loop through the graphs
for graph_name, graph in graphs.items():
    if graph_name in CONSIDERED_GRAPHS:
        # Find communities using the label propagation algorithm
        communities_lp = list(nx.community.label_propagation_communities(graph))
        # Find communities using the greedy modularity maximization algorithm
        communities_greedy = list(nx.community.
→greedy_modularity_communities(graph))

        # Create a dictionary to map nodes to their respective community for
→label propagation
        community_dict_lp = {}
        for i, community in enumerate(communities_lp):
            for node in community:
                community_dict_lp[node] = i

        # Create a dictionary to map nodes to their respective community for
→greedy modularity
        community_dict_greedy = {}
```

```

for i, community in enumerate(communities_greedy):
    for node in community:
        community_dict_greedy[node] = i

    # Create a list of colors for nodes based on their community for label
    ↪propagation
    node_colors_lp = [cmap(community_dict_lp[node]) for node in graph.nodes]

    # Create a list of colors for nodes based on their community for greedy
    ↪modularity
    node_colors_greedy = [cmap(community_dict_greedy[node]) for node in
    ↪graph.nodes]

    # Create subplots to display both label propagation and greedy
    ↪modularity communities
    fig, axes = plt.subplots(1, 2, figsize=(16, 8))

    # Visualize label propagation communities
    pos = nx.spring_layout(graph, seed=42) # Layout for visualization
    edge_colors_lp = [cmap(community_dict_lp[u]) if community_dict_lp[u] ==
    ↪community_dict_lp[v] else 'gray' for u, v in graph.edges]
    axes[0].set_title(f"Graph {graph_name} with Label Propagation
    ↪Communities")
    axes[0].set_axis_off()
    nx.draw_networkx_nodes(graph, pos, node_color=node_colors_lp,
    ↪cmap=cmap, node_size=200, ax=axes[0])
    nx.draw_networkx_edges(graph, pos, edge_color=edge_colors_lp, alpha=0.
    ↪5, ax=axes[0])

    # Visualize greedy modularity communities
    edge_colors_greedy = [cmap(community_dict_greedy[u]) if
    ↪community_dict_greedy[u] == community_dict_greedy[v] else 'gray' for u, v in
    ↪graph.edges]
    axes[1].set_title(f"Graph {graph_name} with Greedy Modularity
    ↪Communities")
    axes[1].set_axis_off()
    nx.draw_networkx_nodes(graph, pos, node_color=node_colors_greedy,
    ↪cmap=cmap, node_size=200, ax=axes[1])
    nx.draw_networkx_edges(graph, pos, edge_color=edge_colors_greedy,
    ↪alpha=0.5, ax=axes[1])

    # Create a legend for label propagation communities
    legend_labels_lp = [f"Community {i+1} ({len(community)})" for i,
    ↪community in enumerate(communities_lp)]

```

```

        legend_handles_lp = [plt.Line2D([0], [0], marker='o', color='w',
↪label=label, markerfacecolor=cmap(i)) for i, label in
↪enumerate(legend_labels_lp)]
        axes[0].legend(handles=legend_handles_lp, title="Communities",
↪loc='upper right', bbox_to_anchor=(1.0, 1.0), ncol=1)

        # Create a legend for greedy modularity communities
        legend_labels_greedy = [f"Community {i+1} ({len(community)})" for i,
↪community in enumerate(communities_greedy)]
        legend_handles_greedy = [plt.Line2D([0], [0], marker='o', color='w',
↪label=label, markerfacecolor=cmap(i)) for i, label in
↪enumerate(legend_labels_greedy)]
        axes[1].legend(handles=legend_handles_greedy, title="Communities",
↪loc='upper right', bbox_to_anchor=(1.0, 1.0), ncol=1)

        # Save the plot
        file_name = f"communities_comparison_{graph_name}.png"
        complete_plot_filename = os.path.join(OUTPUT_PATH_COMMUNITIES,
↪file_name)
        plt.savefig(complete_plot_filename, bbox_inches='tight')
        plt.show()
    else:
        pass


```

```


/usr/local/anaconda3/envs/network-science/lib/python3.11/site-
packages/networkx/drawing/nx_pyplot.py:433: UserWarning: No data for colormapping
provided via 'c'. Parameters 'cmap' will be ignored
    node_collection = ax.scatter(
/var/folders/ck/vgxn_9f907d122j56f3203gm0000gn/T/ipykernel_71014/2056149498.py:3
6: DeprecationWarning: `alltrue` is deprecated as of NumPy 1.25.0, and will be
removed in NumPy 2.0. Please use `all` instead.
    nx.draw_networkx_edges(graph, pos, edge_color=edge_colors_lp, alpha=0.5,
ax=axes[0])
/var/folders/ck/vgxn_9f907d122j56f3203gm0000gn/T/ipykernel_71014/2056149498.py:4
3: DeprecationWarning: `alltrue` is deprecated as of NumPy 1.25.0, and will be
removed in NumPy 2.0. Please use `all` instead.
    nx.draw_networkx_edges(graph, pos, edge_color=edge_colors_greedy, alpha=0.5,
ax=axes[1])

```


Graph graph_Korea with Label Propagation Communities




Graph graph_Korea with Greedy Modularity Communities




Graph graph_starwars with Label Propagation Communities




Graph graph_starwars with Greedy Modularity Communities



Graph graph_madrid with Label Propagation Communities



Graph graph_madrid with Greedy Modularity Communities



4.2 2. Randomise each network and repeat the exercise at point (1).

Compare the number of communities obtained before and after randomisation and the quality of community detection before and after randomisation.

```
[40]: random_graphs = graphs.copy()

for graph_name, g in random_graphs.items():
    random_graphs[graph_name] = nx.algorithms.smallworld.random_reference(G=g,
    ↪ niter=10, connectivity=False, seed=SEED)
```

```
[41]: for graph_name, graph in random_graphs.items():

    if graph_name in CONSIDERED_GRAPHHS:
        # Find communities using the greedy modularity maximization algorithm
        # https://networkx.org/documentation/stable/reference/algorithms/
        ↪ generated/networkx.algorithms.community.modularity_max.
        ↪ greedy_modularity_communities.html
        communities = list(nx.community.greedy_modularity_communities(graph))

        # Create a dictionary to map nodes to their respective community
        community_dict = {}
        for i, community in enumerate(communities):
            for node in community:
                community_dict[node] = i

        # Create a list of colors for nodes based on their community
        node_colors = [community_dict[node] for node in graph.nodes]
```

```

plt.figure(figsize=(12, 8))

# Create a color map for inter-community edges
cmap = plt.get_cmap('Set1', len(communities))

# Create a list of edge colors based on community assignments
# Inner edge: community color (cmap)
# Outside edge: grey
edge_colors = [cmap(community_dict[u]) if community_dict[u] ==
community_dict[v] else COLOR_LIGHT_GRAY for u, v in graph.edges]

# Visualize the graph with community colors and distinguish internal
and inter-community links
pos = nx.spring_layout(graph, seed=42) # Layout for visualization
nx.draw_networkx_nodes(graph, pos, node_color=node_colors, cmap=cmap,
node_size=200)
nx.draw_networkx_labels(graph, pos, font_size=10)
nx.draw_networkx_edges(graph, pos, edge_color=edge_colors, alpha=0.5)
plt.title(f"Graph {graph_name} (randomized) with Greedy Modularity
Communities visualizing different Communities")

# Create a legend for communities with the corresponding colors and
node counts
legend_labels = [f"Community {i+1} ({len(community)})" for i, community
in enumerate(communities)]
legend_handles = [plt.Line2D([0], [0], marker='o', color='w',
label=label, markerfacecolor=cmap(i)) for i, label in
enumerate(legend_labels)]

# Set the bbox_to_anchor to place the legend outside the plotting area
at the bottom in a straight line
plt.legend(handles=legend_handles, title="Communities", loc='upper
center', bbox_to_anchor=(0.5, -0.05), ncol=len(legend_labels))

file_name = f"greedy_modularity_communities_randomized_{graph_name}.png"
complete_plot_filename = os.path.join(OUTPUT_PATH_COMMUNITIES,
file_name)
plt.savefig(complete_plot_filename)
plt.show()
else:
    pass

```

```

/var/folders/ck/vgxn_9f907d122j56f3203gm0000gn/T/ipykernel_71014/3617236443.py:3
1: DeprecationWarning: `alltrue` is deprecated as of NumPy 1.25.0, and will be
removed in NumPy 2.0. Please use `all` instead.


```

```


nx.draw_networkx_edges(graph, pos, edge_color=edge_colors, alpha=0.5)

```



Graph graph_Korea (randomized) with Greedy Modularity Communities visualizing different Communities



Graph graph_starwars (randomized) with Greedy Modularity Communities visualizing different Communities



Graph graph_madrid (randomized) with Greedy Modularity Communities visualizing different Communities



```
[42]: for graph_name, graph in random_graphs.items():

    if graph_name in CONSIDERED_GRAPHS:
        # Find communities using the greedy modularity maximization algorithm
        # https://networkx.org/documentation/stable/reference/algorithms/
        # generated/networkx.algorithms.community.label_propagation.
        # label_propagation_communities.html
        communities = list(nx.community.label_propagation_communities(graph))

        # Create a dictionary to map nodes to their respective community
        community_dict = {}
        for i, community in enumerate(communities):
            for node in community:
                community_dict[node] = i

        # Create a list of colors for nodes based on their community
        node_colors = [community_dict[node] for node in graph.nodes]

        plt.figure(figsize=(12, 8))
```

```

# Create a color map for inter-community edges
cmap = plt.get_cmap('Set1', len(communities))

# Create a list of edge colors based on community assignments
# Inner edge: community color (cmap)
# Outside edge: grey
edge_colors = [cmap(community_dict[u]) if community_dict[u] ==
community_dict[v] else COLOR_LIGHT_GRAY for u, v in graph.edges]

# Visualize the graph with community colors and distinguish internal
and inter-community links
pos = nx.spring_layout(graph, seed=42) # Layout for visualization
nx.draw_networkx_nodes(graph, pos, node_color=node_colors, cmap=cmap,
node_size=200)
nx.draw_networkx_labels(graph, pos, font_size=10)
nx.draw_networkx_edges(graph, pos, edge_color=edge_colors, alpha=0.5)
plt.title(f"Graph {graph_name} (randomized) with Label Propagation
Communities visualizing different Communities")

# Create a legend for communities with the corresponding colors and
node counts
legend_labels = [f"Community {i+1} ({len(community)})" for i, community
in enumerate(communities)]
legend_handles = [plt.Line2D([0], [0], marker='o', color='w',
label=label, markerfacecolor=cmap(i)) for i, label in
enumerate(legend_labels)]

# Set the bbox_to_anchor to place the legend outside the plotting area
at the bottom in a straight line
plt.legend(handles=legend_handles, title="Communities", loc='upper
center', bbox_to_anchor=(0.5, -0.05), ncol=len(legend_labels))


file_name = f"label_propagation_communities_randomized_{graph_name}.png"
complete_plot_filename = os.path.join(OUTPUT_PATH_COMMUNITIES,
file_name)
plt.savefig(complete_plot_filename)
plt.show()
else:
    pass

```

/var/folders/ck/vgxn_9f907d122j56f3203gm0000gn/T/ipykernel_71014/3164377424.py:3
1: DeprecationWarning: `alltrue` is deprecated as of NumPy 1.25.0, and will be
removed in NumPy 2.0. Please use `all` instead.


```
nx.draw_networkx_edges(graph, pos, edge_color=edge_colors, alpha=0.5)
```

Graph graph_Korea (randomized) with Label Propagation Communities visualizing different Communities




Communities
• Community 1 (35)

Graph graph_starwars (randomized) with Label Propagation Communities visualizing different Communities



Communities
• Community 1 (21)

Graph graph_madrid (randomized) with Label Propagation Communities visualizing different Communities



Communities
 • Community 1 (64)

5 IV Power-Laws

5.1 1. Compute the exponent γ of the power-law distribution fit $p(k) \sim k^{-\gamma}$ of the network degree distribution and the corresponding error.

```
[43]: CONSIDERED_GRAPHS = ['graph_eu_airlines', 'graph_macaque', 'graph_internet',
    ↪ 'graph_starwars', 'graph_hep-th']
```

```
[44]: def gamma_dist(graph):
    degrees = [d for n, d in graph.degree()]

    # Fit a power-law distribution to your data
    # https://github.com/jeffalstott/powerlaw
    fit = powerlaw.Fit(data = degrees)

    # Estimated exponent gamma
    gamma = fit.power_law.alpha
```

```

# Calculate standard error of estimated exponent gamma
gamma_error = fit.power_law.sigma

return (gamma, gamma_error)

```

```

[45]: for graph_name, graph in graphs.items():

    if graph_name in CONSIDERED_GRAPHS:
        gamma, gamma_error = gamma_dist(graph=graph)
        print(f"Gamma of the power-law distribution fit from graph {graph_name}:
↪ {gamma:.4f}. Corresponding error: {gamma_error:.4f}")

```

```

Calculating best minimal value for power law fit
/usr/local/anaconda3/envs/network-science/lib/python3.11/site-
packages/powerlaw.py:699: RuntimeWarning: invalid value encountered in divide
(CDF_diff**2) /

```

```

Calculating best minimal value for power law fit
Calculating best minimal value for power law fit
Calculating best minimal value for power law fit

```

```

Gamma of the power-law distribution fit from graph graph_internet: 2.1122.
Corresponding error: 0.0367
Gamma of the power-law distribution fit from graph graph_eu_airlines: 2.2049.
Corresponding error: 0.1086
Gamma of the power-law distribution fit from graph graph_macaque: 17.0449.
Corresponding error: 4.0112
Gamma of the power-law distribution fit from graph graph_hep-th: 3.2578.
Corresponding error: 0.0635
Gamma of the power-law distribution fit from graph graph_starwars: 4.6762.
Corresponding error: 1.2997

```

```

Calculating best minimal value for power law fit

```

5.2 2. Produce a single plot showing:

- the empirical degree distribution,
- the power-law fit,
- the Poisson fit,
- the exponential distribution with mean value equal to k .

```

[46]: def degree_dist(g):
    degrees = sorted([d for n,d in g.degree()], reverse=True)
    degrees, counts = np.unique(degrees, return_counts=True)
    return degrees, counts

def average_degree(g):
    degree_sequence = [d for n, d in g.degree()]
    mu = np.mean(degree_sequence)
    return mu

```

```

#return sum(dict(g.degree()).values()) / g.number_of_nodes()

def plot_degree_dist(degrees, counts, label):
    plt.plot(degrees, counts, label=label)
    plt.title("Degree Distribution")
    plt.xlabel("Degree")
    plt.ylabel("Counts")
    plt.legend()

def poisson_dist(mean, degree):
    # https://en.wikipedia.org/wiki/Poisson_distribution
    return (mean**degree / factorial(degree))*np.exp(-mean)

def exponential_dist(mean, degree):
    # https://en.wikipedia.org/wiki/Exponential_distribution
    return mean * np.exp(-degree / mean)

```

```

[48]: for graph_name, graph in graphs.items():

    if graph_name in CONSIDERED_GRAPHS:
        degrees, counts = degree_dist(graph)
        k = np.asarray([d for d in dict(graph.degree()).values()])
        spacing = np.linspace(min(k), max(k), len(k))
        fit = powerlaw.Fit(data=k, discrete=True)

        fit.power_law.plot_pdf(label="Powerlaw pdf")
        powerlaw.plot_pdf(k, color='b', marker='o', label="Empirical_
↪Distribution") # empirical one, do really plot the pdf
        #plot_degree_dist(degrees, counts, "Empirical Distribution") # DO NOT_
↪plot the degree dist.
        plt.loglog(spacing, exponential_dist(average_degree(graph), spacing),_
↪label="Exponential Distribution")
        plt.loglog(spacing, poisson_dist(average_degree(graph), spacing),_
↪label="Poisson distribution")
        plt.title(f"Different distributions for Graph {graph_name}")
        plt.xlabel('Degree')
        plt.ylabel('Degree Distribution')
        plt.ylim(1e-5, max(counts))
        plt.legend()
        file_name = f"dist_plot_{graph_name}.png"
        complete_plot_filename = os.path.join(OUTPUT_PATH_POWER_LAWS, file_name)
        plt.savefig(complete_plot_filename)
        plt.show()


```

Calculating best minimal value for power law fit


```

/var/folders/ck/vgxn_9f907d122j56f3203gm0000gn/T/ipykernel_71014/1678974088.py:2
2: RuntimeWarning: overflow encountered in power
  return (mean**degree / factorial(degree))*np.exp(-mean)
/var/folders/ck/vgxn_9f907d122j56f3203gm0000gn/T/ipykernel_71014/1678974088.py:2
2: RuntimeWarning: invalid value encountered in divide
  return (mean**degree / factorial(degree))*np.exp(-mean)


```




Calculating best minimal value for power law fit




Calculating best minimal value for power law fit



Calculating best minimal value for power law fit



Calculating best minimal value for power law fit



5.3 3. Provide a comment on the previous plot: based on the real-world origin of the network, explain why the network shows (or does not show) a scale-free behaviour.

In the graphs `graph_internet`, and `graph_hep` we can observe scale-free behavior because the slope of the empirical distribution matches with the powerlaw pdf fit. In the graphs `graph_eu_airlines`, `graph_macaque`, and `graph_starwars` we can not observe scale-free behavior because the slope of the empirical distribution does not match with the powerlaw pdf fit. We classified `graph_eu_airlines` as non-scale-free because the the slopes are kind of similiar, but not as similar as `graph_internet`, and `graph_hep`.

Creating Results: `jupyter nbconvert Assignment_02.ipynb --to pdf --output Assignment_02_Results.pdf`