

Assignment_04_T1_1_2

December 22, 2023

1 Authors

- Raphael Wäspi (18-918-938)
- Nicolas Huber (16-936-205)

```
[140]: import math
# Imports
import numpy as np
import matplotlib.pyplot as plt
import networkx as nx
import os
import glob
import re
import random
from statistics import mean
import pandas as pd
from typing import Iterable, List, Tuple

import scipy.special
from tqdm import tqdm
import shutil
from joblib import Parallel, delayed
from scipy.special import factorial
import powerlaw
from NEMtropy import DirectedGraph, UndirectedGraph
from NEMtropy import matrix_generator as mg
from NEMtropy.network_functions import build_adjacency_from_edgelist
```

```
[141]: # Define colors with reduced opacity from a colormap
COLOR_BLUE = 'dodgerblue'
COLOR_GREEN = 'palegreen'
COLOR_RED = 'lightcoral'
COLOR_YELLOW = 'gold'
COLOR_GREY = 'slategrey'
COLOR_BLACK = 'black'
COLOR_LIGHT_GRAY = 'lightgray'
COLOR_DARK_GRAY = 'darkgray'
```

```
# Define the main data directory
OUTPUT_PATH = "./output"
```

[142]: # Prepare output folder

```
# Delete the entire 'output' directory and its contents
if os.path.exists(OUTPUT_PATH):
    shutil.rmtree(OUTPUT_PATH)

# Create the 'output' directory
os.makedirs(OUTPUT_PATH)

# Define subdirectories
### OUTPUT_PATH_ERGMS = os.path.join(OUTPUT_PATH, "ERGMS")

# Recreate the subdirectories
### os.makedirs(OUTPUT_PATH_ERGMS)
```

[143]: # Define the directory containing the .gml files

```
directory = 'datasets'

# Use glob to get a list of all .gml files in the directory
gml_files = glob.glob(os.path.join(directory, '*.gml'))

# Init an empty dictionary for all graphs - the key is the actual name, and the
↳ value is the graph data
graphs = {}

# Use tqdm to show a progress bar in Jupyter Notebook
with tqdm(total=len(gml_files), desc="Loading GML Files") as pbar:
    # Loop through the list of .gml files and load them
    for file_path in gml_files:
        with open(file_path, 'r') as file:
            content = file.read()

        # Use regex to extract the desired part
        match = re.search(r'/(~/+)\.gml$', file_path)
        if match:
            graph_name = match.group(1)

            # Add to the graph dictionary
            graph = nx.read_gml(file_path)
            graphs[graph_name] = graph

        # Print the graph name when each part is finished
        print(f"Finished loading {graph_name}")
```

```
pbar.update(1) # Update the progress bar
```

```
Loading GML Files: 100%|          | 4/4 [00:00<00:00, 25.70it/s]
```

```
Finished loading graph1.2
```

```
Finished loading graph_madrid
```

```
Finished loading graph_jazz_collab
```

```
Finished loading graph1.1
```

2 1. Compartmental Models on Networks

2.1 1.1

Write a function to simulate the SI dynamic on a generic network and provide a visualisation. The function should take in input: - a network, e.g. if you are using networkx a generic `nx.Graph`, - the infection rate β , - an infected seed node.

You may also want to add other parameters, e.g. the maximum number of steps for the simulation (some bad things may happen if you don't). As an output, the function should return the list of nodes infected in the simulation. Additionally, run the SI function for an adequate number of steps, with $\beta = 0.5$ on the following two graphs (the datasets are provided), with infected seed node "10":
- graph1.1.gml - graph1.2.gml

and provide a visualisation of the final state of the epidemic, where all the infected nodes at the end of the run are red, or blue if they are not infected.

```
[148]: def si_sim(graph, beta, seed_node, max_steps=100):  
    # Set of infected nodes with the seed node  
    infected_nodes = set()  
    infected_nodes.add(seed_node)  
  
    nodes = set(graph.nodes) # Set of all nodes in the graph  
    steps = 0  
  
    while steps < max_steps:  
        infected_nodes_copy = infected_nodes.copy()  
        susceptible_nodes = nodes - infected_nodes_copy # Identify susceptible  
        nodes by subtracting infected nodes from all nodes  
  
        for node in susceptible_nodes:  
            neighbors = set(graph.neighbors(node)) # Get neighbors of current  
            node  
            infected_neighbors = neighbors & infected_nodes_copy # Get infected  
            neighbors of current node  
  
            num_infected_neighbors = len(infected_neighbors)
```

```

        if num_infected_neighbors > 0:
            probb_healthy = (1-beta)**num_infected_neighbors
            probb_infected = 1 - probb_healthy
            if random.random() < probb_infected:
                infected_nodes.add(node) # Node gets infected

    steps += 1

    return list(infected_nodes)

def visualize_epidemic(graph, infected_nodes):
    pos = nx.spring_layout(graph)

    # Draw nodes
    nx.draw_networkx_nodes(graph, pos, nodelist=infected_nodes,
        node_color='red', label='Infected')
    nx.draw_networkx_nodes(graph, pos, nodelist=set(graph.nodes) -
        set(infected_nodes), node_color='blue', label='Susceptible')

    # Draw edges
    nx.draw_networkx_edges(graph, pos)

    # Draw labels
    nx.draw_networkx_labels(graph, pos)

    # Display legend
    plt.legend()



    # Show the plot
    plt.show()

graph1_1 = graphs["graph1.1"]
graph1_2 = graphs["graph1.2"]
beta = 0.5
seed_node = "10"

infected_nodes1_1 = si_sim(graph1_1, beta, seed_node)
visualize_epidemic(graph1_1, infected_nodes1_1)

infected_nodes1_2 = si_sim(graph1_2, beta, seed_node)
visualize_epidemic(graph1_2, infected_nodes1_2)

```



2.2 1.2

To extend the function you wrote for point 1 in order to simulate the SIS model. You need to introduce γ , i.e. the recovery rate, to the input parameters of the function.

Provide a plot of $\hat{I}$ and $\hat{S}$ as a function of the simulation time-step, on graph graph1.1.gml with $\beta = 0.2$ and $\gamma = 0.4$ over 1000 steps (at least). Choose a random seed such that you don't end up in the trivial stationary states $(\hat{I}, \hat{S}) = (0, 1)$

Hint: in order to observe “smoother” result you can use a moving average. You can check out moving average functions on pandas| python module, or implement it yourself.

```
[149]: def sis_sim(graph, beta, gamma, seed_node, max_steps=100):
    infected_nodes = {seed_node}
    nodes = set(graph.nodes)

    infected_ratios = []
    susceptible_ratios = []

    step = 0
    while step < max_steps:
        newly_infected = set()
        newly_recovered = set()

        for infected_node in infected_nodes:
            for neighbor in graph.neighbors(infected_node):
                if neighbor not in infected_nodes and np.random.uniform(0, 1) < beta:
                    newly_infected.add(neighbor)
                if np.random.uniform(0, 1) < gamma:
                    newly_recovered.add(infected_node)

        infected_nodes.update(newly_infected)
        infected_nodes.difference_update(newly_recovered)

        infected_ratio = len(infected_nodes) / len(nodes)
        susceptible_ratio = 1 - infected_ratio

        infected_ratios.append(infected_ratio)
        susceptible_ratios.append(susceptible_ratio)

        step += 1

    return infected_ratios, susceptible_ratios

def moving_average(lst, window_size):
    return pd.Series(lst).rolling(window=window_size).mean()

# Example
```

```

graph1_1 = graphs["graph1.1"]


beta = 0.2
gamma = 0.4
seed_node = np.random.choice(list(graph1_1.nodes))
max_steps = 1000

# Run the SIS simulation
infected_ratios, susceptible_ratios = sis_sim(graph1_1, beta, gamma, seed_node,
↪max_steps)

# Plot infected and susceptible ratios with moving average
window_size = 30
infected_ratios_smooth = moving_average(infected_ratios, window_size)
susceptible_ratios_smooth = moving_average(susceptible_ratios, window_size)

plt.plot(infected_ratios_smooth, label=r'$\rho^I$')
plt.plot(susceptible_ratios_smooth, label=r'$\rho^S$')
plt.xlabel('Time Step')
plt.ylabel('Ratio')
plt.legend()
plt.show()

```



2.3 1.3

Observe how the infected share of the population stationary state is affected by the network topology, in the SIS model. You have to plot the stationary state share of infected nodes $\hat{I}(t = \infty)$ as a function of β/γ , on two different kind of network structures: - For the Erdos-Renyi $N = 500$ and $p = 6/N$ - For the Barabasi-Albert $N = 500$ and $m = 3$

You can use networkx native functions to create the networks. You need to average $\hat{I}$ on multiple SIS runs, a sample size of 100 SIS simulations per β/γ combination will work. For the x-axis of the plot β/γ chose a logarithmic scale with at least 10 values in the interval $[0, 1]$.

On the y-axis you need to plot: - $\hat{I}_{ER}(t = \infty)$, the share of infected nodes in the stationary state for the Erdos-Renyi network, averaged over at least 100 simulations as a function of β/γ - ER critical epidemic threshold RC. - $\hat{I}_{BA}(t = \infty)$, the share of infected nodes in the stationary state for the Barabasi-Albert network, averaged over at least 100 simulations as a function of β/γ - BA critical epidemic threshold RC.

Hint: It may take a while to run the simulations, take this into account.

Look at task_1.3separated.ipynb

2.4 1.4

Observe the effect of different immunisation strategies. Modify your SIS function to introduce the immunised state, a state where the node cannot get infected nor spread any more. Then implement two different immunised strategies:

- Random strategy: immunised a fraction $g \in [0, 1]$ of the population, where the nodes immunised are chosen randomly.
- Target Strategy: consider a fraction g of nodes randomly. For each node randomly chosen, immunised their largest degree neighbour.

To compare the strategies, run the epidemics simulations on a Barabasi-Albert network with $N = 1000$ and $m = 3$ with $\beta/\gamma = 0.3$ and $\beta/\gamma = 0.6$, immunised with g ranging $[0, 1]$. Produce a plot where:

- On the x-axis there is g the share of immunised nodes.
- On the y-axis there is $\hat{I}(t = \infty)$, the stationary state of share of infected nodes, as a function of g , for the two immunisation strategies.

Hint: Keep in mind you want to compute the average value of $\hat{I}(t = \infty)$ over multiple run, to avoid small sample bias.

Hint: It may take a while to run the simulations, take this into account.

Look at task_1.4separated.ipynb