ASRP: Adaptive Support-Based Response Prediction for Test-Time AI Capability Evaluation

Yuhan Chiu
National Taiwan University
Taipei, Taiwan
yhn.chiu@gmail.com

Coauthor name
Affiliation placeholder
Address placeholder
coauthor@example.com

Abstract

With few labels, item-dependent adaptation can overreact to individual outcomes, while a subject-wide success rate ignores differences across item types. We present **ASRP (Adaptive Support-Based Response Prediction)**, which balances a metadata-informed smoothed prior with support-conditioned kernel residuals. Fixed budget-dependent weights favor the prior at low label budgets and local adaptation as evidence accumulates. Shrunk topic corrections adjust systematic errors, and a streaming acquisition rule selects labels using covariance gain. On a public proxy covering 92 source groups and three seeds, ASRP achieves Brier ALC 0.1985 versus 0.2403 for Empirical Mean with identical adaptively acquired labels; switching ASRP from random to adaptive acquisition provides an additional reduction of 0.0022.

1 Introduction

The Predictive AI Evaluation Competition (PAIEC) asks for an AI system's success probability on an individual item with at most 31 revealed labels per subject–benchmark pair. It requires both zero-label prediction and adaptation from sparse responses. Our target is query-level success, following the distinction from confidence in a particular generated answer made by Yang et al. [2026].

Public priors and local evidence address different limitations. Public subject and metadata statistics provide an initial estimate before labels are available, but do not fully describe a subject's relative strengths on the current benchmark. Conversely, adapting to only one or two outcomes can produce unstable probabilities. ASRP therefore combines smoothing toward a public prior with regularized, item-dependent corrections learned from the acquired support set. The label budget controls how strongly the prediction relies on local evidence.

ASRP has two prediction branches. The first updates a metadata-informed prior with revealed success counts. The second uses frozen MiniLM representations [Wang et al., 2020] and lexical features to fit kernel residuals around a Beta-mixture subject baseline. **Budget-dependent mixing** controls their relative influence. Shrunk topic calibration corrects systematic public-data residuals, while covariance-based acquisition selects labels from the candidate stream. A paired evaluation design, released predictions, and acquisition traces make these effects inspectable.

We distinguish predictor improvements from acquisition improvements. Across 92 public source groups and three seeds, ASRP reduces mean Brier ALC from 0.2403 to 0.1985 relative to Empirical Mean under identical Adaptive evidence. Holding ASRP fixed, switching Random to Adaptive acquisition changes ALC from 0.2008 to 0.1985. We also examine removal of an earlier Rasch component using three additional paired draws, and report ablations of the current kernel and calibration components. Official evaluation of the current version is pending (Appendix C).

Preprint.

2 Competition Setting and Data

2.1 Prediction interface and metrics

At runtime the platform supplies a pair of dictionaries $x = (s, i)$ describing a subject and an item, together with a list of previously acquired binary observations. The predictor returns a finite probability in $[0, 1]$. Eligible subject–benchmark groups have at least 80 distinct items. The platform creates a fixed acquisition/evaluation split and evaluates the same evaluation items at the **six label budgets**

$$n \in \{0, 1, 3, 7, 15, 31\}.$$

Acquisition items are never scored and evaluation outcomes are never revealed. The optional acquisition hook receives the current candidate, acquired labels, and remaining-label context; the interface can also supply a current prediction when requested. ASRP uses the first three inputs.

For a budget n and a subject–benchmark group with N_{eval} evaluated responses, the Brier score is the mean squared error between the predicted probability p and the binary outcome y:

$$B_n = \frac{1}{N_{\text{eval}}} \sum_{j=1}^{N_{\text{eval}}} (p_j - y_j)^2.$$

The group-level Brier ALC is the normalized area on the logarithmic budget axis and is equivalent to

$$\text{ALC} = 0.1B_0 + 0.2B_1 + 0.2B_3 + 0.2B_7 + 0.2B_{15} + 0.1B_{31}.$$

The official score averages these group-level ALC values equally across subject–benchmark groups. **Lower is better.** All reported local tables use this same weighting.

2.2 Public data and frozen artifacts

The predictor uses frozen artifacts trained and calibrated from the public `aims-foundations/measurement-db` release [AIMS Foundations, 2026]. Public responses provide subject priors and metadata statistics, while item content supplies semantic features. The local evaluation selects 92 source groups from a fixed inventory of 142 binary sources; Section 4 describes selection and splitting. Appendix B lists the evaluated sources. Upstream metadata and licenses remain authoritative.

The subject prior and metadata statistics are frozen public-response aggregates. Their runtime use and fallback rules are specified in Appendix A; reproducing the reported scores uses the released weights without refitting them. MiniLM is used as a pretrained encoder; the packaged encoder is `sentence-transformers/all-MiniLM-L6-v2`, based on MiniLM [Wang et al., 2020]. Its weights are **frozen at runtime**. The priors, kernel configuration, calibration statistics, and cluster centroids are prepared offline and bundled with the submission; kernel residual coefficients are fitted online from revealed labels. The current submission uses **no external LLM or web search API during scoring**. At runtime, the program uses only the supplied subject and item attributes, anonymous benchmark identifiers, and labels revealed within the allowed budget; it does not access hidden evaluation outcomes.

3 Proposed Method: ASRP

For a query subject s and item i in benchmark b, let $\mathcal{D}_b$ be the revealed support and $\mathcal{D}_s$ its rows for the current subject. Write $n = |\mathcal{D}_s|$ and $S_s = \sum_{r \in \mathcal{D}_s} y_r$. All predictions below concern this query; their arguments are suppressed when unambiguous. Figure 1 shows the computation. Appendix A gives the shared notation, numerical details, and corresponding code functions.




Figure 1: ASRP overview. Frozen public-data artifacts supply prior and calibration estimates. Revealed labels update the smoothed prior and kernel probe before budget-specific ensembling and topic correction. For a complete group of N items, the candidate pool contains $\lceil N/2 \rceil$ items. Random samples uniformly; Adaptive skips up to 16 warm-up candidates before covariance-gain selection. Both supply nested label prefixes.

3.1 Item representations

Two frozen MiniLM encodings serve distinct roles. The normalized item-text embedding $e_i \in \mathbb{R}^{384}$ assigns items to fallback topic clusters. The kernel branch instead combines text, visible metadata, and interactor descriptions into a semantic vector $\mathbf{h}_i \in \mathbb{R}^{384}$ and a hashed lexical vector $\boldsymbol{\ell}_i \in \mathbb{R}^{8192}$. This representation allows acquired responses to inform predictions on similar items. Neither encoder is updated online. Appendix A.1 specifies truncation, pooling, and lexical hashing.

3.2 Public priors and evidence smoothing

A query-specific metadata prior $p_{\text{meta}}(s, i)$ combines frozen subject and visible-feature success counts. Unknown subjects fall back to public global statistics. With n acquired labels and S_s successes for the current subject–benchmark group, the first branch predicts

$$p_{\text{smooth}} = \frac{S_s + \kappa p_{\text{meta}}(s, i)}{n + \kappa}, \qquad \kappa = 4.$$

Thus at $n = 0$, it returns the metadata prior. A separate frozen subject offset o_s, looked up by normalized model name, initializes the kernel branch's Beta prior:

$$\mu_s = \text{clip}(0.5 + 0.5 o_s, 0.05, 0.95).$$

An unknown name has $o_s = 0$. The two priors have distinct roles: p_{meta} is query-dependent, while μ_s sets the initial subject baseline. Appendix A.2 gives the exact count aggregation and lookup rules.

3.3 Support-conditioned kernel probe

The kernel branch adds an item-dependent correction to a conservative subject baseline. It encodes visible text, metadata, and interactor descriptions into semantic vectors $\mathbf{h}_i$ and lexical vectors $\boldsymbol{\ell}_i$. A locally normalized similarity kernel K is fitted using only the support features in $\mathcal{D}_b$; the query does not change this geometry.

For each supported subject s, let n_s and S_s be its revealed-label and success counts. A two-component Beta mixture has concentrations $(c_1, c_2) = (1, 8)$, prior masses $(\pi_1, \pi_2) = (0.3, 0.7)$, and posterior weights ω_{sk}. Its mean is

$$b_s = \sum_{k=1}^{2} \omega_{sk} \frac{c_k \mu_s + S_s}{c_k + n_s}.$$

Subject-centered kernel ridge regression, with penalty $\lambda_K = 0.3$, fits residual coefficients γ from the revealed labels. With query-to-support similarities $\mathbf{k}_i$ and subject mean fitted contribution $\bar{f}_s$, the prediction is

$$p_{\text{kernel}} = \text{clip}\big(b_s + \mathbf{k}_i^\top \gamma - \bar{f}_s, 0, 1\big).$$

Appendix A.3 defines K, the Beta weight update, and the centered linear solve. If the current subject has no revealed labels, this branch returns μ_s. The implementation supports multiple subjects within a benchmark; this proxy uses one subject per group.

The ensemble gives the kernel weights $w_n = (0, 0, 0.2, 0.4, 1, 1)$ at budgets $(0, 1, 3, 7, 15, 31)$. Thus the smoothed metadata prior supplies the cold-start prediction, while a larger support set allows the local residual to receive more weight. These are design choices encoded in the released configuration.

3.4 Topic calibration

A frozen topic correction $\Delta_n(i)$ adjusts the ensemble using the first matching topic entry in visible metadata. Without a match, the model uses the closest of eight frozen embedding centroids. Count-based shrinkage and caps limit the adjustment to 0.06 for explicit topics or 0.03 for clusters. Missing statistics give zero correction.

The budget-specific ensemble is followed by topic correction:

$$p_{\text{final}} = \text{clip}((1 - w_n)p_{\text{smooth}} + w_n p_{\text{kernel}} + \Delta_n(i), 0, 1)\,.$$

Appendix A.4 gives the exact correction and lookup rules.

3.5 Adaptive acquisition

The `adaptive_4_warm` hook skips up to 16 early candidates to establish feature geometry, without revealing their labels. A reference set $\mathcal{P}$ deduplicates the last 64 seen candidates by visible text, metadata, and interactor features. For the current candidate $*$, a conditional covariance gain G_* is a feature-based uncertainty-reduction surrogate over $\mathcal{P}$. It depends on acquired-item features, but not on their outcome values, and does not directly estimate a change in Brier score. Normalizing and capping this gain, then raising it to power four, gives utility V_*.

For L labels and R candidates remaining, including the current candidate, the acquisition probability is

$$\pi_*^{\text{acq}} = \min\left(1, \frac{L}{R}\,\text{clip}\left(\frac{V_*}{\max(\overline{V}_{\mathcal{P}}, 10^{-12})}, 0.05, 20\right)\right), \qquad \overline{V}_{\mathcal{P}} = \frac{1}{|\mathcal{P}|}\sum_{j\in\mathcal{P}} V_j.$$

A deterministic uniform hash supplies the draw. When $R \le L$ and $L > 0$, every remaining candidate is acquired, overriding warm-up. Appendix A.5 defines G_j, V_j, and the boundary cases. The rule uses only acquired support and already-seen/current features; it never accesses future candidates or unseen outcomes.

4 Experimental Setup

We use paired public-data comparisons to separate prediction and acquisition effects. Code, frozen artifacts, and exact reproduction commands are provided in Appendix D.

4.1 Public proxy protocol

Data and repeated splits. We select one eligible subject per source using a fixed seed and keep these subjects unchanged across experiments. Eligible groups contain 80–1,000 distinct items, all retained, yielding **92 source groups** and 44,741 items. The other 50 sources in the 142-source inventory have no qualifying group. The upper limit bounds local evaluation cost. We fix one binary outcome per item when repeated responses exist; official evaluation instead retains all recorded evaluation responses. For each seed (**42, 43, and 44**), items are split approximately equally into disjoint acquisition and evaluation pools. Candidate pools contain 45–500 items, and each seed has **22,357 evaluation outcomes**. The manifest records the data version, selected records, and splits.

Paired comparison. We evaluate **ASRP and Empirical Mean under both Random and Adaptive acquisition**. Random samples uniformly without replacement; Adaptive uses `adaptive_4_warm` from Section 3.5. Within each seed, both policies receive the same candidate order and evaluation pool. Both predictors receive identical acquired labels *within each policy*, while different policies may select different labels. A single acquisition trajectory targets 31 labels and supplies nested evidence

at all six budgets; selection does not restart at each checkpoint. Every checkpoint evaluates the same held-out items.

Evaluation scope. Evaluation outcomes are never revealed online. However, public training, calibration, and proxy evaluation use the same data release, so this is not an independent test of all fitted components and local scores may be optimistic.

4.2 Baseline and score aggregation

We use the **Empirical Mean predictor** from the official PAIEC repository [Truong et al., 2026]:

$$p_{\mathrm{EM}} = \begin{cases} 0.5, & n = 0, \\ \frac{1}{n}\sum_{k=1}^{n} y_k, & n > 0. \end{cases}$$

It uses only the current subject–benchmark group's acquired labels, without item features or a learned prior. Random is its default acquisition policy; the Adaptive variant uses ASRP's selected labels.

We use the metrics and equal-group weighting in Section 2, then average the three seed-level scores equally. We report each seed's ALC and their sample standard deviation (SD), describing split variation. Source-level comparisons average paired ALC differences over the three seeds before counting improvements, with each selected source counted once.

4.3 Rasch removal check

An earlier ASRP version blended a Rasch ability–difficulty prediction into its low-budget branch. We compare that frozen model with the same predictor after setting the Rasch mixing weight to zero, retaining all other weights and calibration statistics. The initial comparison uses seeds 42–44; an additional check uses seeds **45, 46, and 47**. Each pair shares its Adaptive acquisition trajectory and evaluation items. The additional draws use the same 92 selected groups, so they assess split/acquisition stability rather than transfer to new sources. The archived implementation and exact protocol are specified in `experiments/rasch_confirmation.json`.

4.4 Current component ablations

On seeds 42–44, we also remove one component from the current ASRP predictor at a time. **No Kernel Probe** sets $w_n = 0$, retaining the smoothed prior and topic correction; **No topic calibration** sets $\Delta_n(i) = 0$. The comparison uses identical Adaptive labels and evaluation items, with remaining parameters fixed and no refitting. Shared component calculations are checked against the native runtime with the corresponding component disabled.

5 Results and Analysis

5.1 Public proxy results

Table 1 reports the **four predictor–acquisition combinations**, averaged equally over groups and then over seeds 42, 43, and 44. ASRP + Adaptive has a mean Brier ALC of 0.1985, compared with 0.2435 for Empirical Mean + Random (an absolute reduction of 0.0449). Its aggregate Brier score is lower at all six budgets.

Predictor + acquisition	B_0	B_1	B_3	B_7	B_{15}	B_{31}	ALC
Empirical Mean + Random	0.2500	0.3488	0.2518	0.2086	0.1910	0.1842	0.2435
Empirical Mean + Adaptive	0.2500	0.3594	0.2366	0.2003	0.1883	0.1837	0.2403
ASRP + Random	0.2277	0.2165	0.2069	0.1945	0.1845	0.1755	0.2008
ASRP + Adaptive	0.2277	0.2154	0.2035	0.1912	0.1819	0.1738	0.1985

Table 1: Public proxy Brier scores averaged equally over 92 groups and seeds 42, 43, and 44. Lower is better. Evaluation pools are matched across policies; acquired labels are matched across predictors within each policy.




Figure 2: Mean public-proxy Brier curves for the four predictor–acquisition combinations on the official $\log_2(1+n)$ budget axis. Solid lines denote Adaptive acquisition and dashed lines Random; values match Table 1.

Predictor + acquisition	Seed 42	Seed 43	Seed 44	SD
Empirical Mean + Random	0.2467	0.2401	0.2435	0.0033
Empirical Mean + Adaptive	0.2386	0.2427	0.2396	0.0021
ASRP + Random	0.2025	0.1982	0.2016	0.0023
ASRP + Adaptive	0.1990	0.1976	0.1990	0.0008

Table 2: Group-averaged Brier ALC for each split/acquisition seed. SD is the sample standard deviation over the three seed scores. Lower ALC is better.

5.2 Prediction and acquisition effects

Predictor effect with acquisition held fixed. Relative to Empirical Mean with matched labels, ASRP reduces ALC by 0.0427 under Random and 0.0418 under Adaptive acquisition. Empirical Mean + Random rises from 0.2500 at zero labels to 0.3488 at one label: a single outcome makes its prediction either zero or one. ASRP smooths early evidence using public priors. This comparison measures the complete predictor, including its frozen public-data information; component removals are examined in Section 5.4.

Acquisition effect with the predictor held fixed. For ASRP, Adaptive lowers mean ALC by 0.0022 relative to Random, and has lower ALC in all three seeds. For Empirical Mean, Adaptive lowers mean ALC by 0.0031 relative to Random, and has lower ALC in 2 of the three seeds. The closest ASRP pair differs by only -0.00057 (Adaptive minus Random, seed 43). Table 2 shows the individual seed results and their sample standard deviation; three seeds summarize sensitivity to these draws rather than establishing universal superiority.

Variation across sources. Averaging the paired ALC differences over seeds within each source, ASRP beats Empirical Mean on 83 of 92 sources under Adaptive acquisition and loses on 9. For ASRP, Adaptive improves on Random in 56 sources, worsens in 33, and ties in 3 (tolerance 10^{-12}). These counts describe the selected subject per source.

5.3 Rasch removal assessment

Across the six paired draws, removing Rasch produces lower mean ALC by 0.00003 and lower ALC in 4 of the six seeds (Table 3). Mean zero-label Brier changes from 0.2258 to 0.2270. The additional seeds use the same selected sources and frozen artifacts; they are a check of draw sensitivity, not a new-source generalization test. We adopt the simpler prior–kernel predictor, eliminating difficulty inference and ability updates. The measured change is small and includes a cold-start tradeoff; we do not claim uniform improvement across sources.

Draw set	With Rasch	Without Rasch	ΔALC
Initial seeds 42–44	0.19871	0.19853	−0.00018
Additional seeds 45–47	0.19880	0.19892	+0.00012
All six seeds	0.19875	0.19872	−0.00003

Table 3: Paired Adaptive comparisons of the earlier Rasch version and its removal. The additional seeds assess the same source groups under new splits. ΔALC is removal minus retention.

5.4 Component contributions

Variant	B_0	B_1	B_3	B_7	B_{15}	B_{31}	ALC	ΔALC
Full ASRP	0.2277	0.2154	0.2035	0.1912	0.1819	0.1738	0.1985	–
No Kernel Probe	0.2277	0.2154	0.2043	0.1932	0.1865	0.1830	0.2009	+0.0024
No topic calibration	0.2279	0.2160	0.2042	0.1918	0.1820	0.1739	0.1990	+0.0005

Table 4: Component removals with fixed Adaptive evidence and remaining parameters, averaged over 92 groups and three seeds. Positive ΔALC (variant minus full ASRP) indicates worse performance.

Local adaptation and calibration. Removing Kernel Probe increases ALC by 0.0024, from 0.1985 to 0.2009. At budget 31, Brier changes from 0.1738 to 0.1830. Budgets zero and one are unchanged because the kernel weight is already zero. The predictor without Kernel Probe still improves on matched-label Empirical Mean (0.2403), showing that the retained prior smoothing and calibration preserve a substantial part of the advantage. Removing topic calibration increases ALC by 0.0005, to 0.1990. These comparisons isolate removals from the current frozen configuration, with metadata smoothing retained and identical acquired evidence.

6 Limitations and Discussion

Cold-start transfer. The initial prediction still depends on frozen public priors and topic corrections. Additional split seeds on the same public sources do not establish their transfer to unfamiliar benchmarks, and public training and proxy evaluation use the same data release. Cold-start behavior of the simplified submission on private competition data remains unmeasured.

7 Conclusion

ASRP balances metadata-informed initialization with support-conditioned kernel adaptation as labels accumulate. Paired experiments separate the benefits of prediction and acquisition, while the removal study examines whether added psychometric structure is warranted. The revised method retains public-prior smoothing, kernel residuals, topic calibration, and streaming acquisition. Released artifacts, per-item predictions, and matched splits make these comparisons reproducible; transfer of the initial estimates remains an important evaluation target.

A Mathematical and Implementation Details

These equations specify inference with the released frozen artifacts at the six competition budgets. They use the same symbols as Section 3. The reproduction command evaluates these artifacts without repeating their original offline fitting. Throughout, $\mathrm{clip}(x, l, u) = \min(u, \max(l, x))$, applied coordinatewise to vectors, and $\mathrm{norm}(x) = x/\max(\|x\|_2, 10^{-12})$.

Shared notation. A support row r contains a subject s_r, item i_r, and binary outcome y_r. The row collection $\mathcal{D}_b$ contains all revealed responses for benchmark b and has size M. Its subject-specific subset $\mathcal{D}_s$ has n_s rows and S_s successes. For the current query subject, the budget is $n = n_s \le 31$. In this proxy $M = n$; the formulas below also describe the implementation's multi-subject kernel. Runtime subject identity uses the complete subject dictionary, whereas frozen subject-prior lookup uses `normalized_name`.

We distinguish w_n (kernel mixing weight) and λ_K (ridge penalty). Beta component index $k \in \{1, 2\}$ has concentration c_k, prior mass π_k, and posterior mass ω_{sk}. Acquisition uses gain G_j, utility V_j, probability π_*^{acq}, and uniform variate ξ; none denotes an embedding coordinate.

A.1 Feature construction for Section 3.1

The topic-cluster encoder normalizes whitespace, takes the first 6,000 characters of item content, and tokenizes to at most 256 tokens. Masked mean pooling followed by L_2 normalization gives $e_i \in \mathbb{R}^{384}$. This encoder supports the frozen centroid lookup; there is no learned difficulty head in the current predictor.

The kernel encoder uses a separate text construction containing item content, metadata, and interactor descriptions. It pools up to four evenly spaced windows of 254 content tokens, each with special tokens, normalizes each pooled vector, and normalizes their sum to obtain $\mathbf{h}_i \in \mathbb{R}^{384}$. The lexical vector $\boldsymbol{\ell}_i \in \mathbb{R}^{8192}$ uses signed CRC32 hashing of lowercased tokens and adjacent token bigrams, weights $1 + \log(\text{count})$, and L_2 normalization. Only these semantic and lexical coordinates enter the kernel. See `text_encoder.py`, `window_features.py`, and `evidence_features.py` under `src/asrp/`.

A.2 Prior construction for Section 3.2

Two distinct frozen priors. The scalar o_s comes from `binary_subject_prior.json` and defines the kernel prior mean μ_s in Section 3.2. The query-dependent metadata prior $p_{\mathrm{meta}}(s, i)$ instead uses the success/count tables in `feature_prior.json`; it corresponds to `_feature_prior` in `src/asrp/model.py`.

Let (A_0, N_0) be global public successes and counts, and (A_s, N_s) the subject totals. The frozen rates are

$$q_0 = \frac{A_0}{\max(N_0, 1)}, \qquad q_s = \frac{A_s + 8q_0}{N_s + 8}.$$

Unknown subjects use global totals. Their offset o_s is separately zero, so $\mu_s = 0.5$, but $p_{\mathrm{meta}}(s, i)$ need not equal 0.5. All released global totals have positive counts.

For each token t in the query metadata with stored global counts, let $q_t = A_t/\max(N_t, 1)$. When subject–token counts exist,

$$q_{st} = \frac{A_{st} + 8q_t}{N_{st} + 8}, \qquad \rho_{st} = \frac{\min(N_{st}, 80)}{\min(N_{st}, 80) + 12}.$$

Otherwise $q_{st} = q_t$ and $\rho_{st} = \min(N_t, 300)/[\min(N_t, 300) + 100]$. For the set $\mathcal{T}(i)$ of matching tokens,

$$p_{\mathrm{meta}}(s, i) = \mathrm{clip}\left(\frac{2q_s + \sum_{t \in \mathcal{T}(i)} \rho_{st} q_{st}}{2 + \sum_{t \in \mathcal{T}(i)} \rho_{st}}, 0.03, 0.97\right).$$

An empty token set gives clipped q_s. Token parsing, deduplication, and stop words follow `_feature_tokens`. The packaged artifact is present; if it were absent, the runtime fallback would be μ_s.

The smoothing branch uses at most the first 31 matching binary labels in acquisition order, filtering by the complete subject dictionary and benchmark identifier. At zero labels it returns the metadata prior directly. These steps are implemented by `_predict_smooth`.

A.3 Kernel calculations for Section 3.3

Support-only geometry and bandwidth. For $M > 1$ rows in $\mathcal{D}_b$, let $\bar{\mathbf{h}}$ and v_j^{feat} be the coordinatewise semantic mean and population variance (divisor M). Define semantic scales t_j and lexical weights ν_ℓ by

$$t_j = \left[v_j^{\mathrm{feat}} + \max(\mathrm{median}_j\, v_j^{\mathrm{feat}}, 10^{-7})\right]^{-1/2}, \qquad \nu_\ell = \log\frac{1+M}{1+f_\ell} + 0.1,$$

where $f_\ell = \sum_{r\in\mathcal{D}_b} \mathbf{1}[|\ell_{i_r,\ell}| > 10^{-10}]$. Both support and query use

$$\widetilde{\mathbf{h}}_i = \mathrm{norm}((\mathbf{h}_i - \bar{\mathbf{h}}) \odot \mathbf{t}), \qquad \widetilde{\boldsymbol{\ell}}_i = \mathrm{norm}(\boldsymbol{\ell}_i \odot \boldsymbol{\nu}).$$

For $M = 1$, the mean is zero and both weight vectors are all ones. No query feature enters these fitted statistics.

For support rows r, t, define

$$Q_{rt} = \tfrac{1}{2}\left(\widetilde{\mathbf{h}}_{i_r}^\top \widetilde{\mathbf{h}}_{i_t} + \widetilde{\boldsymbol{\ell}}_{i_r}^\top \widetilde{\boldsymbol{\ell}}_{i_t}\right), \qquad K_{rt} = \exp\!\left(\frac{\min(Q_{rt}-1, 0)}{h_K}\right).$$

Take distances $\max(1 - Q_{rt}, 0)$ over unordered off-diagonal pairs, retain those above 10^{-8}, and let d_{med} be their median (or 0.1 if none remain). The bandwidth is $h_K = 4\max(d_{\mathrm{med}}, 10^{-5})$. The vector $\mathbf{k}_i \in \mathbb{R}^M$ uses this same transformation and bandwidth between query i and each support row. These operations correspond to `fit_geometry`, `fit_evidence`, and `predict_fitted` in `src/asrp/project_core.py`.

Beta mixture. For component $k \in \{1, 2\}$, let $\alpha_{sk} = \mu_s c_k$ and $\beta_{sk} = (1 - \mu_s)c_k$, with $(c_1, c_2) = (1, 8)$. The normalized posterior masses are

$$\widetilde{\omega}_{sk} = \pi_k \frac{\mathrm{B}(\alpha_{sk} + S_s, \beta_{sk} + n_s - S_s)}{\mathrm{B}(\alpha_{sk}, \beta_{sk})}, \qquad \omega_{sk} = \frac{\widetilde{\omega}_{sk}}{\sum_{k'=1}^{2} \widetilde{\omega}_{sk'}}, \qquad (\pi_1, \pi_2) = (0.3, 0.7).$$

Here B is the beta function. The implementation evaluates log-beta functions and normalizes by log-sum-exp. These weights give b_s in Section 3.3. If the current subject is absent from the support, `kernel_probe.py` returns μ_s without fitting a residual for that subject.

Centered ridge fit. Let $Z \in \{0, 1\}^{M\times J}$ be the membership matrix for the J subjects present in the support, and $D = \mathrm{diag}(n_1, \ldots, n_J)$. Every diagonal count is positive. Let I_M be the $M \times M$ identity and $\mathbf{y} = (y_r)_{r\in\mathcal{D}_b} \in \mathbb{R}^M$. Define

$$H = I_M - ZD^{-1}Z^\top, \qquad K_c = HKH.$$

$$\gamma = H\left[\tfrac{1}{2}(K_c + K_c^\top) + \lambda_K I_M\right]^{-1} H\mathbf{y}, \qquad \lambda_K = 0.3.$$

The target $H\mathbf{y}$ subtracts each subject's empirical mean; the Beta mean b_s enters the final prediction separately. The code evaluates the inverse expression with a linear solve. Symmetrization matches the floating-point implementation; in exact arithmetic K_c is symmetric. The fitted subject contribution is

$$\bar{f}_s = \frac{1}{n_s}\sum_{r\in\mathcal{D}_s} (K\gamma)_r.$$

Substituting b_s, γ, $\mathbf{k}_i$, and $\bar{f}_s$ into Section 3.3 gives the implemented kernel prediction. At $n_s = 0$ this residual expression is bypassed; at $n = 0, 1$ the final ensemble weight w_n is zero.

A.4 Mixing and calibration for Section 3.4

The six released mixing weights are

n	0	1	3	7	15	31
w_n	0	0	0.2	0.4	1	1

Here w_n maps to `runtime_config.json:probe_weights` and λ_K maps to `probe_config.json:ridge`. The smoothing concentration is `runtime_config.json:kappa`. Between checkpoints, the kernel weight is linearly interpolated and clamped to the endpoint values; the experiment uses only the six official counts.

Let $t = t(i)$ be the first explicit topic key–value entry, in visible metadata order, present in the frozen topic table. If none matches, assign the item-text embedding e_i to the closest of eight frozen centroids by cosine similarity and use its cluster entry. Write C_t^{cal} for that entry's frozen count and $r_{t,n}$ for its signed correction at budget n. Then

$$\Delta_n(i) = \mathrm{clip}\left(\frac{C_t^{\mathrm{cal}}}{C_t^{\mathrm{cal}} + a_t^{\mathrm{cal}}}\, r_{t,n}, -d_t^{\mathrm{cal}}, d_t^{\mathrm{cal}}\right), \qquad (a_t^{\mathrm{cal}}, d_t^{\mathrm{cal}}) = \begin{cases} (40, 0.06), & \text{explicit topic,} \\ (200, 0.03), & \text{cluster.} \end{cases}$$

If no entry exists, $\Delta_n(i) = 0$. Cluster cosine normalization floors norms at 10^{-8} and resolves ties by the first maximum. At the six checkpoints, the residual array index is the corresponding budget index.

The correction $\Delta_n(i)$ is added after mixing the smoothed-prior and kernel predictions with weight w_n. A final clip to $[0, 1]$ completes `predict`.

A.5 Covariance calculation for Section 3.5

The acquisition kernel is denoted K^{acq} to distinguish it from the prediction kernel K. Its geometry is fitted to the concatenation of acquired support $\mathcal{D}_b$, the reference list $\mathcal{P}$, and the current candidate $*$. The same visible item may appear in both support and reference positions; these occurrences remain in the concatenation. Only $\mathcal{P}$ itself is deduplicated. Thus acquisition may use seen but unlabeled features, whereas prediction geometry uses only acquired support features.

Use the feature normalization and RBF rule in Appendix A.3, but compute the median-distance bandwidth from pairs in $\mathcal{P}$ only. Let $\mathcal{U}$ concatenate $\mathcal{P}$ and $*$. For the current subject s, augment the kernel blocks as

$$\begin{aligned} A_{\mathcal{D}\mathcal{D}}[r,t] &= K^{\mathrm{acq}}_{\mathcal{D}\mathcal{D}}[r,t] + 0.25\,\mathbf{1}[s_r = s_t], \\ A_{\mathcal{U}\mathcal{D}}[j,r] &= K^{\mathrm{acq}}_{\mathcal{U}\mathcal{D}}[j,r] + 0.25\,\mathbf{1}[s_r = s], \\ A_{\mathcal{U}\mathcal{U}} &= K^{\mathrm{acq}}_{\mathcal{U}\mathcal{U}} + 0.25\mathbf{1}\mathbf{1}^\top, \end{aligned}$$

where block subscript $\mathcal{D}$ abbreviates $\mathcal{D}_b$. Conditional covariance and gain are

$$\Sigma = A_{\mathcal{U}\mathcal{U}} - A_{\mathcal{U}\mathcal{D}}(A_{\mathcal{D}\mathcal{D}} + I_M)^{-1}A_{\mathcal{U}\mathcal{D}}^\top, \qquad G_j = \max\left(\frac{|\mathcal{P}|^{-1}\sum_{r\in\mathcal{P}}\Sigma_{rj}^2}{1 + \max(\Sigma_{jj}, 0)}, 10^{-12}\right).$$

The identity term implements unit observation noise; without support, the subtraction is omitted. Define

$$\overline{G}_{\mathcal{P}} = |\mathcal{P}|^{-1}\sum_{r\in\mathcal{P}} G_r, \qquad V_j = \left[\min\left(\frac{G_j}{\max(\overline{G}_{\mathcal{P}}, 10^{-12})}, 20\right)\right]^4.$$

These utilities enter π_*^{acq} in Section 3.5. The power four is applied before dividing by mean reference utility. Gain depends on support membership and features; the numerical values of the revealed outcomes do not enter this covariance calculation.

Acquisition rules and reproducibility. Let A be the initial candidate count and $B_{\max} = 31$ the total label allowance in this experiment. Warm-up skips the first $W = \min(16, \max(0, A - B_{\max}))$ candidates. Checks occur in this order: reject if $L \le 0$; acquire if $R \le L$; otherwise skip during warm-up. After warm-up, an empty reference list falls back to probability L/R; otherwise use π_*^{acq}.

To ensure reproducibility, we generate a deterministic pseudorandom value $\xi \in [0, 1)$ from the current context and input using SHA256. We acquire the label when $\xi < \pi_*^{\mathrm{acq}}$, using L/R as the fallback acquisition probability. The reference list uses the last 64 candidates before the current one, deduplicated by the hash of visible item text/metadata/interactor content. Skipped outcomes are never supplied. See `AdaptiveGainPolicy.choose` in `src/asrp/adaptive_gain_policy.py`.

B Public source inventory

The following 92 public binary source identifiers occur in the paired three-seed evaluation. They identify the evaluation sources; the benchmark inventory and upstream licenses remain authoritative.

```
afrieval
agentic_review_perturbation
algotune
alignment_faking
appworld
averimatec
babilong
beavertails
benger
bird_sql
braveguard
bridging_gap
cellverse
critic_discernment_game
crow
devbench
editbench
edu_circuit_hw
egoschema
elicitation_game
engdesign
enginemt_qa
exploitgym
faithcot
fewshot_ttt_bbh
financebench
finegrain_t2i
hallusionbench
harmbench
healthadminbench
helm_bbq
helm_thaiexam
hle
igakuqa119
ikp
jailbreakbench
kernelbench
legal_rag_bench
llmail_inject
llms_lean_formalization
mathconstraint
mathvista_mini
medhelm_ehr_sql
medhelm_head_qa
medhelm_med_mcqa
medhelm_med_qa
medhelm_medbullets
medhelm_medcalc_bench
medhelm_medec
medhelm_medhallu
medhelm_pubmed_qa
medhelm_race_based_med
mj_bench
mmbench_v11
monkey_power_laws
morphkv
mtbbench
multi_swebench
naep_llm_students
naturebench
nester
nyu_ctf_bench
openbiorq
os_harm
perfcodebench
planbench
proofaug
pxplore
real_webagents
realtimeqa
reliancescope
researchcodebench
revolve
risebench
```

```
robust_reasoning_benchmark
safeagentbench
sib200
software_world_models
sustainable_food
swe_smith
swebench_live
swepolybench
tau2_bench
taubench
truthfulqa_mc
tulu_human_eval
tumlu
visual_riddles
visualwebarena
vl_rewardbench
workarena
workbench_revisited
```

C Official Evaluation

Pending. Official six-budget Brier scores and Brier ALC for the current ASRP version will be added after Codabench evaluation.

ASRP + Adaptive	B_0	B_1	B_3	B_7	B_{15}	B_{31}	ALC
Pending	–	–	–	–	–	–	–

Table 5: Official Codabench results for the current ASRP version. Dashes indicate pending evaluation.

D Reproducibility and Disclosure

Code, frozen weights, evaluation manifests, predictions, acquisition traces, and report source are available at `https://github.com/Hubert0916/arsp`. After accepting the measurement-db access conditions, run from the repository root:

```
uv sync --locked
uv run hf auth login
uv run --locked python tools/reproduce.py
```

The pipeline reconstructs the pinned public-data splits, evaluates all four combinations across three seeds on CPU, and checks predictions within 10^{-7} and acquired labels exactly against the published results. Reproduction uses the released frozen artifacts; original offline fitting scripts are not included.

For the fixed-evidence component ablations in Section 5.4, run `tools/score_ablation.py` after the main evaluation; component predictions are saved in the same inference pass. The component predictions can be audited and the ablation table regenerated with `tools/update_ablation_report.py`.

Selection capacity. Across the full experiment, 273 of 276 Adaptive trajectories execute at least one discretionary decision. The 3 trajectories without discretionary choices belong to one 90-item group: 14 warm-up skips leave exactly 31 candidates, all mandatory.

The additional removal check is reproduced with `tools/confirm_rasch_removal.py`, which loads the earlier runtime from its pinned Git revision. File descriptions and build instructions are provided in the repository README.

Competition-specific artifacts use permitted measurement-db data and the pretrained MiniLM encoder. Codex assisted development and report preparation; no external LLM API is used during scoring.

References

Sin-Han Yang, Cheng-Kuang Wu, Chieh-Yen Lin, Yun-Nung Chen, Hung-yi Lee, and Shao-Hua Sun. On calibration of large language models: From response to capability. *arXiv preprint*

arXiv:2602.13540, 2026. URL https://arxiv.org/abs/2602.13540.

Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. MiniLM: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. In *Advances in Neural Information Processing Systems*, 2020. URL https://arxiv.org/abs/2002.10957.

AIMS Foundations. measurement-db: Public benchmark inventory and response data. Hugging Face dataset, 2026. URL https://huggingface.co/datasets/aims-foundations/measurement-db.

Sang Truong, Wale Salaudeen, Nhi Truong, Serena Wang, Angelina Wang, Luke Guerdan, Ziang Xiao, Xing Xie, Nick Haber, and Sanmi Koyejo. PAIEC predictor baselines. GitHub repository, 2026. URL https://github.com/aims-foundations/paiec_baseline.