

namaster-proof: Exact pseudo- C_ℓ window inference and content-bound validation for reproducible spin-2 analyses

Houston Golden
Independent researcher

July 16, 2026 — v2B.0.1

Abstract

namaster-proof is a focused Python verification layer for two error-prone steps in cut-sky spin-2 analyses. First, it evaluates a uniformly rotated EE, EB, BE, BB spectrum through the complete NaMaster bandpower-window operator, avoiding replacement of the operator by bin-centre or effective-multipole templates. Second, it writes JSON results and content-addressed sidecar receipts with atomic per-file replacement and fails closed when result bytes or caller-asserted execution metadata change. The package also supplies explicit multipole-support contracts, fixed-grid rotation-angle recovery, command-line receipt verification, and compatibility tests against the production helpers from which it was extracted. The software is intended for method validation and reproducibility checks; it is not a sky-analysis pipeline, foreground model, or cosmological inference engine.

1 Overview

Keywords. Python; cosmology; pseudo- C_ℓ ; NaMaster; reproducibility; provenance.

2 Introduction

Pseudo- C_ℓ estimators make masked spin-2 analyses computationally practical by relating full-sky spectra to coupled and decoupled bandpowers [1, 2]. Reproducible use of these estimators requires more than recording a best-fit number: the same window operator must be used in simulation and inference, harmonic limits must agree across fields and bins, and intermediate results must remain bound to their execution metadata.

namaster-proof packages these checks behind a small public API. Its numerical module constructs exact windowed responses for uniform polarization rotation, evaluates them at one or many angles, recovers an angle on a declared grid, and compares the window contraction with NaMaster’s couple–decouple operator. Its provenance module publishes a JSON result and a SHA-256-bound receipt using atomic replacement for each file, then verifies the pair and caller-asserted metadata. A third module defines deterministic multipole and binning contracts. NumPy is the only required dependency; a NaMaster workspace is supplied by the user when exercising the physical window operator.

3 Statement of Need

For two spin-2 fields, NaMaster exposes a bandpower-window tensor with spectrum ordering $[EE, EB, BE, BB]$. A common shortcut is to evaluate a theory spectrum at a representative multipole for each bin. That shortcut is not generally identical to applying the complete mode-coupling and binning operator, and a mismatch between the simulation and fitting operators can appear as a parameter-recovery bias.

A separate reproducibility risk arises in long or sharded calculations. Ordinary filenames do not prove that a summary corresponds to the intended seeds, realization count, configuration, or result bytes. A process can also terminate between writing a result and its metadata, leaving a plausible but incomplete artifact. These problems are usually addressed with analysis-local helpers. `namaster-proof` provides a reusable, tested implementation with explicit failure behavior, while remaining narrow enough to audit.

4 Implementation and Architecture

The package is divided into three modules:

windows	Rotation of EE, EB, BE, BB spectra, exact contraction with a <code>get_bandpower_windows()</code> tensor, fixed-grid angle recovery, and an equivalence check against <code>couple_cell()</code> followed by <code>decouple_cell()</code> .
Multipoles	Validation of a common harmonic cutoff and construction of integer bandpower edges whose final exclusive edge is $\ell_{\max} + 1$.
receipts	Atomic JSON publication, streaming SHA-256 calculation, sidecar-receipt construction, and fail-closed content and metadata validation.

The functions accept array-like inputs and return NumPy arrays or plain Python dictionaries. NaMaster is deliberately not an installation dependency: window functions use the small workspace protocol described above, which makes the algebra testable with synthetic linear operators and permits users to pin PyMaster independently.

5 Exact-Window Inference

For an initially vanishing EB spectrum and a uniform rotation angle β , the rotated spectra can be decomposed into angle-independent, $\cos(4\beta)$, and $\sin(4\beta)$ components. In particular,

$$C_\ell^{EE}(\beta) = \frac{1}{2}(C_\ell^{EE} + C_\ell^{BB}) + \frac{1}{2}(C_\ell^{EE} - C_\ell^{BB})\cos(4\beta), \quad (1)$$

$$C_\ell^{BB}(\beta) = \frac{1}{2}(C_\ell^{EE} + C_\ell^{BB}) - \frac{1}{2}(C_\ell^{EE} - C_\ell^{BB})\cos(4\beta), \quad (2)$$

$$C_\ell^{EB}(\beta) = C_\ell^{BE}(\beta) = \frac{1}{2}(C_\ell^{EE} - C_\ell^{BB})\sin(4\beta). \quad (3)$$

Let $W_{b\ell}^{ij}$ be the workspace tensor mapping input spectrum j to output spectrum i in band b . The package precontracts each of the three components,

$$R_b^{i,k} = \sum_{j,\ell} W_{b\ell}^{ij} C_\ell^{j,k}, \quad (4)$$

and subsequently evaluates

$$C_b^i(\beta) = R_b^{i,0} + \cos(4\beta)R_b^{i,c} + \sin(4\beta)R_b^{i,s}. \quad (5)$$

This retains the full window tensor while making repeated grid evaluation inexpensive. The recovery function minimizes a declared weighted or unweighted squared residual over a user-provided grid; its default is 2001 points spanning -1° to $+1^\circ$.

6 Content Validation

`publish_json` serializes a mapping with sorted keys, writes and flushes a process-specific temporary file, atomically replaces the result, and synchronizes the containing directory. It then separately publishes a sidecar receipt containing schema version, result filename, byte count, SHA-256 digest, and caller-supplied execution metadata. The content-binding fields are protected from metadata override.

`verify_json_receipt` requires both files, parses both as JSON objects, and recomputes every protected field. `validate_json_receipt` additionally checks caller-asserted metadata such as a suite identifier, seed range, or realization count. Missing files, malformed objects, changed bytes, changed receipts, or asserted-contract mismatches raise an exception. The two files are not one filesystem transaction, and coordinated replacement of both requires an external receipt anchor or trusted expected metadata to detect. The `namaster-proof verify` and `namaster-proof validate` commands expose the same behavior to shell workflows and return a nonzero status on failure.

7 Quality Control

Version 0.1.1 contains 23 automated tests covering numerical behavior, invalid inputs, the CLI, receipt mutation, protected fields, and compatibility with the original production helpers. The window suite uses an exactly represented synthetic linear workspace to compare the precontracted response with the couple-decouple route and to recover an injected grid angle. Rotation tests check conservation of total $EE + BB$ auto-power. Receipt tests mutate result bytes and receipt digests independently and require rejection.

Compatibility tests load the pre-package production modules and compare windowed bandpowers at negative, zero, and positive angles with zero requested absolute or relative tolerance. They also compare algebraic spectrum rotation, bandpower edges, and harmonic keyword contracts. In the associated physical production artifact, a workspace of shape $[4, 20, 4, 1025]$ gave a maximum absolute difference of 1.41×10^{-18} between direct window contraction and the couple-decouple operator. This recorded execution check used IEEE-754 double-precision arrays and the package’s zero-tolerance compatibility test; the original workspace tensor was not retained, so the scalar is not a self-contained reproducibility claim or a universal error bound.

8 Worked Examples

Minimal synthetic operator. The documentation constructs an identity-like workspace, builds a response from synthetic EE and BB arrays, evaluates a known rotation, and checks operator equivalence. This example has no dependency on a paper-specific dataset and is suitable for installation tests.

Synthetic CMB recovery campaign. The production use case employed CAMB 1.6.6 raw EE/BB spectra, PyMaster 2.6, $N_{\text{side}} = 512$, $\ell_{\text{max}} = 1024$, and deterministic seeds. For each of two nonzero injected angles, a 500-realization, foreground-free synthetic run recovered the injection from the mean bandpowers on the declared 0.001° grid: $0.270^\circ \mapsto 0.270^\circ$ and $0.342^\circ \mapsto 0.342^\circ$. The null injection recovered 0.000° . These are software-recovery checks under the stated simulation contract, not measurements, detection significances, or evidence for a physical birefringence model.

Sharded result validation. Production shards record fields such as suite, realization count, and seed range alongside the content digest. Aggregation can therefore reject a shard whose bytes were altered or whose declared range does not match the requested campaign, rather than silently combining it with valid results.

9 Limitations

namaster-proof does not create masks or maps, estimate covariance matrices, separate cosmic rotation from instrumental polarization calibration, model foregrounds, choose a likelihood, or infer cosmological parameters. Uniform rotation and initially vanishing EB are assumptions of the optimized three-component response; the general algebraic rotation helper accepts all four input spectra, but spatially varying rotation requires another model. Fixed-grid recovery inherits the range and resolution selected by the caller. Receipt validation establishes file integrity and agreement with caller-asserted metadata, not the scientific correctness of that metadata. SHA-256 sidecars are content bindings, not digital signatures, an authorization system, or protection against coordinated replacement without an external anchor. Schema version 1 has no migration requirement yet; a future incompatible schema will require an explicit reader or conversion path.

10 Availability

Operating system. The package is operating-system independent where Python and NumPy are available; CI covers Linux with Python 3.10–3.13.

Programming language and dependencies. Version 0.1.1 requires Python 3.10 or later and NumPy 1.24 or later. PyMaster is optional and is supplied by the user for physical NaMaster workspaces; the retained physical validation used PyMaster 2.6.

Code repository. The MIT-licensed source, issue tracker, installation instructions, API documentation, tests, and examples are available directly at [the namaster-proof package directory](#). Citation metadata are supplied in `CITATION.cff`.

Archive. A persistent archival identifier is not yet available. This is an explicit submission blocker, not a completed release claim. The submission candidate must bind version 0.1.1 to an immutable archive before journal submission.

Validation artifacts. The corrected physical example is bound to `results/physical_spectrum_v2/summary.json` (SHA-256 745b0a2f060773ce69c005ea84b74b305ec26a85f6aaafe58f0b3244b7f39914) and `bandpowers.npz` (SHA-256 b00f850e338007caea6af76f4e9305ab6b54a68e6799efd450bc76f1c325f331).

11 Reuse Potential

Researchers can reuse the window layer to test uniform spin-2 rotation models against any workspace exposing the small NaMaster protocol, reuse the multipole contracts to prevent field/bin support drift, or use the receipt layer for sharded JSON calculations outside cosmology. Extensions can add other angle-dependent spectrum bases, signed receipt anchors, or schema migrations. Questions, bug reports, and contributions are handled through the public repository issue tracker and pull-request workflow.

12 AI Usage Disclosure

AI coding and review agents assisted with implementation review, test generation, documentation, and manuscript editing. Their outputs were checked against committed source and retained numerical artifacts; executable claims were accepted only after local tests or direct recomputation.

Acknowledgements

The exact-window operations build on NaMaster [2] and the MASTER pseudo- C_ℓ method [1]. The production example used CAMB [3] and HEALPix [4].

Funding Statement

No external funding supported this software release.

Competing Interests

The author declares no competing interests.

References

- [1] E. Hivon, K. M. Górski, C. B. Netterfield, B. P. Crill, S. Prunet, and F. Hansen, “MASTER of the CMB anisotropy power spectrum: A fast method for statistical analysis of large and complex cosmic microwave background data sets,” *Astrophysical Journal* 567, 2 (2002), [doi:10.1086/338126](https://doi.org/10.1086/338126).
- [2] D. Alonso, J. Sanchez, and A. Slosar, “A unified pseudo- C_ℓ framework,” *Monthly Notices of the Royal Astronomical Society* 484, 4127–4151 (2019), [doi:10.1093/mnras/stz093](https://doi.org/10.1093/mnras/stz093).
- [3] A. Lewis, A. Challinor, and A. Lasenby, “Efficient computation of cosmic microwave background anisotropies in closed Friedmann–Robertson–Walker models,” *Astrophysical Journal* 538, 473–476 (2000), [doi:10.1086/309179](https://doi.org/10.1086/309179).
- [4] K. M. Górski, E. Hivon, A. J. Banday, B. D. Wandelt, F. K. Hansen, M. Reinecke, and M. Bartelmann, “HEALPix: A framework for high-resolution discretization and fast analysis of data distributed on the sphere,” *Astrophysical Journal* 622, 759–771 (2005), [doi:10.1086/427976](https://doi.org/10.1086/427976).