

VETRA — Site Documentation

This document explains what VETRA is, how the codebase is organized, what every page and feature does, how the pieces fit together, and what to do next if you want to turn this prototype into a production product. It covers the public marketing site, the buyer (customer) app, the vendor app, and the admin console.

1. What VETRA is

VETRA is a marketplace concept for buyers ("customers") and sellers ("vendors") in Nigeria, plus an internal **admin console** for VETRA staff to monitor and moderate the platform. Right now it is a **front-end prototype**: there is no server, no database, and no real authentication. Every page is a static HTML file styled with plain CSS and made interactive with small, dependency-free JavaScript files. Where a page needs to "remember" something between visits (currently only the admin console), it uses the browser's `localStorage` as a stand-in for a real database.

This matters for how you read the rest of this document: numbers like "₦1,284,300 revenue" or "58 orders" are **seed/demo data**, not real transactions. Buttons that say "Add Product," "Approve," or "Suspend" genuinely update the page and (in the admin console) persist across reloads — but only inside your own browser, not on a server other people can see.

2. Tech stack & conventions

- **No build step, no framework.** Plain HTML files, plain CSS files, plain `<script>` tags. Open any `.html` file directly in a browser and it works.
 - **One shared design system per app area.** `customer/assets/style.css`, `vendor/assets/style.css`, and `admin/assets/style.css` each define the *same* base design tokens and layout primitives (sidebar, header, bottom nav, stat cards, tables, modals, forms, switches). This is intentional, established duplication — each area's stylesheet is self-contained so a change in one app doesn't silently break another, at the cost of some repeated CSS between them. The root `style.css` is a separate, simpler design system used only by the public marketing pages (`index.html`, `about.html`, `contact.html`, `signin.html`, `signup.html`).
 - **"App shell" pattern.** Every logged-in page (customer, vendor, admin) uses the same skeleton: a collapsible left sidebar on desktop ($\geq 900\text{px}$), a bottom tab bar on mobile, a dark header with the VETRA logo, and a `<main class="page-shell">` content area. `assets/interactions.js` (customer, vendor) and `assets/ui.js` (admin) wire up the sidebar collapse/expand behavior identically in each area.
 - **Mock data lives in JS.** Product lists, orders, and customer/vendor records are hard-coded into the HTML or into a `assets/data.js` -style file, not fetched from an API.
 - **Live chat.** Every page includes the Smartsupp live-chat snippet, with `hideWidget: true` so it only opens when a page's "Support" icon calls `smartsupp('chat:open')` (see `assets/support.js`, shared verbatim between customer and vendor).
-

3. Folder map

VETRA/	
├─ index.html, about.html, contact.html	Public marketing site
├─ signin.html, signup.html	Buyer/Vendor auth (mock)
├─ style.css, signup.css	Public-site design system
├─ main.js, signin.js, signup.js	Public-site + auth page JS
├─ assets/brand/	Shared logo files (every app references these via <code>../</code>)
├─ assets/banners/	Dashboard banner images — admin-managed, see item 21
	(<code>banner-1.jpg</code> , <code>banner-2.jpg</code> are the seeded defaults)

```

└─ customer/                                Buyer-facing app
  └─ dashboard.html, explore.html (category browsing merged in),
    category.html (redirect stub → explore.html, see §5),
    store.html, vendors.html, product.html, cart.html,
    orders.html, chat.html, notifications.html, settings.html
  └─ assets/ (style.css, interactions.js, filters.js, orders.js,
    report-issue.js, products.js, cart-store.js,
    cart.js, badges.js, vendors.js, support.js)

└─ vendor/                                  Seller-facing app
  └─ dashboard.html, products.html, orders.html,
    earnings.html, profile.html, notifications.html
  └─ assets/ (style.css, interactions.js, product-actions.js,
    add-product.js, orders.js, order-tracking.js,
    reports.js, profile.js, kyc.js, payout.js, support.js)

└─ extras/                                  Retired/unused assets, kept but not referenced
  └─ logo.png, logo-mark.png, logo-mark-white.png, *-avatar-dummy.jpg

└─ admin/                                   NEW — staff-only console (this session)
  └─ login.html                             Admin sign-in gate
  └─ dashboard.html                         Platform overview
  └─ customers.html                         Manage buyer accounts (list)
  └─ customer-detail.html                   One customer's full profile + activity
  └─ vendors.html                           Manage vendor stores (list)
  └─ vendor-detail.html                     One vendor's full profile + activity
  └─ reports.html                           Reports & disputes queue
  └─ activity.html                          Audit trail / activity log
  └─ settings.html                          Admin profile, team, platform switches
  └─ assets/ (style.css, data.js, ui.js, dashboard.js, customers.js,
    customer-detail.js, vendors.js, vendor-detail.js,
    reports.js, activity.js, settings.js)

```

4. Public site

Page	Purpose
<code>index.html</code>	Landing page — hero, featured categories/products, marketing content.
<code>about.html</code>	Brand story / mission.
<code>contact.html</code>	Contact info / form (static).
<code>signin.html</code>	Buyer/Vendor sign-in, toggled by a "Buyer / Vendor" tab. A small "Admin sign in" link at the bottom now routes staff to <code>admin/login.html</code> .
<code>signup.html</code>	Buyer/Vendor account creation, same toggle pattern as sign-in; supports a <code>#Vendor</code> URL hash to land directly on the vendor tab.

How sign-in "works" today: `signin.js` validates only that the visible fields aren't empty, then redirects — Buyer → `customer/dashboard.html`, Vendor → `vendor/dashboard.html`. No password is actually checked and no session is created. `admin/login.html` follows the same mock pattern, redirecting to `admin/dashboard.html`. **This is the single most important thing to replace before going live** — see §9.

index.html

- `.buy-now-btn` (4x, "Popular this week" product cards) — Each button carries `data-product`, `data-price`, `data-vendor`. Click opens the checkout modal via `openCheckout(btn)` in `script.js:92`. Populates `#checkout-vendor`,

`#checkout-product-name`, `#checkout-product-price`, `#checkout-total-price` (`price + flat_deliveryFee = 1500`, `script.js:75`), resets the 4 guest-detail fields, then unhides `#checkout-overlay`. State: none persisted, plain DOM.

- **#checkout-confirm-btn ("Confirm purchase")** — `script.js:125-154`. Validates all 4 fields (`checkout-name`, `checkout-phone`, `checkout-email`, `checkout-address`) are non-empty; email additionally checked against `emailPattern = /^[^\s@]+@[^\s@]+\.[^\s@]+$/` (`script.js:90`). Invalid/empty fields get `style.borderColor = '#e0475c'` and focus jumps to the first bad field. On success: button text → "Processing...", disabled, then after a 700ms `setTimeout` swaps `#checkout-step-review` for `#checkout-step-success` and fills `#checkout-success-text` with an interpolated confirmation message. No real order is created (// TODO: replace with a real checkout/payment API call.).
- **#checkout-cancel-btn / #checkout-close-btn / clicking the overlay backdrop / Escape key** — all call `closeCheckout()` (`script.js:117`), which just sets `checkoutOverlay.hidden = true`.
- **.nav-toggle (mobile hamburger)** — `script.js:2-14`. Toggles `.open` class on `.nav-links` and flips `aria-expanded`; clicking any nav link also closes the menu.
- **Smartsupp support widget** — not present on this page as a dedicated support button (`index.html` has no sidebar); the Smartsupp snippet loads but stays hidden until interacted with globally.

about.html

- No interactive JS-driven elements beyond the shared `.nav-toggle` mobile menu (`script.js:2-14`) — the rest of the page is static marketing content. `script.js`'s FAQ-accordion and checkout-modal code look for elements (`.faq-item`, `#checkout-overlay`) that don't exist on this page, so those code paths simply no-op (`if (!q || !a) return;` etc.).

contact.html

- **.audience-toggle button[data-mode] ("I'm a buyer" / "I'm a Vendor" tabs)** — `script.js:35-48`. Click toggles `.active` on the clicked button, then shows/hides `#buyer-fields` vs `#Vendor-fields` by setting `style.display = 'grid' / 'none'`. Pure DOM toggle, no validation change (both field groups' inputs are optional; only `#name`, `#email`, `#message` on the base form carry `required`).
- **#contact-form submit ("Send message" button)** — `script.js:51-61`. `e.preventDefault()`, swaps the submit button's text to "Message sent", calls `form.reset()`, then restores the original button text after a 2600 ms `setTimeout`. No network request — the reset happens immediately, so the "sent" state is purely cosmetic feedback and the form fields are already cleared before the label reverts.
- **.faq-item .faq-q (4 FAQ questions)** — `script.js:17-32`. Click toggles `.open` on the clicked `.faq-item`; closes any other currently-open item first (single-open accordion), and animates via `el.querySelector('.faq-a').style.maxHeight = a.scrollHeight + 'px'` (or `null` when closing).

signin.html

- **.toggle button[data-mode] (Buyer / Vendor tabs)** — `signin.js:8-30`. Toggles `active / aria-selected` on buttons, shows/hides `#buyer-form` vs `#Vendor-form` via `.hidden` class, updates `.subtitle` copy, and hides `#guest-continue-wrap` when on the Vendor tab (guest checkout is buyer-only). Also runs on page load if URL has `#Vendor` hash (`signin.js:34-37`), auto-clicking the Vendor tab button — this is how `signup.html`'s post-registration redirect and `index.html`'s "Become a Vendor" links land users on the right tab.
- **.continue-btn ("Continue")** — `signin.js:50-82`. Reads whichever form (`buyer-form`'s `#username / #password`, or `Vendor-form`'s `#store-username / #Vendor-password`) matches the active tab. Validation: both fields must be non-empty (no format/regex check) — empty fields get `borderColor = '#e0475c'`. On success: button text → "Signing in...", disabled, then after 250ms redirects via `window.location.href` to `DASHBOARD_PATHS[activeMode]` (`signin.js:45-48`): `customer/dashboard.html` for buyer, `vendor/dashboard.html` for Vendor. No real auth — this is purely a mock gate.
- **.google-btn ("Continue with Google")** — no JS handler attached anywhere; clicking does nothing (dead button, not wired).
- **#guest-continue-link ("Continue as Guest →")** — plain `<a href="customer/dashboard.html">`, no JS — a direct navigation link (buyer tab only; the whole `#guest-continue-wrap` is hidden on the Vendor tab).
- **Password show/hide toggle** — injected by `password-toggle.js:18-50` on every `input[type=password]` on the page (so both `#password` and `#Vendor-password`). Wraps the input in `.password-field-wrap`, appends a `.password-toggle-btn`; click flips `input.type` between `password / text` and swaps the eye/eye-slash SVG icon. Local DOM state only (`input.type`), resets on reload.

signup.html

- **.toggle button[data-mode] (Buyer / Vendor tabs)** — `signup.js:7-31` via `activateMode(mode)` . Same pattern as `signin.js`: toggles active state, shows/hides `#buyer-form` / `#Vendor-form` , updates `.subtitle` . Runs on load if `location.hash === '#Vendor'` (`signup.js:28-31`) — this is the entry point for `index.html` 's `signup.html#Vendor` links and `vendor-protection.html` 's "Become a Vendor" CTA.
- **.continue-btn ("Continue")** — `signup.js:33-62` . Validates every `input` inside whichever form is active is non-empty (`requiredFields.forEach` , checks `field.value.trim()`); the enclosing `.input-wrap` gets `style.borderColor = '#e0475c'` per empty field, cleared to `' '` when valid — no other validation (no email-format or phone-length regex despite `type="email"` / `type="tel"` inputs). On success: button text → "Creating account..." , disabled, then after `400ms` redirects to `signin.html` (buyer) or `signin.html#Vendor` (Vendor) via `window.location.href` (`signup.js:58-60`). No account is actually created anywhere.
- **.google-btn** — unwired, same as `signin.html`.
- **Password toggle** on `#password` and `#Vendor-password` — same `password-toggle.js` behavior as `signin.html`.

buyer-protection.html / vendor-protection.html

- No page-specific JS interactions — purely static informational/marketing content (hero, value-grid cards, step timelines, CTA links). Only the shared `script.js` mobile-nav toggle (`.nav-toggle`) applies, and neither page has the FAQ/checkout/contact-toggle elements those code paths target, so those parts of `script.js` no-op. All links (`start shopping` , `Become a Vendor` , `Talk to support` , etc.) are plain anchor navigation, not JS-driven.

5. Customer (buyer) app

All pages live in `customer/` and share both the sidebar and the mobile bottom nav: **Home, Explore, Orders, Chat, Profile** — item 20 below added Chat to the bottom nav so the two now match exactly (it used to be sidebar-only). Cart and Notifications are header icons rather than sidebar items on every page.

Category and Explore used to be two separate, near-duplicate browse pages (same filter panel, same product-grid pattern) — they were merged into one `explore.html` , and Order History and a direct Support entry point were added to the nav in the same pass; see item 17 below for the full write-up.

Page	What it does
<code>dashboard.html</code>	Home feed: picture-only promo banner carousel, admin-managed (see item 21 and admin's Settings → Site Banners), a category rail that links into <code>explore.html</code> pre-filtered, and a featured product grid — every card opens <code>product.html</code> and has a real Add to Cart .
<code>explore.html</code>	Full product browse grid and category browsing in one page: a picture-only, admin-managed promo banner (same one <code>dashboard.html</code> shows — see item 22) sits above a row of category quick-filter chips (8, styled like the trending chips above them — no image grid), then the filter panel + product grid, whose own category checkboxes cover the same 8 categories plus Sports — this is where <code>category.html</code> 's browsing job now lives. Same real click-through/add-to-cart as <code>dashboard.html</code> .
<code>category.html</code>	Redirect stub only — <code>window.location.replace('explore.html' + location.search)</code> , so old links/bookmarks (including <code>category.html?cat=X</code> deep links) still land correctly. No real page content anymore; see item 17.
<code>store.html</code>	A single vendor's storefront (name, products, and a Reviews section — see below) — <code>id="store-name"</code> is filled in by JS from a query param/mock lookup. Product cards open <code>product.html</code> and add to the real cart, same as the other browse pages. Its vendor data now lives in the shared <code>assets/vendors.js</code> (item 20), not an inline object local to this page.
<code>vendors.html</code>	New — a directory of every vendor on VETRA, with a live search-by-name box. Reached from <code>explore.html</code> 's "TOP VENDORS" → "See more", which was previously an inert button. See item 20.
<code>product.html</code>	New — a single product's full detail page (image, price, description, "Sold by" link, quantity + Add to Cart, reviews). See below.
<code>cart.html</code>	Real cart contents rendered from <code>CartStore</code> — quantity steppers, remove, and an order summary that recomputes from actual line items. No static/dummy data.

Page	What it does
<code>orders.html</code>	New — order history and per-order delivery tracking. Status filter tabs (All/Pending/Processing/Shipped/Out for delivery/Delivered/Cancelled) via <code>wireOrderFilterTabs</code> ; each order card is also a click-to-expand accordion (<code>wireOrderExpand</code> , both in <code>assets/orders.js</code>) revealing a step timeline (Placed → Processing → Shipped → Out for delivery → Delivered) that mirrors the escrow flow described on <code>../buyer-protection.html</code> . Each order's Report an issue button opens a real "File a report" modal (see below) rather than just opening live chat. Now a direct sidebar/bottom-nav item (see item 17) — also still reachable from Settings → Account overview → "View orders" and from the "Order delivered" notification card on <code>notifications.html</code> .
<code>chat.html</code>	Buyer↔vendor messaging UI — conversation list + message thread, styled like a chat app (not connected to a real messaging backend).
<code>notifications.html</code>	List of notification cards (order updates, promos); the "Order delivered" card links to <code>orders.html</code> .
<code>settings.html</code>	Account & preference toggles (notifications, etc.); the "Orders placed" row under Account overview links to <code>orders.html</code> ; a Help & Support card holds the "Contact support" entry point that used to live in the sidebar/bottom-nav (see item 17).

`customer/assets/interactions.js` wires: sidebar collapse/reopen, the banner carousel's dots, `wireProductCardClicks` (any `[data-product-id]` card opens `product.html?id=<id>`), `wireAddToCartButtons` (adds the real product to `CartStore` , see below), and `updateCartBadge` (keeps every page's header cart icon showing a live item count).

Real cart + product catalog (`assets/products.js` , `assets/cart-store.js`). Closes a gap where "Add to Cart" only ever navigated to `cart.html` with nothing in it. `products.js` is a shared, hard-coded `PRODUCTS` catalog (23 entries, keyed by id) covering every product shown on `dashboard.html` / `explore.html` / `store.html` — the same "Gaming Laptop" on the dashboard and on Godsfavour Laptops' store page is now literally one catalog entry (`vendorId: 'gods-favour'`), not two coincidentally-matching listings. `cart-store.js` 's `CartStore` persists `{id, qty}` pairs to `localStorage` (key `vetra_customer_cart`) and always re-resolves name/price/image from the catalog live, so a cart line can never drift out of sync with it. Every product card across those pages carries `data-product-id=<id>` , which is what both the click-to-detail and add-to-cart handlers key off.

Product badges — "New" / "Hot" (`assets/products.js` 's `getProductBadge()` , `assets/badges.js`). Used to be 5 hand-typed `<span class="product-badge hot/new">` elements sitting in `explore.html` 's markup only — the same "Gaming Laptop" showed "New" there but nothing on `dashboard.html` , with no data behind which products got a badge or why (and a "Trending" label that was just alternate text on the same `.hot` CSS class — not a distinct concept in the code). Replaced with real, data-driven logic: every catalog entry in `products.js` now has `createdAt` (an ISO date) and `salesCount` (an int); `getProductBadge(product)` returns "New" if `createdAt` is within the last 21 days, else "Hot" if `salesCount` `>= 50` , else nothing — "New" wins if a product happens to qualify for both. `badges.js` 's `decorateProductBadges()` applies that decision to the DOM: for every `[data-product-id]` card, it clears any existing `.product-badge` and (if `getProductBadge()` returned one) prepends a fresh one into the card's thumbnail wrapper. Called on `DOMContentLoaded` for `dashboard.html` / `explore.html` (static card markup) and right after the grid is built for `store.html` (JS-templated cards) — the same product now shows the identical badge everywhere it appears, which the old hardcoded version never guaranteed. See `BACKEND_GUIDE.md` §3 ("Product badges") for exactly how `createdAt` / `salesCount` should come from real columns/queries once a backend exists — the front-end logic itself doesn't need to change.

Reviews (`store.html`). Each mock vendor in the page's `VENDORS` object now carries a `reviews` array (name, rating, date, text), rendered as an average-score summary plus a review-card list, both tagged "Verified purchase" per the "verified reviews only" claim made elsewhere on the site. A "Write a review" form (star-picker + textarea) prepends a new review in-memory on submit — since there's no backend, it can't actually check for a completed order, so the form's hint text says as much and every submission is treated as if that check passed.

File a report (`orders.html` , `customer/assets/report-issue.js`). Each order's "Report an issue" button now opens a real modal — a reason dropdown, a details textarea, and a note pointing to `../buyer-protection.html` 's escrow-hold explanation — instead of just opening live chat. This was, until item 21, the one place in the customer app that broke the "customer pages never touch admin's `localStorage` " rule (`dashboard.html` 's banner does now too — see item 21): `orders.html` loads `../admin/assets/data.js` directly and calls its new `VetraAdmin.addReport()` function, so a report filed here actually lands in the same `vetra_admin_state_v1` state `admin/reports.html` reads — tested and confirmed to show up there, attributed to the (mock) signed-in buyer "Amaka Obi," with no false "handled by an admin" attribution on the activity-log entry (`logActivity()` gained a `systemEvent` option specifically so a buyer-originated event doesn't get credited to whichever admin last signed in on that browser). Each order card carries a `data-vendor-id` matching a real `admin/assets/data.js` vendor id where one exists (`Naija Home Essentials` → `v3`) and a synthetic one otherwise (the customer app's own separate `store.html` vendor

directory was never unified with admin's vendor list — see §8) — either way the report is created and queued correctly, it just won't deep-link to a real vendor-detail page for the synthetic ids. Submitting swaps the button for a "Report filed" tag so the same order can't be reported twice.

Shared JS loaded on nearly every page: `assets/interactions.js` (sidebar collapse/reopen, banner carousel, global add-to-cart delegation) and `assets/support.js` (Smartsupp live-chat open/close). Both are IIFEs/top-level listeners bound on `DOMContentLoaded`.

Shared interaction reference (applies to every customer page unless noted): - **#header-sidebar-toggle** — `Vetra.wireSidebarToggle()` (`customer/assets/interactions.js:18-37`). Toggles `.hidden-desktop` on `#app-sidebar`, sets inline `display: none / ''`, and shows `#app-sidebar-reopen` (adds `.show`) when hidden. - **#app-sidebar-reopen** (floating ≡ button) — same function, `interactions.js:30-36`; un-hides the sidebar and hides itself. - **#sidebar-collapse-toggle** (chevron inside sidebar) — `Vetra.wireSidebarCollapse()` (`interactions.js:39-47`); toggles `.collapsed` on `#app-sidebar` (icon-only rail mode). - **.support-btn** — no longer in the sidebar/bottom-nav (see item 17); now a single "Contact support" button in `settings.html`'s Help & Support card. Same global delegated click listener in `customer/assets/support.js:75-80` calls `openLiveChat()` (`support.js:68-73`), which adds `body.livechat-open`, calls `smartsupp('chat:open')`, and lazily injects a `#livechat-close-btn` (`ensureCloseButton()`, `support.js:44-66`) whose click calls `smartsupp('chat:close')` then `window.location.reload()` — the listener itself is unchanged, only where the trigger element lives moved. - **[data-product-id] cards** (any product card on dashboard/explore/store) — `Vetra.wireProductCardClicks()` (`interactions.js`); clicking anywhere on the card except a real `<a>` / `<button>` opens `product.html?id=<id>` - **.add-cart / .add-btn** (any "Add to Cart" button on any product card, delegated at `document` level) — `Vetra.wireAddToCartButtons()`; calls `CartStore.addItem(productId, 1)` (reading `data-product-id` off the closest card), shows "Added ✓" on the button for 1200ms, and calls `updateCartBadge()`. Falls back to navigating to `cart.html` only if the button's card has no `data-product-id` at all (shouldn't happen on any current page — a defensive fallback, not the normal path).

customer/dashboard.html

- **Banner carousel (#app-banner)** — now picture-only (no text/color overlay) and admin-managed rather than 2 hard-coded slides; see item 21. An inline script (loaded after `../admin/assets/data.js`) builds `.banner-slide / .dots` markup from `VetraAdmin.getSiteBanners()` on `DOMContentLoaded` — each slide is just an `<img class="banner-slide-img">`, nothing else — falling back to a 2-image `DEFAULT_BANNERS` constant if `VetraAdmin` isn't available or no banners are set, then calls `Vetra.wireBannerCarousel()` itself once the slides exist (the automatic call from `Vetra.init()` runs first and no-ops, since the markup ships empty). Dots — `Vetra.wireBannerCarousel()`. Click on a dot calls `goTo(index)`, swapping `.active` between `.banner-slide` elements and their matching dot; also auto-advances every `4000ms` via `setInterval`.
- **"See more" (.cat-head .see-more)** — plain `<button>`, no `id` / handler anywhere in the codebase; currently inert (does nothing on click).
- **Category rail (.cat-card , 5 tiles)** — click navigates to `explore.html?cat=<name>`, which pre-filters that page's grid to the matching category (or shows an honest "no products yet" if this demo has none in it). Previously an unlinked, inert `<div>` — see §8. Pointed at `category.html` until item 17 merged that page into `explore.html`.
- **Product cards (6, [data-product-id])** — click anywhere on the card (except a real link/button) opens `product.html?id=<id>` (`Vetra.wireProductCardClicks()`); the **Add to Cart** button adds the real product to `CartStore` — see the shared reference above and §8's fix write-up.
- **Header icon links (notifications.html , cart.html , settings.html via avatar)** — plain `<a>` navigation, not JS. The cart icon additionally shows a live `.cart-count-badge` when the cart is non-empty.

customer/explore.html

As of item 17, this page carries everything the old `category.html` used to, in addition to its own original content — there is no longer a separate category-browsing page.

- **Category quick-filter chips (.category-chip , 8 buttons)** — plain `<button>`s reusing the `.trending-chip` pill styling (same look as the "Power bank / Wireless earbuds / ..." row above them), not an image grid — `category.html`'s old `.categories-grid / .category-card` tile grid was removed in favor of this, per direct feedback that it should be simple buttons instead. Each button's `data-category` is read on click and passed to `filterByCategory(name)` (an export from `initProductFilters()`, `filters.js`); since the filter panel now has a matching `[data-filter-category]` checkbox for all 8 of these categories (plus Sports), every chip click resolves through the normal "check the box, re-run `applyFilters()`"

path — including a category with zero matching products in this page's grid, which correctly ends up at 0 visible results and the filter panel's own generic empty-state text (no category-specific wording needed anymore, since there's no longer a case where a clicked category *lacks* a filter-panel checkbox). Also reads a `?cat=<name>` query param on page load and calls the same function, so `dashboard.html` 's category rail (and `category.html` 's redirect) can deep-link in pre-filtered.

- **Filter button** `#exploreFilterBtn` — `initProductFilters()` in `customer/assets/filters.js`, invoked with `{ triggerSelector: '#exploreFilterBtn', panelId: 'exploreFilterPanel', gridSelector: '#app-products .grid' }` (inline script at the bottom of the page). Click toggles `.open` on `#exploreFilterPanel` (`filters.js:78-80`); clicking anywhere outside the panel/button while open closes it (`filters.js:82-86`, delegated document click listener).
- **Filter panel controls** (`#exploreSortSelect`, category checkboxes `[data-filter-category]` — now 9 categories: the 8 quick-filter chips' categories (Appliances, Phones & Tablets, Health & Beauty, Home & Office, Electronics, Fashion, Computing, Supermarket) plus Sports, so every chip and every product's category has a matching checkbox — price checkboxes `[data-filter-price]`) — each `change` event runs `applyFilters()` (`filters.js:28-76`):
- Reads checked `[data-filter-category]` values and checked `[data-filter-price]` values (each price checkbox's value is a "min-max" string, e.g. `"0-20000"`, `"150000-0"` where 0 upper bound means unbounded — `filters.js:44-50`).
- A card matches if `catMatch` && `priceMatch` where `catMatch` requires `card.dataset.category` to be in the selected set (or no categories selected = match-all), and `priceMatch` requires `card.dataset.price` (parsed `Number`) to fall in at least one selected bucket.
- Non-matching cards get `style.display = 'none'`.
- Sorting: `sortValue` from `#exploreSortSelect` — `price-asc / price-desc` sort numerically on `data-price`; `name-asc` uses `data-name.localeCompare`; `featured` preserves original DOM order. Sorted cards are re-appended into the grid (`sorted.forEach((card) => grid.appendChild(card))`).
- Updates `filterBtn` 's `.active` class (non-zero selection count) and the `[data-filter-count]` text ("Showing X of Y" / "Showing all N").
- Creates a `.filter-empty-state` div once, lazily (`ensureEmptyState()`, `filters.js:19-26`), shown/hidden based on `visibleCount`.
- `[data-filter-clear]` ("**Clear filters**") — `filters.js:92-102`. Unchecks every checkbox, resets the sort `<select>` to "featured", re-runs `applyFilters()`.
- **Banner** (`#app-banner`) — picture-only and admin-managed, identical setup to `dashboard.html` 's (same inline script, same `../admin/assets/data.js` load, same `VetraAdmin.getSiteBanners()` call) — see item 22. Previously had its own hard-coded text+image slides with different copy ("Explore" / "Featured Vendors") from `dashboard.html` 's; now both pages render the exact same admin-controlled image list, so there's one banner to manage, not two to keep in sync by hand.
- **Product cards** (12, `[data-product-id]`) — the original 6 plus `category.html` 's 6 (Premium Laptop Stand, Wireless Headset, USB-C Cable, Phone Stand, Power Bank, Screen Protector), re-rendered onto this page's own `.product / .product-img` card markup (they used `.product-card / .product-thumb` on the old page — same catalog entries via `products.js`, just re-templated to match this grid's existing card style). Click → `product.html?id=<id>`; **Add to Cart** → real `CartStore.addItem()`.
- **Vendor mini-cards** (`.vendor-mini-card`, e.g. `store.html?vendor=gods-favour`) — plain anchor links to `store.html`, not JS-driven.
- **"See more" (Top Vendors, .vendor-rail .see-more)** — a plain `<a href="vendors.html">`, not JS. Used to be an inert `<button>`; see item 20.
- **Trending chips** (`.trending-chip`) — plain `<a href="#">`, no handler.

`customer/vendors.html` — new, see item 20

Reached from `explore.html` 's "TOP VENDORS" → "See more". All logic is an inline `<script>` at the bottom of the page.

- **Vendor grid** (`#vendorDirectoryGrid`) — rendered from `getAllVendors()` (`assets/vendors.js`) via a `.map().join('')` template on page load; each card (`.vendor-card`) shows avatar, name, a `.status-pill` (`verified / pending`, reusing the same pill styling `vendor/orders.html` 's shipment-status pills use), category, rating, and location, and links to `store.html?vendor=<id>`.
- **#vendorSearchInput** — `input` event re-renders the grid, filtering `getAllVendors()` client-side by `vendor.name.toLowerCase().includes(query)`. No backend, so this is the same in-memory list every render, not a real search endpoint. An empty result set hides the grid and shows `#vendorDirectoryEmpty` with the literal typed query echoed back (`No vendors match "<query>"`) rather than silently showing nothing.

- **#vendorDirectoryCount** — " `N` vendors on VETRA" with no active search, or "Showing `x` of `N` vendors" while a search query narrows the list.
- **#vendors-back-btn** — same referrer-based `history.back()` / fallback-to- `explore.html` pattern as `store.html` 's and `product.html` 's back buttons.

customer/category.html — now a redirect stub, see item 17

No longer a real page. Its `<head>` fires `window.location.replace('explore.html' + window.location.search)` immediately (plus a `<meta http-equiv="refresh">` fallback and a plain link in the body, in case JS is disabled). This exists only so old links/bookmarks — including `category.html?cat=Electronics` -style deep links — still land somewhere correct; every internal link that used to point at `category.html` was updated to point at `explore.html` directly instead (so the redirect hop isn't actually hit from anywhere in the app itself anymore).

customer/product.html — new

`?id=<id>` looks the product up in `products.js` 's shared `PRODUCTS` catalog (`getProduct(id)`); an unknown/missing id shows a `#product-not-found` empty state with a link back to Explore instead of a blank page. Renders image, category, name, price, location (if the catalog entry has one), a "Sold by `<vendor>`" link (only shown when `vendorId` is set — not every product has one), and the description.

- **Quantity stepper (`#pd-qty-decrement` / `#pd-qty-increment`)** — plain local `qty` variable (min `1`), not tied to stock — this page doesn't model stock levels.
- **#pd-add-to-cart ("Add to Cart")** — `CartStore.addItem(product.id, qty)` , then `Vetra.updateCartBadge()` , then the same "Added ✓" / disabled-for-1200ms feedback pattern the card buttons use. Deliberately **not** given the `.add-cart` class the card buttons use — see §8's bug write-up for why sharing that class here broke the button entirely.
- **Reviews section** — byte-for-byte the same pattern as `store.html` 's (star-input, `#review-form` , `renderReviewSummary()` / `renderReviewList()`), just scoped to `product.reviews` instead of `vendor.reviews` . Same in-memory-only caveat: a submitted review is lost on reload.
- **Back button (`#product-back-btn`)** — same referrer-based `history.back()` / fallback-to- `explore.html` pattern as `store.html` 's back button.

customer/store.html

Most logic lives in an inline `<script>` block at the bottom of the page. Vendor "database" is the shared `VENDORS` object in `assets/vendors.js` (item 20 — previously a hard-coded object local to this file only) keyed by `gods-favour` , `daniel-ice-fish` , `jennet-jeans` , `me-n-u-chops` ; `vendors.html` 's directory reads the same object via that file's `getAllVendors()` .

- **Page load** — reads `?vendor=<id>` from the URL (`new URLSearchParams(window.location.search).get('vendor')`), looks it up in `VENDORS` , falling back to `VENDORS['gods-favour']` if missing/unknown (`store.html:367-369`). Populates `#store-avatar` , `#store-name` , `#store-bio` , `#store-rating` , `#store-orders` , `#store-response-time` , `#store-location` , `#store-member-since` , sets `#store-cover` 's `background-image` (vendor's cover image or `coverGradient` CSS string), sets `#store-category` text + toggles `.pending` class if `vendor.status === 'pending'` , and injects a verified-badge SVG into `#store-verified-badge` only if `vendor.status === 'verified'` .
- **#store-message-link ("Message Vendor")** — its `href` is set programmatically to `chat.html?chat=${vendorKey}` (`store.html:394-395`) so it deep-links straight into that vendor's conversation on `chat.html` .
- **#store-call-btn (phone icon button)** — click handler at `store.html:397-400` just calls `alert('Calling ${vendor.name} — hook this up to your call flow.')` . Not a real call.
- **#store-back-btn (chevron "back" button)** — `store.html:402-410` . If `document.referrer` exists and shares the page's origin, calls `window.history.back()` ; otherwise redirects to `explore.html` .
- **Products grid (`#storeProductsGrid`)** — rendered from `vendor.products` array via a `.map().join('')` template; each product object now also carries an `id` matching an entry in `products.js` 's shared `PRODUCTS` catalog (e.g. `gods-favour-wireless-mouse`), rendered onto the card as `data-product-id` . Click → `product.html?id=<id>` ; each card's "Add to cart" button (`.add-btn`) → the same real `CartStore.addItem()` path every other page's cards use.
- **Star rating input (`#star-input` .`star-btn` , 5 buttons)** — `setStars(value)` (`store.html:470-475`) sets `starInput.dataset.value` and toggles `.active` on every button whose `data-star` is `<=` the clicked value (so clicking star 3 highlights 1-2-3). Local DOM state only (`starInput.dataset.value`), reset to `0` after each successful submission.
- **#review-form submit ("Submit review")** — `store.html:481-507` . Reads `rating = Number(starInput.dataset.value)` and `text = document.getElementById('review-text').value.trim()` . Validation:

```
if (!rating) alert('Please select a star rating before submitting.') and returns; if (!text) {
  textEl.focus(); return; } (empty text silently blocks submit, no message). On success: reviews.unshift({ name:
  'You', rating, date: new Date().toISOString().slice(0,10), text }) — prepends to the in-memory reviews array
(a .slice() copy of vendor.reviews, store.html:430), then re-renders both renderReviewSummary() (average score
+ star count, store.html:432-447) and renderReviewList() (store.html:449-462, every review — including the new
one — tagged "Verified purchase" regardless of any real purchase check, per the page's own comment that this can't actually
verify an order). Resets the star input and clears the textarea. State is entirely in-memory (the reviews array closure
variable) — reloading the page loses the new review.
```

customer/cart.html

Completely rebuilt on top of `CartStore` — no more static/dummy `.cart-item` rows. `renderCart()` reads `CartStore.getItems()` on every change and either shows `#cart-empty-state` (genuinely empty cart — a "Your cart is empty" message + a link to Explore) or `#cart-content` (the real line items + summary), toggled via `hidden` rather than both existing in the DOM with one hand-waved as a placeholder.

- **Per-item row** — image + name link to `product.html?id=<id>`; a "Visit store" link appears only when the product has a `vendorId`. Quantity — / + (`data-action="decrement" / "increment"`) call `CartStore.setQty(id, newQty)` — `setQty` itself removes the line entirely once qty reaches 0, so decrementing from 1 behaves the same as Remove. **Remove** (`data-action="remove"`) → `CartStore.removeItem(id)`. All three re-render the whole cart and call `Vetra.updateCartBadge()`.
- **Order summary** — `subtotal` is `CartStore.getSubtotal()` (sum of `product.price * qty` across real items, always current); `delivery` is a flat `DELIVERY_FEE = 1500` constant (matching the homepage's own mock checkout modal); `total = subtotal + delivery`.
- **"Save for later"** — unchanged placeholder: `alert('Cart saved for later (hook this up to your save-for-later API).')`
- **"Checkout"** — disables itself, shows "Processing...", then after 600ms: `alert('Order placed!...')`, `CartStore.clear()` (the cart is genuinely emptied, not just visually), updates the badge, and redirects to `dashboard.html`.
- Dropped from this rebuild: the old per-item delivery/pickup radio buttons and the "Contact vendor" button that opened the generic chat list — neither was backed by real per-item data; "Visit store" (above) is the real-data replacement where a vendor link makes sense.

customer/orders.html

Loads `../admin/assets/data.js` directly (the **only** place in the customer app that touches the admin `localStorage` state, key `vetra_admin_state_v1`), plus page-specific `customer/assets/orders.js` and `customer/assets/report-issue.js`.

- **Status filter tabs (`#order-filter-tabs .filter-tab[data-filter]`)** — `wireOrderFilterTabs()` (`customer/assets/orders.js:14-34`). Click sets `.active` on the clicked tab only, then shows/hides each `.order-card` in `#order-list` by comparing `filter` to `card.dataset.status` (values: `all`, `pending`, `processing`, `shipped`, `out-for-delivery`, `completed`, `cancelled`) — non-matching cards get `style.display = 'none'`.
- **Order card summary (`.order-card-summary`, `click-to-expand`)** — `wireOrderExpand()` (`orders.js:36-49`), delegated on `#order-list`. Click toggles `.open` on the parent `.order-card` (independent per-card accordion — multiple can be open at once) and sets `aria-expanded` on the summary button. Reveals `.order-track-panel`'s step timeline via CSS keyed off `.open`.
- **"Report an issue" (`[data-action="report-issue"]`, per order card)** — `customer/assets/report-issue.js`. Delegated click on `#order-list` (`report-issue.js:47-52`) finds the closest `.order-card` and calls `openModal(card)` (`report-issue.js:31-39`): sets `#report-order-id / #report-vendor-name` text from the card's `data-order-id / data-vendor-name`, resets `#report-form`, un-hides `#report-modal`, locks page scroll (`document.body.style.overflow = 'hidden'`), focuses `#report-reason`.
- **Close paths** — `#report-modal-close`, `#report-cancel-btn`, clicking the overlay backdrop, or `Escape` — all call `closeModal()` (`report-issue.js:41-45`).
- **#report-form submit ("Submit report")** — `report-issue.js:63-94`. Validation is native HTML5 required on `#report-reason` (a `<select>`) and `#report-details` (a `<textarea>`) — no custom regex. On submit: builds `reason = "${reasonSelect.value} (${orderId}): ${detailsInput.value.trim()}"`, then (if `VetraAdmin` is defined, i.e. the admin script loaded) calls `VetraAdmin.addReport({ type: 'vendor', targetId: vendorId, targetName: vendorName, reporter: CURRENT_BUYER, reason })` (`admin/assets/data.js:361`), where `CURRENT_BUYER = "Amaka Obi"` is hard-coded (`report-issue.js:20`) standing in for a real signed-in session. This writes into the same `localStorage`-backed state `admin/reports.html` reads. Each order card's `data-vendor-id` maps to a real admin vendor id only for `Naija Home`

Essentials → v3 ; the other three order cards use synthetic ids (`jennet-jeans` , `gods-favour` , `me-n-u-chops`) that don't match any admin vendor record, so a report against them lands in the queue but can't deep-link to a real vendor-detail page.

- After submit, the triggering `[data-action="report-issue"]` button is replaced in the DOM with a `<span class="report-filed-tag">Report filed</span>` (`report-issue.js:85-90`), preventing the same order from being reported twice (this state is DOM-only — reloading the page restores the original button since nothing is persisted client-side for the order card itself, though the report itself *does* persist in admin's `localStorage`).
- **"Contact vendor"** (per order's track panel) — plain `<a href="chat.html">` , not JS, opens the chat list (no specific vendor thread).
- Reached directly from the sidebar/bottom-nav "Orders" item now (item 17), in addition to Settings → "View orders" and the "Order delivered" notification card.

customer/chat.html

Entirely inline `<script>` at the bottom of the page; mock conversation data lives in a `chatData` array (`chat.html:185-240`), 4 vendors (`gods-favour` , `daniel-ice-fish` , `jennet-jeans` , `me-n-u-chops`), each with `status: 'verified'|'pending'` , `online` , `unread` , `preview` , `time` , and a `messages` array.

- **Chat section tabs (`#chatTabs .chat-tab[data-section]` , "Pending"/"Verified")** — rendered by `renderChatList()` (`chat.html:255-317`); click sets `selectedSection` (module-level variable) and re-renders. Only chats whose `status` matches `selectedSection` are shown, further filtered by the search box's text.
- **#chatSearch (search input)** — `input` event calls `renderChatList(e.target.value)` (`chat.html:504-507`); filters `chatData` by `chat.name / chat.preview` case-insensitively containing the query.
- **Chat list item (`.chat-item` , per conversation)** — click calls `selectChat(chatId)` (`chat.html:311-316` , `319-395`). Sets `activeChatId` , toggles `.active` class on the clicked item, and — if mobile width (`window.innerWidth <= 900`) — adds `.mobile-chat-open` to `.chat-shell` (`updateMobileView()` , `chat.html:247-253`). Rebuilds `#chatWindow` 's entire innerHTML with that chat's header, message thread, and input bar.
- **.chat-back (mobile back arrow, inside chat header)** — calls `selectChat(null)` , which clears `activeChatId` and restores the "Select a chat" empty-state markup.
- **.chat-close (X button, inside chat header)** — same as `.chat-back` , calls `selectChat(null)` .
- **.chat-call ("Call" button)** — `chat.html:406-431` . Guards against double-click (`if (callBtn.classList.contains('calling')) return`), adds a `.calling / aria-busy` state, builds a hidden `<a href="tel:${chat.phone} || '+0000000000'">` and programmatically `.click()` s it to trigger the OS dialer, then after `1400ms` removes the calling state and the temp element. Falls back to `alert('Calling ${phone}')` in a `catch` if the `tel:` trick throws.
- **.attach-btn (📎 icon) + hidden .file-input** — click on `.attach-btn` calls `fileInput.click()` ; the input's `change` event (`chat.html:440-450`) reads `fileInput.files` , and renders a `<span class="attachment-chip">📎 name (+N more)</span>` into `.attachment-preview` . Files are **never actually sent or uploaded** — purely a local filename preview.
- **.send-btn (➤) and pressing Enter in the message input** — both call `sendMessage()` (`chat.html:459-482`). Trims the input value; if non-empty, pushes `{ role: 'outgoing', text, time }` onto that chat object's own `messages` array (mutating the in-memory `chatData` array directly — this *is* the "sent" message, kept only in JS memory, lost on reload), updates `chat.preview / chat.time` (so the list preview reflects the latest message), appends the message bubble's HTML directly into `.chat-body` and scrolls to bottom, clears the input, and re-runs `renderChatList()` so the sidebar preview/time update immediately.
- **Deep link via `?chat=<id>` query param** — on `DOMContentLoaded` (`chat.html:495-511`), if the param matches a `chatData` entry's `id` , that chat's `status` becomes the initially `selectedSection` and `selectChat()` is called with it immediately — this is how `store.html` 's "Message Vendor" button and `orders.html` 's conversation links (where present) open a specific thread instead of the empty state.

customer/notifications.html

- **"Order delivered" card** — the only notification wrapped in an `<a href="orders.html">` (with `unread` class); plain navigation, no JS. `orders.html` also has its own sidebar/bottom-nav item and a Settings link now (item 17), so this is one of three entry points rather than the only one.
- **"Mark all read" (`.page-link` button)** — no `id` , no JS handler anywhere in the codebase; inert.
- Other notification cards ("Flash sale", "Payment confirmed") are plain non-interactive `<div>` s.

customer/settings.html

All interaction logic is an inline `<script>` at the bottom of the page (no separate JS file); also loads `../password-toggle.js` for the 3 password fields in the Security card.

- **#profile-edit-toggle ("Edit", Profile card)** — `enterEditMode()` (`settings.html:462-468`). Calls `fillProfileForm()` to copy the in-memory `profile` object (`fullName` , `phone` , `email` , `address` , hard-coded at `settings.html:429-434` — "Amaka Obi" etc., the same mock identity `report-issue.js` uses as `CURRENT_BUYER`) into the form inputs, hides `#profile-view` (adds `.hidden`), shows `#profile-form` , hides the edit-toggle button itself, focuses `#full-name` .
- **#profile-cancel (inside the edit form)** — `exitEditMode()` (`settings.html:470-474`); re-hides the form, re-shows the read-only view and the edit-toggle button, without saving anything.
- **#profile-form submit ("Save changes")** — `settings.html:481-490` . No validation (no `required` /regex on these inputs). Writes the 4 input values back onto the `profile` object, calls `renderProfileView()` to re-populate `#view-full-name` / `#view-phone` / `#view-email` / `#view-address` , then `exitEditMode()` . State is a plain JS object in the inline script's closure — resets to the hard-coded values on reload.
- **#password-edit-toggle ("Edit", Security card)** — `enterPasswordEditMode()` . The Security card now follows the exact same show/hide pattern as the Profile card above it, rather than showing a permanently-visible-but-readonly form: `#password-form` carries `.hidden` by default and only 2 fields (`#new-password` , `#confirm-password` — `#current-password` was removed, see item 19), and clicking Edit removes `.hidden` from the form, adds it to the edit-toggle button, and focuses `#new-password` .
- **#password-cancel-btn** — `exitPasswordEditMode()` : `form.reset()` , then re-adds `.hidden` to the form and re-shows the edit-toggle button — the whole form disappears again, not just locks.
- **#password-form submit ("Update password")** — No validation of match/strength/length despite being a password-change form. On submit: `e.preventDefault()` , `form.reset()` , `exitPasswordEditMode()` — no actual password update occurs (// TODO: wire up to real update-password endpoint).
- **#manage-payment-btn ("Manage payment methods")** — `settings.html:531-536` ; click → `alert('Hook this up to your payment methods flow.')` .
- **#deactivate-account-btn ("Deactivate account")** — `settings.html:540-550` . Uses native `confirm('Deactivate your account? ...')` ; if confirmed, `alert('Account deactivation requested (hook this up to your API.')` . No real deactivation.
- **"View orders →" link** (Account overview card) — plain `<a href="orders.html">` , not JS.
- **"Contact support" (Help & Support card)** — a plain `<button class="support-btn">` ; not a JS handler local to this page, it's caught by the same global delegated listener described in the shared interaction reference above (`support.js`). This card is where the sidebar/bottom-nav "Support" entry moved to (item 17) — it's the only `.support-btn` left anywhere in the customer app.
- **"Log out"** — plain `<a href="../signin.html">` , not JS (no session to actually clear).
- **Notification toggles (`.toggle-switch input[type=checkbox]` , 3 rows)** — plain checkboxes, no JS handler; purely visual on/off state that doesn't persist or do anything.
- **Password reveal toggles** — injected by `../password-toggle.js` on all 3 password fields, same mechanism as `signin.html`.

6. Vendor (seller) app

All pages live in `vendor/` and share the sidebar: **Dashboard, Products, Orders, Earnings, Profile**.

Page	What it does
<code>dashboard.html</code>	Store KPIs (revenue, orders, active listings, store views), a recent-orders list, and a "My Products" preview grid. Has the Add Product button, which opens a modal form.
<code>products.html</code>	Full product grid with Edit / Remove actions per card (<code>vendor/assets/products.js</code>).
<code>orders.html</code>	Order list with status filter tabs (Pending/Processing/Shipped/Out for delivery/Delivered/Cancelled) via <code>wireOrderFilterTabs</code> in <code>orders.js</code> . Each order has an Update shipment button opening a modal (<code>assets/order-tracking.js</code>) to set shipment status, carrier, and tracking number — updates that order row's status pill and tracking line in place. Below the order list, a Reports against your store panel (read-only — see below) shows reports filed against this vendor.

Page	What it does
<code>earnings.html</code>	Revenue breakdown / earnings history, plus a Payout Account section (see below) above the payout history list.
<code>profile.html</code>	Store profile form (name, owner, email, phone, address, bio — starts read-only, "Edit Profile" unlocks the fields), a Business Verification (KYC) section (see below), notification toggles, security section (change password, 2FA, sign out), and a Danger Zone (deactivate store / delete account).
<code>notifications.html</code>	Vendor-side notification feed.

Add Product modal (`vendor/assets/add-product.js`): a full form — name, category, price, a stock quantity stepper, description, up to 4 image upload slots with live preview, and one optional video upload slot — that builds a new product card and prepends it to the grid on submit (`handleSubmit` → `buildProductCard`). This is in-memory only: reloading the page loses any product you added, because (like the customer app) nothing here persists to `localStorage` .

Reports against your store (`orders.html` , `vendor/assets/reports.js`). A vendor can see reports filed against their store but can't resolve or dismiss them — that stays admin-only (`admin/reports.html`), keeping one place where a report is actually closed out. What a vendor *can* do is respond: an open report's **Submit evidence** button opens a modal (a response textarea plus a mocked photo-upload slot borrowed from the Add Product modal's media-upload UI) — submitting it swaps the button for an "Evidence submitted — awaiting review" tag on that card. This is deliberately a read-only mirror of the same report data admin sees, not a second copy of the moderation queue.

Business Verification / KYC (`profile.html` , `vendor/assets/kyc.js`). Closes a gap where the site's buyer-facing copy claimed "every Vendor passes ID and business verification before their first listing ever goes live" (`buyer-protection.html`) with no actual UI for a vendor to do that verification. The form takes a CAC registration number plus two uploads — a valid ID and a CAC certificate (image preview for photos, a filename chip for a PDF) — reusing the Add Product modal's upload-slot pattern. Submitting requires all three fields, then locks the form and flips the status badge to "Pending review." Like the rest of this app, it's a page-local mock with no persistence — reloading resets it, and it does **not** write into the admin console's `localStorage` . The admin-side review (`admin/vendor-detail.html` 's "Business Verification (KYC)" card, described below) is separate seed data representing documents an admin has already reviewed, not something this form actually submits to.

Payout Account (`earnings.html` , `vendor/assets/payout.js`). Closes a gap where `vendor-protection.html` describes payouts running "straight to the bank account on file" and this same page already captioned every payout-history row "Payout to bank account" — with no UI anywhere to actually set one, on either the vendor form or the admin data model. The new section (above Payout History) takes a bank, a 10-digit account number, and an account name; saving validates the account number's length, then swaps to a read-only view showing the account masked (`•••• 6789`) with an **Edit Account** button. Page-local mock, like KYC — nothing persists past a reload, and (deliberately, for a real version) even this demo never shows the full account number again once saved, only the masked form, modeling what a real implementation's display rule should be even though the underlying mock data is trivial to inspect.

Shared JS: `assets/interactions.js` (`VetraUI` , sidebar toggle/collapse only — no banner carousel or add-to-cart delegation, since the vendor app has neither banners nor a public product grid) and `assets/support.js` (identical Smartsupp open/close logic to the customer copy, but targets `#header-support-btn` on vendor pages, which carries the `.support-btn` class the same delegated listener matches).

Shared reference: - `#header-sidebar-toggle` / `#app-sidebar-reopen` / `#sidebar-collapse-toggle` — `VetraUI.wireSidebarToggle()` / `wireSidebarCollapse()` (`vendor/assets/interactions.js:15-44`), functionally identical to the customer version. - `#header-support-btn` (header icon) — opens Smartsupp via the same `openLiveChat()` / `ensureCloseButton()` pattern in `vendor/assets/support.js:68-80` .

vendor/dashboard.html

- **#add-product-btn** ("Add Product") — `wireAddProductButton()` in `vendor/assets/product-actions.js:34-40` ; calls `window.VetraAddProduct.open()` (`vendor/assets/add-product.js:228-234`), which stores `document.activeElement` for focus restoration, un-hides `#add-product-modal` , locks body scroll, focuses `#ap-name` .
- **Add Product modal** — see full breakdown under "Add Product modal (shared)" below.
- **Product grid actions** (`.edit-btn` / `.remove-btn` , delegated on `.vendor-products-grid`) — `wireVendorProductActions()` (`product-actions.js:13-32`). Reads the product name from the closest `.vendor-product-card` `.product-name` . `edit-btn` → `alert('Edit "${name}")` — hook this up to your `edit-product`

page.') (no real edit page exists). `remove-btn` → native `confirm('Remove "${name}" from your store?')`; if confirmed, `card.remove()` — removes the DOM node only (no backend delete, so it reappears on reload).

- **"See all" links** (Recent Orders → `orders.html`, My Products → `products.html`) — plain `<a>`, not JS.

vendor/products.html

- **#add-product-btn** — identical wiring to `dashboard.html` (`product-actions.js` + `add-product.js`, same modal markup duplicated in this page's HTML).
- **.edit-btn / .remove-btn** — identical `wireVendorProductActions()` behavior as `dashboard.html`, operating on this page's own `.vendor-products-grid` (9 static product cards).

Add Product modal (shared markup/JS across dashboard.html and products.html) — `vendor/assets/add-product.js`, module `VetraAddProduct` : - **Form fields**: `#ap-name` (text, required), `#ap-category` (`<select>`, required, one of 8 fixed categories), `#ap-price` (number, `min="0" step="1"`, required), `#ap-stock` (number, `min="0" step="1"`, required, default 0), `#ap-description` (`<textarea>`, required). - **Stock stepper** (`#ap-stock-decrement` / `#ap-stock-increment`) — `wireStockStepper()` (`add-product.js:120-133`); `step(delta)` clamps to `Math.max(min, current + delta)` where `min = Number(stockInput.min) || 0`. - **Image upload slots (4x, #ap-image-grid .media-upload-slot[data-slot-index])** — `wireImageSlots()` (`add-product.js:108-118`); each slot's hidden `<input type="file">` change event calls `setImagePreview(index, file)` (`add-product.js:42-87`), which creates an object URL (`URL.createObjectURL(file)`), injects an `<img class="media-preview-img">` into the slot, adds a per-slot remove (`×`) button that clears the file and revokes the object URL, and toggles `.has-media` on the slot. - **Video upload slot** (`#ap-video-slot` / `#ap-video-input` / `#ap-video-remove`) — `wireVideoSlot()` (`add-product.js:135-155`); same object-URL preview pattern via `setVideoPreview(file)` (`add-product.js:89-106`), shows the filename in `.video-file-name`. - **Form submit ("Add Product")** — `handleSubmit(e)` (`add-product.js:196-226`). Calls native `form.reportValidity()` first (enforces all required fields + number min/step) and returns early if invalid. Then checks `imageFiles.some(Boolean)` — if no image was ever attached, scrolls to the first image slot and `alert('Add at least one product photo before saving.')`, blocking submission (this check exists *in addition to* the native validity check, since the file inputs themselves aren't marked required). On success: builds a new card via `buildProductCard({ name, price, stock, imageUrl })` (`add-product.js:176-194`) — `imageUrl` is a **fresh** `URL.createObjectURL()` call on the first attached image file (kept independent of the form's own preview URLs, which get revoked on close) — HTML-escapes `name` via `escapeHtml()` (`add-product.js:30-37`) to prevent injection, computes the stock-pill via `stockPillMarkup(stock)` (`add-product.js:170-174`, "low" styling when `stock === 0 || stock <= 5`), then `grid.prepend(card)` onto whichever `.vendor-products-grid` exists on the current page, and scrolls the new card into view. Finally calls `close()`. - **close()** (`add-product.js:236-242`) — hides the modal, unlocks scroll, calls `resetForm()` (clears all inputs/previews and revokes every object URL), restores focus to `lastFocusedEl`. - **Close paths**: `#add-product-close`, `#add-product-cancel`, clicking the overlay backdrop, or `Escape` — all call `close()`. - **State**: entirely in-memory (closure variables `imageFiles`, `videoFile`, etc., and the DOM card itself) — a newly added product disappears on page reload, exactly like Edit/Remove.

vendor/orders.html

Loads `assets/orders.js`, `assets/order-tracking.js`, `assets/reports.js` in that order (no shared "orders" state object between them beyond the DOM itself).

- **Status filter tabs** (`#order-filter-tabs .filter-tab[data-filter]`) — `wireOrderFilterTabs()` (`vendor/assets/orders.js`), functionally similar to the customer orders.js version (targets `.order-item` rows inside `#order-list`, not `.order-card`, comparing against `row.dataset.status`) but also caps how many *matching* rows are visible at once — see the next bullet — since this page's version now does pagination, not just show/hide.
- **"Show more"** (`#orders-show-more-btn`) — requested directly ("no more than 5 orders should show unless the show more button is clicked"). `ORDERS_MAX_VISIBLE = 5` in `orders.js`; `applyVisibility()` filters the 9 static `.order-item` rows down to whichever match the active tab, then shows only the first `ORDERS_MAX_VISIBLE` of *those* (not the first 5 of the unfiltered list) and hides the rest, updating the button's label to `Show N more orders` (hidden entirely once nothing's left to reveal). Clicking it sets an `expanded` flag and re-runs `applyVisibility()` with no cap. Switching filter tabs resets `expanded` back to `false`, so paging back to "All" after expanding it returns to a capped 5 rather than staying expanded — each filter starts capped. State is a closure variable, like the rest of this page's interactions; resets on reload.
- **"Update shipment"** (`.order-manage-btn`, per order row) — `vendor/assets/order-tracking.js`. Delegated click on `#order-list` (`order-tracking.js:55-59`) finds the closest `.order-item` and calls `openModal(row)` (`order-tracking.js:39-47`): sets `#shipment-order-id` from the row's `.order-id` text, pre-fills `#shipment-status` from `row.dataset.status` (default "pending"), `#shipment-carrier` / `#shipment-tracking` from `row.dataset.carrier` / `row.dataset.tracking`, un-hides `#shipment-modal`, locks scroll.

- **#shipment-form submit ("Save update")** — `order-tracking.js:71-108`. No required-field validation (carrier/tracking are optional per the form's own label). On submit: writes `status / carrier / tracking` back onto `activeRow.dataset.*`, updates the row's `.status-pill` class to `status-pill ${status}` and its text via the `STATUS_LABEL` map (`order-tracking.js:21-28` — note `completed` displays as **"delivered"**, matching the customer-facing wording), and either creates or removes a `.order-tracking-line` element depending on whether `carrier / tracking` are set (inserted right before `.order-manage-btn` via `insertBefore`). All 6 status values map 1:1 with `customer/orders.js`'s filter tabs (`pending`, `processing`, `shipped`, `out-for-delivery`, `completed`, `cancelled`).
- **Close paths:** `#shipment-modal-close`, `#shipment-cancel-btn`, backdrop click, `Escape` — call `closeModal()` (`order-tracking.js:49-53`).
- **State:** DOM-only (`row.dataset.*` + the row's own child elements) — resets on reload, no cross-page sync back to `customer/orders.js`'s mock data.
- **"Submit evidence" ([data-action="evidence"] , per open report card in the "Reports against your store" panel)** — `vendor/assets/reports.js`. Delegated click on `#report-list` (`reports.js:37-42`) finds the closest `.report-card` and opens `#evidence-modal` (`reports.js:23-29`), clearing/focusing `#evidence-text`.
- **#evidence-form submit ("Submit")** — `reports.js:53-66`. `#evidence-text` textarea is required (native validation only — no length/content check). On submit, replaces that card's entire `.report-actions` innerHTML with `<span class="badge dismissed evidence-sent-tag">Evidence submitted — awaiting review</span>` — a vendor cannot resolve/dismiss the report itself (that stays admin-only via `admin/reports.html`); this is purely a "vendor responded" marker, DOM-only, resets on reload.
- **Close paths:** `#evidence-modal-close`, `#evidence-cancel-btn`, backdrop click, `Escape` — `closeModal()` (`reports.js:31-35`).
- Report data itself (`#report-list .report-card`, e.g. `rep-1`, `rep-2`) is static seed markup in `orders.html`, **not** pulled from `admin/assets/data.js`'s `localStorage` state — this panel is a page-local mock mirror, unlike `customer/orders.html`'s report-filing which does write into admin's real state.

vendor/earnings.html

`vendor/assets/payout.js` — Payout Account section only; the stat cards and Payout History list are static, non-interactive.

- **#payout-account-form submit ("Save Payout Account")** — `payout.js:50-61`. Fields: `#payout-bank` (`<select>`, required, one of 9 banks/ Other), `#payout-account-number` (`text`, `maxlength="10"`, `inputmode="numeric"`, required), `#payout-account-name` (`text`, required). **Validation:** `/^\d{10}$/.test(numberInput.value.trim())` — must be exactly 10 digits (a NUBAN); on failure, sets `numberInput.style.borderColor = '#e0475c'` and focuses it, blocking submit. On success, calls `showSavedView()` (`payout.js:31-42`): populates `#payout-view-bank` / `#payout-view-number` (masked via `maskAccountNumber()`, `payout.js:27-29` → `"....." + number.slice(-4)`, so the plaintext number is **never re-displayed** once saved, though it is briefly present in the `numberInput.value` until the form is hidden) / `#payout-view-name`, changes `#payout-status-badge` text to "Account on file" and swaps its class from `.status-not-set` to `.status-set`, hides the form and shows `#payout-account-view`.
- **#payout-edit-btn ("Edit Account", shown once an account is saved)** — `payout.js:63`, calls `showForm()` (`payout.js:44-48`): hides the saved view, re-shows the form, and un-hides `#payout-cancel-btn` **only if** the badge is not `.status-not-set` (i.e., cancel only appears once an account already exists, so a first-time setup can't be "cancelled" back to an undefined state).
- **#payout-cancel-btn** — `payout.js:65-67`, calls `showSavedView()` directly (re-shows whatever was last saved, discarding in-progress edits — note it does **not** call `form.reset()`, so the form fields retain the edited-but-uncommitted values if reopened).
- **State:** DOM-only via the module-level `badge / view / form` element references — nothing persists past a reload; the account number, once saved, is not stored anywhere real (per the file's own header comment, this demo intentionally still holds the plaintext briefly in the input to allow the masked-view demo, but never re-displays it).

vendor/profile.html

Two JS files: `vendor/assets/profile.js` (summary card, store-details form, security, danger zone, sign-out) and `vendor/assets/kyc.js` (Business Verification section).

- **#avatar-edit-btn (small pencil badge on the avatar)** — `wireAvatarEditButton()` (`profile.js:12-19`); click → `alert('Hook this up to your avatar upload flow.')`. No real upload.
- **#profile-edit-btn ("Edit Profile", header shortcut)** — `wireProfileEditButton()` (`profile.js:36-46`); calls `setProfileFormEditable(true)` (`profile.js:26-33`, clears `readOnly` on every `.form-input` / `.form-textarea` inside

`#profile-form` and adds `.is-editing` to the form), focuses `#store-name`, and smooth-scrolls the form into view. All 6 fields (`#store-name`, `#owner-name`, `#store-email`, `#store-phone`, `#store-address`, `#store-bio`) ship with the `readonly` HTML attribute by default, so nothing is editable until this button is clicked.

- **#profile-form submit ("Save Changes")** — `wireProfileForm()` (`profile.js:49-76`). No validation logic beyond native (none of the fields carry `required` / `pattern`). On submit: reads `#store-name` / `#owner-name` values (trimmed) and, if non-empty, writes them back onto the summary card's `#profile-store-name` text and `#profile-owner-name` (interpolated as `"${ownerName} • Vendor since Jan 2026"` — the "Jan 2026" join date is hard-coded, not derived from any real data), calls `setProfileFormEditable(false)` to re-lock the form, then `alert('Profile saved (hook this up to your save API).')`.
- **#profile-cancel-btn** — `profile.js:69-75`; calls `form.reset()` (reverts to the HTML's original `value` attributes) then re-locks via `setProfileFormEditable(false)`.
- **Business Verification (KYC) form (#kyc-form)** — `vendor/assets/kyc.js`. Fields: `#kyc-cac-number` (text, `required`), two upload slots (`#kyc-id-slot` / `#kyc-id-input`, `#kyc-cac-slot` / `#kyc-cac-input`, accepting `image/*` and `image/*,.pdf` respectively). Each slot's `change` event calls `setPreview(key, file)` (`kyc.js:34-81`) — same object-URL preview pattern as `add-product.js`, except a non-image file (e.g. a PDF CAC certificate) renders a `.media-file-name` chip with the filename instead of an `<img>` (`kyc.js:57-64`), since PDFs can't be previewed as an image.
- **#kyc-form submit ("Submit for verification")** — `kyc.js:99-119`. **Validation:** `cacNumberInput.value.trim()` non-empty and both `slots.id.file` and `slots.cac.file` must be set — all three or nothing; failure sets `#kyc-note` text to "Enter your CAC number and upload both documents before submitting." in red (`#b91c1c`) and returns, without alerting or blocking via native validity (the file inputs aren't marked `required` in HTML, so this JS check is the only enforcement). On success: sets `#kyc-status-badge` text to "Pending review" and swaps its class from `.status-not-submitted` to `.status-pending`, clears the note's color and sets it to "Submitted — Vetra usually reviews new documents within 24 hours.", then calls `setLocked(true)` (`kyc.js:90-97`) which makes `#kyc-cac-number` `readOnly`, disables both file inputs, adds `.is-locked` to both slots, and hides the submit button (`submitBtn.hidden = true` — there is no unlock/edit path after submission within this page).
- **State:** page-local, in-memory only; does **not** write to `localStorage` or reach into the admin console's data at all (explicitly the opposite convention from `customer/orders.js`'s report-filing) — reload fully resets the KYC section back to "Not submitted".
- **#change-password-btn** — `wireChangePasswordButton()` (`profile.js:79-86`); → `alert('Hook this up to your change-password flow.')`.
- **#deactivate-store-btn** — `wireDangerZoneButtons()` (`profile.js:89-101`); native `confirm('Deactivate your store? ...')`, then on confirm `alert('Store deactivated (hook this up to your API).')`.
- **#delete-account-btn** — same function (`profile.js:103-112`); `confirm('Delete your vendor account? This cannot be undone.')`, then `alert('Account deletion requested (hook this up to your API).')`.
- **#sign-out-btn** — `wireSignOutButton()` (`profile.js:116-125`); `confirm('Sign out of your vendor account?')`, and if confirmed, `window.location.href = '../signin.html'` (an actual redirect, unlike the other danger-zone buttons which just alert).
- **Notification toggle switches (.switch input[type=checkbox] , 4 rows) and 2FA toggle** — plain checkboxes, no JS handler, purely visual.

vendor/notifications.html

- **"Mark all read" (.page-link button)** — no `id` / handler in the codebase; inert, same as the customer equivalent.
- All 4 notification cards are static, non-interactive `<div>`s (no links, no click handlers) — this is the one notifications page across both apps where even the "top" notification isn't wrapped in a navigable link.
- Only shared sidebar/support/header behavior applies (`vendor/assets/interactions.js`, `vendor/assets/support.js`).

7. Admin console — new in this session

Why it was built

The request was for a place where VETRA staff can monitor customers and vendors platform-wide and suspend accounts, plus "other things that should be on the admin section." The console lives entirely under `admin/`, reuses the exact same app-shell/design system as the vendor app (so it feels native to the site, not bolted on), and — unlike the rest of the prototype — **persists its state to `localStorage`** under the key `vetra_admin_state_v1`, because moderation actions (suspending someone,

resolving a report) need to survive a page reload to feel real. `admin/assets/data.js` is the single place that owns this state; every admin page reads and writes through its functions (`VetraAdmin.*`) instead of touching `localStorage` directly, so swapping in a real backend later means changing one file.

Getting in — and "who's logged in"

`admin/login.html` — a staff-only sign-in screen, styled like `signin.html` but with no Buyer/Vendor toggle. It's linked from the bottom of `signin.html` ("Vetra staff? Admin sign in"). Like the rest of the site's auth, it doesn't check a real password — but it does do one real thing: it looks the email you typed up against the admin team roster in `admin/assets/data.js` and, if it matches, tells the data layer **which admin is now "logged in"** (`VetraAdmin.setCurrentAdminByEmail()`). That simulated session is what makes the rest of this section possible — every action taken anywhere in the console is attributed to whoever is currently "logged in," and the console's own role check (Super Admin vs. Moderator vs. Support) reads from it too. The sign-in page lists the three seeded demo accounts and their roles so you can try each one. See §9 for what a real version needs (this is still just an email lookup, not a password check).

Passwords, photos, and "who did what"

Three things were added on top of the original monitor/suspend request, all in direct response to follow-up asks in this session:

- **Reset Password (customers & vendors).** Every customer/vendor row (on `customers.html` / `vendors.html`) and every detail page has a **Reset Password** button. Confirming it generates a temporary password and shows it to the admin in a "share this with them securely" panel — there's no real account system to actually change a password against, so this is as far as a backend-less prototype can go, but the action is logged to that account's activity history like any other.
- **Admin profile photos.** Settings → Admin Profile has a real, working **Change Photo** upload (not a placeholder): it reads the chosen image with `FileReader` , stores it as a base64 data URL on that admin's team record, and immediately reflects it in the profile card, the header avatar on every admin page, and the Admin Team list. This works because the admin console already persists to `localStorage` , unlike the rest of the prototype.
- **Attribution — "which admin attended to a case."** Every activity log entry now records who performed it (`actorId` / `actorName`), and every report gets an `attendedBy` / `attendedAt` pair the moment it's resolved, dismissed, or resolved-via-suspend. That attribution shows up everywhere the relevant record appears — the activity feed ("by Adaeze Umeh"), a report card ("Attended by Adaeze Umeh"), and a customer/vendor's own activity history — regardless of which admin is viewing it. Case-level attribution is intentionally visible to *every* admin; it's the console-wide activity *browsing* below that's role-gated.

Pages

`dashboard.html` — **Platform overview.** Six KPI cards (Total Customers, Total Vendors, Platform Orders, Platform Revenue, Suspended Accounts, Open Reports), a **Quick Actions** row linking straight into a pre-filtered view of the other pages, a **Recent Activity** preview (last 6 audit-log entries), and a **Pending Vendor Applications** table where a new store's application can be **Approved** or **Rejected** right from the dashboard.

`customers.html` — **Manage buyers.** A searchable, filterable table of every customer (name/email, join date, order count, lifetime spend, status). Each row has **View** and either **Suspend** or **Reactivate** depending on current status. Suspending asks for an optional reason via a confirm modal — the reason is stored in the activity log so there's a record of *why*.

`customer-detail.html?id=<id>` — **One customer, in full.** Clicking a customer's name or **View** opens their complete profile instead of a quick-look popup: contact info (phone, delivery address), how and when they signed up, last login, lifetime order/spend stats, a **Recent Orders** list (item, vendor, amount, status pill, carrier/tracking line where shipped — `VetraAdmin.getOrdersForCustomer()` , hidden entirely if empty), **any reports filed against their account** (pulled from the Reports queue), and their **entire activity history** — every suspend/reactivate action ever taken on this specific account, not just the platform-wide feed. Suspend/Reactivate works from here too, so a moderator reviewing an account doesn't have to bounce back to the list to act on what they just read.

`vendors.html` — **Manage stores.** Same shape as Customers, plus a **Pending Approval** state: new vendor applications show **Approve/Reject** instead of Suspend until an admin acts on them. Filter tabs: All / Active / Pending Approval / Suspended.

`vendor-detail.html?id=<id>` — **One store, in full.** Same idea as the customer detail page: store contact info, category, a short description, owner, join date, last login, products/orders/revenue stats, a **Recent Orders** list scoped to this vendor (`VetraAdmin.getOrdersForVendor()` , same rendering as the customer version, listing the buyer instead of the vendor per row),

any reports filed against the store, and its complete activity history. The action buttons adapt to status — **Approve/Reject** while pending, **Suspend/Reactivate** once live. A **Business Verification (KYC)** card shows the vendor's submitted CAC number and the actual ID/CAC document images as clickable thumbnails (`admin/assets/data.js` 's per-vendor `kyc` object — status one of `not_submitted` / `pending` / `verified` / `rejected`) — an admin can open either document full-size in a new tab before deciding, not just see a filename (an earlier version of this card only showed the filename string, which meant "Verify Documents" had nothing to actually verify against; see §8 for the fix); a `pending` submission gets **Verify Documents/Reject** actions through the shared confirm modal (`VetraAdmin.setVendorKycStatus()`), logged to that vendor's activity history like any other action. This is independent of the account-level Approve/Reject status — a vendor can in principle be `active` with KYC still `pending` , since the two aren't currently forced to move together (see §8 for why).

reports.html — **Reports & disputes.** A moderation queue of flagged accounts, listings, and buyer↔vendor disputes (e.g. "item didn't match description," a chargeback dispute, a suspicious listing). Each open report can be **Marked Resolved, Dismissed**, or — if it's against a customer or vendor — resolved with a one-click **Suspend Account**, which suspends the account *and* marks the report resolved in a single confirmation.

activity.html — **Activity log / audit trail.** Every suspend, reactivate, approve, reject, resolve, dismiss, password reset, invite, and admin-removal action performed anywhere in the admin console is appended here automatically, newest first, with a relative timestamp ("2h ago"), a type tag, and — for anything an admin actually did — **who did it** ("by Adaeze Umeh"). Filterable by Account Actions / Vendor Approvals / Reports / Orders / Logins. This is what makes the console feel like a real moderation tool rather than a set of disconnected switches — every destructive action leaves a trace.

Visibility here depends on role: a **Super Admin** sees everyone's activity and gets a **"filter by admin"** dropdown to narrow it to one person; a **Moderator or Support** admin only sees platform events (orders, customer/vendor logins — nothing admin-specific) plus their *own* actions, with a note explaining that Super Admins can see more. This is enforced by `VetraAdmin.getVisibleActivity()` , which every activity view (this page and the dashboard's preview) calls instead of the raw log — but, like every other role check in this prototype, it's a client-side filter, not a real permission boundary (see §9).

settings.html — **Admin profile & platform controls.** - **My Profile:** reflects whoever actually signed in (name, email, role badge), with a working **Change Photo** upload. - **Platform Controls:** toggles for "require approval for new vendors," "require ID/business verification for new vendors" (governs the KYC requirement described in §6/§7 — **on by default**), "auto-flag suspicious listings," "allow guest checkout" (**on by default** — buyers can check out without an account unless an admin turns it off here), "maintenance mode" (cosmetic switches — see §9). - **Site Banners** — **new, see items 21-22.** A real, working image list, not a cosmetic switch: each row is a thumbnail + Up/Down (disabled at either end of the list) + **Remove** (through the shared confirm modal), plus a **+ Add banner image** button that opens a file picker, reads the chosen image via `FileReader` as a base64 data URL (same pattern as the admin avatar/Change Photo upload above — no real file storage exists yet), and appends it. This list — order and all — is exactly what both `customer/dashboard.html` 's and `customer/explore.html` 's promo carousels render, picture-only, with changes here showing up on both pages on their next load; see

`VetraAdmin.getSiteBanners() / addSiteBanner() / removeSiteBanner() / moveSiteBanner()` in `admin/assets/data.js` . -

Admin Team: the full list of who has console access and their role (Super Admin / Moderator / Support), each with their photo if they've set one, and a **Remove** action that goes through the shared confirm modal. Removing the platform's *last* Super Admin is blocked with an explanation, so the console can't be locked with zero full-access admins. - **Add Admin — invite + email verification.** Clicking **Add Admin** doesn't add someone immediately: it collects name/email/role and creates a *pending invitation*, then opens a **Verify Email** step. Since this prototype has no mail server to actually deliver anything, the code that "would have been emailed" is shown right in the UI, and — per how this was asked for — **entering anything in the verification field completes it**; this is a simulated verification step to demonstrate the invite→verify shape of a real onboarding flow, not a real code check (see `VetraAdmin.verifyTeamInvite()` in `admin/assets/data.js` , and §9). Pending invitations appear in their own list with **Verify/Cancel** actions until completed. - **Notifications and Security** sections matching the vendor profile page's pattern (password, 2FA, sign out). - **Data & Danger Zone** → **Reset Demo Data:** wipes the admin console's `localStorage` state and reloads the original seed data (team roster and any pending invites included). This exists *specifically because* this is a prototype with no real backend — it's how you get back to a clean demo state after clicking around, and it would not exist in a production build.

The shared confirm modal

Every destructive or state-changing action (suspend, approve, reject, resolve, dismiss, reset demo data) goes through **one reusable confirm dialog** (`AdminUI.confirm()` in `admin/assets/ui.js`), not a bare `window.confirm()` . It shows exactly what's about to happen, names the target by name, optionally collects a reason, and only then calls into `VetraAdmin.*` to make the change. This was a deliberate choice: an admin console where "Suspend" fires immediately on click, with no confirmation, is a foot-gun.

What "add other things that should be on the admin section" became

Beyond the explicitly requested monitoring + suspend features, this session added: 1. **Vendor approval workflow** (pending → active/rejected) — without this, every new vendor signup would go live unmoderated. 2. **Reports & disputes queue** — a place for the "someone flagged this" workflow that any marketplace needs; suspending straight from a report closes the loop between "a problem was reported" and "an admin acted on it." 3. **Activity log / audit trail** — accountability for who did what, which also makes the console testable/demoable (you can see the effect of your own actions). 4. **Admin team/roles list** — a console with a hardcoded single admin user doesn't reflect that real platforms have multiple staff with different permission levels. 5. **Reset Demo Data** — a prototype-specific affordance so the demo doesn't get "stuck" in a suspended/modified state after someone tries the buttons. 6. **Admin login gate** (`admin/login.html`) — the original ask assumed an admin section existed on the site already reachable somehow; since it didn't, this is the entry point, reachable from `signin.html`. 7. **Full customer/vendor detail pages** (`customer-detail.html`, `vendor-detail.html`) — requested directly: monitoring "all their account activity and user data" needed more room than a quick-look popup could give, so each account now gets its own page with full profile info, a filtered activity history, and any reports against it. 8. **Add/Remove Admin on Settings** — also requested directly: the console needed a real way to grow (or shrink) its own staff list, not just display three hardcoded names. 9. **Password reset for customers and vendors** — requested directly: an admin console that can suspend an account but can't help someone locked out of it is missing a basic support tool. 10. **Admin profile photos** — requested directly, with a real (client-side) upload rather than a placeholder, since the console already has somewhere to persist it. 11. **Per-admin activity attribution + role-gated activity browsing** — requested directly ("let super admins see the activities of other admins... let all admins see which admin attended to a case"): every log entry and every report now records who acted on it, visible to all; but *browsing* the full log is Super-Admin-only, with everyone else scoped to platform events and their own actions. 12. **Admin invite + simulated email verification** — requested directly: adding a new admin now goes through an invite-and-verify step instead of adding them outright, standing in for the real "confirm your email" step a production onboarding flow would have. 13. **Guest checkout, on by default** — requested directly: `admin/settings.html`'s "Allow guest checkout" toggle now starts checked, and `signin.html` gained a "**Continue as Guest** →" link (buyer tab only) straight into `customer/dashboard.html`, so the platform-control setting has a matching entry point on the actual sign-in page. 14. **A vendor-verification kill switch** — requested directly: `admin/settings.html`'s Platform Controls gained a "Require ID/business verification for new vendors" toggle (on by default), alongside the pre-existing "Require approval for new vendors" one — the two are deliberately separate switches, since account approval and KYC review aren't forced to move together (see §7's `vendor-detail.html` note). 15. **Order visibility for both sides of a transaction** — requested directly ("let admins be able to check ordered and sent out items from the customer and the vendor"): before this, a customer/vendor detail page only showed lifetime order *counts*, with no way to see an actual order, its item, or its shipment status. Added a shared `orders` sample dataset to `admin/assets/data.js` (`getOrdersForCustomer()` / `getOrdersForVendor()`) and a **Recent Orders** list to both detail pages — see the updated descriptions above. 16. **A real cart, real product-detail pages with reviews, and working category filtering** — requested directly, reporting that Add to Cart didn't actually add anything, `cart.html` showed hardcoded dummy items, clicking a product showed nothing, and clicking a category didn't filter. All four were real: there was no shared product catalog anywhere in the customer app, so a product card had nowhere to link to and nothing to persist into a cart. Built `customer/assets/products.js` (a shared 23-product catalog — the same "Gaming Laptop" the dashboard and Godsfavour Laptops' store page both show is now one catalog entry, not two coincidentally-matching listings) and `customer/assets/cart-store.js` (`CartStore`, `localStorage`-backed); rewrote `cart.html` / `cart.js` to render real cart contents with no dummy data; added `customer/product.html` (detail + reviews, same pattern as `store.html`'s); wired every product card across dashboard/explore/category/store to both `CartStore` and click-through; and gave `category.html`'s category tiles (and `dashboard.html`'s category rail) a real `filterByCategory()` instead of a dead `href="#"`. Found and fixed one bug of its own along the way: `product.html`'s Add to Cart button initially reused the `.add-cart` class the `card-level` delegated handler also matches, which — since that button has no `[data-product-id]` ancestor card — made the *global* handler's fallback fire and navigate the whole page to `cart.html` on click, on top of the page's own handler. See §5's updated page descriptions and interaction reference above. 17. **Merged Category into Explore, added Orders to the nav, moved Support into Profile** — requested directly, as an information-architecture cleanup: Category and Explore were two separate pages doing almost the same job (identical filter-panel + product-grid pattern; Category's only real addition was its 8-tile "shop by category" grid), Order History had no nav entry at all (only reachable from Settings and one notification card, despite being something every buyer needs often), and Support — a rare action — was taking up a permanent nav slot on both the sidebar and the bottom tab bar. Moved `category.html`'s browsing job, its 2 extra filter-panel category chips, and its 6 products into `explore.html` (now 12 products total); turned `category.html` into a `window.location.replace('explore.html' + location.search)` redirect stub so old `category.html?cat=X` links keep working; updated every internal link that pointed at `category.html` (`dashboard.html`'s category rail, and every page's own nav) to point at `explore.html` directly. Removed the `.support-btn` sidebar link and bottom-nav item from all 9 pages that had it and added a "Contact support" button to `settings.html`'s new **Help & Support** card instead — no JS changes needed there since `support.js`'s click listener is already delegated on `document`, so it fires for a `.support-btn` anywhere on the page. Added a new **Orders** entry (originally a package icon, changed to a receipt icon in item 20 to match the vendor app's own Orders icon) to both the sidebar and bottom-nav on all 9 customer pages, in the slot Category vacated, marked active on `orders.html` itself. Net

nav change: bottom-nav went from 5 items (Home, Category, Explore, Support, Profile) to 4 (Home, Explore, Orders, Profile); sidebar went from 6 (Home, Category, Explore, Chat, Support, Profile) to 5 (Home, Explore, Orders, Chat, Profile). **Follow-up, same session:** the initial merge carried `category.html` 's 8-tile image grid over as-is; direct feedback said to drop the grid entirely and represent categories as plain filter buttons instead, matching the trending-chips row already on the page. Replaced `.categories-grid / .category-card` with 8 `.category-chip` buttons styled via the existing `.trending-chip` class (added `font-family: inherit; cursor: pointer;` to that class so it renders correctly on a `<button>`, not just an `<a>`), and expanded the filter panel's category checkboxes from 5 to 9 (every chip's category, plus Sports) so every quick-filter chip now has a real matching checkbox — closing the gap where a clicked category without one used to need a special-cased "no products yet" empty state; now every chip resolves through the same `applyFilters()` path a manually-checked box would. Verified live across all 9 pages: zero console errors, consistent nav item counts/labels, chip-based filtering and the `?cat=` deep link both work, the `category.html` redirect preserves its query string, and the settings.html support button still opens live chat (`body.livechat-open`). 18. **Real "New"/"Hot" product badges instead of 5 hardcoded ones** — asked directly to either remove the Hot/Trending/New badges or wire them up to real logic and document the real-backend version, choosing the latter to stay consistent with how every other "fake claim" gap in this prototype (cart, reviews, KYC docs, orders) has been handled this session — build it real, don't delete the feature. The 5 existing badges (`explore.html` only — the identical products on `dashboard.html` showed none) were plain hardcoded `<span>` s with no data behind them, and "Trending" turned out to just be alternate text on the same `.hot` CSS class, not a real third category. Added `createdAt / salesCount` to every entry in `products.js` 's catalog and a new `getProductBadge(product)` function there (New = created within 21 days, else Hot = `salesCount >= 50`, else no badge — New wins if both apply); added `assets/badges.js` 's `decorateProductBadges()` to apply that to the DOM on `dashboard.html`, `explore.html`, and `store.html`; removed the 5 hardcoded spans from `explore.html`. Documented the real-backend version in `BACKEND_GUIDE.md` §3 ("Product badges") and its `GET /api/products / GET /api/products/:id` response shape in §5 — `created_at` is an ordinary row timestamp, `sales_count` is a `COUNT / SUM` aggregate over completed `order_items`, and the front-end's threshold logic doesn't need to change once those two fields come from real columns instead of hard-coded catalog values. See §5's updated page descriptions above. 19. **Security card (`settings.html`) hidden until Edit, and dropped the fake "Current password" field** — requested directly. Previously the whole password form was always visible but `readOnly / disabled` until "Edit" was pressed (a locked-but-shown state); it now follows the exact same show/hide pattern the Profile card above it already used — `#password-form` carries `.hidden` by default and Edit/Cancel/submit toggle that class, rather than toggling `readOnly` on inputs that stay on-screen the whole time. Also removed the `#current-password` field entirely: there's no backend to check it against, so asking for it was asking the user to type a real secret into a field that verified nothing — the form now only asks for the new password twice, honest about what this prototype can actually do (nothing, yet — see the existing `// TODO: wire up to real update-password endpoint`). Cleaned up the now-dead `.field-group input[readonly]` and `#password-submit-btn:disabled` CSS rules in `settings.html` 's own `<style>` block, since neither state exists anymore. See the updated `settings.html` interaction reference above. 20. **A real "See more" destination for Top Vendors, plus two nav follow-ups requested in the same breath** — three related asks: (1) `explore.html` 's "TOP VENDORS" → "See more" was an inert `<button>`; it should go to a vendors page with a name search. (2) Change the Orders nav icon. (3) Add Chat/Messages to the mobile bottom nav (it was sidebar-only). For (1): extracted `store.html` 's previously page-local `VENDORS` object into a new shared `assets/vendors.js` (`getVendor() / getAllVendors()`, same pattern as `products.js`) so the data isn't duplicated a third time on top of the two-vendor-lists gap §8 already documents; built `customer/vendors.html` — a directory grid of every vendor (avatar, name, `verified / pending` status pill, category, rating, location) with a live `#vendorSearchInput` that filters by name and an honest "No vendors match" empty state, each card linking to `store.html?vendor=<id>`; pointed the "See more" `<a>` at it. For (2): swapped the Orders nav icon (a package/box, from item 17) for the receipt icon `vendor/dashboard.html` 's own Orders nav link already uses, for visual consistency between the two apps' Orders entries — same 5 icon instances per page (sidebar) plus 5 more (bottom-nav) across all 10 customer pages now share this one icon. For (3): added a Chat bottom-nav item (icon + label, matching the sidebar's) to all 10 customer pages, marked active on `chat.html` — the sidebar and bottom nav now list the identical 5 items (Home, Explore, Orders, Chat, Profile) instead of the bottom nav dropping Chat as it did right after item 17. Verified live: `explore.html` 's See more → `vendors.html` → search "jen" narrows to 1 card → click-through lands on the correct `store.html?vendor=` page with zero console errors; both navs render 5 matching items site-wide. 21. **Picture-only dashboard banner, made admin-editable** — two related asks in the same breath: (1) the dashboard banner's promo text and color block were covering half of every image — make it picture only. (2) Move the banner images into their own file, and give admins a way to change the site-wide banner from the console. For (1): removed the `.banner-text` block from both of `dashboard.html` 's slides entirely (not just visually hidden) and made the `<img>` fill the slide at 100%×100%; this took a second pass to actually land — the first attempt left a visible sliver of the `.banner` gradient around the image because of a pre-existing, undocumented second `.banner-slide { padding: 20px }` rule later in `style.css` that this project's own CSS comment already flagged as needing reconciling — fixed by scoping every picture-only override under one new `.banner--picture-only` class (2-3 class specificity) rather than fighting the cascade — `explore.html` 's text+image banner was deliberately left alone in this pass (see item 22 for why that changed right after). For (2): moved the banner image files from `customer/assets/images/` into a new shared `assets/banners/` at the project root (alongside the existing `assets/brand/` convention every app already references via `../`); added a `siteBanners` array to `admin/assets/data.js` 's state

(`getSiteBanners()` / `addSiteBanner()` / `removeSiteBanner()` / `moveSiteBanner()` , seeded with the 2 moved images) and a new **Site Banners** card to `admin/settings.html` (thumbnail + Up/Down reorder + Remove per row, plus an "+ Add banner image" file picker using the same `FileReader -to-base64` pattern as the admin avatar upload — no real file storage exists yet, same caveat as that feature). `dashboard.html` now loads `../admin/assets/data.js` directly and builds its banner slides from `VetraAdmin.getSiteBanners()` on load (falling back to 2 default images if unavailable) — this is the **second** place (after `report-issue.js`) a customer page reaches into admin's `localStorage` state on purpose. Verified live end-to-end: removing a banner in admin Settings and reloading `dashboard.html` shows one fewer slide, with zero console errors throughout. See `BACKEND_GUIDE.md` 's new `site_banners` table (§3) and `/api/site-banners` routes (§5) for how this should work once a backend exists — including replacing the direct `localStorage` read with a real `fetch()` call, the one part of this feature that doesn't fit the rest of the site's eventual API-based shape. 22. **The same picture-only, admin-managed banner extended to explore.html** — asked directly ("do the same thing for the explore section") right after item 21 shipped for `dashboard.html` only. `explore.html` 's banner previously had its own separate hard-coded text+image slides ("Explore" / "Featured Vendors" copy, different from `dashboard.html` 's), which would have silently drifted out of sync with whatever an admin sets in Site Banners otherwise. Applied the exact same treatment: emptied the slide markup down to `.banner.banner--picture-only + .dots` shells, loaded `../admin/assets/data.js` , and copied the identical banner-building inline script from `dashboard.html` (same `DEFAULT_BANNERS` fallback, same `Vetra.wireBannerCarousel()` re-wiring after building slides). Updated `admin/settings.html` 's Site Banners description and `admin/assets/data.js` 's `siteBanners` comment, both of which previously said "the buyer dashboard" singular, to name both pages — this list is genuinely site-wide now, matching what its own label already claimed. Verified live: removing a banner in admin Settings now removes it from both `dashboard.html` and `explore.html` on reload, with zero console errors on either page. 23. **Capped the vendor Orders list to 5 rows with a "Show more" button** — requested directly. `vendor/orders.html` 's "ALL ORDERS" list (9 static rows) previously rendered every row at once regardless of the active status filter. Rewrote `vendor/assets/orders.js` 's `wireOrderFilterTabs()` around a single `applyVisibility()` function: it first narrows to rows matching the active tab, then shows only the first `ORDERS_MAX_VISIBLE = 5` of *that* filtered set (not 5 of the unfiltered list, which would've hidden rows a filter should surely include), hiding the rest and showing a **"Show N more orders"** button (`#orders-show-more-btn` , new — styled to match the page's existing button language) whose label reflects exactly how many are hidden and which disappears entirely once nothing's left. Clicking it reveals the rest for the current filter; switching filter tabs resets back to a capped view rather than staying expanded, so paging never leaves a stale "everything's already shown" state behind after a filter change. Verified live: loads with 5 of 9 visible and a "Show 4 more orders" button, Show more reveals all 9 and hides the button, filtering to "Processing" (2 matches) shows both with the button correctly hidden, and returning to "All" re-caps to 5 — zero console errors throughout. 24. **Full codebase audit for errors and unused code, then a cleanup pass on every finding** — requested directly. Ran `node --check` on every `.js` file site-wide, live-loaded every page across all four apps (plus `backend/`) checking for console errors and broken `<script>` / `<link>` / `<img>` references, and scanned every stylesheet for classes with zero textual match anywhere in their app (including inside JS template strings, not just static `class="..."` attributes) — this last check was done twice: once per-app by background agents, once again by hand with a small Python script (parses each stylesheet into top-level rule blocks, flags any whose selector's classes are **all** absent from that app's HTML/JS) so the removal step below could be automated rather than hand-verifying dozens of rules one at a time. Zero functional bugs were found anywhere — no syntax errors, no broken links, no broken `id` references, no live console errors. Everything found was dead weight: - **Dead functions removed:** `customer/assets/products.js` 's `getAllProducts()` , `customer/assets/vendors.js` 's `getVendor(id)` (both `store.html` / `vendors.html` resolve products/vendors a different way already), and `admin/assets/data.js` 's `isSuperAdmin()` , `getActivity()` , `getOrders()` (each had zero call sites, including from within `data.js` itself — `getVisibleActivity()` / `getOrdersForCustomer()` / `getOrdersForVendor()` are what every page actually calls). - **Dead CSS removed:** ~102 fully-unused rule blocks from `vendor/assets/style.css` and ~27 from `admin/assets/style.css` — both files had a large chunk of customer-storefront-shaped CSS (banner carousel, chat widget, categories rail, cart, generic `.product-card`) copy-pasted in that neither app's own pages ever use; a few more compound selectors (`.chat-tab.active` , `.stock-pill.low` , etc.) were removed by hand since their base class was dead even though the modifier half (`active` / `low`) is a generic class used elsewhere for other elements. One 3-way grouped selector in vendor's stylesheet (`.page-card` , `.summary-card` , `.notification-card { ... }`) was trimmed rather than removed outright — `.notification-card` is genuinely live in `vendor/notifications.html` , so only the two dead names were dropped from the group, its styling left intact. - **The customer/assets/style.css duplicate/conflicting .banner block flagged in items 17/21 was finally reconciled**, not just worked around: since both `dashboard.html` and `explore.html` are picture-only now (item 22), the old text+image variant (`.banner-text` + 4 sub-rules, `.banner-art`) was 100% dead and removed outright, and the two competing copies of `.banner` / `.banner-slide` / `.dots` (previously ~140 lines total, including a second pair of conflicting `height` values inside two separate `@media (min-width: 900px)` blocks) were merged into one definition — the temporary `.banner--picture-only` modifier class from item 21 no longer needed to exist as a separate scope and was folded directly into the base `.banner` / `.banner-slide` rules, so `dashboard.html` / `explore.html` now just use plain `class="banner"` . One judgment call: the two conflicting copies of `.dots span.active` 's `color ( var(--navy) vs. a hardcoded #7b5cf0 duplicate of --purple1 )` couldn't both survive — kept the token-based one as the more clearly-intentional version rather than the hardcoded copy-paste duplicate; the visual difference is a single small carousel dot and was a pre-existing inconsistency either way, not something this

pass introduced. - **Root-level style.css dead code removed:** `.eyebrow.on-dark`, `.logo .dot`, `.hero-proof (+ b)`, `.stats / .stat (+ b / span`, plus a responsive override), `.timeline / .tl-row (+ :last-child / h4 / p) / .tl-year` (plus a responsive override) — roughly 90 lines from an earlier design (a stat bar, a timeline component) that no longer exists on any page. `main.js` — loaded only on `signup.html`, where both of its behaviors (nav-link highlighting, a mobile menu toggle) targeted elements that don't exist on that page, making it fully inert — had its `<script>` include removed from `signup.html` and, since nothing else referenced it, the file itself was deleted. - **Orphaned images removed:** `customer/assets/images/cat-electronics.jpg`, `cat-sports.jpg`, `cat-supermarket.jpg` — leftover from the "shop by category" tile grid that item 20's follow-up replaced with plain text buttons. (A fourth candidate, `cat-home.jpg`, was *not* removed — it looked unused from inside `customer/` alone, but a whole-repo check found the root `index.html` still references it directly.)

```
Verified after every removal: `node --check` re-run on every touched `.js` file, every touched stylesheet r
```

Full interaction reference (every button, exact behavior)

The page-by-page tour above says what each page is for; this is the granular version — every interactive control, the function that handles it, and where its state actually lives. All of it is driven through `VetraAdmin.*` (`admin/assets/data.js`) and `AdminUI.*` (`admin/assets/ui.js`), so those two files are named throughout rather than repeated per page.

Shared across every admin page (`admin/assets/ui.js`): - The header's sidebar-collapse icon (`#header-sidebar-toggle`) toggles `.hidden-desktop` on `#app-sidebar` and shows a floating reopen button (`#app-sidebar-reopen`) — `wireSidebarToggle()`. - The sidebar's own collapse arrow (`#sidebar-collapse-toggle`) toggles a `.collapsed` class (icon-only rail) — `wireSidebarCollapse()`. - Every header avatar image (`.header-avatar img`) is kept in sync with whichever admin is "logged in" — `applyCurrentAdminAvatar()`, called on every page load and again after a photo upload. - **The shared confirm modal** (`#confirm-modal`, `AdminUI.confirm({title, bodyHtml, confirmLabel, danger, showReason, onConfirm})`) is what every suspend/approve/reject/resolve/dismiss/remove action across the whole console routes through — no page wires its own modal. `danger: true` turns the confirm button red; `showReason: true` reveals an optional textarea whose value is passed to `onConfirm(reason)`. If a page's markup doesn't include `#confirm-modal` at all, `confirm()` silently falls back to a native `window.confirm()` so it never hard-fails. - **The shared info modal** (`AdminUI.info({title, bodyHtml, confirmLabel})`) is the same overlay in a one-button mode, used only to show a value back to the admin (a generated temp password, "admin added" confirmation) — no `onConfirm`, no reason field. - **The shared activity-feed renderer** (`AdminUI.renderActivityFeed(container, entries)`) is what `dashboard.html`'s preview, `activity.html`'s full list, and both detail pages' "Account Activity"/"Activity History" sections all call — one function, so a change to how an entry renders (its icon, its "by X" attribution) updates everywhere at once.

dashboard.html (`admin/assets/dashboard.js`): - Six KPI cards are pure display, computed once from `VetraAdmin.getStats()` on load (`renderStats()`) — no interaction. - The "Pending Vendor Applications" table (`renderPendingVendors()`, capped at 4 rows) reads `VetraAdmin.getVendors().filter(v => v.status === "pending")`. Its **Approve** button opens a confirm dialog ("Their store and listings will go live immediately") whose `onConfirm` calls `VetraAdmin.setVendorStatus(id, "active")`, then re-renders the pending table, stats, and activity feed. **Reject** opens a `danger: true, showReason: true` confirm ("They can re-apply later") calling `setVendorStatus(id, "rejected", reason)`. - The Recent Activity preview shows `VetraAdmin.getVisibleActivity().slice(0, 6)` — role-scoped (see the Activity Log entry below), not the raw log.

customers.html (`admin/assets/customers.js`): - The search input (`#customer-search`, `input` event) and status dropdown (`#customer-status-filter`, `change` event) both call one `render()` that filters `VetraAdmin.getCustomers()` by `name / email` substring match (lowercased) and by exact `status`, then rebuilds the table body from scratch every time — there's no diffing, the whole `<tbody>` is replaced. - The status filter's initial value can come from the URL: `customers.html?filter=suspended` (used by `dashboard.html`'s "View Suspended Accounts" quick action) pre-selects that filter on load. - Each row's name/avatar cell and its **View** button both link to `customer-detail.html?id=<id>` — same destination, two click targets. - **Reset Password** opens a confirm dialog; on confirm, `VetraAdmin.resetCustomerPassword(id)` generates a temporary password (returned as a plain string — see `admin/assets/data.js`) and `AdminUI.info()` displays it in a `.reveal-panel` for the admin to copy and relay manually. This is the prototype's stand-in for "email a reset link" — see DOCUMENTATION.md §9 for why a real backend must never show this value to the admin. - **Suspend** (`danger: true, showReason: true`) calls `VetraAdmin.setCustomerStatus(id, "suspended", reason)`; **Reactivate** (shown instead, once suspended) calls the same function with `"active"` and no reason.

vendors.html (admin/assets/vendors.js): - Same search-input pattern as customers, plus **filter tabs** (#vendor-filter-tabs .filter-tab , click-to-activate) instead of a dropdown: All / Active / Pending Approval / Suspended. ?filter=pending in the URL pre-activates a tab the same way customers.html 's query param does. - render() always excludes status === "rejected" vendors from every view, even "All" — a rejected application isn't shown anywhere in this list (it still exists in VetraAdmin.getVendors() , just filtered out here). - A **pending** row shows **Approve/Reject** instead of Suspend; both behave exactly as dashboard.html 's versions (same confirm copy, same setVendorStatus() calls) — this file and dashboard.js each have their own copy of that logic rather than sharing one function, which is a small, acknowledged duplication (same pattern noted for customer/assets/interactions.js vs vendor/assets/interactions.js in DOCUMENTATION.md §8). - **Reset Password** behaves identically to the customers page, via VetraAdmin.resetVendorPassword(id) .

customer-detail.html?id=<id> (admin/assets/customer-detail.js): - On load, reads id from the URL and calls VetraAdmin.getCustomer(id) ; if it returns nothing (bad/missing id, or the customer was removed by a demo-data reset), the page swaps to a #customer-not-found empty state and never calls render() . - render() populates every field (name, email, signup method, phone, address, joined date, last login with a relative "time ago" via VetraAdmin.formatDateWithRelative()) directly by element id, then calls five sub-renderers: renderStats() (orders/spend/status tiles), renderActions() (Reset Password + Suspend-or-Reactivate, same confirm/action pattern as the list view, but note the button click handler here is attached with wrap.querySelector('[data-action="suspend"]', [data-action="activate"]') — a single selector matching whichever one actually rendered, since only one of the two exists in the DOM at a time), renderOrders() (see below), renderReports() (see below), renderActivity() . - **Recent Orders** (renderOrders()): VetraAdmin.getOrdersForCustomer(id) , sorted newest-first by placedAt . Each row shows the item, the vendor name (looked up live via VetraAdmin.getVendor() , so it always reflects the vendor's current store name), the amount, a status pill (pending/processing/shipped/out-for-delivery/delivered/cancelled — "completed" is relabeled "delivered" here, matching what a customer/vendor sees on their own tracking pages), and a carrier/tracking line when either is set. Section is hidden entirely (not an empty-state message) when this customer has no sample orders — same convention as the Reports section. - **Reports filed against this account:** VetraAdmin.getReportsForTarget("customer", id) . If empty, the entire section is hidden = true rather than showing an empty state — a customer with no reports shows no reports section at all, not a "no reports" message. - **Activity History:** VetraAdmin.getActivityForTarget("customer", id) — every log entry for this specific account, not the platform-wide feed, rendered through the same AdminUI.renderActivityFeed() used everywhere else.

vendor-detail.html?id=<id> (admin/assets/vendor-detail.js): - Same not-found/render split as customer-detail. renderActions() branches three ways instead of two: pending → Approve/Reject, suspended → Reactivate, else → Suspend — matching vendors.html 's three-state list view. - **Business Verification (KYC)** (renderKyc() , added when the KYC feature was built): reads vendor.kyc ({status, cacNumber, idDocumentName, idDocumentUrl, cacDocumentName, cacDocumentUrl, submittedAt, reviewedAt}). not_submitted shows a plain "nothing to review" message with no actions. pending shows the CAC number and both documents via docChip(fileName, url) — when a url is present this renders an actual clickable thumbnail (wrapping a small) that opens the full document in a new tab, not just the filename; docChip() falls back to a filename-only chip if url is missing, and to "Not uploaded" in muted text if there's no file at all. (An earlier version of this only ever showed the filename — an admin asked to "Verify Documents" had nothing to actually look at; fixed by generating two clearly-watermarked "DEMO / SAMPLE" placeholder document images under admin/assets/images/kyc-samples/ and wiring every seeded vendor's kyc object to point at them, since this prototype has no real uploaded-file storage to reference instead.) Below the documents, pending also shows **Verify Documents** (VetraAdmin.setVendorKycStatus(id, "verified")) and **Reject** (danger: true, showReason: true, → setVendorKycStatus(id, "rejected", reason)) buttons. verified / rejected show the same fields plus a "Reviewed \<date>" line and no action buttons — a decision, once made, isn't reversible from this screen. - **Recent Orders** (renderOrders()): mirrors the customer-detail version — VetraAdmin.getOrdersForVendor(id) , newest-first, same status-pill labeling — but each row shows the buyer's name (VetraAdmin.getCustomer()) instead of a vendor name, since here the vendor side of the order is already fixed (it's this page) and the customer side is what varies per row. - Reports/Activity sections work exactly like the customer-detail page, scoped to ("vendor", id) instead of ("customer", id) .

reports.html (admin/assets/reports.js): - Filter tabs (#report-filter-tabs , All/Open/Resolved/Dismissed) work the same click-to-activate pattern as the vendors page; ?filter=open etc. in the URL pre-selects one. - Every report card shows **Mark Resolved** and **Dismiss** when status === "open" ; a report against a customer or vendor (not a product) additionally shows **Suspend Account**. Nothing shows once a report is resolved/dismissed — a decided report has no further actions here. - **Mark Resolved** → confirm → VetraAdmin.setReportStatus(id, "resolved") . **Dismiss** → confirm → setReportStatus(id, "dismissed") . - **Suspend Account** is the one three-way action on this page: its confirm dialog is danger: true, showReason: true with the label "Suspend & resolve," and its onConfirm calls both VetraAdmin.setVendorStatus() / setCustomerStatus() (whichever report.type is) and VetraAdmin.setReportStatus(id, "resolved") in the same click — suspending the account and closing the report out in one confirmation, rather than requiring two separate actions for what's conceptually one decision.

activity.html (`admin/assets/activity.js`):- Filter tabs narrow by `type` (Account/Vendor/Report/Order/Login/All) — pure client-side array filter on whatever `VetraAdmin.getVisibleActivity()` already returned. - **The one page whose behavior literally differs by who's logged in:** if `VetraAdmin.getCurrentAdmin().role === "Super Admin"`, an admin-filter dropdown (`#activity-admin-filter-wrap`) appears, populated from `VetraAdmin.getTeam()`, letting a Super Admin narrow the feed to one person's actions (`entries.filter(a => a.actorId === adminFilter)`, layered on top of the type filter). Anyone else instead sees a static note (`#activity-scope-note`) explaining they're seeing platform events plus their own actions only — and their query never even reaches for other admins' actions, since `getVisibleActivity()` itself is already scoped (see `admin/assets/data.js` below).

settings.html (`admin/assets/settings.js`) — the most interaction-dense page: - **My Profile:** `renderMyProfile()` shows whoever `VetraAdmin.getCurrentAdmin()` currently resolves to. **Change Photo** (`wireAvatarUpload()`) is a real, working upload: clicking the button forwards the click to a hidden `<input type="file">`, then a `FileReader` reads the chosen image as a base64 data URL and calls `VetraAdmin.setTeamMemberAvatar(me.id, dataUrl)` — which persists it to that admin's `localStorage` record, re-renders the profile card and team list, and calls `AdminUI.applyCurrentAdminAvatar()` so the header avatar updates immediately without a reload. - **Admin Team** (`renderTeam()`): each row's **Remove** button opens a `danger: true` confirm; on confirm, `VetraAdmin.removeTeamMember(id)` either succeeds (re-renders the list) or returns `{ok: false, error: "last-super-admin"}`, in which case an `AdminUI.info()` dialog explains the block instead of removing anyone — the UI never lets the console reach zero Super Admins. - **Add Admin** is a two-step flow, not one form: 1. `wireAddAdminModal()` — the **Add Admin** button opens `#add-admin-modal` (name/email/role fields). Submitting calls `VetraAdmin.inviteTeamMember({name, email, role})`, which creates a pending-invite record with a freshly generated verification code, closes the invite modal, re-renders the pending-invites list, and immediately opens the verify modal for the invite that was just created. 2. `openVerifyModal(inviteId)` / `wireVerifyInviteModal()` — the verify modal just asks for a code (any non-empty value is accepted, per how this was explicitly requested — see DOCUMENTATION.md §7). Submitting calls `VetraAdmin.verifyTeamInvite(inviteId, codeEntered)`; on success it closes the modal, re-renders both the team list and pending-invites list, and shows an `AdminUI.info()` "Admin added" confirmation naming the new member's role. - **Pending Invitations** (`renderPendingInvites()`, section hidden entirely when the list is empty): each row's **Verify** button re-opens the same verify modal as step 2 above; **Cancel** opens a `danger: true` confirm calling `VetraAdmin.cancelInvite(id)`. - **Reset Demo Data:** a `danger: true` confirm warning that "any changes you've made in this browser will be lost," calling `VetraAdmin.resetDemoData()` (wipes the `localStorage` key and re-seeds it) and then hard-navigating to `dashboard.html`. - **Sign Out:** a plain confirm, no state change beyond navigating to `../signin.html` — it doesn't actually clear `currentAdminId`, so reopening any admin page in the same browser still resolves to the same "logged in" admin (a known limitation of simulating a session with a single `localStorage` field instead of a real one — see DOCUMENTATION.md §9). - Platform-control toggles (require vendor approval, auto-flag listings, guest checkout, maintenance mode) have no JS behind them at all — flipping one changes nothing else on the page or in `localStorage`; they're purely cosmetic, matching the equivalent switches on `vendor/profile.html`.

login.html — no dedicated JS file; the sign-in logic is a `<script>` block inline in the page itself. Clicking **Sign in to console** validates both fields are non-empty (turns the field's border red if not, via inline `style.borderColor`), then calls `VetraAdmin.setCurrentAdminByEmail(emailField.value.trim())` — a case-insensitive lookup against `admin/assets/data.js`'s seeded team roster by email only, **no password comparison happens at all**, matching the "any password works" note printed right on the page. If the email doesn't match any team member, `setCurrentAdminByEmail()` returns `null` and the "current admin" simply doesn't change — the page still redirects to `dashboard.html` regardless, where everything renders based on whichever admin was last successfully resolved (possibly from a previous session), not a fresh "no one is logged in" state. There's a 250ms `setTimeout` before the redirect purely for a "Signing in..." button-state effect, not for anything asynchronous actually happening.

Where the state actually lives (`admin/assets/data.js`)

Everything above eventually bottoms out in one `const VetraAdmin = (() => {...})();` module, backed by a single `localStorage` key, `vetra_admin_state_v1`. A few implementation details worth knowing if you're extending this file:

- **load()** reads that key on first script execution; if it's missing/unparseable (private browsing, first visit, cleared storage), it deep-clones the `SEED` constant and persists that instead — so the app never renders with truly empty state. It also backfills fields that didn't exist in older saved states (`pendingInvites`, `currentAdminId`, and — added with the KYC feature — a default `kyc: {status: "not_submitted", ...}` on any vendor record missing one), so a browser with state saved from before a feature existed doesn't crash reading `undefined.status`.
- **Every mutating function follows the same shape:** look up the record, mutate the in-memory `state` object directly (not immutably — no copies), call the module-private `save()` (which just `JSON.stringify`s the whole state back into `localStorage`), then call `logActivity()` with a human-readable message built from the record's own fields (never a generic

"record updated"). This is why every action across the console is independently auditable — the log entry is written from inside the same function that made the change, not bolted on by whichever page called it.

- `logActivity(type, message, target, opts)` : `target` is `{type, id}` for anything with a detail page to link back to (`null` for pure login/system events). The fourth parameter, `opts.systemEvent`, is a later addition (added alongside the buyer-report-filing feature) that skips attributing the entry to `getCurrentAdmin()` — needed because a report filed from a customer's browser has no admin actor at all, and without this flag the log would wrongly credit whichever admin last signed in on that machine.
- `getVisibleActivity()` is the one function everything role-sensitive routes through instead of the raw `state.activity` array: a Super Admin gets it unfiltered; anyone else gets it filtered to `actorId === null || actorId === getCurrentAdmin().id`. This is a **client-side filter only** — see DOCUMENTATION.md §9 for why that's not a real permission boundary, and `backend/src/routes/admin.routes.js` 's `GET /api/admin/activity` for the server-side version that actually enforces it.
- `addReport()` (added for the buyer-report-filing feature) is the one function in this file explicitly designed to be called from *outside* the admin console — see `customer/assets/report-issue.js`, which loads this file directly via `<script src='../admin/assets/data.js'>` rather than treating it as admin-only.

8. Site-wide review: redundancies, fixes, and what still needs attention

An audit pass was run across the public site, customer app, and vendor app (the admin section was excluded from the audit since it was just built and independently verified separately — every stat card, table, filter tab, search box, and confirm-modal flow on all six admin pages was clicked through in an automated browser test and confirmed to work, including that suspending a customer persists after a page reload). Everything below that was flagged as an actual bug was fixed in this session and re-verified with another automated browser pass (checked live: cart quantity/price/subtotal math, "Contact vendor" navigation, the checkout flow, the chat Send button, both settings buttons, the vendor product grid after the JS consolidation, and the signup→signin vendor-mode handoff — zero console errors).

Fixed

Where	Problem	Fix
<code>customer/cart.html</code>	The Checkout , Save for later , quantity <code>-/+</code> steppers, and Contact vendor buttons had no JS behind them at all — clicking any of them did nothing. This is the site's core purchase flow, so it was the highest-impact finding.	Added <code>customer/assets/cart.js</code> : quantity steppers now recompute that line's price and the whole order summary (subtotal + total) live; "Contact vendor" opens the chat app; "Checkout"/"Save for later" give real click feedback (a processing state, then a confirmation) in place of the mock payment/save API this prototype doesn't have.
<code>customer/chat.html</code>	The Send button (and pressing Enter) did nothing — messages could never actually be sent in the demo chat UI.	Wired <code>sendMessage()</code> into the chat-window render: it appends the message to that conversation's history, renders it into the thread, updates the sidebar preview/time, and clears the input.

Where	Problem	Fix
<code>customer/settings.html</code>	"Manage payment methods" and "Deactivate account" had no <code>id</code> and no handler — every other button on that page was wired, these two were an apparent oversight.	Gave both an <code>id</code> and a handler matching the same <code>confirm+alert</code> "hook this up to your API" placeholder pattern already used by <code>vendor/assets/profile.js</code> 's danger-zone buttons, so the whole site's mock-action convention now applies consistently here too.
<code>signup.js</code>	After validating the form, the Continue button just sat on "Creating account..." forever — the signup flow had no redirect at all, unlike sign-in.	Added the same delayed-redirect pattern <code>signin.js</code> uses, sending the new account to <code>signin.html</code> (or <code>signin.html#Vendor</code> if they registered as a vendor).
<code>signin.js</code>	Didn't handle a <code>#Vendor</code> URL hash, even though <code>signup.js</code> already produced/expected that pattern for its own hash-based deep link — a latent inconsistency that the signup fix above would otherwise have silently tripped over (landing on the Buyer tab after registering as a Vendor).	Added the matching hash check so <code>signin.html#Vendor</code> now pre-selects the Vendor tab, closing the gap between the two auth pages.
<code>vendor/assets/dashboard.js</code> + <code>vendor/assets/products.js</code>	Both files contained byte-for-byte identical <code>wireVendorProductActions()</code> / <code>wireAddProductButton()</code> functions — accidental copy-paste, not the intentional shared-CSS convention used elsewhere, so a future edit to one copy could silently drift from the other.	Merged both into one <code>vendor/assets/product-actions.js</code> , updated <code>dashboard.html</code> and <code>products.html</code> to load it, deleted the two duplicates. Re-verified Edit/Remove and the Add Product modal still work on both pages.

Reviewed and left as-is (working as intended)

- **Sidebar/bottom-nav links** across every customer and vendor page resolve correctly and are consistent sibling-to-sibling.
- `vendor/assets/add-product.js` **modal** (shared by `dashboard.html` and `products.html`) opens/closes correctly via its close button, Cancel, backdrop click, and Escape.
- **Contact form, FAQ accordion** (`script.js`) on the public pages work.
- Several buttons intentionally `alert()` a "hook this up" placeholder rather than navigate (vendor Edit product, avatar edit, change password) — this is the established, deliberate pattern for "the backend doesn't exist yet" across the codebase, not a bug, so these were left alone.
- `customer/assets/interactions.js` vs `vendor/assets/interactions.js` and `signin.js` vs `signup.js`'s buyer/vendor toggle logic are near-duplicates of each other by the same intentional per-area convention described in §2/§6 — low-priority, cosmetic overlap, not touched.

Still open (needs a human decision, not a quick fix)

- `customer/cart.html`'s "Visit store" link (previously "Contact vendor") only appears for cart lines whose product has a `vendorId` in `products.js` — most of the dashboard/explore/category catalog doesn't (see the two-vendor-lists note below), so it won't show on most lines. A real vendor-linked catalog would remove this gap entirely rather than needing a per-item workaround.
- **Two separate, unreconciled fictional vendor lists.** `admin/assets/data.js`'s `SEED.vendors` (the vendors admin actually manages, `v1 – v7`) and `customer/store.html`'s own `VENDORS` object (`gods-favour`, `daniel-ice-fish`, `jennet-jeans`, `me-n-u-chops`, used across `store.html` and now `orders.html`'s report-filing) were built independently and only coincidentally overlap once (`Naija Home Essentials = v3`). A report filed against one of the other three shows up correctly in `admin/reports.html`'s main queue (see §5/§8) but won't deep-link to a real vendor-detail page, since its `targetId` doesn't match any admin vendor record. Fixing this properly means picking one vendor list and having both apps reference it — bigger than a quick patch, so flagged here rather than partially addressed.

- Everything in §9 below (auth, database, uploads, cart/chat persistence) — these are architecture-level gaps, not bugs in the existing code.

Feature gaps closed by a follow-up audit

A later audit pass (live-rendering check across 15 priority pages at mobile and desktop widths, plus a static sweep for orphaned images and dead JS) found zero rendering bugs but three gaps between what the site *claims* and what it actually lets someone do — all three closed in this session:

1. **No order history or delivery tracking**, despite "real-time delivery tracking" being advertised on `index.html` and `buyer-protection.html`, and vendors being told to "log tracking details" on `vendor-protection.html`. Added `customer/orders.html` (order history + expandable tracking timeline) and an **Update shipment** modal on `vendor/orders.html` (status/carrier/tracking-number, per order) — see §5 and §6 above.
2. **No customer-facing review UI**, despite "verified reviews only" being a repeated selling point. Added a Reviews section (summary + review list + write-a-review form) to `customer/store.html` — see §5 above.
3. **No vendor-facing view of reports filed against their store** — admin had a full moderation queue (`admin/reports.html`) but a vendor had no way to even see a report existed, let alone respond to it, despite `vendor-protection.html` walking vendors through exactly that flow. Added a read-only **Reports against your store** panel to `vendor/orders.html` — see §6 above.

The same audit also found 5 image files with zero references anywhere in the codebase (the original `logo.png` before the brand-asset generation pass, two unused mark-only logo variants, and two duplicate `avatar-dummy.jpg` files shadowed by an identically-purposed `.png`). Moved to `extras/` rather than deleted outright, in case they're wanted later.

A fourth gap of the same shape was reported directly by name afterward, not found by an audit pass:

1. **No vendor-facing KYC/business-verification UI**, despite `buyer-protection.html` stating "every Vendor passes ID and business verification before their first listing ever goes live." Added a **Business Verification (KYC)** section to `vendor/profile.html` (CAC number + ID/CAC certificate upload, `vendor/assets/kyc.js`) and a matching review card to `admin/vendor-detail.html` (`VetraAdmin.setVendorKycStatus()`) — see §6 and §7 above.

A follow-up audit, specifically hunting for this exact pattern (a claim in the site's copy with no matching feature anywhere), found two more — both reported and then closed in the same session:

1. **No way for a buyer to actually file a dispute/report against an order.** `buyer-protection.html` and `vendor-protection.html` both describe a detailed "buyer reports an issue → escrow stays held → vendor gets 48 hours to respond → admin rules" flow, and `admin/reports.html` exists to review exactly that — but `customer/orders.html`'s "Report an issue" button just opened generic live chat, and `admin/assets/data.js` had no `addReport()` function for anything to call at all. Added a **File a report** modal to `customer/orders.html` (`customer/assets/report-issue.js`) and a new `VetraAdmin.addReport()` — see §5 above for how this one deliberately reaches across into the admin console's `localStorage`, unlike every other customer/vendor feature.
2. **No vendor UI to set or view a payout bank account**, despite `vendor-protection.html` describing payouts running "straight to the bank account on file," and `vendor/earnings.html` itself captioning payout-history rows "Payout to bank account" as if one already existed — the field was missing from both the vendor form and the admin data model, not just missing a form. Added a **Payout Account** section to `vendor/earnings.html` (`vendor/assets/payout.js`) — see §6 above.

Both of those were fixed in the same session they were found. A seventh gap of this shape was reported directly by name afterward:

1. **Admin couldn't actually see a vendor's submitted KYC documents, only a filename** — the "Business Verification (KYC)" card added for gap #4 rendered `idDocumentName / cacDocumentName` as plain text, so **Verify Documents** asked an admin to confirm something they had no way to look at. Generated two clearly-watermarked "DEMO / SAMPLE" placeholder document images (`admin/assets/images/kyc-samples/id-document-sample.jpg`, `cac-certificate-sample.jpg` — deliberately generic and obviously-fake rather than resembling any real identity document or government certificate, since this prototype has no real uploaded-file storage to reference instead) and wired every seeded vendor's `kyc` object to point at them; `docChip()` in `admin/assets/vendor-detail.js` now renders an actual clickable thumbnail that opens the full document in a new tab — see §7 above.

9. What a real backend needs to replace

This prototype intentionally fakes several things. **A real backend now exists in `backend/`** (see `BACKEND_GUIDE.md` for the full build plan, data model, API reference, and — as of this session — a shared-hosting-to-VPS scaling guide for when the site outgrows Namecheap shared hosting) — it isn't wired up to any of the frontend below yet, so every point here still describes the frontend's *current* behavior, not a remaining unbuilt gap in all cases. Where the real backend already covers a point, that's noted inline.

1. **Authentication.** `signin.js`, `signup.js`, and `admin/login.html` 's inline script all just check "is this field non-empty" (`admin/login.html` additionally matches the email against the team roster to know *which* admin it is, but never checks a password) and redirect. There is no real password check, no session/token, and — critically — **no server-side check that a signed-in admin is actually an admin**. Anyone who knows the URL can open `admin/dashboard.html` directly and, via `localStorage`, even set `currentAdminId` to any admin's id. `backend/ 's /api/auth/*` routes (`BACKEND_GUIDE.md` §5) already implement real password hashing, JWTs, and role-based checks server-side — this frontend just doesn't call them yet.
2. **Admin roles gate almost nothing server-side.** The one real enforcement right now is client-side: `getVisibleActivity()` filters what a non-Super-Admin's activity log shows, and `removeTeamMember()` blocks deleting the last Super Admin. Nothing stops a Moderator or Support admin from calling `setVendorStatus`, `resetCustomerPassword`, etc. directly — the UI just doesn't currently offer every action to every role by design intent, not by enforcement. `backend/src/routes/admin.routes.js` already enforces `requireRole("admin")` and, on two Super-Admin-only routes, `requireAdminRole("Super Admin")` — again, unused by this frontend so far.
3. **The admin invite/verification flow is fully simulated.** `inviteTeamMember()` generates a code and displays it directly in the UI instead of emailing it, and `verifyTeamInvite()` accepts *any* non-empty value as correct — there is no real email delivery or code matching. The real `POST /api/admin/invites / .../verify` routes hash the code and check it for real, but still log the raw code to the server console instead of emailing it (`BACKEND_GUIDE.md` §5 flags this as the one deliberately incomplete piece, pending an email provider).
4. **Password reset doesn't reset anything real.** `resetCustomerPassword()` / `resetVendorPassword()` generate a temporary string and show it to the admin — there's no real customer/vendor password store to write it to, since buyer/vendor accounts aren't real accounts in this prototype either (see point 1). Same email-provider gap as point 3 on the real backend's equivalent routes.
5. **A real database.** Every "list of customers/vendors/products/orders" is hard-coded JS or, in the admin console, `localStorage` — which is per-browser and never seen by anyone else. `backend/ 's MySQL schema` (`BACKEND_GUIDE.md` §3) already models all of it; the frontend just isn't reading from it.
6. **`admin/assets/data.js` is the seam.** It already isolates every read/write behind named functions (`getCustomers`, `setCustomerStatus`, `resetCustomerPassword`, `getVendors`, `setVendorStatus`, `resetVendorPassword`, `getReports`, `setReportStatus`, `getActivity`, `getVisibleActivity`, `logActivity`, `getTeam`, `setTeamMemberAvatar`, `removeTeamMember`, `inviteTeamMember`, `verifyTeamInvite`, `getCurrentAdmin`, `setCurrentAdminByEmail`, `getStats`, plus the `getActivityForTarget` / `getReportsForTarget` lookups the detail pages use). Swapping its internals from `localStorage` to `fetch()` calls against `backend/ 's` already-built API — and its avatar storage from base64 data URLs to real file uploads (still 🕒 planned, per `BACKEND_GUIDE.md` §5's summary table) — is the intended upgrade path; no other admin file talks to storage directly.
7. **Platform-control toggles** on `admin/settings.html` (require vendor approval, auto-flag listings, guest checkout, maintenance mode) are currently cosmetic switches with no effect — they need to be wired to real server-side flags that other parts of the app actually check. Not yet built on the backend either.
8. **File uploads** (product images/video in the vendor "Add Product" modal, avatar edit buttons) only preview locally in the browser; nothing is actually uploaded anywhere. 🕒 planned on the backend too (`BACKEND_GUIDE.md` §7 step 8).
9. **Chat** (`customer/chat.html`) is UI-only — no real messages are sent, and the real backend doesn't have this yet either (it needs polling rather than WebSockets on shared hosting — see `BACKEND_GUIDE.md` §2 and, for what changes once the site moves to a VPS, its new §9). **Cart is the exception here** — `customer/cart.html` now runs on a real `CartStore` (`customer/assets/cart-store.js`, `localStorage` -backed) that persists across pages and reloads, added earlier this session; it's still not backed by a server (a `POST /api/orders` checkout call, per `BACKEND_GUIDE.md` §5, is what replaces it), but it's no longer just UI with nothing behind it the way chat still is.

10. Design system reference (for anyone extending a page)

Shared building blocks used across customer, vendor, and admin (defined per-area in each `assets/style.css`, kept visually identical):

- **Layout:** `.app-shell` → `.sidebar` (desktop) + `.phone` (scroll container) → `header#app-header` → `main.page-shell` → `nav.bottom-nav` (mobile).
- **Cards/sections:** `.vendor-section` (generic card container, used well beyond vendor pages), `.stat-grid` / `.stat-card` (KPI tiles).
- **Tables (admin only):** `.table-wrap` + `table.data-table`, row actions via `.table-actions` button with semantic classes `.btn-view/.btn-suspend/.btn-activate/.btn-approve/.btn-reject`.
- **Status pills:** `.status-pill` (orders: pending/processing/shipped/out-for-delivery/completed/cancelled — the last two states added for order tracking), `.badge` (admin + vendor reports panel: active/suspended/pending/resolved/dismissed/open).
- **Forms:** `.form-grid` / `.form-group` / `.form-input` / `.form-textarea`, `.switch` (toggle), `.danger-zone` (destructive settings). `customer/assets/style.css` also defines a lighter `.field-group` (label + input/select/textarea) shared by `settings.html` and `store.html`'s review form.
- **Modals:** `.modal-overlay` + `.modal-panel` (Add Product, confirm dialogs, detail views, vendor/orders.html's Update Shipment and Submit Evidence modals). `customer/assets/style.css` gained its own copy of this block for `orders.html`'s File a Report modal — same class names as vendor/admin, kept in its own file per the usual convention.
- **Filter tabs:** `.order-filter-tabs` `.filter-tab.active`.
- **Report cards:** `.report-list` / `.report-card` / `.report-card-head` / `.report-reason` / `.report-meta-row` / `.report-actions` — originally admin-only (`admin/assets/style.css`), the same class names/shapes now also exist in `vendor/assets/style.css` for the read-only vendor-side view, so a report renders identically in both places.

If you add a new page to any app, copy the closest existing sibling page's `<head>` /`sidebar/header/bottom-nav` markup rather than writing it from scratch — this is how every existing page in the codebase was built, and it's what keeps the three apps visually consistent.