

3D Computer Graphics



Rasterization

Dr. Zhigang Deng



UNIVERSITY *of* HOUSTON

DEPARTMENT OF COMPUTER SCIENCE

Polygon Meshes



Life of Pi
(2012)




UNIVERSITY *of* **HOUSTON**

DEPARTMENT OF COMPUTER SCIENCE



Triangle Meshes




UNIVERSITY *of* **HOUSTON**

DEPARTMENT OF COMPUTER SCIENCE



Triangle Meshes




UNIVERSITY *of* **HOUSTON**

DEPARTMENT OF COMPUTER SCIENCE


Triangles - Fundamental Shape Primitives

Why triangles?


- Most basic polygon
 - Break up other polygons
- Unique properties
 - Guaranteed to be planar
 - Well-defined interior
 - Well-defined method for interpolating values at vertices over triangle (barycentric interpolation)



What Pixel Values Approximate a Triangle?



Input: position of triangle
vertices projected on screen





A Simple Approach: Sampling





Sampling a Function

Evaluating a function at a point is sampling.

We can **discretize** a function by sampling.


```
for (int x = 0; x < xmax; ++x)
    output[x] = f(x);
```

Sampling is a core idea in graphics.


We sample time (1D), area (2D), direction (2D), volume (3D) ...




Rasterization As 2D Sampling



Sample If Each Pixel Center Is Inside Triangle



Sample If Each Pixel Center Is Inside Triangle






Define Binary Function: `inside (tri, x, y)`

`x, y`: not necessarily integers

`inside (t, x, y)` = $\begin{cases} 1 & \text{Point (x, y) in triangle t} \\ 0 & \text{otherwise} \end{cases}$






Rasterization = Sampling A 2D Indicator Function

```
for (int x = 0; x < xmax; ++x)
    for (int y = 0; y < ymax; ++y)
        image[x][y] = inside(tri,
                               x + 0.5,
                               y + 0.5);
```



Recall: Sample Locations



Sample location for pixel (x, y)






Evaluating `inside(tri, x, y)`




Inside? Recall: Three Cross Products!




Edge Cases (Literally)

Is this sample point covered by triangle 1, triangle 2, or both?




Handling Edge Pixels

Don't use edges ($e==0$) – missing pixels




Always use edges ($e==0$) – waste & flicker



Need to include edge pixels on left or right edges (also determined by sort) to avoid pinholes between tris.



Checking All Pixels on the Screen?




Use a **Bounding Box**!



UNIVERSITY *of* **HOUSTON**


DEPARTMENT OF COMPUTER SCIENCE

Incremental Triangle Traversal (Faster?)



suitable for thin and rotated triangles







Rasterization on Real Displays



Real LCD Screen Pixels (Closeup)



iPhone 6S



Galaxy S5


Notice R,G,B pixel geometry! But in this class, we will assume a colored square full-color pixel.



UNIVERSITY *of* **HOUSTON**

DEPARTMENT OF COMPUTER SCIENCE

Aside: What About Other Display Methods?




UNIVERSITY *of* **HOUSTON**

DEPARTMENT OF COMPUTER SCIENCE

Color print: observe half-tone pattern


Assume Display Pixels Emit Square of Light




LCD pixel on laptop





* LCD pixels do not actually emit light in a square of uniform color, but this approximation suffices for our current discussion




So, If We Send the Display the Sampled Signal




The Display Physically Emits This Signal



Compare: The Continuous Triangle Function





What's Wrong With This Picture?



Jaggies!



Aliasing (Jaggies)




Is this the best we can do?



UNIVERSITY *of* **HOUSTON**

DEPARTMENT OF COMPUTER SCIENCE



Thank you!

(And thank Prof. lingqi Yan, Prof. Ravi Ramamoorthi and Prof. Ren Ng for many of the slides!)



UNIVERSITY *of* **HOUSTON**

DEPARTMENT OF COMPUTER SCIENCE