

Bym model for spatial effects

Parametrization

This model is simply the sum of a besag model and a iid model.

The benefite is that this allows to get the posterior marginals of the sum of the spatial and iid model; otherwise it offers no advantages.

Hyperparameters

The hyperparameters are the precision τ_1 of the iid model and the precision τ_2 of the besag model. The precision parameters are represented as

$$\theta = (\theta_1, \theta_2) = (\log \tau_1, \log \tau_2)$$

and the prior is defined on θ .

Specification

The bym model is specified inside the `f()` function as

```
f(<whatever>, model="bym", graph.file=<graph file name>,  
  hyper=<hyper>, adjust.for.con.comp = TRUE)
```

The neighbourhood structure of `x` is passed to the program through the `graph.file` argument. The structure of this file is described below.

The option `adjust.for.con.comp` adjust the model if the graph has more than one connected compoment, and this adjustment can be disabled setting this option to `FALSE`.

Hyperparameter spesification and default values

hyper

theta1

```
name  log unstructured precision  
short.name  prec.unstruct  
prior  loggamma  
param  1 5e-04  
initial  4  
fixed  FALSE  
to.theta  function(x) log(x)  
from.theta  function(x) exp(x)
```

theta2

```
name  log spatial precision  
short.name  prec.spatial  
prior  normal  
param  0 5e-05  
initial  4  
fixed  FALSE  
to.theta  function(x) log(x)  
from.theta  function(x) exp(x)
```

```
constr TRUE
nrow.ncol FALSE
augmented TRUE
aug.factor 2
aug.constr 2
n.div.by
n.required TRUE
set.default.values TRUE
pdf bym
```

Structure of the graph file

We describe the required format for the graph file using a small example. Let the file `gra.dat`, relative to a small graph of only 5 elements, be

```
5
1 1 2
2 2 1 3
3 3 2 4 5
4 1 3
5 1 3
```

Line 1 declares the total number of nodes in the graph (5), then, in lines 2-6 each node is described. For example, line 4 states that node 3 has 4 neighbours and these are nodes 2, 4 and 5.

The graph file can either have nodes indexed from 1 to n , or from 0 to $n - 1$. Note that in the latter case, node i seen from R corresponds to node $i - 1$ in the 0-indexed graph.

Example

For examples of application of this model see the `Bym` example in Volume I.

Notes

None