

Hugh Baldwin
up2157117

Discrete Mathematics and Functional Programming

M21274

TB2

University of Portsmouth
BSc Computer Science
2nd Year

Contents

I	Discrete Mathematics	2
1	Lecture - Sets	3
II	Functional Programming	5
2	Lecture - Introduction to Funprog	6

Part I

Discrete Mathematics

Lecture - Sets

17:00

23/01/24

Janka Chlebkova

A set is a collection of objects, known as elements or members (I will stick to members). Each member only appears once in the set. There is no particular order for members of a set, so there are several different ways to represent the same set. The members of a set can be just about anything, as long as they all abide by the same rules, and are in some way related.

Notation

There are several ways of noting a set, such as writing out all of the members of the set, or by using a rule which describes all of the members of a set.

For example, the following sets are equivalent

- $A = \{1, 2, 3, 4, 5\}$
- $A = \{x \mid 0 < x \leq 5\}$

If the object, x is in the set S , you would write it as $x \in S$. If not, it would be written as $x \notin S$. You can also describe a set by specifying a property that the members share, e.g.

- $B = \{3, 6, 9, 12\}$
- $B = \{x \mid x \text{ is a multiple of 3, and } 0 < x \leq 15\}$

$$S = \{\dots, -3, -1, 1, 3, \dots\}$$

$$= \{x \mid x \text{ is an odd integer}\}$$

- $= \{x \mid x = 2k + 1 \text{ for some integer } k\}$
- $= \{x \mid x = 2k + 1 \text{ for some } k \in \mathbb{Z}\}$
- $= \{2k + 1 \mid k \in \mathbb{Z}\}$

The Number Sets

Some letters are reserved for specific sets of numbers which can be used elsewhere to simplify definitions, the following are the most commonly used number sets

- \mathbb{N} is used for the set of natural numbers, $\mathbb{N} = \{0, 1, 2, 3, 4, \dots\}$
- \mathbb{Z} is used for the set of integers, $\mathbb{Z} = \{\dots, -2, -1, 0, 1, 2, \dots\}$
- \mathbb{Q} is used for the set of rational numbers, $\mathbb{Q} = \{0, \frac{1}{2}, \frac{1}{3}, \dots\}$
- There is also the empty or null set, \emptyset which contains no items, so $\emptyset = \{\}$

A set can either be finite or infinite, and the cardinality of a set is the number of members, e.g. $|S|$ = the number of members of S . For example, \mathbb{N} and \mathbb{Z} are infinite sets, and the set $A = \{1, 2, 3\}$ is a finite set with a cardinality of 3, so $|A| = 3$

Subsets

If every member of A is also a member of B , A is said to be a subset of B , which can be written as $A \subseteq B$. If B also has at least 1 member which is not a member of A , then A is a proper subset of B , which can be written as $A \subset B$. If A is not a subset of B , it can be written as $A \not\subseteq B$. Since the null set, \emptyset contains no elements, it is a subset of every other set.

Equality of Sets

If two sets, A and B are equal, they have exactly the same members, which can be written as $A = B$. Alternatively, $A = B$ if the following conditions are true:

- $A \subseteq B$, and so for each x , if $x \in A$ then $x \in B$
- $B \subseteq A$, and so for each y , if $y \in B$ then $y \in A$

Operations

The intersection of two sets, A and B is every member in both sets, $A \cap B$. For example, the intersection of the sets $X = \{1, 2, 3, 4, 5\}$ and $Y = \{4, 5, 6, 7, 8\}$ is $X \cap Y = \{4, 5\}$. If there are no common members, then the two sets are said to be disjoint. You can remember this by the fact that \cap looks like an n, and therefore is the **I**ntersection of two sets.

The union of two sets, A and B is every member in either set, $A \cup B$. For example, the union of the sets $X = \{1, 2, 3, 4, 5\}$ and $Y = \{4, 5, 6, 7, 8\}$ is $X \cup Y = \{1, 2, 3, 4, 5, 6, 7, 8\}$. You can remember this by the fact that \cup looks like a U, and therefore is the **U**nion of two sets.

The difference of two sets, A and B are all members of the first set which are not members of the second set, $A \setminus B$. For example, the difference of the sets $X = \{1, 2, 3, 4, 5\}$ and $Y = \{4, 5, 6, 7, 8\}$ is $X \setminus Y = \{1, 2, 3\}$. This is the effectively subtracting the sets, $X - Y$.

If we consider all of the sets to be a subset of a particular set, U which contains all of the members of the “Universe of Discourse”, then the complement of a set, A is any members of U which are not in A . This is represented as either A' or \bar{A} .

All of these operations can be represented using a Venn diagram.

Like binary arithmetic, these operations follow a few rules:

- Commutative - $A \cup B = B \cup A$ and $A \cap B = B \cap A$
- Associative - $(A \cup B) \cup C = A \cup (B \cup C)$ and $(A \cap B) \cap C = A \cap (B \cap C)$
- Distributive - $A \cap (B \cup C) = (A \cap B) \cup (A \cap C)$ and $A \cup (B \cap C) = (A \cup B) \cap (A \cup C)$
- de Morgan's - $(A \cap B)' = A' \cup B'$ and $(A \cup B)' = A' \cap B'$

To get the cardinality of the union of two finite sets, you might think it would just be $|A \cup B| = |A| + |B|$, however, this results in counting $|A \cap B|$ twice, and so the correct cardinality is $|A \cup B| = |A| + |B| - |A \cap B|$.

The Power Set

The power set is a set containing all subsets of the set, so if $S = \{a, b, c\}$, then the power set $P(S)$ would be $P(S) = \{\emptyset, \{a\}, \{b\}, \{c\}, \{a, b\}, \{b, c\}, \{a, c\}, \{a, b, c\}\}$. If the set S has n members, $P(S)$ has 2^n members.

Part II

Functional Programming

Lecture - Introduction to Funprog

12:00

22/01/24

Matthew Poole

- For this module, we will be using the GHC (Glasgow Haskell Compiler), or more specifically it's interactive shell, GHCi

Imperative VS Functional Programming

- Most programming languages are imperative
 - Such as Python, JavaScript, C, etc
- Functional programming is another programming paradigm, which is based upon the mathematical concept of a function
- Imperative programming has state, statements (or commands) and side effects
- Pure Functional programming has no state, statements, or side effects
- A side effect is the change of state caused by calling a functionl assigning a variable, etc
 - This means that it is not always possible to predict the result of running a program, even with access to it's source code
- Since most programs need to cause a side effect (usually outputting data), most functional programming languages are not purely functional, but tend to organise the code such that only one part causes side effects

Functional Programming Languages

- There are two types of functional programming languages
- Pure
 - Languages such as Haskell
 - Has absolutely no state or side effects
- Impure
 - Languages such as ML, Clojure, Lisp, Scheme, OCaml, F#
 - Has some state or side effects, either everywhere or in a specific part of code
- There are also some functional constructs in major imperative languages such as Python, JavaScript, and more

FP Basics

Expressions

- An expression is a piece of text which has a value
- To get the value from the expression, you evaluate it
- This gives you the value of the expression
- e.g.
- Expression \rightarrow evaluate \rightarrow Value
 $2 * 3 + 1$ -----> 7

Functions

- A function whose output relies only upon the values that are input into it
- The result will always be the same, given the same values
- This is the same as a mathematical function, which is where the name Functional Programming comes from

Haskell Basics

- In Haskell, all functions have higher precedence than operators
- This means that you have to explicitly use brackets to ensure the correct order of operations