

NT219-Cryptography

Week 09: Asymmetric Cryptography (P3)

PhD. Ngoc-Tu Nguyen

tunn@uit.edu.vn

Outline

- Why asymmetric cryptography?
- Factoring Based Cryptography (P1)
 - RSA
 - *Rabin*
- Logarithm Based Cryptography (P2)
- Elliptic Curve Cryptography (P3)
- Some advanced cryptography system (quantum resistance)

ElGamal parameters

Large prime number: p

Multiplicative group

$$G = \langle g \rangle = \mathbb{Z}_p \setminus \{0\} = \{1, 2, \dots, p - 1\}$$


Key generation (

Secret key: $x \in_R [1, p - 1]$

Public key: $h = g^x \bmod p \in \mathbb{Z}_p$

ElGamal cipher

- **Encryption message $m < p - 1$ (using public key $h = g^x$)**
 - Choose a random number: $r \in_R [1, p - 1]$
 - Compute $C_1 = g^r \bmod p$;
 - Compute $C_2 = m \cdot h^r \bmod p$
 - Output cipher message (C_1, C_2)
- **Decryption (C_1, C_2) (using secret key x)**
 - Compute $(C_1)^x \bmod p = g^{r \cdot x} \bmod p$;
 - Compute $\frac{C_2}{(C_1)^x} \bmod p = \frac{m \cdot g^{x \cdot r}}{g^{r \cdot x}} \bmod p = m$
 - Output message m



Input: $M < p$

Select a random number: $r < p - 1$

Compute: $C_1 = g^r \bmod p$
 $C_2 = m \cdot h_B^r \bmod p$

(C_1, C_2)

Compute:


$$\begin{aligned} & \frac{C_2}{(C_1)^{x_B}} \bmod p \\ &= \frac{m \cdot g^{x_B \cdot r}}{g^{r \cdot x_B}} \bmod p = m \end{aligned}$$

Outline

- Why asymmetric cryptography?
- Factoring Based Cryptography (P1)
 - RSA signature;
- Logarithm Based Cryptography (P2)
 - ElGamal cipher
 - **Diffie-Hellman key exchange;**
- Elliptic Curve Cryptography (P3)
- Some advanced cryptography system (quantum resistance)

Diffie-Hellman key exchange

- A and B never met and share no secrets;
- Public info: the prime number p and g
 - p is a large prime number, g is a generator of Z_p^*
 - $Z_p^* = \{1, 2 \dots p-1: \forall a \in Z_p^* \exists i \text{ such that } a = g^i \bmod p\}$



Diffie-Hellman exchange Protocol (DHE)

$p = 1606938044258990275541962092341162602522202993782792835301301$
 $g = 123456789$



$g^a \bmod p =$

78467374529422653579754596319852702575499692980085777948593



$g^b \bmod p =$

560048104293218128667441021342483133802626271394299410128798

$a =$

685408003627063
 761059275919665
 781694368639459
 527871881531452

$(g^b)^a \bmod p$

$b =$

362059131912941
 987637880257325
 269696682836735
 524942246807440

$(g^a)^b \bmod p$

$g^{ab} \bmod p =$

437452857085801785219961443000
 845969831329749878767465041215


Why Is Diffie-Hellman Secure?

- Discrete Logarithm (DL) problem:
given $g^x \bmod p$, it's hard to extract x
 - There is no known efficient algorithm for doing this
 - This is not enough for Diffie-Hellman to be secure!
- Computational Diffie-Hellman (CDH) problem:
given g^x and g^y , it's hard to compute $g^{xy} \bmod p$
 - ... unless you know x or y , in which case it's easy
- Decisional Diffie-Hellman (DDH) problem:
given g^x and g^y , it's hard to tell the difference between $g^{xy} \bmod p$ and $g^r \bmod p$ where r is random


Properties of Diffie-Hellman

- Assuming DDH problem is hard, Diffie-Hellman protocol is a secure key establishment protocol against passive attackers
 - Eavesdropper can't tell the difference between the established key and a random value
 - Can use the new key for symmetric cryptography
- Basic Diffie-Hellman protocol does not provide authentication
 - IPsec combines Diffie-Hellman with signatures, anti-DoS cookies, etc.


Man-in-the middle attacks the DHE



man-in-the-middle attack!



RSA cipher (Review)



ElGamal cipher

Encryption message $m < p - 1$ (using public key $h = g^x$)

- Choose a random number: $r \in_R [1, p - 1]$ **why?**
- Compute $C_1 = g^r \bmod p$;
- Compute $C_2 = m \cdot h^r \bmod p = m \cdot g^{x \cdot r} \bmod p$
- Output cipher message (C_1, C_2)

Decryption (C_1, C_2) (using secret key x)

- Compute
$$\frac{C_2}{(C_1)^x} \bmod p = \frac{m \cdot g^{x \cdot r}}{g^{r \cdot x}} \bmod p = m$$

Computational hardness assumptions

- Integer factorization Problem ;

$$n(= p \cdot q) \not\mapsto \varphi(n) = (p - 1)(q - 1)$$

- Discrete Log Problem (DLP):

$$g, p, y = g^x \bmod p \not\mapsto x$$

- Diffie-Hellman Problem (DHP):

$$g, p, A = g^a \bmod p, B = g^b \bmod p \not\mapsto g^{ab}$$

Motivations

Group $(G, +)$ can do $+$ $-$
lightweight computational overhead?

Ring $(R, +, \times)$ can do $+$ $-$ $\times$
 $\square Z_{2^n} = \{0, 1, \dots, 2^n - 1\}$

Field $(F, +, \times)$ can do $+$ $-$ $\times$ $\div$
 $\square Z_p = \{0, 1, \dots, p - 1\}$

Elliptic curve

An elliptic curve is a group defined over a field K


elliptic curve group $(E, \oplus)$	can do $\oplus \ominus$
underlying field $(K, +, \times)$	can do $+, -, \times, \div$

operations in underlying field are used and combined to compute the elliptic curve operation $\oplus$


Elliptic curves

Weierstrass form

$$E/K: y^2 = x^3 + ax + b \quad \leftarrow E \text{ specified by } K, a, b$$



$$E/\mathbb{R}: y^2 = x^3 + x + 1$$




$$E/\mathbb{R}: y^2 = x^3 - x$$

Elliptic curves

Weierstrass form

$$E/\mathbb{R} : y^2 = x^3 + x + 1$$

$$E/\mathbb{Z}_7 : y^2 = x^3 + x + 1$$




Elliptic curves

Montgomery form

$$E/K: By^2 = x^3 + Ax^2 + x$$

← E specified
by K, A, B




$E/\mathbb{R} :$

$$\frac{1}{4}y^2 = x^3 + \frac{5}{2}x^2 + x$$

Curve25519

$$E/K: y^2 = x^3 + 486662x^2 + x$$

where field $K = \mathbb{Z}_{2^{255}-19}$



The diagram illustrates the structure of a Curve25519 Keypair, showing the layout of the Private Key and Public Key information, including their respective lengths and the underlying curve equation.

Curve25519 Keypair as defined in RFC 8410

Private Key Structure:

- 46 Bytes [Asymmetric Key]
 - 1 Byte [Version] 0
 - 5 Bytes [Private Key Algorithm] 1.3.101.112
 - 3 Bytes [Algorithm] 1.3.101.112
 - 34 Bytes [Private Key] Ed25519
 - 32 Bytes [Key] 9.63[...] e76

Public Key Structure:

- 42 Bytes [Public Key Information]
 - 5 Bytes [Algorithm Identifier] 1.3.101.112
 - 3 Bytes [Algorithm] 1.3.101.112
 - 33 Bytes [Public Key] Ed25519
 - x = 1.16[...] e76

ASN.1 Types:

- 02 xx Integer
- 06 xx OID
- 03 xx Bit String
- 30 xx Sequence
- xx Bytes
- 04 xx Octet String

Curve Equations:


$$y^2 = x^3 + 486662x^2 + x$$

In X25519, the 'y' coordinate is calculated rather than

Elliptic curves

Twisted Edwards form

$$E/K: ax^2 + y^2 = 1 + dx^2y^2 \leftarrow E \text{ specified by: } K, a, d$$



$E/\mathbb{R} :$


$$10x^2 + y^2 = 1 + 6x^2y^2$$



<https://safecurves.cr.yp.to/>

Elliptic group


Addition of two points:




- If P_1 and P_2 are on E , we can define sum $P_1 + P_2 = P_2 + P_1 \stackrel{\text{def}}{=} P_3$ as shown in picture

Elliptic group

Point Doubling




Special case



$$P + P = \infty \text{ (infinity)}$$

Elliptic group




$$P + (-P) = \infty \text{ (infinity)}$$

$$P + \infty = P$$

$$\infty + P = P$$

Elliptic group

Example



Elliptic group


Given two points P, Q in E/K , there is a third point, denoted by $P + Q$ on E/K , and the following relations hold for all P, Q, R in E/K , where K be a finite field

- $P + Q = Q + P$ (*commutativity*)
- $(P + Q) + R = P + (Q + R)$ (*associativity*)
- $P + O = O + P = P$ (*existence of an identity element*)
- there exists $(-P)$ such that $-P + P = P + (-P) = O$ (*existence of inverses*)

Elliptic group

- Group points E/K
- Subgroup generated by a point G

$$\langle G \rangle = \{G, 2G, \dots, kG, \dots\} = \{kG : k \in K\} \subset E/K$$




$$n = |\langle G \rangle| = |\{kG : k \in K\}|$$

$$h = \frac{|E/K|}{|\langle G \rangle|} \text{ is small!}$$

Elliptic group

- **ECC group parameters:**
 - ✓ ECC equation (type, coefficient): $a, b, \dots$
 - ✓ Modulo: p or $f(x)$
 - ✓ Generator point: G
 - ✓ Order of G : $n = \# \langle G \rangle = \# \{kG : k \in K\}$
 - ✓ Cofactor: $h = \frac{|E/K|}{|\langle G \rangle|}$

$$\langle G \rangle = \{kG : k \in K\} \subset E/K$$



<http://www.secg.org/sec2-v2.pdf>

Using Elliptic Curves In Cryptography

- Hardness assumption.

- Elliptic curve discrete logarithm problem (ECDLP)

$$G, Q(=dG) \not\mapsto d$$

$$\text{where } dG = \underbrace{G + G + \dots + G}_{d \text{ times}}$$

- Discrete Log Problem (DLP):
 $g, p, y = g^x \bmod p \not\mapsto x$

Elliptic Curve Cryptosystems (ECC)

Algorithm	Encryption/Decryption	Digital Signature	Key Exchange
RSA	Yes	Yes	Yes
Elliptic Curve	Yes	Yes	Yes
Diffie–Hellman	No	No	Yes
DSS	No	Yes	No

What Is ECC?

- Elliptic curve cryptography [ECC] is a **public-key** cryptosystem just like RSA, Rabin, and El Gamal.
- Every user has a **public key** $Q(= dG)$ and a **private key** d .
 - Public key is used for encryption/signature verification.
 - Private key is used for decryption/signature generation.
- Elliptic curves are used as an extension to other current cryptosystems.
 - Elliptic Curve Diffie-Hellman Key Exchange
 - Elliptic Curve Digital Signature Algorithm


Generic Procedures of ECC

- Both parties agree to some publicly-known data items
 - The elliptic curve equation
 - Type, values of ***a*** and ***b*** (or others)
 - Modulo: prime ***p*** or ***f(x)***
 - A base point, ***G***, taken from the elliptic group;
 - Others parameters (assure security)
- Each user generates their public/private key pair
 - Private Key: ***d*** $\in [1, p - 1]$
 - Public Key: $Q = d \cdot G = \underbrace{G + G + \dots + G}_{d \text{ times}}$

ECC Cipher

- Suppose **Alice** wants to send to **Bob** an encrypted message.
 - Both agree on a ECC curver and a base point G .
 - Alice and Bob create public/private keys.
 - Alice
 - Private Key = a
 - Public Key = $Q_A = a \cdot G$
 - Bob
 - Private Key = b
 - Public Key = $Q_B = b \cdot G$

ECC Cipher



- Input: $M \in E/K$
- Select a random integer $k \in [1, p - 1]$, compute
- **Encrypt**
 $R = kG, C = M + k PK_B$


(R, C)

- **Decrypt**

$$\begin{aligned}
 C - b R &= M + kb G - b kG \\
 &= M
 \end{aligned}$$


ECC Diffie-Hellman (ECDHE)

- **Public:** Elliptic curve and a point $G=(x,y)$ on curve
- **Secret:** Alice's a and Bob's b




- Alice computes $K_A = a \cdot Q_B = ab \cdot G$
- Bob computes $K_B = b \cdot Q_A = ba \cdot G$
- These are the same since $K_A = K_B = ab \cdot G$

Diffie-Hellman key exchange attack





man-in-the-middle attack!



Diffie-Hellman key exchange attack



Alice




Bob

man-in-the-middle attack!



$(a, Q_A = aG)$



$(b, Q_B = bG)$

Why use ECC?

- How do we analyze Cryptosystems?
 - How difficult is the **underlying problem** that it is based upon
 - RSA – Integer Factorization
 - DH – Discrete Logarithms
 - ECC - Elliptic Curve Discrete Logarithm problem
 - How do we measure difficulty?
 - We examine the algorithms used to solve these problems

Security of ECC

- To **protect** a 128 bit AES key it would take a:
 - RSA Key Size: 3072 bits
 - ECC Key Size: 256 bits
- How do we strengthen RSA?
 - Increase the key length
- **Impractical?**



<https://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-57pt1r5.pdf>

Symmetric Encryption (Key Size in bits)	RSA and Diffie-Hellman (modulus size in bits)	ECC Key Size in bits
56	512	112
80	1024	160
112	2048	224
128	3072	256
192	7680	384
256	15360	512

3

4

5

Applications of ECC

- Many devices are small and have limited storage and computational power
- Where can we apply ECC?
 - **Wireless communication devices**
 - Smart cards
 - Web servers that need to handle many encryption sessions
 - **Any application where security is needed but lacks the power, storage and computational power that is necessary for our current cryptosystems**

Benefits of ECC

- Same benefits of the other cryptosystems: confidentiality, integrity, authentication and non-repudiation but...
- Shorter key lengths
 - Encryption, Decryption and Signature Verification speed up
 - Storage and bandwidth savings

Summary of ECC

- **“Hard problem”** analogous to discrete log
 - $Q=kG$, where Q, G belong to a prime curve
 - given $k, G \rightarrow$ “easy” to compute Q
 - given $Q, G \rightarrow$ “hard” to find k
 - known as the elliptic curve logarithm problem
 - k must be large enough
- ECC security relies on elliptic curve logarithm problem
 - compared to factoring, can use much smaller key sizes than with RSA etc
 - ➔ for similar security ECC offers significant computational advantages