


Simplifying, Regularizing and Strengthening Sum-Product Network Structure Learning

Antonio Vergari, Nicola Di Mauro and Floriana Esposito

{firstname.lastname@uniba.it}




University of Bari “Aldo Moro”, Italy
Department of Computer Science



LACAM
Machine Learning

Sum-Product Networks and Tractable Models

Probabilistic Graphical Models (PGMs) provide a tool to compactly represent joint probability distributions $P(\mathbf{X})$. However, **inference**, the main task one may want to perform on a PGM, is generally **untractable**.



To ensure polynomial inference, tractable models trade off expressiveness.


Sum-Product Networks (SPNs) are DAGs *compiling* a pdf $P(\mathbf{X})$ into a **deep** architecture of **sum** and **product** nodes over univariate distributions X_1, \dots, X_n as leaves. The parameters of the network are the weights w_{ij} associated to sum nodes children edges. Product nodes define factorizations over independent vars, sum nodes mixtures. Products over nodes with different scopes (*decomposability*) and sums over nodes with same scopes (*completeness*) guarantee modeling a pdf (*validity*).



Bottom-up evaluation of the network:

$$S_{X_i}(x_j) = P(X_i = x_j)$$
$$S_+(\mathbf{x}) = \sum_{i \in ch(+)} w_i S_i(\mathbf{x}) \quad S_{\times}(\mathbf{x}) = \prod_{i \in ch(\times)} S_i(\mathbf{x})$$


- Inferences linear in the **size of the network** (# edges):
- $\oplus Z = S(*)$ (all leaves output 1)
 - $\oplus P(\mathbf{e}) = S(\mathbf{e})/S(*)$
 - $\oplus P(\mathbf{q}|\mathbf{e}) = \frac{P(\mathbf{q},\mathbf{e})}{P(\mathbf{e})} = \frac{S(\mathbf{q},\mathbf{e})}{S(\mathbf{e})}$
 - $\oplus MPE(\mathbf{q}, \mathbf{e}) = \max_{\mathbf{q}} P(\mathbf{q}, \mathbf{e}) = S^{max}(\mathbf{e})$, turning sum nodes into max nodes



The **depth of the network** (# layers) determines expressive efficiency [4, 8].

How and why to perform structure learning

SPN structure learning is a constraint-based search. Main ideas: to discover hidden variables for sum nodes and independences for product nodes by applying some form of clustering along matrix axis. Different variations: using K-Means on features [1]; merging features bottom-up with IB heuristics [6]; **LearnSPN** [2] is the first principled top-down greedy algorithm.



LearnSPN builds a tree-like SPN by recursively split the data matrix. It splits columns in pairs by a greedy **G Test** based procedure with threshold ρ : $G(X_i, X_j) = 2 \sum_{x_i \sim X_i} \sum_{x_j \sim X_j} c(x_i, x_j) \cdot \log \frac{c(x_i, x_j) \cdot |T|}{c(x_i) c(x_j)}$ (Figure 1.c); it clusters instances in $|C|$ sets with **online Hard-EM** (Figure 1.b) with cluster number penalty λ : $Pr(\mathbf{X}) = \sum_{C_i \in C} \prod_{X_j \in X} Pr(X_j, C_i)$. Weights are the cluster proportions.

If there are less than m instances, it puts a **naive factorization** over leaves (Figure 1.d). For each univariate distribution it gets its **ML estimation** smoothed by α . LearnSPN hyperparameter space is thus: $\{\rho, \lambda, m, \alpha\}$.

The state-of-the-art, in terms of test likelihood, is **ID-SPN**: it turns LearnSPN in log-likelihood guided expansion of sub-networks approximated by Arithmetic Circuits [7]. However it is overparametrized, and slower.

Tractability is guaranteed if the network size is polynomial in # vars. **Structure quality matters** as much as likelihood. comparing network sizes is more solid than comparing inference times.


LearnSPN is too greedy and the resulting SPNs are overcomplex networks that may not generalize well. **Structure quality desiderata**: *smaller* but *accurate*, *deeper* but not wider, SPNs.

Simplifying by limiting node splits

LearSPN performs two interleaved **greedy hierarchical** divisive **clustering** processes. Each process benefits from the other one improvements and similarly suffers from the other's mistakes.

Idea: slowing down the processes by limiting the number of nodes to split into. SPN-B, variant of LearnSPN that uses EM for mixture modeling but doing only Binary splits for sum nodes children ($k = 2$) when clustering rows.

Objectives: not committing to complex structures too early while retaining same expressive power, indeed successive row splits can represent sum nodes with more than two children; moreover, reducing the node out fan increases the network depth. Plus, there is no need for λ anymore.



By increasingly limiting the max number of allowed splits the depth of the structures increases and the network size rate of growth decreases.





Figure 2. Comparing network sizes and depths while varying the max number of sum node children splits ($k \in \{10, 4, 2\}$). Each dot is an experiment in the grid search hyperparameter space performed by SPN-B on the datasets NLTCS (left) and Plants (right).

Regularizing by introducing tree distributions as leaves

LearnSPN regularization is is governed by the hyperparameters α and m , however using naive factorizations can be ineffective. In order to get accurate networks, the algorithm prefers smaller values for m , resulting in more complex networks

Idea: substitute naive factorizations with Bayesian trees as **multivariate tractable tree distributions**. SPN-BT learns such Trees with the Chow-Liu algorithm while stopping the search.

Objectives: represent more information allowing for larger values of m to be chosen, while preserving tractability for marginals, conditionals and MPE inference.



SPN-BT reduces the size of the networks even more while preserving SPN-B accuracy. At larger values of m , when both SPN-B and LearnSPN accuracies tend to decrease, SPN-BT seems to preserve or improve its likelihood.




Figure 3. Comparing network sizes (left) and values for m against the average test log-likelihood obtained by LearnSPN, SPN-B and SPN-BT number of sum node children splits. Each dot is an experiment in the grid search performed for the dataset Pumsb-star.

Strengthening by model averaging

The structure building process can still be too greedy and the resulting networks not so accurate.

Idea: interpreting sum nodes as *general additive estimators* by leveraging classic statistical tools to learn them: **bagging**.

We draw k bootstrapped samples from the data, then grow an SPN S_{B_i} on each of them. Join them into a single SPN \hat{S} with a sum node: $\hat{S} = \sum_{i=1}^k \frac{1}{k} S_{B_i}$.

Two new variants, SPN-BB and SPN-BTB, apply Bagging to SPN-B and SPN-BT.

Objectives: more robustness and less variance in the model. However, the number of nodes can grow exponential if we bootstrap c times for each sum node, thus we apply it once, at the root level only.

Both SPN-BB and SPN-BTB improve their respective variants accuracies a lot and beat ID-SPN on 14 datasets (see Table 1). Monitoring the test log-likelihood gain can help decide the proper number of components.




Figure 3. Comparing test log-likelihoods for SPN-BB and SPN-BTB while increasing the number of components against LearnSPN, MT and ID-SPN best models accuracies for DNA (left) and Pumsb_star (right).

Experiments

Classical setting for **generative** graphical models structure learning [2]:

- \oplus 19 binary datasets from classification, recommendation, frequent pattern mining...[3]
- \oplus Training 75% Validation 10% Test 15% splits (no cv)

Comparing both accuracy and structure quality:


- \oplus **average log-likelihood** on predicting test instances
- \oplus networks sizes (# edges)
- \oplus network depth (# alternated type layers)

Comparing the state-of-the-art, LearnSPN, ID-SPN and MT [5], against our variations:

- \oplus SPN-B using only Binary splits
- \oplus SPN-BT with Binary splits and Trees as leaves
- \oplus SPN-BB combining Binary splits and Bagging
- \oplus SPN-BTB including all variants

Model selection via *grid search* in the same parameter space:

- $\oplus \lambda \in \{0.2, 0.4, 0.6, 0.8\}$, $\oplus m \in \{1, 50, 100, 500\}$,
- $\oplus \rho \in \{5, 10, 15, 20\}$, $\oplus \alpha \in \{0.1, 0.2, 0.5, 1.0, 2.0\}$.



	LearnSPN	SPN-B	SPN-BT	ID-SPN	SPN-BB	SPN-BTB	MT
NLTCS	-6.110	-6.048	-6.048	-5.998	-6.014	-6.014	-6.008
MSNBC	-6.099	-6.040	-6.039	-6.040	-6.032	-6.033	-6.076
KDDCup2k	-2.185	-2.141	-2.141	-2.134	-2.122	-2.121	-2.135
Plants	-12.878	-12.813	-12.683	-12.537	-12.167	-12.089	-12.926
Audio	-40.360	-40.571	-40.484	-39.794	-39.685	-39.616	-40.142
Jester	-53.300	-53.537	-53.546	-52.858	-52.873	-53.600	-53.057
Netflix	-57.191	-57.730	-57.450	-56.355	-56.610	-56.371	-56.706
Accidents	-30.490	-29.342	-29.265	-26.982	-28.510	-28.351	-29.692
Retail	-11.029	-10.944	10.942	-10.846	-10.858	-10.858	-10.836
Pumsb-star	-24.743	-23.315	-23.077	-22.405	-22.866	-22.664	-23.702
DNA	-80.982	-81.913	-81.840	-81.211	-80.730	-80.068	-85.568
Kosarek	-10.894	-10.719	-10.685	-10.599	-10.690	-10.578	-10.615
MSWeb	-10.108	-9.833	-9.838	-9.726	-9.630	-9.614	-9.819
Book	-34.969	-34.306	-34.280	-34.136	-34.366	-33.818	-34.694
EachMovie	-52.615	-51.368	-51.388	-51.512	-50.263	-50.414	-54.513
WebKB	-158.164	-154.283	-153.911	-151.838	-151.341	-149.851	-157.001
Reuters-52	-85.414	-83.349	-83.361	-83.346	-81.544	-81.587	-86.531
BBC	-249.466	-247.301	-247.254	-248.929	-226.359	-226.560	-259.962
Ad	-19.760	-16.234	-15.885	-19.053	-13.785	-13.595	-16.012

Table : Average test log likelihoods for all algorithms. In bold the best values after a Wilcoxon signed rank test with p -value of 0.05.

References

\oplus Aaron Dennis and Dan Ventura. ``Learning the Architecture of Sum-Product Networks Using Clustering on Variables''. In: *Advances in Neural Information Processing Systems 25*. Curran Associates, Inc., 2012, pp. 2033–2041.

\oplus Robert Gens and Pedro Domingos. ``Learning the Structure of Sum-Product Networks''. In: *Proceedings of the 30th International Conference on Machine Learning*. JMLR Workshop and Conference Proceedings, 2013, pp. 873–880.

\oplus Jan Van Haaren and Jesse Davis. ``Markov Network Structure Learning: A Randomized Feature Generation Approach''. In: *Proceedings of the 26th Conference on Artificial Intelligence*. AAAI Press, 2012.

\oplus James Martens and Venkatesh Medabalmi. ``On the Expressive Efficiency of Sum Product Networks''. In: *CoRR abs/1411.7717* (2014).

\oplus Marina Meilă and Michael I. Jordan. ``Learning with mixtures of trees''. In: *Journal of Machine Learning Research* 1 (2000), pp. 1–48.

\oplus Robert Peharz, Bernhard Geiger, and Franz Pernkopf. ``Greedy Part-Wise Learning of Sum-Product Networks''. In: *Machine Learning and Knowledge Discovery in Databases*. Vol. 8189. LNCS. Springer, 2013, pp. 612–627.

\oplus Amirmohammad Rooshenas and Daniel Lowd. ``Learning Sum-Product Networks with Direct and Indirect Variable Interactions''. In: *Proceedings of the 31st International Conference on Machine Learning*. JMLR Workshop and Conference Proceedings, 2014, pp. 710–718.

\oplus Han Zhao, Mazen Melibari, and Pascal Poupart. ``On the Relationship between Sum-Product Networks and Bayesian Networks''. In: *CoRR abs/1501.01239* (2015). URL: <http://arxiv.org/abs/1501.01239>.