Snap Lock

Foreman Name	Customer Name	Reviewed with foreman
Cleanliness The Jobsite is clean and free of nails The deck, sidewalk and window sills are blown off The roof and gutters are clean and free of debris The shrubbery is not crushed Quality Proper number of screws are used Metal rakes looks straight Valleys look straight There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Foreman Name	
The Jobsite is clean and free of nails The deck, sidewalk and window sills are blown off The roof and gutters are clean and free of debris The shrubbery is not crushed Quality Proper number of screws are used Metal rakes looks straight Valleys look straight There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Final Picture	
The deck, sidewalk and window sills are blown off The roof and gutters are clean and free of debris The shrubbery is not crushed Quality Proper number of screws are used Metal rakes looks straight Valleys look straight There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Cleanliness	
The roof and gutters are clean and free of debris The shrubbery is not crushed Quality Proper number of screws are used Metal rakes looks straight Valleys look straight There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	The Jobsite is clean and free of nails	
The shrubbery is not crushed Quality Proper number of screws are used Metal rakes looks straight Valleys look straight There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	The deck, sidewalk and window sills are blown off	
Proper number of screws are used Metal rakes looks straight Valleys look straight There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	The roof and gutters are clean and free of debris	
Proper number of screws are used Metal rakes looks straight Valleys look straight There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	The shrubbery is not crushed	
Metal rakes looks straight Valleys look straight There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Quality	
Valleys look straight There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Proper number of screws are used	
There is no excess scuffing or dents on panels Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Metal rakes looks straight	
Metal panel rows are straight Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Valleys look straight	
Matched ridges on the panels on pitch change Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	There is no excess scuffing or dents on panels	
Matched the exposure at the panels on the rakes Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Metal panel rows are straight	
Eaves are seamed evenly Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Matched ridges on the panels on pitch change	
Hip metal are straight Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Matched the exposure at the panels on the rakes	
Drip-edge corners are neat Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Eaves are seamed evenly	
Pipe boot installed plenty screws and caulking Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Hip metal are straight	
Flashing is cut-in, neat, and tight to the wall Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Drip-edge corners are neat	
Over slap pitch change metal and apron flashing at least 4 inches used enough rivets on ridge cap metal Caulking is properly pressed in	Pipe boot installed plenty screws and caulking	
used enough rivets on ridge cap metal Caulking is properly pressed in	Flashing is cut-in, neat, and tight to the wall	
Caulking is properly pressed in	Over slap pitch change metal and apron flashing at least 4 inch	es
	used enough rivets on ridge cap metal	
Quality Notes	Caulking is properly pressed in	
	Quality Notes	

Additional Notes:	