

Index

Note: Page numbers followed by *f* indicate figures and *t* indicate tables.

A

Acoustic properties of metallic foam materials
 pressure fluctuation, 345
 sound absorption, 345
 sound dissipation, 345
 vibration, 345

Additive manufacturing (AM)

additive manufacturing processes, 377*t*, 379*t*
 applications of additive manufacturing,
 384–395
 direct energy deposition (DED), 375–376
 heat source:nomenclature for electron beam
 (EB), 363
 heat source:nomenclature for gas metal arc
 (GMA), 363
 heat source:nomenclature for laser (L), 363
 heat source:nomenclature for plasma arc (PA),
 363
 powder bed fusion (PBF), 375–376
 powders for additive manufacturing
 processes, 376–383
 principles for additive manufacturing,
 374–375
 selective laser melting (SLM), 375
 standard guide for characterizing properties of
 metal powders used for additive
 manufacturing processes, 933–934*t*

ADMA Product Inc., 558

Admissible concentration limit of lead in
 aqueous medium, 857

All-Russian Light Alloys Institute (VILS),
 490

Aluminized explosives

air blast, 478
 “Alex[®]”, 477
 aluminothermic reduction, 478
 ammonal, 477
 ammonium perchlorate, 478
 antidetonants, 478
 aquarium tests, 477
 bubble energies, 477
 detonation pressure, 477–478
 detonation products, 477–478
 detonation temperature, 478
 energetic materials, 477
 explosion fireball, 478
 expanding detonation products, 478
 expansion of gases, 477
 exploding wires in nitrogen atmosphere,
 477–478
 explosive transformation, 477

flame temperature, 477
 high chemical activity, 477–478
 high-energy carrier, 477
 high explosives, 477–478
 incendiary effects, 477
 industrial explosives, 477
 nanometric aluminum powder, 477
 PBX compositions, 477
 plasmochemical method, 477–478
 plastic-bonded explosives, 477
 plate dent depth tests, 477
 pyrotechnic flakes, 477
 reducing agent, 478
 rock ammonites, 477
 rocket propellants, 477
 shock compressibility, 477
 shock wave loading, 477
 shock wave reflection, 477
 small-scale performance testing, 477
 spherical particles, 477
 surface of Al particles, 477
 surface temperature, 478
 thermite mix, 478
 trinitrotoluene (TNT), 477–478
 velocity of detonation, 477
 ultrafine aluminum powder, 477
 underwater weapons, 477

Aluminothermic reduction

burning temperature, 478
 polymerization of ethyls, 478
 production of aluminum alkyls, 478
 thermite mix containing, 478

Aluminum

aluminum groats, 478
 high-purity aluminum, 478
 porous aluminum, 478
 technical-purity aluminum, 478
 Aluminum alloy powder production by water
 atomization
 aluminum hydrate, 505
 Al–Mg system alloys, 516–520
 aluminum oxide hydroxide, 505
 aluminum oxide surface film, 505
 Al–Zn–Mg system alloys, 518
 boehmite film, 505
 contact-convection drying process, 505, 507,
 509–510
 conduction–convection drying, 505, 507,
 509–510
 conductive drying, 509
 conductive vacuum drying, 509

elevated temperature aluminum alloys,
 513–515
 gas emission kinetics, 507
 high-strength aluminum alloy, 505
 high-strength quaternary system, 507
 hydraulic size classification, 505
 hydroclassification, 508*f*, 510
 hydrogen ion control, 505
 inhibitors from the group of weak electrolytes,
 505
 interparticle boundaries, 505
 oxide film, 505, 507
 pilot plant of IPMS, 507, 518
 recycling of secondary aluminum, 511–513
 surface oxide film, 505, 506*f*
 suspended powder, 507
 suspension temperature, 505

Aluminum and magnesium alloys (applications of additive manufacturing)

building direction, 385
 built part, 384–385, 386*f*
 cell size, 385
 cell spacing, 385
 cooling rate, 385
 Elektron MAP+43, 386
 energy density, 387
 evaporation temperature, 386
 gas pore, 385
 heat input, 387
 laser beam machining process, 385
 laser powder bed processing, 385
 laser power, 386–387
 laser scanning speed, 387
 layer height step, 386
 layer thickness, 386–387
 Magnesium Elektron powder grade, 386
 near-eutectic composition, 385
 powder flow rate, 386
 powder particles sphericity, 384–385
 laser pulsed input, 387
 rapidly solidified, 385–386
 scan speed, 386
 select laser melting (SLM), 386–387
 shielding gas, 386, 390
 solidification range, 385
 stereological effect, 385
 thermal conductivity, 385
 transition metals, 385–386
 travel speed, 386
 thin layers of metal powder, 385–386
 ytterbium fibre laser, 385–386

- Aluminum based composite
 - accumulative roll bonding (APB) process, 364
 - alumina nanofibres, 364
 - aluminum carbide phase, 364
 - aluminum matrix composites, 364
 - aluminum metal composites (AMCs), 363–364
 - aluminum titanium dioxide composites, 364
 - ball milling, 364
 - introduction of nanodiamond, 364
 - reinforcing particles, 364
 - repetitive press roll bonding (RPRB), 364
 - severe plastic deformation (SPD), 364
 - titanium dioxide (TiO₂) particles, 364
- Aluminum based composite powders
 - aluminum matrix composite powders, 352
 - aluminum oxide films, 354
 - boron carbide, 353
 - cells, 352–353
 - cryomilling technique, 353
 - gas and water atomized powders, 352
 - hot extrusion, 352
 - interfacial debonding, 353
 - mechanical alloying (MA), 352
- Aluminum oxide surface film
 - boehmite film, 505
 - interparticle boundaries, 505
 - main metallic surfaces, 505
 - non-uniform in thickness, 506f
 - particles surface, 505
 - interparticle boundaries, 505
 - segregation zones, 505
 - three-dimensional film islets, 505
 - uneven surface, 505
- Aluminum scrap recycling
 - crushing in cutting units, 474
 - dry crushing, 474
 - foil processing, 474
 - grit, 474
 - processing of recycled aluminum to granules, 477
 - production of powder products from waste
 - aluminum foil, 474
 - recycling of aluminum scrap, 474
 - waste aluminum foil, 474–476
 - waste products, 474
 - wet crushing, 474
- Al–Mg system alloys
 - additions of scandium, zirconium, chromium, 516
 - mechanical properties, 516
 - non-heat treatment alloys, 516
 - PM/WA alloys, 516, 520
 - precipitation hardening, 516
 - Scalmalloy 0.7, 516
 - solid–solution hardening, 516
 - transition metals, 516
 - weldable alloys, 516
- Al–Zn–Mg system alloys
 - cooling rate, 516–518
 - corrosion cracking point, 516–518
 - corrosion cracking resistance, 516–518
 - chromium doping, 520
 - formability, 516–518
 - doping elements, 520
 - doping refractory metals, 520
 - G/T alloy 1970, 518
 - Guinier–Preston zones, 520
 - heat-treatable alloys, 516–518
 - hot extrusion of billets, 518
 - mechanical properties, 518
 - non-dendritic grains, 518
 - rod extrusion, 518
 - pulsed forging, 518
 - rare earth metals, 516–518
 - rod extrusion, 518
 - scandium addition, 520
 - structural materials, 516–518
 - transitional refractory metals, 516–518
 - PM/WA technology, 518
 - weldability, 516–518
 - wrought alloys, 520
- Amalgam metallurgy methods
 - amalgam cementation of a more negative metal, 263
 - electrolyzer with amalgam bipolar electrodes, 266
 - mercury electrode, 263
 - Nernst equation, 263–265
 - nuclei crystallization, 265
 - oversaturated amalgams, 263
 - standard potential, 265t
- Amalgam metallurgy technique (production of titanium and titanium alloy powders)
 - black powder, 562–563
 - electrolysis with mercury cathode, 562
 - inert atmosphere, 562
 - mercury, 562–563
 - mercury cathode, 562
 - sodium amalgam, 562
 - sodium chloride, 562–563
 - titanium chlorides, 562–563
 - titanium crystals, 562–563
 - titanium sponge, 562–563
 - vacuum furnace, 562–563
- Amalgam techniques
 - agitated mercury cathode, 681
 - anode and cathode current densities, 681
 - electric precipitation of cobalt, 681
 - soluble cobalt anode, 681
 - sulfate electrolyte, 681
- Angle of repose
 - factors influencing on angle of repose, 56
 - measuring the angle, 55
 - ultimate angle, 55
- Anticorrosive zinc-rich coatings for roll and sheet steel metal ware
 - DACROMET, 630
 - GEOMET, 630
 - PLAS, 630
 - ZINCOMET, 630
- Anthrahydroquinone, 646, 671
- Anthraquinone, 228, 646, 651–652, 671
- Apparent density, 3, 47, 49–51, 50t, 53t, 119, 555–556, 577, 585, 588, 598, 642t
- Apparatuses for powder analysis
 - Analissette 22 Nano Tec Plus, 60t
 - ASAP 2020, 60t
 - AutoPore IV 9500, 60t
 - FlowSorb III, 60t
 - Master Tech 052 Autosampler, 60t
 - Microtrac S3500 particle size analyser, 60t
 - Multisizer 4 Coulter Counter, 60t
 - Multivolume pycnometer 1305, 60t
 - Tristar 1000, 60t
 - Saturn Digsizer 5205, 60t
 - Sedigraph III PLUS particle size analyzer, 60t
- Application fields for aluminum powders
 - aluminum alloy powders, 478
 - aluminum alloys, 478
 - aluminum-based elevated temperature alloys, 513–515
 - aluminum-based high strength alloys, 478
 - aluminum granules, 478
 - aluminothermic reduction, 478
 - automobile tires, 479
 - cold solder, 479
 - constructional materials, 478
 - energetic materials, 477
 - explosives, 477–478
 - ferrous metallurgy, 478
 - filler material in plastics, 479
 - increase the thermal resistance and mechanical strength of refractory material, 479
 - lubricant in producing ceramic details, 479
 - production of high density refractory materials, 479
 - production of porous adsorption materials for cryogenic equipment, 479
 - production of a welding wire and cutting emulsions, 479
 - protective rubber, 479
 - pyrotechnic, 477
 - rocket propellants, 477
- Applications of additive manufacturing
 - aluminum and magnesium alloys, 384–387
 - nickel base alloys, 392–395
 - titanium alloys, 387–392
- Applications of beryllium, 807–810
 - aerospace applications, 808
 - apparatus applications, 808
 - beryllium alloys, 808–810
 - high temperature conditions, 808
 - optical beryllium grades, 808
 - nuclear and x-ray applications, 807–808
- Applications of chemically reduced powders and sols
 - catalyst, 225
 - chemically reduced metal, 225
 - colloid adsorption, 225
 - metal colloid, 225
 - metallized dispersed carrier, 225
 - preliminary activation, 225
 - reducer solution, 225
 - salt, 225
 - selective precipitation, 225
- Applications of nanomaterials
 - cemented carbides, 300–302
 - electrical storage systems, 306–307
 - fibre-reinforced material, 302
 - gradient materials, 302–303

- miniaturized systems, 307
- nanopowder-polymer composites, 303–304
- semiconductors, 305–306
- thin film technique, 304–305
- vapor deposition in vacuum, 297–300
- Applications of thorium
 - antireflection material, 823
 - alloying in alloys, 823
 - catalyst compositions, 824
 - electronic tubes, 823
 - gas mantles, 823
 - gas tungsten arc welding, 823
 - heat-resistant ceramics, 823
 - high-quality lenses, 823
 - Incandescent filaments, 823
 - organic synthesis, 824
 - TD-Ni alloy, 823
 - thoriated tungsten wires, 823
 - thorium dioxide, 823–824
 - tungsten thermocathodes, 823
- Aqueous solution method
 - photoluminescence (PL), 306
 - photoluminescent nanoparticles, 306
 - surfactants, 306
 - syntheses of highly photoluminescent semiconductor nanoparticles, 306
 - thioglycerol, 306
 - thioglycolic acid, 306
- Archimedes' law, 42–43
- Armstrong process
 - continuous process, 550–551
 - Cristal Metals Inc., 550–551
 - International Titanium powders (ITP) process, 550–551
 - liquid sodium, 550–551
 - reduction of titanium tetrachloride with sodium, 550–551
 - sodium chloride, 550–551
 - sodium stream, 550–551
 - solid titanium powder, 550–551
- Aspiration in combustible powder conditions
 - cascade equipment location, 897
 - chemically active metals, 897
 - closed-loop shielding gaseous change system, 897
 - controlled protective atmospheres, 897
 - film-forming composition, 897
 - organosilicon compound, 897
 - shielding gas, 897
 - silico calcium powder, 897
 - surfactant, 897
 - transportable containers, 897
- Atomic adsorption spectrometry (AAS)
 - flame atomic absorption spectrometry, 36
 - flame atomic emission spectrometry, 36
 - flame atomic fluorescence spectrometry, 36
- Atomic-force microscopy (AFM)
 - cantilever, 275–276
 - contact mode, 275–276
 - frequency modulation, 276
 - measuring the tip-to-sample distance, 276
 - non-contact mode, 276
 - oscillation, 276
- tapping mode, 276
- tip (probe), 276
- Atomization
 - centrifugal atomization, 167–172
 - explosive atomization, 176–177
 - flame spray pyrolysis, 176–177
 - gas atomization, 143–167
 - impact atomization, 173
 - impulse atomization method, 173–174, 174*t*
 - hot gas atomization, 165–166
 - melt drop orifice technique, 173–175
 - melt drop vibrating orifice method, 174
 - oil atomization, 142
 - plasma atomization process, 175
 - pulsated orifice ejection method, 174–175
 - roller atomization, 175
 - vacuum-dynamic atomization, 167
 - vibrating electrode atomization, 173
 - water atomization, 128–142
- Atomization and granulation
 - atomization, 125–177
 - granulation, 177–181
- Atomization mechanism
 - models of gas atomization, 149–158
 - water atomization mechanism, 128–142
- Atomization of copper alloy powders, 576–581
- Atomization of copper powder, 572–576
- Atomized nickel alloy powders
 - gas atomization, 655
 - hardfacing powders, 652–654
 - hardfacing process, 652
 - Haynes alloy 176, 654
 - water atomization, 652
- Atomized powders of cobalt-base alloys
 - atomization, 674–676
 - carbide-containing alloys, 674–675
 - cellular structure, 676, 677*f*
 - cobalt-base matrix, 674–675
 - elevated temperature hardness, 675
 - gas atomization, 675–676
 - hardfacing applications, 674–675
 - hardfacing powders, 674
 - interdendritic eutectic carbide, 676
 - Laves phase, 674–675
 - melt spinning, 676
 - nontransferred arc, 676
 - plasma transferred arc, 676
 - plasma transferred arc hardfacing process, 676, 676*f*
 - plasma spray coating, 674–675
 - plasma spray hardfacing, 674–675
 - solid-solution strengthening, 676
- Attritors
 - attritor in horizontal performance, 97–98, 98–99*f*
 - batch attritors, 97
 - circulation attritor system, 102
 - continuous mode, 101–102
 - dry grind attritors, 101–102, 103*f*
 - high speed attritors (HAS), 101–102
 - laboratory Simoloyer attritors, 99*f*
 - Netzsch attritors, 98, 98*t*, 101
 - Union process attritors, 98, 99*f*
 - vertical attritors, 97, 97*f*
- Auger electron spectroscopy (AES)
 - Auger effect, 30–31
 - Auger electrons, 31
 - electron transition process, 31
- Autoclave(s)
 - discharging units, 231
 - double-pipe heat exchanger, 230–231
 - horizontal autoclaves, 230
 - mechanical stirring, 230
 - powder pulp transportation, 231
 - process characteristics control, 230
 - protective cladding, 230
 - safety fittings, 230
 - self-evaporator, 230–231
 - thermal protection, 230
 - vertical autoclaves, 230
- Autoclave precipitation of metal powders
 - autoclave, 226–227
 - autoclave precipitations of metal powders from organic phases, 230
 - autoclave processing of hydroxide and metal carbonate pulps, 229
 - hydrodynamics, 227
 - hydrogen reduction, 225
 - reaction gas pressure, 227
 - safety engineering, 231
 - seed, 228
 - Sheritt process, 225
 - solution composition, 228
 - surfactants, 228–229
- Autoclave precipitations of metal powders from organic phases
 - contamination, 230
 - extraction-precipitation cycle, 230
 - fire-risk, 230
 - leaching-extraction process, 230
 - organic phase, 230
 - organometallic phases, 230
 - power-consumption, 230
- Autoclave processing of nickel hydroxide and carbonate pulps
 - alkaline accumulators, 651–652
 - ammonia-carbonate leaching, 652
 - ammonium-carbonate solution, 651
 - aqueous carbonate pulp, 651–652
 - nickel hydroxide aqueous, 652
 - nickel seed powder, 651
 - palladium chloride, 651–652
 - reduction of aqueous carbonate pulp, 651–652
- Autoclave processing of hydroxide and metal carbonate pulps
 - catalytically active powders, 229
 - dissolved hydrogen concentration, 229
 - hydrothermal conditions, 229
 - metal hydroxide, 229
 - metal hydroxide solubility, 229
 - narrow size distribution, 229
 - roundish shape particles, 229
- Average pressure carbonyl technique
 - carbon monoxide carrier gas, 637
 - carbonyl sublimates, 637
 - Copper Cliff refinery, 637, 637*f*
 - elevated pressure, 637, 637*f*
 - high copper concentration, 637

Average pressure carbonyl technique
(*Continued*)

- nickel pellet, 637
- nickel tetracarbonyl vapor, 637
- slightly above atmospheric pressure, 638
- sulfides of nickel, 637

B

Beryllium

- applications of beryllium, 807–810
- beryllate (MeBeO_2), 798–799
- beryllium carbide, 798, 804
- beryllium compounds, 798–799
- beryllium nitride, 798
- beryllium oxide, 798
- beryllium oxide powder production, 804
- beryllium powder production, 801–804
- electrolysis from chloride electrolyte, 800–801
- gas atomization, 802–803
- grinding, 801–802
- hexagonal beryllium crystals, 798
- magnesium thermal reduction of beryllium fluoride, 800
- microalloying influences, 804
- powder consolidation and production of wrought products, 804–806
- production of leafed beryllium by electrorefining of melts, 801
- sources of raw material, 800
- workplace atmosphere safety, 810
- wrought beryllium, 798, 807*t*
- wrought product forms, 806–807

Beryllium alloys

- AlBeMet, 808
- aluminum–beryllium–lithium alloys, 808, 809*t*

E-material metal-matrix composite, 810

Beryllium oxide powder production, 804

- beryllia ceramic, 804
- beryllium hydroxide, 799–800, 804
- beryllium sulfate crystals, 804
- calcining in air, 804

Beryllium powder production

- beryllium oxide powder production, 804
- gas atomization, 802–803
- grinding, 801–802
- microalloying influences, 804

Biomedical implants, 328, 346, 546

Brass powders, 576

Bronze powders, 324, 577–581

Bubble test of pore size

- air bubbles discharge, 46
- first air bubble, 46

Bulk analysis

- atomic adsorption spectroscopy (AAS), 36–38
- determination of oxygen content by reduction methods, 38
- inductively coupled plasma atomic emission spectroscopy (ICP-AES), 36
- inert gas fusion, 35
- x-ray fluorescence spectrometry, 35–36
- x-ray powder diffraction (XRPD), 33–35

Bulk density

- apparent density, 49–50
- Funnel method, 51
- Scott volumeter, 51–52

Bulk properties of powders

- angle repose, 55–56
- bulk density, 49–52
- flow rate, 54
- fluidization, 55
- frictional properties, 48–49
- multiaimed powder tester, 57
- screening model (also called sifting phenomenon), 54
- segregation of particles, 54
- sliding at impact point, 54
- tap density, 52–53
- trajectory effect, 54

Bayer process

- alumina production, 818
- high content of scandium, 818
- red mud, 818

C

Cadmium powder, 625–628

Calcination-reduction-carburization (CRC) process, 707–709, 711

Calcium hydride reduction process, 550, 553, 568*t*

Capacity of local suction

- mass balance equation, 896
- leakinesses (openings), 896–897
- local exhaust, 896–897
- resistance coefficients, 896–897
- underpressure in aspiration cover, 896–897

Carbon nanotube (CNT) reinforced metal

- composite powders
- acid-treated CNTs (ATCNTs), 357
- aluminum alloy matrix, 357
- aluminum carbide (Al_4C_3) crystals, 357
- carbon nanotubes (CNTs), 357
- dispersion of CNTs, 357
- multiwalled carbon nanotubes MWCNT, 357

Carbonyl method for cobalt powder production

- black cobalt powder, 678
- carbon monoxide, 678
- carbonyl decomposition, 678
- cobalt carbonyl, 678
- halide salts, 676–678
- hydrogen atmosphere, 678

Carbonyl process of nickel powder production

- average pressure carbonyl technique, 637–638
- Clydach refinery, 634–635, 636*f*
- health and environment protection measures in carbonyl nickel production, 638
- high pressure carbonyl technique, 638
- low pressure carbonyl technique, 635–636
- Ludwig Mond, 633
- Mond–Langer process, 635
- nickel tetracarbonyl, 633
- nickel tetracarbonyl formation and decomposition, 634–635
- Norilsk Nickel Company, Russia, 635
- powder properties an applications, 638–644

Carbothermic method (production of RE metal-alloy powders)

- cooled condenser, 788
- dissociation of carbide in vacuum, 788
- lanthanide carbide, 788
- reduction of lanthanide oxide by carbon, 781
- sublimation of lanthanide, 788
- surplus carbon, 788

Carney funnel, 51–52

Cemented carbides

- gas phase carburization, 301
- grain growth preventing, 301
- high energy milling, 301
- mechanochemical synthesis, 301
- Nanodyne Process, 301
- nanostuctured cemented carbides, 301
- WC–Co powders, 301–302

Cemented tungsten carbides

- cemented carbides with low and medium carbon levels, 798
- mischmetal, 798
- RE-doped cemented carbides, 798

Centrifugal atomization methods, 169–172

- melt spinning centrifugal atomization, 125
- melt spinning roller technique, 171–172
- models of centrifugal atomization, 167–169
- rapid solidification rate (RSR) process, 171
- spinning disc atomization, 169–171

Centrifugal pumping system

- analyze agglomerating samples, 21
- rapid flow rate, 21
- rotating electrode atomization, 172

Chemical precipitation from solution

- chemical precipitation, 221
- coexistence with water, 221
- oxidation–reduction reaction, 221

Chemical reduction

- application of chemically reduced powders and sols, 225
- chemical precipitation from solutions, 221
- kinetics of solid phase formation in solution, 223–225
- thermodynamic peculiarities of metal chemical reduction, 221–222

Chemical reduction (production of titanium and titanium alloy powders)

- Armstrong process, 550–551
- calcium hydride reduction process, 553
- hydrogenation/dehydrogenation (HDH) process, 553–554
- magnesium reduction method (Kroll process), 551–553
- sodium reduction method (Hunter process), 550

Chemical synthesis of nano size titanium

- powders
- argon atmosphere, 565
- chemical methods, 565
- hydrogen atmosphere, 565
- ilmenite, 565
- titanium catecholate/gallate, 565
- titanium hydride, 565
- vacuum dehydrogenation, 565

- Chemical vapor deposition (CVD) process
 - aerosol assisted CVD (AACVD), 197
 - aluminum and copper deposited by CVD, 198
 - atmospheric pressure CVD (APCVD), 197
 - chemical vapor infiltration, 302
 - CVD for refractory metals, including
 - molybdenum, tantalum, niobium, and rhenium, 198
 - direct liquid injection CVD (DLICVD), 197
 - installation for deposition by CVD technique, 198*f*
 - metal carbonyl gas, 198
 - microwave plasma-assisted CVD (MPCVD), 197
 - low-pressure CVD (LPCVD), 197–198
 - parallel-plate reactor of plasma enhanced CVD process, 199*f*
 - plasma-enhanced CVD (PECVD), 197–198
 - refractory metal foams, 198
 - remote plasma-enhanced CVD (RPECVD), 197
 - tungsten hexafluoride, 197–198
 - ultrahigh vacuum CVD (UHVCVD), 197
 - volatile precursors, 197
 - wear-resistant and thermostable covering, 198
- Chinuka process
 - cheap, 560
 - directly treat impure ores, 560
 - high-purity metals, 560
 - impure metal oxides, 560
 - low operating temperature, 560
 - low power consumption, 560
 - nontoxic electrolyte, 560
 - single process, 560
- Classification in centrifugal field
 - Bahco classifier, 17
 - cyclone classifier, 17–18
- Classification in gravitational field,
 - sedimentation method, 13–16
- Closed-cell materials, 338–346
- Closed-cell metallic foams, 330–333
 - foaming of ingots containing blowing agents (Formgrip/Foamcast), 332
 - foaming of melts by gas injection (Hydro/Alcan), 331–332
 - foaming of melts with blowing agents (Alporas), 330–331
 - solid–gas eutectic solidification (Gasar), 332
- Coating steel products
 - enamels, 478
 - paints, 478
 - plasma spraying, 478
 - protect products, 478
 - protective pigment, 478
 - thermal diffusion, 478
 - silvery color, 478
 - spray deposition, 478
 - varnishes, 478
- Cobalt
 - amalgam techniques, 681
 - atomization, 674–676
 - carbonyl processing, 676–678
 - cobalt-alloy powders, 678–680, 680*r*
 - coating, 673
 - electrolytic techniques, 678–680
 - hardmetals, 673
 - health and environment protection measures, 683–684
 - hydrometallurgical process, 669–673
 - leach autoclave method, 669–673
 - production of cobalt and cobalt alloy powders by electrolysis, 678–680
 - ultrasonic spray pyrolysis (USP), 681–683, 683*f*
- Cohesive strength
 - arch form, 47–48
 - consolidation pressure, 47–48
 - hollow form, 47
 - Jenike apparatus, 47–48, 48*f*
 - shear normal stress, 48
 - shear stress, 48
 - shear tester, 47–48
 - stagnant zones, 47
 - yield locus, 48
- Cold isostatic pressing and extrusion (beryllium and beryllium comprising alloy powders)
 - copper mold, 806
 - cylindrical shape, 806
 - extruded AlBeMet rod and bar, 806
 - taper die, 806
- Cold isostatic pressing and sintering (beryllium powder)
 - CIP chamber, 806
 - cold isostatic pressing (CIP), 806
 - green preforms, 806
 - latex bag, 806
 - near-net shape (NNS), 806
 - nuclear limiter tiles, 806
 - vacuum mold, 806
 - vacuum sintered, 806
- Coldstream process, 722
- Combustion synthesis of zirconium nitrides
 - conducting materials, 771
 - electronic application, 771
 - phosphorus, 771
 - refractory corrosion-resistant coatings, 771
 - single-phase supersaturated solutions, 771
 - stoichiometric compound, 771
- Compaction methods
 - centrifugal slurry casting, 326
 - cold welding, 325
 - die compaction, 325
 - direct typing method, 326
 - extrusion, 326
 - gravity sintering process, 325
 - isostatic pressing, 325
 - laser deposition by direct typing, 326
 - lower compaction forces, 325
 - roll compaction, 325–326
 - wet powder spraying, 326
- Composite manufacturing methods
 - coprecipitation, 363
 - hybrid consolidation nanotube (CNT), 363
 - internal oxidation, 363
 - powder metallurgy methods, 363
 - press sinter-extrude, 363
- Compressibility
 - compacting pressure, 57–58
 - lubricants, 57–58
 - lubrication techniques, 57–58
 - powder lubrication method, 57–58
 - theoretical density, 57
 - wall lubrication, 57–58
- Compressibility and compactibility of metal powders
 - compactibility, 57
 - compressibility, 57–58
 - green strength, 58–59
 - dendrite deposit, 238
 - dendrite growth rate, 238
 - specified green density, 57
 - unsintered (“green”) compacts, 57, 59, 59*f*
- 3D Computer-aided design (CAD), 375, 566–567, 664–666
- Conforma Clad Process, 714
- Consolidation and manufacturing of molybdenum semi-products
 - alloying additions, 747
 - cold isostatic pressing, 746
 - corrosion-resistant heat exchangers, 747
 - nonisothermal sintering, 746
 - interstitial impurity elements, 746
 - microalloying additions, 747
 - preventing embrittlement, 747
 - volatile silicon monoxide, 747
- Contact displacement method (cementation)
 - cementing metal (precipitator), 254–256
 - chemical treatment, 258
 - complexing ligands, 257–258
 - diffusion control, 255–257
 - electrolytic precipitation, 254–258
 - flat growth front, 257–258
 - heterogeneous reaction, 254
 - potential of reduction reaction, 255
 - precipitable metal, 255–256
 - precipitation rate, 256
 - spherical diffusion on the tips, 256
 - tangential growth, 255–256
 - tangentially spread film, 256
 - tip radius, 255, 257
- Contact displacement reactions
 - combustion reaction, 108–109
 - conjugated dissolution, 108
 - critical milling time, 108
 - diffusion process, 108
 - fracturing of powder particles, 108
 - gradual conversion, 108
 - high surface defects, 108
 - ignition time, 108–109
 - interparticle welding, 109
 - preventing the risk of explosion, 108
 - reactive reductant, 108–109
 - self-propagating combustion reactions, 109
 - welding of powder particles, 108
- Contact-convection drying process
 - conductive vacuum drying, 509
 - dryer, 507, 509, 509*f*
 - drying agent, 507, 509–510
 - explosion safety, 507
 - heat-and-mass transfer, 507
 - loosener, 509

Contact-convection drying process (*Continued*)
 maximum permissible temperature, 509–510, 510f
 particle aggregates, 507, 509
 self-ignition danger, 509–510
 specific humidity, 509–510, 510f
 Copper alloy powders, 571–612
 Copper based composite powders
 carbon nanostructures, 364–365, 365f
 carbon nanofibres (CNFs), 364–365
 carbon nanotubes (CNTs), 364–365
 chemical vapor deposition (CVD), 365
 copper-based metal matrix composites (MMCs), 364
 copper-graphite composites, 364–365
 copper matrix composites, 354, 366
 copper powder, 365
 copper reinforcement, 353–354
 dispersed oxides particle, 354
 high energy ball milling, 354, 354f
 internal oxidation, 366
 mechanical alloying, 366
 nanocrystalline alloy, 353–354
 reinforcing component, 364–365
 sliding electrical contacts, 364–365
 Copper powder, 571–612
 Copper precipitation
 from ammonia media, 599–600
 from organic phases, 600
 from sulfuric acid media, 595–599
 Copper precipitation in industrial electrolysis
 advanced control method, 245
 cathode rod, 245
 cell section, 245
 cell voltage, 248
 commercial electrolytic cell, 245, 248
 crusting effect, 245
 dendritic copper powder, 245
 dendritic copper sediment, 245
 deposition period, 245–248
 electrolysis efficiency, 245
 electrolysis process, 245
 electrolyte, 248
 formation of copper sediment, 245
 galvanostatic conditions, 245
 globular tips, 245
 growth front, 245–248
 hydrogen bubbles, 245
 kinetics of electrolysis process, 245
 near-electrode space, 245, 249–250
 overpotential, 245–248, 247f
 potentiostatic conditions, 245–248
 spherulite, 245
 structural parameter, 245, 247f
 Uralélektromed' Joint Stock Company, 245
 video recording of copper deposit growth, 245
 Coulter counter
 aperture format, 21–22, 22f
 aperture sizes, 22
 continuous sample analysis, 22
 flow cell format, 21
 flow channel, 22
 orifice in electric field, 21–22
 particle traversing the orifice, 21

suspended particles, 21
 suspension vessel, 21
 voltage pulses, 21
 Counting and sizing of particles by indirect measures
 coulter counter, 21–22
 Fisher subsieve sizer, 18–19
 light scattering, 20–21
 turbidimetry, 19–20
 Crystallization centers, 224, 260, 468
 Crushers
 jaw crusher, 74
 gyratory crushers, 74
 hammer crushers, 74–75
 Crushing and grinding. *See* Mechanical crushing and grinding
 Cryogenic methods (production of zinc powder)
 frozen aqueous medium, 625
 ultrafine powder, 625
 ultrasonic impact, 625
 Crystal defects
 dislocations, 104–105
 stacking faults, 104–105
 vacancies, 104–105
 CSIR process
 alkali metal chloride salt, 564–565
 continuous process, 564–565
 CSIR-Ti process, 564–565
 leach liquor, 564–565
 metallothermic reduction, 564–565
 reaction temperature, 564–565
 reactor, 564–565
 relevant salt, 564–565
 residual salt, 564–565
 solidified mass, 564–565
 stirred tank reactor, 564–565

D

Dangerous and harmful manufacturing factors
 abrasiveness, 869
 adhesion, 868
 ambient noise and vibration, 866
 dust, gaseous, and vapor emissions, 866
 heat radiation, 866
 hydroscopic and wettability, 868–869
 inflammability and explosivity of powders, 869–875
 thermophysical properties, 875–879
 Dependence the ignitability and explosibility of
 the gas–suspended solid mixture on the oxygen content in oxidizing gas
 combustible gas–suspended solid mixture, 875
 electric spark, 875
 Four liter IPMS unit, 875
 Godbert–Greenwald furnace, 875
 ignition source, 875
 limiting oxygen concentration (LOC), 875
 minimum oxygen concentration, 875
 permissible oxygen content, 875
 Determination of oxygen content
 Karl Fisher's reagent, 38
 reducing tube with closed end, 38
 reduction in hydrogen, 38

running reducing tube, 38
 stream of pure dry hydrogen, 38
 Direct energy deposition (DED)
 computer aided design (CAD), 375
 DED processes, 375
 electric arc, 375
 electron beam, 375
 feedstock material, 375–376
 filler wire, 375
 fusion welding, 375
 laser beam (L), 375–376
 layer-by-layer deposition, 375
 molten pool, 375
 powder stream, 375
 shielding gas, 375
 substrate plate, 375
 3D parts, 375
 Dispersing units
 dry dispersing units, 21
 liquid dispersing units, 21
 suspension preparation, 21
 vibratory feeder, 21
 ultrasonic bath, 21
 Dust explosion venting
 calculation of rupture diaphragm, 889
 explosion flameless venting, 889–890
 Fike Corporation, 891f
 flame-quenching unit, 889–890, 890f
 flap valve, 890, 891f
 float valve, 890, 891f
 location of the vent, 888
 maximum explosion overpressure, 887
 passive explosion isolations systems, 891f
 pressure venting devices, 887
 rupture diaphragms, 889
 vent, 888–889

E

EDS apparatus
 analyzer, 29
 electron beam/x-ray beam, 29
 Peltier cooling systems, 29
 pulse processor, 29
 Si(Li) detector, 29
 X-ray detector, 29
 X-ray fluorescence spectrometer, 29
 Ejection pressure
 aspirated air consumption, 892
 aspiration cover, 892
 aspiration cover with double walls, 892
 belt conveyor reloading, 892, 893i, 893f
 closed chutes, 892
 ejected air motion, 892
 ejected air velocity, 892
 non-hermetic units, 892
 quasi-interconnected motion, 892
 powder gravitation flow, 892
 reloading from one conveyor to another, 892
 reloading units, 892, 893i, 893f
 Electrical explosion
 electrical explosion of wires technology (EEW), 176, 291–292
 electroexplosive powders, 291, 292f
 explosion of aluminum wires in water, 292

- high-voltage pulse, 291
- installation for producing electroexplosive powders, 291, 292^f
- metal wire, 291
- spherical particles shape, 292
- Electrical explosion of wires technology, 176, 291–292
- explosive destruction, 176, 291
- time of explosion, 176, 291
- velocity of product recession, 291
- Electrical storage systems
 - electric driven vehicles, 306
 - gel polymer electrolytes, 307
 - large-scale lithium-ion-batteries, 306
 - polymer composite electrolytes, 307
 - portable electronic devices, 306
 - primary batteries, 306
 - secondary batteries, 306
 - solvent-free polymer electrolytes, 307
- Electrochemical methods
 - amalgam metallurgy method, 263–267, 265–266^f
 - contact displacement method (cementation), 254–258, 255^f
 - copper precipitation in industrial electrolysis, 245–248, 258^t
 - electrolysis of aqueous solution, 240–254
 - physical and chemical principles of
 - electrolytic crystallization of dendrite deposit, 236–240
 - production of multicomponent alloy powders, 252–254
 - production of powders by electrolysis from melts, 258–262
 - reduction from solution through film of surfactants, 248–250
- Electrochemical methods (production of RE metal-alloy powders)
 - alkaline-earth metal chlorides, 787
 - cerium subgroup, 786–787
 - electrolysis of molten salt, 786–787
 - electrolyte temperatures, 787
 - lanthanide chlorides, 787
 - mischmetal, 786–787, 787^f
 - non-aqueous RE chlorides, 786–787
- Electrochemical methods (production of zinc powders), 621–624
 - adatoms, 622–624
 - alkaline zincate electrolytes, 622
 - cathodic precipitates, 621–622
 - columnar structure, 622
 - combined mode, 622, 624
 - crystalline particles, 621
 - dendritic structure, 622
 - dendritic zinc deposits, 622, 623–624^f, 624, 624^t
 - flaky particles, 621
 - galvanostatic mode, 622
 - honeycomb structure, 622–624
 - lamellar structure, 622–624
 - polarization modes, 622, 624, 624^t
 - potentiostatic mode, 622
 - pulsed galvanostatic mode, 622
 - spongy soft precipitates, 621
- Electrodeoxidation (EDO) titanium powder process, 558
- Electrolysis from beryllium chloride electrolyte, 800–801
 - beryllium flakes, 801
 - electrolytic cell, 801
 - graphite anode, 800–801
 - impurities of more electropositive metals, 801
 - nickel electrodes, 800–801
- Electrolysis of aqueous solution, 235–237, 240–254
 - anode current efficiency, 242
 - cathode current efficiency, 241–243
 - copper precipitation in industrial electrolysis, 245–248
 - current density, 240–242
 - current load on the electrolyzer, 242–243
 - depletion factor, 240–241, 254
 - deposit resistivity, 240–241
 - diffusion coefficient, 236
 - diffusion layer, 241
 - electrode potential, 256
 - electrolyzer, 240, 242, 243–244^f
 - equilibrium potential, 241
 - exchange current density, 237–238
 - Faraday constant, 236
 - galvanodynamic electrolysis, 241
 - galvanostatic, 245
 - hydrogen emission, 240
 - mechanism of diffusion-limited aggregation
 - of metal particles, 240
 - metal ion charge, 241–242
 - overpotential, 245
 - potentiostatic, 245–248
 - polarization, 240–241
 - radius of dendrite tip, 241
 - rate of dendrite elongation, 260
 - solution resistivity, 240–241
 - specific surface energy, 241
 - tip radius, 239
 - transfer factor, 258
- Electrolysis of melts (thorium powder production), 821
 - chloride–fluoride melts, 821
 - hydride process, 821
 - lathe turning, 821
 - molybdenum cathode, 821
 - saw chips, 821
 - thorium anode, 821
 - thorium chloride, 821
 - thorium dihydride, 821
 - thorium powder, 821, 822^f
- Electrolysis of titanium compounds, 558–562
 - Chinuka process, 560, 560^f
 - electrolytic refining process, 561–562, 561^f
 - FFC-Cambridge process, 559, 559^f
 - MER process, 559, 560^f
- Electrolytic deposition process, 337
 - catalytic devices, 337
 - deposition, 337
 - dissolution, 337
 - electrode, 337
 - electrically conductive, 337
 - electrolytic deposition, 337
- ionic deposition ionic deposition, 337
- Ni–metal hydride batteries, 337
- polymer template cathode, 337
- sputtering, 337
- Electrolytic methods for production/refining of zirconium powders
 - argon atmosphere, 770
 - cathode deposit, 769
 - electrolyzer, 768–769, 770^f
 - fluorine ions, 769
 - graphite electrodes, 769
 - potassium chloride, 768–769
 - production of zirconium powders by
 - electrolysis, 768–770
 - sodium chloride, 768–769
 - sodium dioxide, 768–769
 - solidified electrolyte, 770
 - zirconium halides, 768–769
- Electrolytic refining of titanium, 561–562
 - capacity of electrolyzer, 562
 - content of impurities, 561
 - crystalline titanium, 561
- Electrolytic refining process
 - electrolyzer of VAMI design, 561
 - high purity, 562
 - powder purification, 562
 - soluble anode, 561, 561^f
 - tetrachloride reduction, 561
 - titanium extraction, 562
 - titanium scrap, 561
 - titanium sponge, 561
 - valency of titanium ions, 561
 - VAMI institute, 561
- Electron beam directed vapor deposition, 337
 - axial electron beam gun, 337
 - deposition template, 337
 - He carrier gas jet, 337
 - nickel based superalloy, 337
 - polymer foam templates, 337
 - thermal decomposition, 337
- Electron beam installation, 297–298, 297^f
 - all-purpose electron beam installation UE-209, 297, 297^f
 - electron beam guns, 298
 - gun chambers, 298
 - working chamber, 298
- Electron probe x-ray microanalysis (EPMA), 29–30
 - beam of accelerated electrons, 29
 - electron microprobes, 29
 - energy dispersive spectrometry (EDS), 29
 - wavelength dispersive x-ray spectroscopy (WDS), 29–30
- Electrons generated by electron beam, 28, 28^f
 - Auger electrons, 28
 - backscattered electrons, 28
 - elastically scattered electrons, 28, 28^f
 - inelastically scattered electrons, 28, 28^f
 - secondary electrons, 28
- Elevated temperature aluminum alloys, 513–515
 - alloying with transition metals, 513
 - heterogenization, 513
 - high-temperature applications, 513–514
 - insoluble in aluminum, 513

Elevated temperature aluminum alloys

(Continued)

- intermetallic phases, 513
- mechanical properties, 513–514, 515–516*t*
- nonequilibrium composition, 513–514
- oxygen content, 514
- pulsed hot pressing, 514
- quasicrystalline phases, 513
- supersaturated solid solutions in aluminum, 513
- vapor deposition method, 513–514
- water-atomized (WA) powders, 514, 515*f*

Energy absorption of metallic foams, 345

- aluminum face sheets, 345
- aluminum foam core, 345
- damping capacities, 345
- elastic modulus, 345
- sandwiches, 345
- stress-strain curve, 345
- vibrational bending test, 345

Energy dispersive spectrometer (EDS), 29

- EDS apparatus, 29
- electron hole, 29
- electron shell bound, 29
- energy dispersive x-ray analysis, 29
- high-energy beam, 29

EO Paton Electric Welding Institute, 281, 297

Evaporation–condensation method (production of zinc powders), 615–620

- combustion chamber, 617
- condensation of zinc vapor, 617
- condensation conditions, 617
- condenser, 617, 619
- electrothermal process, 617, 620*f*
- rectification column, 615, 616*f*, 618*t*
- rectification method, 617
- reverberating furnace, 615
- zinc vapor, 617

Evaporation–condensation process

- adiabate expansion of gas medium, 189
- condensation in vapor jet, 189
- cooled substrate surface, 189
- diffusion condensation, 189
- growth of condensation nuclei, 190
- precipitating of the particles, 189
- rate of condensation, 191
- supercooling, 189
- thermo- and diffusion-phoretic forces, 189

Evaporation means

- electron beam, 195
- hollow cathode, 195
- induction heating, 195
- laser beam heating, 195
- low-voltage arc, 195

Explosion flameless venting, 889–890

- cylindrical flame-quenching unit, 889–890
- flame-quenching unit, 889–890, 890*f*
- layers of stainless steel mesh, 889–890
- rectangular flame-quenching unit, 889–890
- segmented flame-quenching unit, 889–890
- vent duct, 889–890
- venting efficiency, 889–890

Explosion isolation, 890–891

- active explosion isolations systems, 891*f*

chemical barrier standard rate discharge, 891*f*explosion isolation pinch valve, 891*f*explosion isolation valve, 891*f*

extinguishing agent, 890

flame front, 890

flame propagation, 890

gate valves, 890

pinch valves, 890, 891*f*

prevent deflagration, 890

prevent detonation transition in pipes, 890

prevent flame propagation, 890

time for mechanical barrier to close, 891

time for pressure growth, 891

total time for the isolation process, 891

Explosion suppression, 890

dispersion nozzles, 890

dust cloud, 890

high rate discharge suppressor, 890

pressure sensors, 890

suppressant agent, 890

suppression system, 890

Explosive atomization, 176–177

electrical explosion of wires technology, 176

steam explosion method, 176, 176*f*

F

Factors influencing on angle of repose, 56

Features of nanoparticles, 272–274

electromagnetic properties, 274

mechanical properties, 274

optical properties, 274

structural characteristics, 272

thermodynamic data, 273–274

FFC-Cambridge process, 559, 559*f*

extrusion die, 559

graphite anode, 559

Magnelli phase, 559

metal oxide electrode, 559

molten salt bath, 559

oxide ions, 559

process time, 559

solid titanium dioxide, 559

titanium dioxide, 559

University of Cambridge, 559

Fisher subsieve seizer, 18–19, 695, 699, 709–711

air permeability, 19

constant sample packing, 19

Fisher subsieve numbers, 19

Kozeny–Carman equation, 18–19

Kozeny constant, 18–19

mean particle size, 19

packed bed, 19

pore structure, 19

permeability of powder bed, 19

quality control process, 19

Subsieve Auto Sizer, 19

Flame atomic emission spectrometry (AES), 37*f*

atomizer, 36

background signal values, 36

hot flame gases, 36

Flame atomic fluorescence spectrometry (AFS), 37*f*

atomic emission signals, 36

emission method, 36

excite analyte atoms radiatively, 36

external light beam, 36

light signal, 36

Flame spray pyrolysis, 176–177

cluster formation, 176

coalescence, 176

droplet evaporation, 176

finally agglomeration, 176

flamelets feed, 176

hexamethyldisiloxane, 176

liquid fuel, 176

metallic precursors, 176

nucleation, 176

permanent ignition of the spray, 176

pressure swirl nozzle, 176–177, 177*f*

two-substance nozzle, 176

xylene, 176

Flow rate, 21, 47, 130–131, 133, 135, 145–146,

148, 153, 158, 162, 164–166, 168–171,

173–175, 205, 207, 287, 287*f*, 386,

408–409, 423–424, 446, 449, 493–494,

538, 555–556, 572, 574–576, 598, 601, 617,

620, 652, 682, 692, 852, 887, 896–897, 922

die cavity, 54

flow through the orifice, 54

Hall funnel, 54

non-free flowing powder, 54

standard funnel, 54

Fluidization, 378

air entrainment, 55

airborne fine particles, 55

funnel flow patterns, 55

interparticle motion, 55

mass flow pattern, 55

trajectory effect segregation, 55

wide particle size distribution, 55

Foaming agents, 330, 339–340, 342, 858

calcium carbonate, 334–336

decomposition, 334–337

decomposition temperature, 334–337

dolomite, 335

foamable precursors, 335

foaming process, 334–335

liquidus temperature, 335–336

magnesium carbonate, 335–336

magnesium hydroxide, 335

titanium hydride, 334–335

zirconium hydride, 334

Foaming of ingots containing blowing agents

(Formgrip/Foamcast)

aluminum melt, 332

gas release, 332

heating rates, 332

pore structures, 332

precursors, 332

reinforced metals, 332

titanium–hydride particles, 332

Foaming of melts by gas injection (Hydro/Alcan)

direct-foaming process, 332

gas bubbles, 331–332

impeller, 331–332

injecting gases, 331–332

metal-matrix composite, 331

- mixing techniques, 331
 - vibrating nozzles, 331–332
 - viscous mixture, 331–332
 - Foaming of melts with blowing agents (Alporas)
 - blowing agent, 330–331
 - calcium metal, 330–331
 - foaming process, 331
 - titanium hydride, 331
 - viscous liquid, 331
 - Foaming of powder compacts (Foaminal/Alulight), 333
 - blowing agent, 333
 - heat treatment, 333
 - metal matrix, 333
 - mixing of metal powders, 333
 - powder blends, 333
 - Foaming process, 331–332, 334–335, 345
 - accumulative roll bonding process, 336, 336f
 - cell structures, 335–336
 - cell wall, 335–336
 - decomposition, 334–337
 - decomposition gas, 335–336
 - decomposition temperature, 334–337
 - released gas, 335–336
 - rounded cell structure, 335–336
 - spherical cell structure, 335–336
 - Frictional properties, 54
 - angle of internal friction, 48–49
 - coefficient of sliding friction, 48–49
 - effective angle, 48–49
 - external friction, 48–49
 - internal friction, 48–49
 - shear cell, 48–49, 48–49f
 - shear tester, 48–49
 - sliding friction, 48–49
 - wall friction angle, 48–49, 49f
 - Funnel method, 378
 - Carney funnel, 51
 - discharge opening, 51
 - Hall funnel, 51, 51f
- G**
- Gas adsorption, 59–61
 - adsorbed layers, 39
 - adsorbate pressure, 39
 - Brunauer–Emmet–Teller (BET) model, 39–40, 40f
 - closed pores, 39
 - isotherm of nitrogen adsorption, 39–40
 - multilayer adsorption theory, 39
 - pressure transducers, 40–41
 - specific surface area, 39–41, 40f
 - Gas atomization, 169, 172, 324, 340–341, 381–385
 - gas atomized powders, 158–162, 317
 - gas atomizing units, 144–147
 - hot gas atomization, 165–166
 - internal mixing nozzles, 162–163, 162f
 - models of gas atomization, 149–158
 - other gas atomization methods, 162–167
 - powder cleanliness, 161–162
 - process parameters, 148–149
 - ultrasonic gas atomization, 163–165
 - vacuum-dynamic atomization, 167, 167f
 - Gas atomization (production of titanium and titanium alloy powders)
 - argon atmosphere, 555–556
 - ceramic-free Ti alloy, 556
 - electron-beam furnaces, 556
 - gas atomization process, 556–557, 557f
 - plasma atomization process, 555–556, 555f
 - plasma melting induction guiding gas atomization (PIGA), 556
 - pre-mixed raw material, 556–557
 - spherical titanium powder, 555–557, 555f
 - vacuum induction gas atomizing (VIGA), 557–558, 558f
 - Gas atomization beryllium
 - anisotropic components, 802
 - dendritic structure, 803
 - increased isotropy of consolidated material, 802
 - high pressure jet of inert gas, 802–803
 - inert gas atomization, 802–803
 - optical systems, 802
 - vacuum induction melting, 802–803
 - Gas atomization of aluminum powders
 - Alcoa process, 461, 462f
 - annular gas jet, 463
 - atomizer, 462, 465f
 - atomizing nozzle, 461
 - atomizing torch, 460
 - chiller chamber, 461–462
 - ejection nozzle, 462, 465f
 - heated gas, 463
 - horizontal aspirating installations, 460
 - microstructure of powder particles, 460
 - RUSAL PM manufacturing plant, 462, 465f
 - spraying torch, 463
 - suction (ejection) effect, 461, 463
 - top-down atomization, 462
 - tundish, 463
 - vertically upward aspirating plants, 460–461
 - Volgograd Aluminum plant, 466
 - Gas atomized powders, 142, 148, 317, 385–386, 462, 466, 496, 514, 524, 541–542, 545, 652, 655, 676, 677f, 740, 791, 795, 808, 833
 - cellular structure, 160–161
 - cooling rate during solidification, 160
 - dendritic morphology, 160
 - internal porosity, 161
 - Lubanska's formula, 158, 159f
 - microstructure, 160–161, 161f
 - model for solidification time, 159–160
 - particle size, 158–161
 - solidification time, 159–160
 - specific gas consumption, 158
 - spheroidization time, 160
 - surface morphology, 158–161
 - Weber number, 158–159
 - Gas atomizing units, 144–147
 - confined nozzle designs, 145, 145f
 - free fall design, 145f
 - Nanoval nozzle design, 146, 147f
 - prefilming hybrid atomizer, 146–147, 147f
 - prefilming nozzle design, 145–146, 146f
 - pressure-swirl hybrid prefilming atomizer, 146, 147f
 - ultrasonic gas atomizer, 158, 163–165
 - VAMI aspirating nozzle design, 144, 144f
 - WIDEFLOW confined linear nozzle design, 145
 - Gas-phase method of metal powder production
 - application of gas-phases processes, 194–199
 - chemical vapor deposition (CVD) process, 197–198
 - controlled condensation process, 194
 - evaporation means, 195
 - formation of alloy powders, 193
 - gas-phase precipitation, 198
 - health and environment protection, 198–199
 - inert gas condensation (IGC), 187, 194
 - Gleiter's installation, 280, 280f
 - Gold alloy powders, 29
 - Gold brazing alloy powders, 142
 - Gold–platinum powder, 835, 838f
 - Gold powder production
 - apparent density, 832f
 - aqueous gold chloride solution, 837
 - ball milling, 837
 - gold chloride solutions, 835–837
 - gold flake, 837
 - gold foil, 837
 - gold powder production, 835–837
 - gold vaporization, 835
 - mechanical comminution, 837
 - physical properties, 832r, 835
 - sheets of gold, 837
 - spherical gold particles, 837
 - thermolysis, 835
 - Gradient materials
 - coated cutting tools, 302
 - combination of different layers, 302
 - core-coat type, 302–303
 - functionally different materials, 302
 - parallel layers, 302–303
 - Graphene oxide composite powders
 - aluminum composites reinforced with graphene nanosheets, 360
 - cetyl trimethyl ammonium bromide (CTAB), 360
 - graphene oxide sheets, 360–361
 - high lithium-ion diffusion rate, 362
 - lithium-ion batteries (LIBs), 360–361
 - metal oxide–RGO composite powder, 360–361
 - reduced graphene oxide (GO), 360–361
 - spray pyrolysis, 360–362
 - zinc sulfide RGO composite powder, 361–362, 361–362f
 - Gravity filling of shaped molds, 326
 - Green strength, 57, 141, 160, 211, 325, 558–559, 566–567, 572, 576–577, 581, 581f, 590, 592f, 609, 702, 742
 - bending stress, 59
 - device for testing of green strength, 59f
 - green specimen, 58–59

- Green strength (*Continued*)
 non-sintered material, 59, 59f
 plastic deformation, 58–59
 sample strength, 59
- Grinding (production of RE powders)
 adiabatic gas cooling, 802
 anisotropic effect, 801–802
 attrition milling, 801
 ball milling, 801–802
 characteristics of beryllium powders, 802, 803t
 coldstream impact process, 802
 embrittlement effect, 802
 grain size, 802
 high energy ball milling process, 801
- Grinding in attritors (production of zinc powders)
 addition of surfactants, 625
 salts of oleic acid, 625
 salts of stearic acid, 625
 substances preventing autoignition, 625
 wet grinding, 625
- Grinding medium
 agate, 103t
 high-density media, 102
 media hardness, 103
 powder contamination, 103
 silicon nitride, 103t
 sintered corundum, 103t
 stainless steel, 103t
 tungsten carbide, 103t
 zirconium oxide, 103t
- Grinding techniques
 ball mills, 75–78, 76–78f
 ball-to-powder weight ratio (BPR), 108–110, 119, 482
 batch attrition mills, 82
 circulation attrition mills, 82, 84
 cold stream process, 85
 colliding balls, 75
 cone inertia crusher, 80, 81f, 83t
 conical ball mills, 77–78, 78f
 continuous attrition mills, 84, 84f
 cylindrical ball mills, 78–79, 79f
 fluidized bed jet mill, 85, 85–86f, 86t
 Fritsch planetary ball mill Pulverisette, 79f, 87–88t
 grinding kinetics, 75
 grinding media, 78–82
 high-energy milling methods, 85–88
 jet mills, 85, 85–86f, 86–87t
 medium agitating mills, 81–84
 other high-energy milling methods, 85–88
 planetary mills, 79, 79f
 rod mills, 78
 shaker mill, 88
 tumbling ball mills, 75–78
 vibrating grinders, 80–81, 82t, 82f
 vibratory ball mills, 80, 80f
- Grinding units
 covers with inside and outside chambers, 898
 pulsating motion, 898
- suction capacity, 898
 tumbling mills, 898, 901f
 Guinier–Preston zones, 520, 815
- ## H
- Hall funnel, 51, 51f, 54
 Hardfacing, 714–717
 Hardfacing process, 653t, 674
 carbide-containing alloys, 652, 654
 cobalt-base hardfacing alloys, 676
 plasma transferred arc hardfacing process, 676, 676f
 laves phase, 652, 674–675
- Health and environment protection, 198–199, 209–210, 638, 683–684
 admissible concentration limit in aqueous medium, 857
 encapsulation, 857
 extinguishment by burning, 858
 explosion pressure, 857–858
 explosion risk, 857
 flame propagation limit, 858
 heat of combustion, 858
 high-performance cleaning, 857
 industrial safety measures, 857
 inflammability, 857
 occupational exposure limits in the workplace atmosphere, 854–857
 self-ignition temperature, 857–858
 toxic agent, 854–857
 voluminal quenching method, 858
 workplace atmosphere, 854–857
- Health and environment protection (cobalt and cobalt alloy powders)
 allergic reactions, 684
 amalgam techniques, 684
 carbon monoxide, 684
 cobalt carbonyl processing, 684
 cobalt metal fume and dust, 684
 dicobalt octacarbonyl, 684
 enclose operations, 684
 environment protection, 684
 general ventilation, 684
 health hazards, 684
 irritation, 683
 legal airborne permissible limit, 684
 local exhaust ventilation, 684
 mercury, 684
 nickel carbonyl, 683
 personal protective equipment, 684
 safety engineering, 684
 workplace atmosphere, 683–684
- Health and environment protection measures in carbonyl nickel production
 nickel carbonyl dangerous, 638
 nickel carbonyl dissolves, 638
 toxic carbon monoxide, 638
- Heat pressure, 906, 908t
 aspiration cover, 895
 density of environment medium, 895
 density of gaseous medium in lower aspiration cover, 895
 elevated temperature materials, 895
 heat exchange during processing, 895
- Hertz–Knudsen equation, 188, 281
- High-energy milling process
 HE (high-energy) ball mill, 85, 88, 91, 354, 354f, 357–358, 482, 565, 657, 705, 732, 860
 large-diameter tumbling ball mills, 85, 289
- High pressure carbonyl techniques
 carbon monoxide, 638
 condensation, 638
 distillation, 638
 feed concentrates, 638
 high-grade pyrite ores, 638
 nickel–copper–palladium deposits, 638
 Norilsk Nickel group companies, 638
 Norilsk–Talnakh ore, 638
 Severonickel refinery, 638
 thermal shock, 638
 vaporization, 638
- High-strength aluminum alloys
 alloying elements, 511
 aluminum matrix, 511
 aluminum scrap, 511
 Al–Zn–Mg–Cu system alloys, 511, 512–513f, 512t
 corrosion resistance, 511
 fatigue strength, 511
 grain boundaries, 511
 hardly-deformable inclusion, 511
 high-strength quaternary system, 507
 impurity concentration, 513
 mechanical properties, 511, 513, 513f
 particle size distributions, 511–512, 512f
 PM Al–Zn–Mg–Cu system alloys, 513
 recycling of secondary aluminum, 511–513
 secondary aluminum, 511–513
 superheat of melt temperature, 511–512
 water atomized powders, 511–512
- Hot gas atomization
 closed-coupled atomizer, 165–166
 effect of gas temperature, 165
 glass-forming alloys, 165–166
 nozzle freezing, 165
- Hot isostatic pressing (HIP) (beryllium powders)
 fine grain size, 805
 full theoretical density, 804–805
 high degree of isotropy, 805
 high purity beryllium powders, 804–805
 low-oxygen containing argon, 804–805
 near-net shape, 804–805
 nearly theoretical density, 804–805
 pressure medium, 804–805
- Hybrid core/shell nanoparticles
 encapsulation, 303–304
 magnetic encapsulated polymer, 303
 microsphere composite, 303–304
 microwave plasma synthesis, 303–304
 inorganic core, 303
 polymer matrix, 303
 polymerizable organic shell, 303
 Sn-nanoparticles encapsulated, 303
- Hydraulic size classifications
 classified powders, 507
 suspended powder, 507
 suspension reservoir, 507

- hydraulic classifier, 434*t*
- various size fractions, 507
- Hydrogen reduction by autoclave processing
 - (production of nickel powders)
 - alkaline medium, 646
 - autoclave precipitation, 647
 - briquetting operation, 648–649
 - densification cycles, 647–648, 649*f*
 - heterolytic mechanism, 646
 - hydrogen ions, 647
 - hydrogen potential, 646
 - hydrogen pressure, 647
 - kinetic equations, 647
 - nucleation stage, 647
 - powder formation, 648
 - reducing agent, 646
 - seed powder, 646–647
 - Sherritt's hydrometallurgical processing, 649
 - surfactant, 646
- Hydrometallurgical processing (production of nickel powders)
 - cobalt separation, 646
 - copper removal, 646
 - elevated pressures and temperatures
 - processing, 647
 - feed processing, 644–645
 - hydrogen reduction by autoclave processing, 646–649
 - leaching, 645–646
 - Moa Bay deposits, 644–645
 - metal recovery operations, 644
 - nickel–cobalt sulfide, 644–645
 - oxidation and hydrolysis, 646
 - selective dissolution, 644–645
 - separation of nickel and cobalt, 646
 - Sherritt process, 644
 - Sherritt refinery, 644–645
 - solution purification, 644, 646
 - sulfide precipitation, 649–650
 - sulfuric acid, 644–645, 650
- Hydrometallurgical process of cobalt powder
 - chemical dissolution (leaching), 669
 - leach autoclave method, 669–673
 - metal recovery, 669
 - solution purification, 669–670
- Hydrophobization
 - corrosion resistance, 445–446
 - electrolytic copper powder, 446
 - electrolysis kinetics, 446
 - stability of powder, 446
 - surfactant and organic compounds, 445
 - volatile inhibitors, 446
- Hysteresis mercury
 - contact angle hysteresis, 46, 46*f*
 - connectivity model, 46
 - extrusion curves, 46
 - ink-bottle theory, 46
 - intrusion curves, 46
- Ignition of dust deposits and powder layers by
 - self-heating or hot surfaces
 - dust deposits, 869–870
 - exothermic reaction rate, 869–870
 - external ignition source, 869–870
 - glow fires, 869
 - hot-plate test, 870
 - ignition temperature, 869–870
 - International Electrotechnical Commission, 870
 - minimum ignition temperature, 869–870
 - powder deposit, 869
 - reacting chamber, 870
 - self-ignition temperature, 870
 - smoldering combustion, 869
 - smoldering temperature, 869
 - spontaneous flame production, 870
 - U.S. Bureau of Mines test, 869–870
- Impact atomization
 - heat of evaporation, 173
 - heat of solidification, 173
 - impeller, 173
 - molten metal feed rate, 173
 - powder yield, 173
 - superheat, 173
 - vaporization, 173
 - volatile liquid coolant, 173
- Impact point, 54
- Impulse atomization method, 174*t*
 - gas atmosphere, 173
 - gravity impulse mode, 173
 - impulse generator, 173
 - impulse mode, 173–174
 - mass throughput, 173–174
 - melt superheat temperature, 173
 - monosized granules, 173
 - narrow particle size distribution, 173
 - nozzle plate complete with orifices, 173
 - orifice shape, 173
 - orifice size, 173
 - thermal model of melt droplets cooling, 174
- Inconel alloy 625 nickel based superalloy, 337
- Indium
 - air atomization of melt, 775
 - black indium, 775
 - cementation technique, 775
 - control rods in nuclear techniques, 775
 - francite, 774
 - high cross-section capture for thermal neutrons, 774–775
 - hot gas atomization, 775
 - indium concentrate, 774–775
 - indium powders, 775
 - indium recovery technique, 775
 - indium sponge production, 775
 - kilindrite, 774
 - production of preliminary indium, 775
 - semi-conductor technique, 775
 - solders for joining of metals, glass, quartz and ceramics, 775
 - source of indium, 775
 - sphalerites, 774
 - wear-resistant coatings of indium, 775
- Inductively coupled plasma atomic emission spectroscopy (ICP-AES)
 - atomic emission spectroscopy, 36
 - excitation source, 36
 - highly ionized gas, 36
 - inductive coupled plasma, 36
 - multi-element analysis, 36
- Inert gas condensation (production of zinc powders)
 - spherical powder, 619–620, 621*f*
 - 'Tuman' ('Fog') installation, 619, 620*f*
- Inert gas fusion
 - fusion area, 35
 - gas/metal bonding, 35
 - inert carrier gas, 35
 - physical and chemical bonding, 35
- Infiltration (INF), 842
- Inflammability and explosivity of powders
 - dependence the ignitability and explosibility of the gas suspended solid mixture on the oxygen content in oxidizing gas, 875
 - ignition of dust deposits and powder layers by self-heating or hot surfaces, 869–870
 - maximum explosive pressure at constant volume, 873–874, 875*f*
 - maximum rate of explosion pressure rise at a constant volume, 874–875
 - minimum electrical spark ignition energy of dust clouds, 872–873, 873*f*
 - minimum explosive dust concentration, 870–871
 - minimum ignition temperature of dust clouds, 872
- Initial compounds for metals production
 - (production of RE metal alloy powders)
 - production of chlorides, 785–786
 - production of fluorides, 786
- Institute for Problems of Materials Science (Kiev, UA), 318, 505
- Instrumental indentation
 - Berkovich indenter, 276
 - impression, 276
 - indentation depth, 276
 - indentation load, 276
 - indentation load-depth curve, 276
 - indenter, 276–278, 277*t*
 - local strength, 276
 - plastic deformation, 276
 - Poisson's ratio, 276–278
 - residual stress, 276
 - unloading process, 276–278, 277*f*
 - specimen holder, 278
 - Young's modulus, 276–278
- Internal mixing nozzles, 162*f*
 - nozzle exit, 162–163
 - prefilming spin nozzle, 162–163
 - pressure swirl hybrid prefilming atomizer, 162–163
 - ring gas atomizer, 162–163
 - tangential inlet, 162–163
- International Center for Electron Beam Technology (ICEBT), 297, 297*f*
- Inter-stage transport
 - belt conveyors, 452
 - bucket elevator, 453
 - bypass tube, 452
 - cone valve system, 452, 452*f*
 - containers, 452
 - continuous inter-stage transports, 452

Inter-stage transport (*Continued*)

- discontinuous inter-stage transports, 452
- dustproof performance, 452–453
- gravel pumps, 452
- loading devices, 452
- material handling equipment, 452
- pneumatic transport, 454
- processing equipment, 452
- spiral conveyors, 452–453, 453*f*
- transportation of dry mixtures, 452
- unloading devices, 452
- vibrating conveyors, 452–453
- vertical spiral vibrating conveyors, 452
- worm conveyors, (Not found)

Ion guns, 31

- cesium gun, 33
- duoplasmatron, 33
- electron ionization, 33
- liquid metal ion gun, 33
- surface ionization source, 33

Iridium

- chemical composition, 838*t*
- particle size, 841
- precipitated from acid-salt solution, 839
- property, 841
- surface area, 839

Isostatic compaction

- cold isostatic pressing (CIP), 325
- hot isostatic pressing (HIP), 325
- near-net shapes, 325
- sintering, 325
- uniform density, 325

J

Jaw crusher, 65, 74, 74*f*, 583–584, 897

JCPDS International Centre for diffraction data, 34

Jenike AM

- Jenike shear cell, 48–49, 48*f*

Jet mills, 85, 85–86*f*, 86–87*t*, 289, 289–290*f*, 612

JET reactor, 806

Joining, powder metallurgy materials, 341

Joining, refractory metal powders

- brazing, 721
- fusion welding, 375

K

Kinetics and mechanism of the process (solid-phase reduction)

- adsorption-autocatalytic theory, 212–213
- active surface centers, 214
- chemisorption of reducing gas, 214
- crystal chemical transformation, 214
- diffusion conditions, 213
- diffusion-kinetics range of the reduction process, 214
- indirect reaction, 212
- kinetic equation, 214
- multistage mechanism, 214

Kinetics of solid phase formation in solution

- aqueous solution, 224
- autocatalytic effect, 223, 225
- chemical reagents, 225

cluster, 223–224

- constant of process rate, 223
- crystallization centers, 224
- induction period, 223–224
- kinetic factors, 223
- kinetic reduction curve, 224
- ligand, 225
- metal ions, 224–225
- metallic colloids, 225
- nucleation rate, 224–225
- oxidation–reduction potential, 223–225
- particle shape, 224–225
- particle size, 223–225
- protective colloids, 225
- reduced metal rate, 224
- reduction reaction, 224
- Rostovtsev kinetic equation, 214
- Kozeny–Carman equation, 18–19, 41

L

Laboratory mills for mechanical alloying,

- 100–101
- attritors, 99*f*
- HE (high-energy) mill, 100, 100*f*
- laboratory ball mill, 100*f*
- planetary mills, 101
- SPEX mill, 100
- Uni-Ball mill, 101
- vertical rod mill, 101

Langmuir formula, 281

Lanthano-thermic method

- reducing agent, 787
- reduction by lanthanum, 787
- samarium oxide, 787
- tantalum crucible, 787

Laves phase, 652, 674–675

Leaching (first stage in refining process)

- ammonium sulfate, 645
- cobalt separation, 646
- elevated temperature and pressure, 645
- leach liquor, 646
- leaching process, 645–646
- metal sulfides, 645
- oxidative dissolution, 645
- refining process, 645–646
- sulfide feed, 645

Leaching autoclave process

- ammonium sulfate, 670–673
- autoclave cobalt coating, 673
- cobalt hexamine sulfate complexes, 669
- cobalt–nickel hexamine salt, 670–671
- cobalt sulfate, 673
- densification reduction, 672
- hydrometallurgical process, 669–673
- kinetics of the reducing autoclave process, 671
- metal carbides, 673*t*
- nickel sulfide concentrate, 669–670
- nucleation reduction, 671
- pure crystalline cobaltic hexamine salt, 670
- purification steps, 670
- refining process, 669–670, 670*f*
- Sherritt cobalt refining process, 670*f*
- Sherritt refinery, 669–670
- soluble amine complexes, 669–670

Lead-acid batteries, 642, 848

- automotive industry, 858
- fuel saving technologies, 858
- Global Automotive Battery Market, 858
- micro hybrid systems, 858

Lead oxide powder production

- acid adsorption, 850*t*
- apparent density, 850*t*
- automotive lead-acid batteries, 848
- ball milling, 848–849
- Barton pot process, 848
- grey/lead oxide, 848
- heat generating during milling, 848
- high-speed blades, 848
- lead ortho-plumbate, 848
- lead oxidation in air, 848
- lead oxide powder production, 848
- particle size, 848
- rate of oxidation, 850*t*
- red lead oxide, 848

Lead powder production, 847–850, 849*t*, 849*f*

- apparent density, 849*t*
- electrolysis, 850
- electrolyte composition, 851–852*t*
- health and environment protection, 854–858
- hot gas atomization, 847
- lead-acid batteries, 848
- lead–bismuth, 851–852*t*
- lead oxide, 848, 850*t*
- lead–tin, 851–852*t*
- lubricant compositions, 850
- nominal composition, 849*t*
- properties, 849*t*
- roundish particles, 850
- sieve analysis, 847, 849*t*
- standard grades, 849*t*
- superheat, 847
- thermolysis, 850

Lead zirconate titanate (PZT) ceramics

- piezoelectric property, 772
- press-sinter method, 772–773
- PZT polymers composite, 773
- PZT powder, 772
- sensor, 772

Light scattering, 695

- centrifugal pumping system, 21
- dispersing units, 21
- laser light, 20–21
- laser particle sizer, 21
- Mie theory, 20–21
- parallel laser beam deflect, 20
- scattering angle, 20
- sensor elements, 20
- unified scatter technique, 21

Localization of powder-gas emissions

- aspiration for particulate material reloading in closed gravity chutes, 901–909
- aspiration in combustible powder conditions, 897
- capacity of local suction, 896–897
- definition of the local exhaust capacity, 901–918
- ejection pressure, 892
- grinding units, 898–901

heat pressure, 895
 melt atomization units, 897
 overpressure of closed chambers, 893–894
 pressure created by equipment moving parts, 895
 pressure — mass transfer result, 896
 single rotary hammer mills, 912–918
 Low pressure carbonyl technique
 atmospheric pressure carbonyl technique, 635
 circulation of formed pellets, 635
 decomposition device, 635
 extraction of nickel, 635
 heat-insulated decomposer, 635
 Inco Ltd, 635
 Mond–Langer process, 635
 nickel carbonyl cleaning, 635
 nickel matte feed, 635
 nickel tetracarbonyl vapor, 635
 nickel yield, 635
 pellets coalescence, 635
 preheated hydrogen, 635
 synthesis stage, 635

M

Magnesium

magnesium alloy powders, 533–541
 magnesium alloys, 384–387, 491f, 539, 541, 545–546, 766, 790
 magnesium chips, 535
 magnesium grit, 535
 magnesium granules, 173–174, 538–539, 538f
 magnesium powder, 171, 386, 533–535, 535f, 536–537t, 539–540, 543, 543f
 production of magnesium granules, 538–539
 production of magnesium and magnesium alloy powders, 533–541
 production of magnesium powders, 533–535
 Magnesium alloy powders
 AMX602, 544–545, 545f
 AZ31B, 536–537t, 545
 AZ91E, 536–537t
 Electron MAP 21, 536–537t, 542
 Electron MAP 43, 536–537t, 542
 Electron MAP 91, 536–537t
 Electron MAP+ 21, 536–537t
 Electron MAP+ 43, 536–537t
 Electron MAP+ 91, 536–537t
 ground magnesium alloy powders, 543
 nanocrystalline $\text{Mg}_{97}\text{Zn}_1\text{Y}_2$ (at%), 543
 WE43B, 552t
 ZAXE1711, 544
 ZM21, 546
 Magnesium granules
 active magnesium, 538
 apparent density, 538–539
 applications, 538–539
 coarse spherical granules, 539
 content of metallic magnesium, 539
 dense structure, 539
 granule structure, 539
 monodisperse granules, 539
 oxide-salt film, 538
 particle shape, 539
 production of magnesium granules, 538–539

shining metal surface, 539
 size of granules, 539
 spherical granules, 539
 Magnesium reduction method (Kroll Process), 550–553, 568t
 Magnesium-thermal reduction of beryllium fluoride
 beryllium fluoride BeF_2 , 800
 flux composition, 800
 inert atmosphere, 800
 magnesium fluoride, 800
 reducing agent, 800
 Magneto-hydrodynamic method (MGD), 539
 Manufacture of composite(s)
 aluminum-based composites, 363–364
 composite manufacturing methods, 363
 copper-based composites, 364–366
 refractory metal and carbide-based composites, 366–368
 silver-based composites, 363
 Manufacture of composite powders
 aluminum-based composite powders, 352–353
 carbon nanotube (CNT)-reinforced metal composite powders, 357–360
 copper-based composite powders, 353–354
 graphene oxide composite powders, 360–363
 nickel-clad aluminum powders, 351–352
 refractory-based composite powders, 355
 titanium-based composite powders, 355
 Manufacture of electrodes (RE comprising)
 carburization process of La_2O_3 –Mo cathodes, 794
 carburized filament, 794
 carburized La_2O_3 doped Mo filament cathodes, 794
 discharge lamps, 794
 electrical discharge machining, 794
 La–Mo cathodes, 794
 La_2O_3 –Mo cathodes aluminum-based composite, 794
 La_2O_3 – Y_2O_3 –Mo cermet cathode, 794
 plasma cutting, 794
 plasma spraying, 794
 RE_2O_3 layer, 794
 thermionic emission, 794
 ThO_2 cathodes, 794
 tungsten-arc inert-gas welding (TIG), 794
 tungsten cathode material, 794
 W– CeO_2 electrodes, 792–794
 W– ThO_2 electrodes, 792–794
 Manufacturing technique of quasicrystalline powders
 argon atmosphere, 315
 argon atomization, 317
 atomization in helium atmosphere, 316
 centrifugal atomization, 316
 cooled copper crucible, 315
 cooling rate, 316–318
 crushing of ingots, 315
 evaporated powders, 315
 extrusion of water atomized powder, 318–319
 faceted shape, 314
 flake shape, 315

gas atomized powders, 317
 high-frequency furnace, 315
 high-speed-rotating disc, 316
 icosahedral QC phase, 314–315, 316t, 317
 mechanical alloying, 314
 nanocrystalline structure, 314
 nozzle atomizer, 316
 oxygen content, 317
 pulse energy, 315
 polyhedral shape, 315
 QC structure, 313–314
 rotating target, 315
 spherical shape, 317
 tumbling ball mill, 315
 vaporization by laser beam, 315
 water atomized powders, 318–319
 wave length, 315
 Young modulus of QC, 319

Mass analyzer

electrostatic analyzer, 33
 magnetic analyzer, 33
 quadrupole mass analyzer, 33
 sector instrument, 33
 time of flight mass spectrometry, 33

Material selection (Porous materials)

bronze, 324, 324f
 nickel, 324, 325f
 nickel alloys, 324
 nonferrous metals, 324
 prealloyed powders, 324
 premixed elemental powder, 324

Maximum explosive pressure at constant volume

American Society for Testing and Materials, 874

closed vessel, 873
 electric sparks, 873, 875
 explosion chamber, 872f, 873–874
 explosion of airborne powder, 873
 glowing resistance wire coils, 873
 Hartmann bomb, 873, 874f
 ignition sources, 873
 ISO vessel, 873–874
 maximum explosion pressure of dust clouds, 873
 pyrotechnical ignitor, 873–874
 Siwek 20-liter sphere apparatus, 874
 synchronized chemical ignitors, 873

Maximum rate of explosion pressure rise at a

constant volume
 closed vessel, 874–875
 explosion violence, 874–875
 International Standards Organization, Explosion Protection Systems, 874–875
 maximum rate of pressure rise, 874–875

Measuring angle of repose

base cone, 55
 circular method, 55
 crater method, 55
 dynamic angle of repose, 56
 height cone, 55
 ledge method, 55
 powder heap, 55
 rotating cylinder, 55
 titling table, 55

- Mechanical activation, 87–88, 94–96, 108, 121, 290
- Mechanical alloying
- aluminum-base alloys, 107, 113–118
 - applications, 112–119
 - attritors, 94, 97–99
 - brittle–brittle component systems, 107
 - commercial mills, 101–102
 - consolidation, 94
 - contact displacement reactions, 108–109
 - cobalt-base alloys, 113
 - copper-base alloys, 119
 - ductile–brittle component systems, 92, 104–106
 - ductile–ductile component systems, 105, 106*f*
 - equilibrium materials, 91
 - friction effect, 94
 - grinding medium, 92, 97, 102–104
 - high-energy milling process, 91, 104
 - high-energy mills, 100, 113–114
 - impact effect, 94
 - laboratory mills, 100–101
 - mechanical alloying fundamentals, 104–107
 - mechanical alloying process, 92–94, 114*f*, 119
 - milling equipment, 94–104
 - nickel-base alloys, 112–113
 - nonequilibrium alloys, 91
 - oxide dispersion strengthened (ODS) alloys, 107
 - powder contamination, 94, 103, 109–111, 111*t*
 - prealloyed powders, 91–92, 107
 - precipitation strengthened, 91
 - process control agent (PCA), 92–93
 - Rehbinder's effect, 92
 - selection of grinding medium, 102–104
 - shaker mills, 94, 96–97, 100
- Mechanical alloying (production of titanium and titanium alloy powders)
- amorphous phases, 565
 - dispersion-hardened alloys, 565
 - elemental powders, 565–566
 - equilibrium phases, 565
 - high-energy ball mill, 565
 - metastable crystalline phases, 565
 - nanosstructured intermetallic composites, 565
 - nanosstructured materials, 565
 - non-equilibrium phases, 565
 - planetary ball mill, 565
 - simple technique, 565
 - supersaturated solid solutions, 565
 - titanium based alloys, 565
- Mechanical alloying fundamentals
- agglomeration, 104–105, 113–114
 - diffusion distances, 105, 108
 - dislocation, 104–105
 - chemical conversion, 104
 - cold welding, 104–105, 113–114
 - convoluted lamellae, 104–105
 - crystal defects, 104–105
 - fatigue failure mechanism, 104
 - flattened particles, 105
 - fracture, 104
 - fragile flakes, 104
 - grain boundaries, 104–105
 - interatomic forces, 104
 - plastic deformation, 104, 107
 - structural refinement, 104–105
 - surface deformation, 107
 - work hardened, 104–105
- Mechanical crushing and grinding
- Bong's Work Index, 72
 - brittle materials, 66, 74
 - comminution, 65, 70
 - crushers, 74–75
 - disintegration process, 66
 - disruption, 66
 - ductile metal, 66–68
 - grindability, 70–72
 - grinding techniques, 75–81
 - hardgrove grindability index, 71
 - mechanism of the ductile metal deformation, 66–68
 - regularities of milling, 68–73
 - temperature rise during milling, 72–73
- Mechanical plating
- activating solution, 630
 - cadmium powder mixtures of Zn and Cd powders, 630
 - glass beads, 630
 - mixtures of Zn and Cd powders, 630
 - zinc powder, 630
- Mechanical properties of metallic foam
- materials, 338–346
 - cell wall, 344
 - collapse, 344
 - densification, 344
 - elastic buckling, 344
 - fracture, 344
 - plastic collapse stress, 344
 - roughly constant stress plateau, 344
 - tetrahedra unit, 344
 - x-ray tomography, 344
 - yield strength, 344
 - yielding, 344
- Mechanical properties of porous materials, 323–328, 328*f*
- Mechanism of ductile metal deformation
- accumulation of dislocations, 66–67
 - Griffith's relation, 67–68
 - Griffith–Irwin–Orowan's relation, 67
 - microcracks, 66–67
 - multiphase disintegration, 66
 - Rehbinder effect, 67
 - shear stress, 67
- Melt atomization (production of zinc powders))
- centrifugal atomization, 620
 - gas atomization, 620, 621*f*
 - gas pressure, 620
 - hot gas atomisation, 620
 - irregular particle shape, 620
 - rapid solidification, 619*f*, 620, 622
 - ultrasonic impact, 620, 625
 - water atomization, 620
- Melt atomization units
- aspiration cover, 897, 899*f*
 - crucible, 897
 - dust-gas emission source, 897
 - exhaust duct, 897
 - induction furnace, 897, 900*t*
 - tundish, 897, 899*f*
- Melt drop orifice techniques
- impulse atomization method, 173–174
 - melt drop vibrating orifice method, 174
 - pulsated orifice ejection method, 174–175, 175*f*
- Melt spinning centrifugal atomization
- melt spinning roller technique, 171–172
 - rapid solidification rate (RSR) process, 171
 - rotating electrode atomization, 172
 - spinning cup, 169, 179
 - spinning disc atomization, 169–171
- Melt spinning roller techniques
- centrifugal force, 171
 - cooling rate, 171
 - copper roller, 171
 - flakes, 171
 - flaky magnesium powder, 171
 - flaky powders, 171, 172*f*
 - heat abstraction, 171
 - heat contact, 171
 - nonequilibrium solubility, 171
 - ribbon thickness, 171
 - ribbons, 171
 - roller circumferential speed, 171
 - rotating roller, 171
 - spinning roller technique, 171, 172*f*
- Melt spinning techniques
- Al-based amorphous alloys, 503
 - closed processing system, 503
 - helium gas atomization, 504–505
 - high-strength crystalline PM alloys, 503
 - vacuum-type glove box, 503
- MER process
- anode technology, 559
 - batch products, 559
 - bubble form, 559
 - carbonaceous material, 559
 - composite anode, 559
 - fused halides, 559
 - rutile powders, 559
 - solid deposit, 559
- Mercury porosimetry
- capillary radius, 43–44
 - hysteresis mercury, 44
 - mercury intrusion porosimetry, 43, 46
 - mercury meniscus, 43–44
 - penetrometer unit, 44
 - pressure transducer, 44
 - sessile drop mode, 44
 - shadowgraph, 44
 - surface area determination, 45
 - surface tension, 45
 - x-ray and ultrasonic flow-detection, 44
 - Young–Laplace–Washburn equation, 43–44
- Metal injection molding (MIM), 165–166, 283, 307, 326, 343, 556, 566, 612, 740–741, 761
- Metallic foams. *See also* Porous powder and metallic foams
- cellular materials, 328–330
 - closed-cell materials, 330–333
 - foaming agents, 334–336

- metallic foams materials, 338–346
- open-cell materials, 338
- open-cell metallic foams, 336–338
- Metallic foams (materials for functional application)
 - biomaterials, 343
 - acetabular system, 343
 - bone cement, 343
 - buoys, life buoys, 346_r
 - dental implants, 343
 - electrodes for NiMH and NiCd batteries, 346
 - encapsulating of noise sources, 346_r
 - filler material, 343
 - fuel cells, 343
 - high temperature filtration, 342
 - high temperature resistant materials, 342
 - hip implants, 343
 - Inconel-alloy-based foams, 342
 - lightweight molybdenum foam, 343
 - nickel foam strip, 343
 - orthopedic applications, 343
 - soot-filter, 343
 - space holder, 343
 - space holder mixtures, 343
 - thin porous bead coatings, 343
 - vertebra fusion, 343, 346
- Metallic foams (materials for structural application)
 - biporous metallic foams, 340–341
 - diffusion welding technique, 341
 - heat exchangers, 341
 - high pressure molding, 340
 - liquid metal matrix composites, 340
 - metallic hollow sphere structures, 340
 - nozzle system, 340
 - sandwich foam production, 341
 - spray coating process, 340
- Metallic foams materials
 - materials for functional applications, 342–344
 - materials for structural applications, 338–342
- Metallographic microscopy
 - automatic image analysis, 10
 - coating thickness measurement, 10
 - failure analysis, 10
 - glass plate, 10
 - grain size analysis, 10
 - grain structure analysis, 10
 - pore morphology, 10
 - powder particles surface, 10
 - transmission principle, 10
- Metallurgical methods (production of RE metal-alloy powders)
 - carbothermic method, 788
 - lanthano-thermic method, 787
 - sublimation in vacuum, 787
- Method of disproportionation of lower titanium halogenides
 - high temperatures, 564
 - low chlorides, 564
 - ores, 564
 - scrap metal, 564
 - titanium chloride, 564
 - titanium tetrachloride, 564
- Method of RE elements separation
 - molecular recognition technology, 785
 - RE separation by ion-exchange chromatography, 783–784
 - separation of REE by extraction, 782–783
 - schemes of complete separation, 784–785
- Method of weight samples
 - Andreasen's pipette, 16
 - Andreasen–Esenwein's pipette, (AU: Not found)
 - IPMS pipette, (AU: Not found)
 - pipette method, 16
 - residual weight, 16, 20
 - suspended powder, 16
- Microalloying influences (beryllium properties)
 - act on recrystallization, 804
 - compound FeAlBe₄, 804
 - embrittlement action, 804
 - growth of beryllium oxide, 804
 - impurity elements, 804
 - non-metallic impurities, 804
- Microanalysis
 - electron probe x-ray microanalysis (EPMA), 29–30
 - scanning electron microscopy (SEM), 27–29
- Microencapsulation
 - chemical methods, 446
 - film-forming material, 446
 - fluidized bed, 446
 - physical methods, 446
 - polycondensation, 446
- Microencapsulation of nanoparticles
 - glyoxal, 293
 - hydrophobic protective layer, 293
 - low-molecular-weight organic substances, 293
 - metal content, 294
 - mono either, 293
 - oxidation rate, 293–294
 - oxide layers, 293–294
 - polymers, 293
 - protective coatings, 293
 - stearic acid, 293
 - storage period, 294
 - surface of metal nanoparticles, 293
 - thickness of layer, 294
 - water vapor, 293–294
- Micromerograph
 - micrograph apparatus, 15–16
 - particle size distribution analysis, 15–16
 - sediment accumulation, 15–16
 - sediment weight, 15–16
- Milling equipment
 - grinding medium, 102–104, 110
 - milling containers, 110
- Minimum electrical spark ignition energy of dust clouds
 - electric sparks and arcs, 872–873
 - explosible dust clouds, 872–873
 - Hartmann tube, 873
 - hazardous electrostatic discharges, 872–873
 - paper diaphragm, 873
 - powder gravitation flow, 872–873
 - spark energy, 873
- stored capacitor energy, 873
- USBM method, 873
- Minimum explosive dust concentration
 - continuous induction spark source, 870
 - critical mass of dust, 870
 - dust cloud, 870
 - empirical correlation, 870
 - explosion chamber, 871, 872_f
 - explosion criterion of ISO standard, 870–871
 - four liter installation IPMS, 871
 - Hartmann tube, 870
 - International Electrotechnical Commission, 870–871
 - International Standards Organization (ISO), 870–871, 871_f
 - minimum explosive concentration, 870–871
 - one cubic meter ISO vessel, 870–871
 - standard test, 870
 - suspended solid sampling, 871, 872_f
 - U.S. Bureau of miners (USBM) method, 870
- Minimum ignition temperature of dust clouds
 - dust cloud, 872
 - Godbert–Greenwald furnace, 872
 - hot surface, 872
 - internal surface, 872
 - minimum ignition temperature, 872
 - standard for determining minimum ignition temperature of dust cloud, 872
 - vertical cylindrical ceramic tube, 872
- Models of centrifugal atomization
 - angular velocity, 168
 - centrifugal acceleration, 169
 - direct drop formation (DDF) mode, 167
 - formation disintegration, 168
 - ligament formation mode, 167
 - protuberances, 167
 - rotating electrode process, 167–168
 - rotating speed, 167
 - size distribution, 167
 - surface tension forces, 167–168
- Models of gas atomization
 - above WCP atomization, 154
 - aspiration pressure, 154–155, 154_f
 - below WCP atomization, 153–154
 - Bradley's mathematical model, 149
 - capillary wave model, 149–150
 - close-coupled gas atomization, 152–153, 152_f
 - closed wake, 152–155, 152_f
 - critical dependences, 149
 - droplet diameter definition, 150–151
 - film hollow cone, 151
 - hysteresis type aspiration behavior, 155
 - Ingebo equation, 150
 - Large–Eddy simulation, 155–156
 - Mach number, 149–150
 - Mach shock disc, 153
 - melt film formation, 152, 156
 - model of droplet formation, 149
 - model of pressure-swirl atomization, 151, 151_f, 152_r
 - model for disintegration of liquid sheet, 150_f
 - Newtonian fluids, 149
 - open wake, 152–153, 152_f
 - pulsatile gas atomization model, 153

Models of gas atomization (*Continued*)

- Reynolds number, 150
 - subambient pressure region, 153
 - wake closure effect, 153
 - wake-closure pressure (WCP), 153
 - wave length, 149
 - wave models of Ingebo, 150
 - Weber number, 149
- Molecular recognition technology
- carbonate salt, 785
 - cation ionic radius, 785
 - selective transport of metal ions, 785
 - supported SuperLig products, 785
 - three step process, 785
- Molybdenum and molybdenum alloy powders
- cold-isostatic pressing, 731–732
 - composite carbides, 726
 - creep resistance, 726–727
 - die bodies, 726
 - die inserts, 726
 - ductility, 726–727, 731
 - electrical make-break contacts, 726, 729*t*
 - hafnium carbide, 726
 - heat shields, 726
 - heating elements, 726
 - high-energy ball milling, 732
 - linings for furnaces, 726
 - immiscible sodium and yttrium elements, 732
 - mechanical alloying, 726–728, 732
 - mechanical alloying-mechanical disordering, 733, 734*f*
 - microhardness, 732
 - molybdenum–lanthana alloy, 731
 - molybdenum–silver composites, 726, 729*t*
 - molybdenum–yttria alloy, 731
 - near stoichiometric mixture of powder components, 733
 - punches for hot stamping, 726
 - recrystallization temperature, 725–727
 - rocket nozzles, 726
 - self-propagating high-temperature synthesis (SHS), 733
 - sintering temperature, 731–732
 - spark plasma sintering (SPS), 727–728, 732, 733*f*
 - structural parts, 726
 - thermo-explosion mode, 733
 - thin sheets, 726–727, 731–732
 - titanium carbide, 726–727
 - TZM molybdenum alloy, 726
 - wet doping technique, 731
 - zirconium carbides, 726–728
- Multiaimed powder tester FT4
- basic flow energy, 57
 - downward traverse, 57
 - Freeman Technology, 57
 - FT4 equipment, 57
 - force signal, 57
 - torque signal, 57
 - upwards traverse, 57

N

Nanopowder(s)

- applications, 296–307

- cemented carbides, 300–302, 301*t*
 - electrical storage systems, 306–307
 - features of nanoparticles, 272–274
 - fibre-reinforced material, 302
 - microencapsulation of nanoparticles, 293–294
 - miniaturized systems, 307
 - nanopowder chemical passivation, 293
 - nanopowder–polymer composites, 303–304
 - powder processing methods, 294–295
 - production methods, 278–292
 - semiconductors, 305–306
 - testing of nanopowders, 275–278
 - thin film technique, 304–305
 - safety aspects of nanopowders production, 295–296
- Nanopowder-polymer composites
- composite nanoparticles, 303
 - microsphere composite nanoparticles, 303–304
 - polymer-matrix composites, 303
- Netsch attritors, 98*t*, 101, 102*f*
- Nickel, 119, 162, 173, 204–209, 208*f*, 216, 221, 225, 235–236, 236*f*, 252, 287*f*, 325–326, 352, 633–657, 645*f*, 661–667
- Nickel-alloy powders
- atomized nickel alloy powders, 652–657
 - autoclave processing of nickel hydroxide and carbonate pulps, 651–652
 - carbonyl process of nickel powder production, 633–644
 - hardfacing powders, 652–654
 - hydrometallurgical processing, 644–652, 645*f*
 - mechanically alloyed nickel superalloy powders, 657
 - powder covered by nickel, 650–651
 - production of nickel powder by electrolysis, 663–664
 - production of nickel powder by reduction processes, 661–663
 - production of nickel and nickel-alloy powders, 633–667
 - superalloy powders, 654–657
- Nickel base alloys (related to applications of additive manufacturing)
- DED-L (direct energy deposition by laser heat source), 392
 - DED-PA (direct energy deposition by plasma arc heat source), 392
 - direct energy deposition (DED) process, 392
 - electron beam melting (EBM), 392
 - elevated temperatures, 392
 - functionally graded system, 392
 - Inconel 625, 392, 394*t*
 - Inconel 718, 392, 394*t*
 - Intermetallides, 392
 - Invar 36, 392–393, 393*f*, 394*t*
 - laser scanning speed, 393, 393*f*
 - laser scanning tracks, 393
 - Ni-base superalloys, 392
 - NiCr superalloy enriched by titanium, 392
 - nickel chrome superalloy matrix, 392
 - PBF-EB (powder bed fusion by electron beam heat source), 392, 394*t*

- PBF-L (powder bed fusion by laser heat source), 392, 394*t*
 - powder bed fusion (PBF) process, 392, 394*t*
 - powder bed layers, 392
 - Rene 142, 392
 - selective laser melting (SLM), 392–393, 393*f*
 - 3D layerwise laser cladding, 392
 - turbine blades, 392
 - turbine engines, 392
- Nickel-clad aluminum powders, 351–352, 474
- carbonyl process, 351
 - compounds clad by nickel, 351, 474
 - Co-base superalloys, 392
 - EBM scanning, 392
 - melt pool, 392
 - nickel coating, 474
 - plasma coatings, 474
 - properties of nickel-clad aluminum powders, 474
 - spraying of coatings, 474
 - thickness of the coating layer, 474
 - vibro-fluidized bed, 351
- Nickel powders, 208–209, 208*f*, 287, 294, 325*f*, 378, 380*f*, 385–386, 600, 633, 635, 638–639, 640–641*f*, 641–642, 643*f*, 644, 646–651, 662–664, 663–664*f*, 670
- Niobium alloys, 162, 290, 734–742
- arc melting, 740
 - direction of crystallization, 742
 - directional solidification, 740
 - electric contacts, 738
 - electrode induction melting, 740–741
 - hot extrusion, 740
 - hot isostatic pressing, 740–741
 - microwaves absorber, 738
 - niobium composites, 742
 - niobium–aluminum alloys, 741–742
 - niobium-based silicide intermetallic composites, 740
 - niobium–copper alloys, 738
 - niobium powders, 73, 736–738, 736*f*, 738*t*, 740*f*
 - niobium–silicon alloys, 740–742
 - oriented crystallization melting, 741–742
 - physical vapor deposition, 740
 - production of niobium powders, 734, 736–738
 - silicide parameters, 741
 - valence electron concentration, 741
 - welding electrodes, 738
- Nitriding and oxide formation
- nitride film, 446
 - nitriding treatment, 446
 - nitrogen-containing compound, 446
 - oxide film, 446
- Noble metal powders
- gold powders, 835–837
 - iridium powder, 837
 - osmium powder, 839
 - palladium powder, 839
 - platinum powder, 839
 - platinum-group powders, 837–842
 - production of noble metal powders, 842–844
 - rhodium powder, 839

ruthenium powder, 839
 silver powders, 832–835
 Nontransferred arc, 447–448, 448*f*, 676
 Non-sag tungsten wires
 doping elements—aluminum, silicon,
 potassium, 699–701
 elongated interlocked grain structure, 701
 incandescent lamp, 699–701
 potassium bubbles, 701
 tungsten filaments, 699–701
 tungsten lattice, 699–701
 tungsten metal powder particles, 699–701
 Norilsk Nickel Concern, 351, 474
 Nucleation stage, 647, 671–672

O
 Occupational exposure limits of bismuth in
 workplace atmosphere, 854–857
 Occupational exposure limits of lead in
 workplace atmosphere, 854–857
 Occupational Safety and Health Administration
 (OSHA), 209, 612–613, 683–684, 773, 776,
 810
 Open-cell materials
 nickel alloys, 338
 nickel foams, 338
 supercapacitor, 338
 Open-cell metallic foams
 catalysts, 336–337
 diffusion process, 338
 flow fluids, 336–337
 heat transfer, 336–337
 high-temperature supports, 336–337
 electrochemical cells, 336–337
 multifunctional load supporting, 336–337
 synthesis of open-cell metal foams, 336–337
 ultralightweight metal foams, 337
 Optical microscopy, 6–7, 38
 automatic counting devices, 8
 bank register, 9
 contiguity and overlap, 9
 dispersing fluid, 8
 dissolving collodion, 9
 eyepiece graticules, 9, 9*f*
 filar micrometer eyepiece, 9
 particle images, 9
 particle photographs, 9
 preparation techniques of slides, 8
 recognition of the particles, 9
 recording micrometer eyepiece, 9
 segregation of particle sizes, 8
 slit scanning method, 9
 spot scanning devices, 9
 Vigdorchik's denumerably-measuring, 9
 Orowan loop, 815
 Orowan mechanism, 815
 OSHA. *See* Occupational Safety and Health
 Administration (OSHA)
 Osmium
 chemical composition, 841
 particle size, 839
 Oxide dispersion strengthened alloys, 112–113,
 179, 482
 corrosion resistance, 107

elevated temperature strength, 107
 extrusion, 107
 high oxidation resistance, 107
 homogenization of the powders, 107
 hot corrosion resistance, 107
 inhibit the recovery process, 107
 inhibit the recrystallization, 107
 prealloyed powders, 107
 stable oxides, 107
 tumbling ball mills, 107
 uniform dispersion, 107

P

Packaging

proportioning and packaging of powders, 451
 rotary table, 451–452
 vibrating densification, 452–453
 volume batching, 451
 weight batching, 451

Palladium powder

autoclave precipitation, 841–842
 average particle size, 833, 840*t*
 beginning of oxidation, 840*t*
 carbonyl process, 840–841
 chemical reduction, 839
 chemical precipitation from pulp, 844*f*
 chemical precipitation from solution, 832,
 843*f*
 palladium–copper, 836–837*t*
 palladium–nickel, 836–837*t*
 palladium–platinum, 836–837*t*
 palladium–silver, 836–837*t*
 particle size, 831–833, 837
 production of powders of alloys based on
 noble metals, 831
 properties of palladium powders, 840–841,
 840*t*
 silver–palladium composition, 842
 specific surface, 833, 839–841
 synthesis of palladium nanoparticles by
 methods of zone electrochemistry, 845
 tap density, 840*t*
 water solution electrolysis, 845

Particle image analysis

chemistry analysis, 6–7
 morphological analysis, 6–7
 particle shape, 6–8
 size measurements, 7

Particle shape

acicular, 7
 angular, 7
 crystalline, 7
 dendritic, 7
 fibrous, 7
 film boiling conditions, 137–139
 flaky, 7
 granular, 8
 irregular, 8
 lamellar, 8
 shape factors, 8
 spherical, 8
 spheroidization time, 137–139, 141

Particle size distribution analysis

classification in centrifugal field, 16–18

classification in gravitational field, 13–16
 classification in inertia force field, 18
 counting and sizing of particles by indirect
 measures, 18–21
 metallographic microscopy, 10
 optical microscopy, 8–9
 regularities of granulometric composition,
 22–26
 scanning electron microscopy, 10
 sieve analysis, 11–13
 transition electron microscopy, 10–11

Passivation methods

inhibition of cathode processes, 444
 reduction of the degree of thermodynamic
 instability, 444–445
 rising of ohmic resistance, 444–445

Passivation techniques

hydrophobization, 445–446
 inhibition of cathode processes, 444
 microencapsulation, 446
 nitriding and oxide formation, 446
 passivation methods, 444–446
 thermodynamic instability, 442, 444–445

Permanent magnets

binder agent, 796
 compression molded, 796
 coercive force, 794
 direct-current motors, 797
 electronic watches, 797
 electronics segment, 797–798
 gas atomized powders, 795
 generators, 797
 hydrometallurgical method, 797
 hysteresis loop, 794
 injected molded magnets, 796
 mechanical alloying, 796–797
 medical devices, 797
 melt spinning technique, 796
 nanocrystalline multicomponent systems,
 796–797
 Nd–Dy–Fe–Co–Nb–Al–Cu–B sintered
 magnets, 795
 NdFeB permanent magnets, 794
 Nd_{13.6}Fe_{73.7}Co_{6.6}Ga_{0.6}B_{5.5} ribbon powder,
 795
 (PrNd)FeB system, 796–797
 ribbon powder magnets, 796
 rare earth alloys magnets, 794
 residual induction, 794
 single-phase demagnetization curves,
 796–797
 SmCo₅ single phase magnets, 794
 synchronous motors, 797
 traveling wave tubes, 797
 Permeability of metallic foams
 fluid velocity, 345
 gas diffuses, 345
 perforation, 345
 porous media, 345
 pressure drop, 345
 surface modification, 345
 wettability, 345
 Permeametry
 gas permeability, 41

Permeametry (*Continued*)

- Kozeny–Carman equation, 41
- pressure drop, 41
- specific surface area, 41
- Tovarov's apparatus, 41
- velocity of fluid flow, 41

Permissible exposure limit (PEL), 209, 612–613, 773, 776, 810, 881

Physical and chemical principles of electrolytic crystallization of dendrite deposits

- cathode overvoltage, 236
- crystal-spherulite, 238
- diffusion limitations, 237
- dendrite deposit growing, 238–239, 241
- dendrite growth, 236–238
- electric precipitation, 236
- electrochemical reaction, 237
- Faraday constant, 236
- galvanostatic electrolysis, 237
- metal deposition, 236
- ohmic control, 240
- Pomoshov depletion factor, 237
- potentiostatic conditions, 237–238
- Runge–Kutt method, 239
- smooth spheroidal spherulite-globules, 236
- spherical diffusion rate, 238
- tip shape, 238
- transfer control, 240

Physical and chemical properties (thorium, uranium)

- face centered cubic lattice, 819
- orthorhombic system, 819
- thorium oxide, 819
- thorium hydride, 819
- thorium nitrides, 819
- uranium hexafluoride, 819
- uranium hydride, 819
- uranium nitrides, 819
- uranium–oxygen system, 819
- uranium tetrafluoride, 819

Physical vapor deposition (PVD)

- arc-vapor deposition, 337
- evaporation–condensation process, 195
- evaporation means, 195
- metal spray deposition, 337
- powder formation, during vapor condensation, 189–192
- properties of powders, 196
- PVD process installations, 195
- reactive sputtering, 337
- theoretical basis, 194
- thermal evaporation, 337

Pycnometry

- Archimedes' law, 42–43
- bulk volume, 42
- density of PM materials, 42
- displacement principle, 42–43
- gas pycnometry, 42–43
- helium-filled sample system, 43
- liquid pycnometry, 42–43
- pycnometer, 43
- porosity, 42
- powder density, 43
- pressure/volume relationship, 43

- specific volume, 42
- submerged powder, 43

Plasma atomization process

- argon atmosphere, 175
- cooling rate, 175
- plasma torch, 175
- spherical titanium powder, 175
- wire feedstock, 175

Plasma-rotating electrode process (PREP)

- centrifugal atomization process, 554–555
- consumable metal bar, 554–555
- helium plasma, 554–555
- rotating electrode process (REP), 554–555
- spherical powder particles, 554–555

Plasma transferred arc hardfacing process, 676, 676f

Platinum alloy powders, 845

Platinum powders

- apparent density, 833, 840–841
- autoclave precipitation, 841–842
- black powder, 844–846
- chemical composition, 838t
- chemical precipitation, 831–832
- particle size, 831–832
- platinization, 844
- platinum black powder, 844–846
- platinum carbonyl compounds, 840
- platinum–cobalt, 836–837t
- platinum electrode, 844
- platinum niello production, 839
- platinum oxide, 839
- water solution electrolysis, 836–837t

Poisson's ratio, 68, 276–278

Porosimetry

- bubble test of pore size, 46
- capillary rise phenomenon, 43–44
- contact angle, 43–44, 44f
- gas porosimetry, 43
- mercury porosimetry, 43–44

Porous aluminum

- aluminum powder slurry, 478
- boiling cooling system, 478
- boiling heat transfer, 478
- boiling heat transfer coefficient, 478
- ebullient cooling system, 478
- fin heat sink, 479
- heat conductivity, 478
- heat removal from the electronic equipment, 478
- heat sink, 478
- heat sink cooling materials, 478
- polyvinyl alcohol water solution, 478
- powder injection molding, 479
- technology of foil processing, 474
- vacuum heat-treatment furnace, 478
- ultrasonic treatment, 478

Porous materials

- battery electrodes, 323, 326
- bearings, 323–324
- biomedical implants, 328
- diesel soot filters, 329–330t
- filters, 323–324, 326
- flexible porous sheet material, 327

fuel cells, 328

volumetric-flow-restricting devices, 328

Porous PM materials. Application areas

- boundary layer control, 323, 328
- filtration/separation technology, 326
- flow control devices, 323, 328
- gas–liquid contacting, 328
- reservoirs and capillary attraction, 329–330t
- surface area devices, 329–330t

Porous powders.. *See also* Porous powder and metallic foams

- compaction methods, 325–326
- material selection, 324
- mechanical properties, 326
- porous aluminum, 334f
- powder preparation, 324–325
- sintering, 326

Porous powders and metallic foams

- cellular PM materials, 323
- compaction methods, 325–326
- metallic foams, 328–346
- material selection, 324
- metal sponge, 323
- porous aluminum, 334f
- porous powders, 323–328
- powder preparation, 324–325

Powder bed fusion (PBF)

- formation of the powder bed, 376
- laser beam heat source (L), 375–376
- printing process, 375–376
- packing density, 376
- part's cross-section, 375–376
- powder bed, 375–376
- powder packing, 376

Powder characterization and testing

- bulk properties of powders, 47–57
- particle image analysis, 6–8
- particle shape, 7–8
- particle size distribution analysis, 8–26
- sampling of powders, 4–6
- size measurements, 7
- surface area and porosity of powders, 38–46
- techniques of chemical analysis for powders, 26–38

Powder cleanliness

- atomization nozzle design, 162
- atomizing gas, 162
- carbon, oxygen, nitrogen, and hydrogen impurities, 162
- ceramic-free pouring nozzle, 162
- crucible- and ceramic-free, 162
- electrode induction melting gas atomization process, 162
- EIGA process, 162
- electroslag remelting, 162
- impurity control, 161
- inclusion capture, 162
- inductively melted without crucible, 162
- inert gas jet, 162
- initial charge impurities, 162
- interstitial impurity, 162
- non-metallic inclusions, 161
- melting atmosphere, 162
- oxygen level, 162

- prealloyed rods, 162
- primary sources of intermediate impurities, 162
- refractory ceramics, 162
- vapor pressure, 162
- Powder characteristics (water atomized powders)
 - Bramley's formula, 138
 - bubble boiling conditions, 137–138
 - cellular structure, 142
 - dendrite parameter, 139
 - effect of pouring temperature, 135, 136*f*
 - film boiling conditions, 137–139
 - film-bubble heat emission conditions, 138
 - first critical heat current density, 137–138
 - heat transfer coefficient, 135, 137–138, 139*f*
 - heat transfer process, 137
 - irregular shape, 134, 138–141
 - liquid drop cooling process, 137–138
 - liquidus temperature, 137, 139
 - log normal size distribution, 135
 - melt drop cooling time, 137
 - melt drop size, 139–141
 - melt strand, 137
 - non-dendrite grain, 138
 - non-dendritic structure, 142
 - oxide film, 141–142
 - particle shape, 136–141, 137*f*, 139–140*f*
 - particle size distribution, 135–142
 - particle structure, 138
 - pouring melt temperature, 138–141, 140*f*
 - second critical heat current density, 137–138
 - spherical shape, 137
 - spheroidization time, 137–139, 141
 - standard deviations, 135
 - steam film, 137–138
 - unevenness surface, 238
 - water boiling, 137
- Powder consolidation and wrought products (beryllium and beryllium alloy powders)
 - cold isostatic pressing and sintering, 806
 - hot isostatic pressing (HIP), 804–806, 805*t*
 - vacuum hot pressing (VHP), 804, 805*t*
 - wrought product forms, 806–807, 807*t*
- Powder contamination
 - chemical purity, 110
 - flushing by argon, 110
 - grinding medium, 109–110
 - magnitude contamination, 109–110
 - milling atmosphere, 110
 - milling equipment, 110
 - minimizing powder contamination, 110
 - nitrogen, 110, 111*t*
 - oxygen, 110, 111*t*
 - proper cleaning, 110
 - reactive metals, 110
 - sealing quality, 110
- Powder preparation
 - blending, 325
 - centrifugal separation, 324
 - cleanliness, 325
 - narrow size distributions, 324
 - particle size distributions, 324
 - secondary processing, 324
 - separation, 324
 - ultrasonic sieve screening, 324
 - vibratory sieve screening, 324
- Powder production by PVD
 - bronze powder, 196*t*
 - copper powder, 195, 196*t*
 - lead powder, 195, 196*t*
 - zinc powder, 195–196, 196*t*
- Powder production using the method of zone electrochemistry
 - current impulse, 254
 - electrochemical impulse, 254
 - electrolysis duration, 254
 - ultrasonic (zone) impulse, 254
- Powder properties and applications (carbonyl nickel powders)
 - acicular powder particles, 638
 - apparent density classification, 641, 642*t*
 - catalysts, 642–643, 643*t*
 - chemical industry, 641
 - coatings, 642–644
 - conductive resins and plastics, 642
 - electronic alloys, 642
 - ferrites, 642
 - filamentary chain-type nickel, 324
 - fuel-cell electrodes, 642
 - getter, 642
 - hard alloys, 642
 - high density semi-smooth particles, 638
 - high surface area powders, 638
 - Inco types of carbonyl nickel powders, 638–639, 639*t*, 642, 643*t*
 - lamination structure, 639–640
 - magnets, 642
 - Norilsk Nickel types of carbonyl nickel powders, 638–640, 639*t*, 642, 643*t*
 - pigments, 642
 - rechargeable batteries, 642
 - shaped like an onion, 639–640
 - spherical granules, 639–640
 - welding products, 642
- Powder sample preparation (for SEM and TEM)
 - automatic image analyzer, 10
 - carbon film, 10
 - carbon substrate grid, 10
 - dispersing agent, 10
 - electron microscope grid, 10
 - ethylene glycol sublimates, 10
 - fused metal, 11
 - particle thicknesses, 11
 - precipitation of carbon vapor, 10
 - shadowing particle dispersions, 11
 - smooth substrate, 10
 - substrate, 10
 - viewing screen, 10
 - viscous liquid, 10
- Powders for additive manufacturing
 - angle of repose, 378
 - avalanche angle, 378, 380*f*, 385
 - avalanche surface fractal, 378
 - composition, 385–386
 - computed tomography (CT), 377
 - feedstock material, 373, 375–377
 - flowability, 377–378, 379*t*, 382, 385
 - gas atomization (GA), 377, 381–385
 - gas metal arc welding processes, 376–377
 - microhardness testing, 392
 - multiple reuse cycles, 381
 - plasma rotating electrode process (PREP), 377, 383, 384*f*
 - porosity, 377*t*, 379*t*, 383–385, 387, 390, 393, 393*f*
 - powder characterization and testing, 377–381, 379*t*, 380–381*f*
 - powder feeding rate, 376–377
 - powder properties, 381–383, 381*t*, 382–384*f*
 - revolution powder analyzer, 378, 380*f*, 385–386
 - rheological measurements, 395
 - ring shear cell tester, 378, 380*f*
 - rolled sheet, 375–377
 - rotary atomization, 383
 - shape, 377–381, 379*t*, 381*f*
 - size distribution, 377–378, 379*t*, 380*f*
 - surface morphology, 377–381, 381*f*
 - Vickers microindentation hardness, 392
- Powders for composites
 - composite manufacturing methods, 363
 - manufacture of composite powders, 351–352
 - manufacture of composites, 363–368
- Powder spheroidization by thermal plasma processes
 - DC thermal plasma treatment, 448
 - densification of particles, 446–447
 - direct current (DC) arc plasma torches, 446–447
 - inductively coupled plasma (ICP) technology, 446–447
 - laser cladding process, 448
 - non-transferred arc DC torches, 447–448, 448*f*
 - plasma gas, 447
 - radio frequency (RF), 447
 - recycling of nickel based powders, 448
 - RF induction plasma systems, 447–448, 447*f*
 - spheroidization of particles, 446–447
 - spheroidization of titanium powders, 448, 448*t*
 - Tekna inductively coupled plasma torch, 448
 - Tekna Systems Incorporated, 447–448
 - thermal plasmas, 446–448
- Powders with quasicrystalline structure
 - discovery and structure of quasicrystalline materials, 313–314, 314*f*
 - manufacturing technique of quasicrystalline powders, 314–319
 - properties and applications of quasicrystalline materials, 313–314, 315*t*
- Precipitation from gaseous phase of tungsten
 - hexafluoride and tungsten hexachloride decomposition of tungsten hexachloride, 691
 - dissociation of tungsten hexafluoride in hydrogen, 691
 - gaseous substances, 691
 - halide evaporator, 692
 - high temperature decomposition, 691
 - reactor of fluidized bed, 692
 - spherical particle shape, 692
 - tungsten hexafluoride, 691–692, 692*f*

Precipitation from gaseous phase of tungsten hexafluoride and tungsten hexachloride (*Continued*)

tungsten oxyfluoride, 692
tungsten reduction, 692

Preparation techniques of slides

Canada balsam, 9
cover slip, 8
glass slide, 8
permanent slide, 8–9
shearing action, 8
staircase effect, 374
thin films, 9

Press-sinter method, 702, 772–773

Press-sinter-re-press (PSR) process, 702

Principles of additive manufacturing
computer-aided design (CAD), 374
fusing, 374

layer processing time, 374
rapid prototyping, 374
recoating time, 374
selective laser melting (SLM), 375
sintering, 374, 374f
thickness of layer, 374
work platform, 374

Process control agent (PCA)

dispersion strengthening, 92–93
embrittling the powders, 92–93
interstitial compounds, 92–93
organic compounds, 92
surfactant, 92–93

Processing of powders and processing equipment

dehydration, 403–413, 405t
interstage transport, 452–454
mixing, 435–441
packaging, 451–452
passivation techniques, 442–446
powder classification by size, 424–435
proportioning, 449–451
thermal drying, 413–424

Processing of recycled aluminum to granules

aluminum scrap, 477
chips, 477
drink cans, 477
ferrous metallurgy, 477
impurities, 477
mechanical impurities, 477
processing of aluminum scrap, 477
recycled aluminum, 477
remelting, 477
remelting–casting technologies, 477
steel deoxidation, 477

Production methods

chemical precipitation from solutions, 282–285
condensation technique, 278–282
high-energy disintegration, 289–292
plasma chemical synthesis, 286–288
spray conversion method, 285

Production of cadmium powders

cementation (contact displacement) method, 625
centrifugal reactor-separators, 625

copper–cadmium cake, 625

electrolysis of aqueous solution, 626t
electrolysis of non-aqueous solution, 626t
electrolytic deposition, 625
reduction from the solid phase, 626t
waste electrolyte, 625

Production of chlorides (RE chlorides)

ammonium chloride, 786
anhydrous RE chlorides, 786
carbon tetrachloride, 786
dehydration of lanthanide crystalhydrate, 785
hydrogen chloride, 786
oxide chlorination, 785
oxychlorides, 786

Production of cobalt and cobalt alloy powders by electrolysis

alkaline cobalt carbonate, 681
ammonium sulfates, 670–673, 679
anode dissolution of cobalt, 678
cobalt current efficiency, 678, 680t
cobalt formate, 681
current density, 678, 680t
dendritic microstructure, 680
electrochemical precipitation, 679
electrolytic cobalt powder, 679–680
electrolyzer, 678
metal dissolution, 678
properties of the electrolytic cobalt powder, 678–679
soluble cobalt anodes, 678, 681
sulfate electrolyte, 678, 681
suspended solid, 678
titanium disc cathodes, 678

Production of flakes, pigments, paints and pastes

aluminum flake pigments, 470
aluminum flake production, 472
aluminum flakes, 468, 470, 471t, 472–473
aluminum pastes, 472–473, 472f, 473t
aluminum pigments, 470
cold welding, 470
fatty additive, 470
lamellar particle shape, 470
leafing aluminum pastes, 472, 473t
leafing paste, 472
leak-tight mill working, 470
liquid hydrocarbons, 472
lumpy flakes, 470, 471t
melt stream, 466
metallic shine, 472, 473t
non-leafing aluminum pastes, 472, 473t
production of pastes, 472
porous aluminum, 478, 479f
roof coatings, 472
slurry, 472
stearin acid, 472
varnish film, 472
volatile liquids, 472

Production of fluorides (RE fluorides)

anhydrous fluoride, 786
dehydration of hydrated salts, 786
fluoridation, 786
hydrofluoric acid, 786
hydrogen fluoride, 786

muriatic solution, 786

nitrate solution, 786

precipitates, 786

Production of granules

aluminum granulation, 465–468, 468f
aluminum granules, 466, 468, 469t
automotive coatings, 472
centrifugal atomization, 466, 467t, 468f
cold welding, 470
cooling in gas atmosphere, 466, 468f
cooling in liquid, 466, 468f
cooling on cold surface, 466, 468f
drop casting, 466
drop-shaped granules, 466
dry grinding, 472
fatty additive, 470, 472
free casting into water, 466, 468f
gallium cementation, 466
gas forming agent, 473
granulated alloys, 466, 468
granulated aluminum, 465–466
granulated aluminum alloys, 466
granule size, 466
impulse atomization, 468
melt centrifuging, 466–468
melt stream, 466
monodisperse droplets, 468
needle-shaped granules, 466
nozzle plate, 468
orifice size, 468
orifice shape, 468
polychromatic effect, 472
protection of particle surface, 466
spherical granules, 466
spinning cup, 466
Volgograd Aluminum plant, 466
wet grinding, 472
water-cooled metal disk, 466
water-filled explosives, 473
water paste, 473

Production of leafed beryllium by

electrorefining from melts
cathode deposits, 801
gradually extending anode, 801
insoluble anodes, 801
preliminary beryllium disks, 801
refined beryllium, 801

Production of magnesium and magnesium alloy powders

production of magnesium granules, 538–539, 538f
production of magnesium powders, 533–541, 535f, 536–537t

Production of magnesium granules, 538–539, 538f

Production of molybdenum powders

ammonium molybdate, 723–724
calcinations in oxygen, 725
carbonyl molybdenum, 725, 725t
carbonyl process for molybdenum powder, 725
iron chloride, 724
molybdenum chlorides, 724–725
molybdenum disulfide, 723

- molybdenum pentachloride, 724–725
- molybdenum trioxide, 724
- reduction by hydrogen, 725
- rotary furnaces, 723
- solvent extraction processes, 723
- tube push furnace, 723
- Production of multicomponent alloy powders
 - chemical compounds, 254
 - combined anodes, 253
 - constant solution composition, 253
 - dendrite tips, 252–253
 - diffusion control, 252–253
 - growing depletion factor, 254
 - kinetics of electrochemical reduction, 254
 - metal ions, 252–254
 - metal salt, 253
 - soluble anodes, 253
 - spherical diffusion, 253
- Production of nickel alloy powders by
 - mechanical alloying
 - contamination of powders, 658
 - close-coupled gas atomization, 659–660
 - dispersion-strengthened superalloys, 657
 - gas atomization reaction synthesis (GARS), 658, 660f
 - gas turbine engines, 658
 - grinding medium, 658
 - high-energy ball milling technique, 657
 - high-temperature particle strengthening, 658
 - highly alloyed matrix, 657
 - hot isostatic pressing (HIP), 657–658, 660
 - mechanism of alloying, 657
 - milling atmosphere, 658
 - minimizing contamination, 658
 - nanometric oxide dispersoids, 658
 - Ni-based superalloys, 661
 - ODS layer, 661
 - Oxide dispersion strengthening (ODS), 657–658
 - plasma activated sintering, 657–658
 - powder rolling, 657–658
 - precursor Ni–Cr–Y–Ti powder, 659–660
 - precursor powders, 658
 - superalloy MA 754, 658
 - superalloy MA 760, 658
 - superalloy MA 6000, 658
 - turbine blades and vanes, 658
- Production of nickel powder by electrolysis
 - anode current, 663
 - aqueous ammonia, 663–664
 - chloride-ions, 663
 - coral-like dendritic structure, 663–664
 - electrolyte composition, 663
 - electrolytic nickel powder, 663–664, 664t, 664f
 - fir branches, 663–664
 - hollow disc cathodes, 663
 - hydrochloric acid, 663
 - powder precipitate, 663
 - soluble anodes, 663
 - sulfate electrolyte, 663
- Production of nickel powder by reduction
 - processes
 - reduction by organic reagents, 662–663
 - solid phase reduction, 661
- Production of niobium powders
 - carbothermic reduction, 736
 - electrolysis of melt, 737, 737f, 738t
 - hydride-dehydride process, 738
 - metallothermic reduction, 736, 736f
 - reduction by sodium, 737
- Production of niobium powders by carbothermic
 - reduction
 - graphite cartridge, 736–737
 - graphite-tube, 736–737
 - hydrogen atmosphere, 736–737
 - lower oxide formation, 736–737
 - niobium carbide, 736
 - niobium carbide particles, 736–737
 - niobium oxide vapor, 736–737
 - push type furnaces, 736–737
 - reduction in two-steps, 736
- Production of niobium powders by electrolysis
 - of melt
 - alkali metal chlorides, 737
 - cathode current density, 737
 - cathode product, 737–738
 - electrolysis cell, 737–738
 - electrolysis of bromide, 737
 - electrolyte temperature, 737
 - graphite rod, 737
 - nickel crucible (cathode), 737
 - niobium pentoxide, 737
 - niobium sponge, 737
- Production of niobium powders by
 - metallothermic reduction
 - aluminothermic reduction, 736
 - chlorination process, 736
 - columbite ore, 736
 - cyclone separator assembly, 736
 - electron beam purification, 736
 - exothermic reaction, 736
 - magnesiothermic reduction process, 736
 - magnesium vapor reduction process, 736, 736f
 - moderate boiling temperature, 736
 - niobium pentachlorate, 736
 - oxygen content, 736
 - pyrochlore concentrates, 736
 - tantalite ore, 736
 - vapor pressure, 736
- Production of platinum-group powders
 - alloys based on noble metals, 842–844, 843–844f
 - autoclave precipitation, 841–842
 - carbonyl process, 840–841
 - chemical reduction, 839
 - electrolysis, 835
 - electrolysis from double-layer cell, 836–837t
 - water solution electrolysis, 836–837t
- Production of powder products from waste
 - aluminum foil
 - aerated concrete, 474
 - aluminum flake powders, 474–476, 475–476f
 - aluminum foil scraps, 474–476
 - ball milling, 474–476
 - crushing in cutting units, 474
 - dry crushing, 474
 - fingerprint detection, 474, 476
 - foil thickness, 474–476, 475–476f
 - foil waste products, 474
 - grinding in mills, 474
 - grit, 474
 - inks, 474, 476
 - inorganic solvent, 474, 476
 - laminated flake powder, 475
 - milling time, 475
 - mineral spirits, 474, 476
 - oleic acid, 476, 476f
 - paints, 474, 476
 - paste manufacturing industry, 474, 476
 - recycling, 474
 - recycling of aluminum scrap, 474–477
 - saving material, 474
 - technology of foil processing, 474
 - wet crushing, 474
- Production of powders by electrolysis from
 - melts
 - chloride and fluoride salts of metals, 260
 - dendrite crystallization, 262
 - dendrite length, 265–266
 - dendrite precipitate, 262
 - electronegative metal powders, 258
 - flat growth front, 258
 - metal chlorides, 260
 - soluble anode, 260, 262
- Production of rare earth metal alloy powders
 - electrochemical methods, 786–787, 787f
 - initial compounds for metal production, 785–786
 - metallothermic methods, 787
 - methods of RE elements separation, 782–785, 783–784f
 - refinement of RE by distillation, 788
 - sources of raw material, 781–782, 800
- Production of silver powders
 - atomization, 833
 - chemical processes, 832–833
 - chemical reduction with electrochemical
 - reduction of the reducer, 835
 - electrolysis from double-layer cell, 836–837t
 - evaporation of silver, 832
 - fibrous dendritic silver residue from molten
 - electrolytes, 835, 837f
 - mechanical comminution, 833–834
 - silver anode, 834–835
 - spray pyrolysis technique, 833
 - water solution electrolysis, 836–837t
- Production of thorium compacts
 - calcium thermic thorium powder, 821
 - electric-arc furnace, 821
 - electrolytic thorium powder, 821
 - pressed billets, 821
 - vacuum induction furnace, 821
- Production of titanium and titanium alloy
 - powders
 - amalgam metallurgy technique, 562–563, 563f
 - chemical reduction, 550–554
 - chemical synthesis of nano size titanium powders, 565
 - CSIR process, 564–565

- Production of titanium and titanium alloy
 powders (*Continued*)
 electrolysis of titanium compounds, 558–562
 gas atomization, 555–558, 555–558f
 mechanical alloying, 565
 method of disproportionation of lower
 titanium halogenides, 564
 plasma-rotating electrode process (PREP),
 554–555, 555f
 TIRO method, 563–564, 564t, 564f
 titanium, 549
 titanium alloy powders, 549
 titanium powder-based materials selection,
 567–568
- Production of tungsten carbide powders
 calcination–reduction–carburization (CRC)
 process, 707–708
 carbon black, 707–709
 carburization, 708–709
 chemical vapor reaction process, 709
 direct carburizing process, 709
 gas phase reaction, 709
 Menstruum process, 708–709
 Menstruum tungsten carbide powders,
 708–709
 production of fine grained powder, 709
 pure tungsten powder, 707–708
 single tube pusher type furnaces, 707–708
 spray conversion process, 709
 tungsten carbide crystallites, 709
 tungsten ore concentrates, 708–709
 vertical reactor, 709
- Production of tungsten powder by a plasma
 process
 boiling point, 692
 coagulation, 692
 condensation, 692
 crystallization, 692
 direct current arc, 693
 polymorphous transformations, 692
 radio-frequency plasma, 693
 two stage scheme, 692–693
 vaporous state, 692
- Production of zinc and cadmium alloys powders
 atomization of melt, 625
 cyanide solutions, 625
 dendrite shape, 625
 electrochemical method, 625
 reduction from the solid phase, 626t
 zinc–copper alloy powders, 625
- Production of zinc, cadmium, and their alloy
 powders
 production of cadmium and zinc alloy
 powders, 625–626, 627–628t
 production of cadmium powders, 625, 626t
 production of zinc powders, 615–625
 safety measures in cadmium and zinc powders
 production and handling, 626–628
- Production of zinc, cadmium, and their alloy
 powders, applications
 anticorrosive zinc-rich coatings for roll and
 sheet steel metal ware, 630
 cathodic protection, 628
 manufacture of reducing agents, 628
 mechanical plating, 630
 pigments in anticorrosive coatings, 628–629
 powder coating, 628
 powders with flaky particles, 629
 protective coatings, 628–629, 629t
 purification of zinc solutions, 628
 recycling of tungsten carbide powders, 631
 sherardizing, 630, 630f
 zinc-rich compounds, 628
 zinc-rich paints, 628
 zinc-rich primers, 628–629
- Production of zinc powders
 cryogenic methods, 625
 electrochemical methods, 621–624, 623t
 evaporation–condensation method, 615–620,
 616f, 618–619t, 619–620f
 inert gas condensation, 619–620, 620–621f
 mechanical grinding, 624
 melt atomization, 620, 621–622f
 rectification of the melt, 616f
 reduction from the solid phase, 623t
- Properties and applications of quasicrystalline
 materials
 CRISTOME quasicrystalline powders, 317,
 318t
 electric resistivity, 313–314
 electronic structure of QC, 313–314
 Fermi surface, 313–314
 hardness, 314, 315t
 icosahedral QC phases, 314–315, 316t, 317
 mechanical alloying, 314, 316t
 mechanical properties, 314, 315t
 nanoquasicrystalline strengthening, 319, 320t
 Peierls stress, 314
 phason defects, 314
 phonon and phason components, 314
 polyamide composite reinforced by QC
 particles, 317
 polymer-matrix composites reinforced with
 QC particles, 317
 QC Al–Cu–Fe coatings, 319
 QC interatomic bonds, 313–314
 quasicrystals (QC), 313–314
 rapid solidification, 316t
 selective laser sintering (SLS), 317
 semiconductors, 313–314
 specific electric resistance, 313–314
 surface hardened composite layers, 319
 thermal conductivity, 313–314, 315t, 318t,
 319
 thermal diffusivity, 318t
 thermal dilatation coefficient, 318t
 ultrasonic impact processing, 319
 yield strength, 314
 Young's modulus, 314
- Properties of tungsten powders
 alpha emitters, 699
 ammonium paratungstate, 695, 699
 apparent density, 695, 699
 carbon content, 695, 697–699, 698t
 carbonyl tungsten powders, 698t, 699
 chemical properties, 695
 chemical vapor deposition (CVD), 699
 decomposition, 695, 697–699, 698t
 demonstration fusion reactor (DEMO), 699
 Fisher subsieve sizer (FSSS), 699
 flowability, 699
 gravity sedimentation scattering, 695
 green density, 695
 green strength, 695, 702
 hexagonal close-packed lattice, 699
 high density, 695, 701–702
 high intensity discharge (HID) lamps, 699
 hydrofluoric medium, 695
 light scattering techniques, 695
 morphology of tungsten powders, 695, 699,
 704f
 particle size distributions, 695, 699, 701, 701t
 physical properties, 695
 physical vapor deposition (PVD), 699
 plasma facing material, 699
 properties of carbonyl powders, 697
 pure tungsten powders, 699
 semiconductor manufacture, 699
 sintering temperature, 698, 702–703
 spherical shape, 698–699
 surface of tungsten particles, 697–698
 thermal conductivity, 699
 thermal decomposition, 698
 trace elements, 695, 699–701
 tungsten hexafluoride, 695
 ultrahigh purity powders, 699
 vacuum plasma spray, 699
- Proportioning
 annular slot, 450
 Auger dosing system, 451
 automatic dosing machines, 451
 feeder-activator design, 450
 feed hopper, 449
 feed rate, 451
 fluidized state, 450
 funnel flow mode, 450
 milled product dosing, 451
 powder feeders, 449
 semi-automatic powder filling machines, 451
 wheel feeder, 451
- Pulsated orifice ejection method
 driving device, 174–175
 mono-sized spherical particles, 174–175
 narrow particle size distribution, 174–175
 rectangular waves, 174–175
- Pure tungsten powders, 699, 704f, 707–708
- PVD process installations
 physical sputtering, 195
 plate-type rectifying columns, 195
 powder production by PDV, 195–196
 reactant gas medium, 195
 “Tuman” unit, 195–196, 196f
 zinc powder manufacturing, 195, 195f
- Pyrophorus, 673, 824–825
- ## Q
- Quantum confinement effects
 Bohr radius, 305
 conduction band, 305
 electron energy band, 305
 valence band, 305
 wavelength of the electron, 305

- Quasicrystalline films
 annealing, 304–305
 flash evaporation method, 304
 heat treatment, 304
 low thermal conductivity, 305
 magnetron sputtering, 304
 multilayer films, 304
 nanosized quasicrystalline films, 304
 thermal barrier coating, 305
- Quasicrystalline materials
 applications of quasicrystalline materials, 313–314, 315*t*
 crystallographic structure, 313
 decagonal QC structure, 313
 discovery of quasicrystals, 313–314
 five-fold symmetry, 313, 314*f*, 319, 319*f*
 icosahedron geometric figure, 313
 low electric and thermal conductivity, 313–314
 manufacturing technique of quasicrystalline powders, 314–319
 metastable, 313
 rapid crystallization, 313
 rapid solidification, 313, 316*t*
 rotational symmetries, 313
 semiconductors, 313–314
 Shahtman, 313
 specific electric resistance, 313–314
 structure of the quasicrystals (QC), 313
- Quenching
 electrical contact materials, 726
 hardfacing, 714–717
 refractory metal powders, 702
- R**
- Radioactive metals: thorium and uranium
 applications, 822–824
 physical and chemical properties, 819, 820*t*
 production of thorium compacts, 821
 thorium powder production, 820–821
- Range of applications (RE metals, alloys, compounds)
 agriculture, 789
 cemented tungsten carbides, 798
 chemical industry, 789
 glass and ceramic production, 789
 laser technique, 789
 lighting technique, 789
 manufacture of electrodes, 792–794
 medicine, 789
 nuclear power, 789
 permanent magnets, 794–798, 795–797*f*, 795–796*t*
 refractory and elevated temperature alloys, 789–792
 television technique, 789
 traditional metallurgy, 789
- Rapid prototyping
 built platform, 374
 infrared (IR) laser, 374
 polymer resin, 374
 selective laser sintering (SLS), 374
 stereolithography (SLA), 374
- thermoplastic materials, 374
 UV light, 374
- Rapid solidification process
 cooling rate, 488–490, 489*t*, 491*f*, 492
 crystallization process, 490
 dendrite parameter, 488–489
 equilibrium diagram, 489*t*, 491*t*, 492, 492*f*
 eutectic systems, 492
 extension of solubility limits, 487
 hyperbolic equation, 488
 metastable equilibrium diagram, 492, 492*f*
 metastable process, 487
 non-dendritic grains, 488–490, 491*f*
 nucleation, 488–491
 peritectic systems, 492
 precrystallization undercooling, 490–491
 rapid crystallization, 491
 solidification, 487–492, 489*t*
 supersaturated solid solution, 492
- Rare earth (RE) elements
 cerium, 778–779, 780*t*, 781, 784, 786*t*, 788
 cerium subgroup, 779, 781, 784, 786–787
 ferromagnetic properties, 781
 ‘heavy’ (HREEs) elements, 778–779, 784–785
 ‘lanthanide compression’, 779
 lanthanide elements, 778
 lanthanide hydroxides, 781
 lanthanum, 778, 780*t*, 781–782, 784, 784*f*, 786, 786*t*
 ‘light’ (LREEs) elements, 778–779, 784–785
 lutetium, 778–779, 780*t*, 781–782, 783–784*f*, 784
 paramagnetic, 781
 yttrium, 778–779, 780*t*, 782
 yttrium subgroup, 779, 781–782, 784, 787–788
- Rare metal powders
 bastnaesite, 781
 chlorides, 759, 781, 785–787, 798, 800, 820–821
 composite compounds, 779, 781
 euxenite, 781–782
 fluorides, 768, 781, 786–787, 800
 initial compounds for metals production, 785–786
 loparite, 781
 methods of RE elements separation, 782–785
 monazite, 781
 niobium tantalates, 781
 nitrates, 781–782, 784, 786
 oxalates, 781
 parisite, 781
 phosphates, 781
 production of rare earth metal-alloy powders, 778–798
 sources of raw material, 781–782, 800, 811–812
 sulfates, 775–776, 781, 783, 798, 800
 titanium niobates, 781
 vanadium, 758–766, 758–760*t*, 766*t*, 773, 778, 786, 795, 813*t*
 xenotime, 781–782
- Recycling of tungsten carbide powders
 ball milling, 631
 crushing, 631
 graded powder, 631
 hardmetal scrap direct conversion, 631
 protective atmosphere, 631
 reaction in molten zinc, 631
 screening, 631
 vacuum distillation, 631
 Zn process, 631
- Reduction by organic reagents (production of nickel powders)
 alkaline nickel carbonate, 662
 catalysts, 662–663
 colloidal structure, 662
 hydrazine-hydrate, 662
 narrow particle size distribution, 662
 nickel borate solution, 662
 nickel carbonate pulp, 662
 nickel sulfate solution, 663–664
 phase transformations, 662
 polyacrilamide oligomer, 662
 polymer compositions, 663
 roasting of sulfide materials, 661
 sodium formate, 662
 thermal decomposition, 661
- Reduction from solution through film of surfactants
 absorbed surfactant layer, 249
 bottom electrolyte layer, 248–249
 electrocrystallization process, 249
 ferromagnetic particles, 249–250
 hydrogen emission, 249
 organic liquid, 249–250
 running magnetic field, 249–250
 two-layer electrolyte, 248–249
 ultrafine elongated whiskers, 249
 upper layer, 248–249
- Reduction methods of powder production
 application of chemically reduced powders and salts, 225
 autoclave precipitation of metal powders, 225–231, 226*f*
 carbochlorination process, 767–768
 chemical reduction, 221–225
 metallurgy, 221
 solid-phase reduction of metal oxides and salts, 211–218
- Reduction of thorium dioxide by calcium
 calcium chips, 820
 calcium oxide, 820–821
 concentration table, 820
 dilute hydrochloric acid, 820
 furnace processing, 820
 molybdenum sheet, 820
 separation of fine fractions, 820
 thermal decomposition, 820
 thorium dioxide, 820, 821*f*
 thorium oxalate, 820
 thorium recovery yield, 820–821
- Reduction of tungsten oxide by solid carbon
 carbon tube, 691
 high temperature zone, 691
 pusher type furnaces, 691

- Reduction of zirconium dioxide by calcium or calcium hydride
 - briquetted mixture, 768
 - calcium thermic process, 768
 - reduction process, 768
 - self-sustained process, 768
- Reduction of zirconium dioxide by magnesium using autoclave processing
 - Let-Lok apparatus, 772
 - pure metallic zirconium, 772
 - RAPET method, 772
 - reacting zirconium dioxide with magnesium, 772
 - reaction under autogenic pressure at elevated temperatures, 772
 - thermal dissociation of reactants, 772
- Reduction of zirconium tetrachloride by magnesium
 - high-temperature vacuum distillation, 768
 - Kroll process, 767–768
 - magnesium chloride, 767–768
 - pyrophoric zirconium sponge, 768
 - vacuum arc remelting, 768
 - Van Arkel–De Boer process, 768
 - zirconium tetrachloride, 767
- Refinement of RE by distillation
 - distillation in vacuum, 788
 - tantalum condenser, 788
 - tantalum crucible, 788
 - yttrium subgroup, 788
- Refractory and elevated temperature alloys
 - (alloying RE elements)
 - Al–Fe–Ce system alloys, 791
 - alloying addition RE elements, 790
 - aluminum alloys, 790
 - aqueous lanthanum nitrate solution, 789
 - gas atomized powder, 791
 - magnesium alloys, 791
 - modified water atomization technology, 791
 - ODS molybdenum–lanthana alloys, 789, 790f
 - ODS molybdenum–yttria alloys, 789
 - RE–molybdenum disilicide composites, 789–790
 - RE–MoSi₂ composites, 789–790
 - self-propagating high-temperature synthesis (SHS), 789–790
 - W–Y system, 789
 - yttria-doped material, 789
 - zirconium doped material, 789
- Refractory-based composite powders
 - ball milling, 355
 - chemical synthetic, 355
 - composite refractories, 355
 - freeze–drying technique, 355
 - high-temperature applications, 355
 - mechanochemical methods, 355
 - non-oxide refractories, 355
 - oxide co-reduction, 355
 - oxide refractories, 355
 - tungsten–copper alloy powders, 355
- Refractory metal and carbide-based composites
 - acid treated carbon nanotubes (ATCNTs), 366, 367f
 - composite contact material, 366
 - infiltrated composite contacts, 366
 - molybdenum–silver composites, 366
 - press-sinter-infiltrate method, 366
 - suspension based technique, 366
- Refractory metal foams
 - aircraft wing, 337
 - catalytic filtration devices, 337
 - fuselage structures, 337
 - nozzle flaps, 337
 - thermal insulation, 337
- Refractory metal powders
 - accident prevention when working with the tungsten powders, 707
 - cemented carbides, 717–721
 - hardfacing, 714–717
 - molybdenum, 723–734
 - niobium, 734–742
 - production of refractory metal powders, 686–714, 717–721, 723–751
 - production of tungsten and tungsten carbide powders, 686–714
 - recovery of metallic tungsten, 705–707
 - recycling, 721–722
 - rhenium, 747–751
 - tantalum, 742–744
 - tungsten, 686–707
 - tungsten carbide powders, 707–712
 - tungsten metal powders, 686–707
 - tungsten powder applications, 699–705
- Regularities of granulometric composition
 - log-normal distribution, 23
 - normal distribution, 23
 - Rosin–Rammler distribution, 23
- Regularities of milling
 - agglomeration, 70
 - agglomeration of particles, 70
 - bonding by welding, 68–69
 - cold welding, 70
 - impacting force, 68, 69f
 - impact process by colliding balls, 68–70, 69–71f
 - particle fragmentation, 70
 - particle size growth, 65
 - particle size reduction, 65
- RE-separation by ion-exchange chromatography
 - anion lanthanide complexes, 783
 - cationite resins, 783
 - elution chromatography, 783
 - elution solutions, 783
 - ethylenediaminetetraacetic acid (EDTA), 783–784, 784f
 - hydrated ion size, 783
 - ion-exchange capacity, 783
 - REE adsorption, 783
 - RE elements desorption, 783
 - RE ions, 783
 - RE magnet, 783
 - salmon milt, 783
 - separation of lanthanides, 783
 - separation of RE elements, 783
- Restriction and limitation
 - pressure limitation, 804
 - mercury penetration, 45
- Rhenium powders
 - electrical contacts, 750
 - electrical resistivity, 749–750
 - electronic tube components, 750
 - gyroscopes, 750
 - isostatic pressing, 750–751
 - near-shape technique, 750–751
 - nuclear reactors, 750
 - pusher type furnaces, 748–749
 - reduction of ammonium perrhenate, 747–748
 - resistant to hydrochloric acid, 750
 - rubber-lined drums, 748–749
 - semi-conductors, 750
 - thermionic converters, 750
 - thermocouples, 750
 - uniaxial pressing, 750
- Rhodium powder
 - autoclave precipitation, 841–842
 - chemical composition, 748–749, 749t
 - filament applications, 749–750
 - low vapor pressure, 749–750
 - properties, 749f
 - thermolysis of mixture of salts, 843
- Roll compaction
 - connected pores formation, 325–326
 - honeycomb-like structure, 325–326
 - porous nickel sheet materials, 325–326
 - titanium porous plates, 325–326
- Roller atomization
 - acicular, 175
 - conductive heat transfer, 175
 - contra-rotated rolls, 175
 - epoxy coatings, 175
 - flaky particles, 175
 - irregular, 175
 - phenolic resin coatings, 175
 - ribbon particles, 175
 - roll coatings, 175
 - spheroidal particles, 175
 - twin rollers, 175
- Rotating electrode atomization
 - anode rotational speeds, 172
 - arc plasma, 172
 - consumable rotating bar, 172
 - plasma rotating electrode process (PREP), 172
 - rapidly rotating impeller, 173
 - rotating electrode process (REP), 172
 - rotational speed, 172
 - tungsten tipped device, 172
- RSR (rapid solidification rate) process
 - atomizer rotor, 493–494
 - closed-loop helium recirculation, 493–494
 - cooling helium jets, 493–494
 - helium gas, 493–494
 - high thermal conductivity gas, 494
 - narrow size distribution powders, 494
 - nickel base superalloys, 494
 - specialty aluminum alloy, 494
- Ruthenium
 - copper–nickel sulfide ores, 776
 - minerals of the osmium–iridium group, 776
 - platinum group metals, 776
 - ruthenium concentrate, 777

- Ruthenium powder
 alkali metal hypochlorites, 776–777
 autoclave precipitation, 841–842
 catalysts in the synthesis of organic and inorganic products, 778
 chemical composition, 777–778, 777*t*
 iridium–ruthenium alloys, 778
 particle size, 778
 reduction in hydrogen current, 777
 refining process, 777
 ruthenium additions, 777–778, 777*t*, 779*f*
 ruthenium ammonium hexachloride, 777
 ruthenium dioxide, 776–777
 ruthenium niello, 776–777
 ruthenium tetroxide, 777
 thermocouples, 778
 wear-resistant parts, 778
- S**
- Safety engineering in production of powders
 clarification of recirculated water, 918–922
 dangerous and harmful manufacturing factors, 866–868
 dust and gas cleaning, 923–924
 technique of the prevention exposure hazards, 879–918
 waste products utilization, storing and transportation, 924–927
- Safety measures in cadmium and zinc powders
 production and handling
 fire and explosion safety measures, 626–628
 ignition temperature, 626–628
 inhalation zinc powder, 628
 lower explosive limit, 626–628
 toxicity of zinc powder, 628
 zinc oxide, 628
- Sampling of powders
 chute splitting, 6
 composite sample, 4
 conical pouring, 6
 free-flowing powders, 4
 keystone sampler, 4
 point samplers, 4
 quartering, 6
 rotary sample divider, 4, 4*f*
 sample preparation procedures, 5
 sampling flowing powder streams, 4
 scoop sampling, 6
 selected samples, 4
 stream sampling ladles, 4
 travers cutter, 4
 weight of powders, 6
- Scandium
 applications, 813–819
 physical properties, 810–811
 scandium production, 812
 sources of raw material for scandium production, 811–812
- Scandium applications
 additional strengthening effect, 815–816
 Al–Mg–Sc system, 817
 Al–Sc master alloys, 818
 aluminum alloys, 814–815
 concept of precipitation strengthening, 815
 control of suspension temperature, 818
 corrosion resistance, 815
 crystalline lattice, 813
 dislocation cellular structure, 815
 dislocation movement, 815
 equiaxial microstructure, 817
 Guinier–Preston zones, 815
 high cooling rate, 815
 hot degassing, 815
 intermetallic Al₃Sc, 813
 intermetallic Al₃(Sc_{1–x}Zr_x), 815–816
 intermetallic MgZn₂, 815
 melt solidification rate, 817
 nanoparticles of intermetallides, 818
 non-dendritic structure, 813, 815
 Orowan mechanism, 815
 oxide films, 818
 polygonal cell structure, 815
 refractory transition metals, 815
 ring-shaped dislocation loop, 815
 secondary dispersoids, 815, 817*f*
 structural lattice, 813
 supersaturated solid solutions, 813, 815–816
 surface microstructure, 815, 815*f*
 thermally non-strengthened weldable Al–Mg base alloys, 814
 thermally strengthened high-strength Al–Zn–Mg–Cu base alloys, 815
 thermally strengthened high-strength weldable Al–Zn–Mg base alloys, 814
 thermal treatment, 815
 water atomized powders, 815, 818
 weldability, 817
- Scandium production
 electrorefining, 812
 high-purity metallic scandium, 812, 814*f*
 inert gas atmosphere, 812
 lithium fluoride, 812
 metallic scandium, 812
 metallothermic reduction, 812
 metallothermic scandium, 813*r*
 monocrystalline ingot, 812
 scandium chloride, 812
 scandium fluoride, 812
 scandium oxides, 812
 sponge scandium, 812
 vacuum distillation, 812
 vacuum fusion, 812
 volatile impurities, 812
 zone melting, 812
- Scanning electron beam instruments, 29–30, 30–31*t*, 35
- Scanning electron microscopy (SEM)
 automatic image analyzer, 10
 backscattered detector, 27–28
 chemical analysis of micron-size area, 27–28
 crystallographic orientations, 27–28
 electron beam instruments, 28
 electrons generated by the electron beam, 28
 magnifications, 30*r*
 polydisperse granulometric composition, 10
 powder sample preparation, 29
 secondary electron detector, 27–28
- Scanning tunneling microscope
 map of heights, 275
 needle (probe), 275
 surface topography, 275
 tracking loop, 275
- Scheme of complete separation (RE separation)
 cerium subgroup elements, 784, 785*f*
 chloride-thiocyanate system, 784
 countercurrent extraction, 784
 extracting agent, 784–785
 extracting agent D2EHPA (di-(2-ethylhexyl) phosphoric acid), 785
 extraction, 784–785
 ion-exchange chromatography, 784
 light RE, 784
 middle RE, 784
 neodymium magnet leachate, 784–785
 nitrate solution, 784
 separation of cerium subgroup, 784
 three fractions, 784
 yttrium subgroup, 784
- Scintillation detectors, 36
- Scott volumeter
 density cup, 52
 gravitational powder jet, 51–52
- Screening model, 54
- Secondary ion mass spectrometer
 ion beam, 32–33
 ion column, 33
 ion gun, 33
 mass analyzer, 33
 ratio ion detection unit, 33
 vacuum sample chamber, 33
- Secondary ion mass spectroscopy (SIMS)
 impinging primary ions, 32
 impurity analysis, 32
 in-depth concentration profile, 32
 ion bombardment, 32
 mass spectrometer, 32–33
 primary beams, 32–33
 quadrupole mass spectrometer, 32
 secondary ion mass spectrometer, 33
 secondary ions, 32–33
 sputtering rates, 32
- Sedimentation method
 accumulation of the sediment, 15
 dispersion suspension, 14
 liquid for suspension, 14*r*
 method of weight samples, 16
 micromerograph, 15–16
- Segregation of particles, 54
 heterogeneity, 54
- Selective laser melting (SLM)
 basic principles, 375
 deposition, 375
 fiber laser scan, 375
 inert gas atmosphere, 375
 laser technology, 375
 layer of powder, 375
 loose powder, 375
 melting machine, 375
 molten pool, 375
 substrate platform, 375
 3D functional system, 375

- Self-propagating combustion reactions, 108–109
- Self-propagating high temperature synthesis (SHS)
 - combustion wave, 527
 - functionally graded materials, 526
 - metastable phases, 527
 - reactant mixture, 527
- Semiconductor nanostructures
 - de Broglie wavelength, 305
 - 0D, 1D, 2D, 3D, 305
- Semiconductors
 - aqueous solution method, 306
 - classification of semiconductor nanostructures, 305
 - photoluminescent semiconductor, 306
 - quantum confinement effects, 305
 - sol-gel method, 306
- Separation of REE by extraction
 - countercurrent system, 782
 - extraction methods, 782
 - extraction reaction, 782
 - heavy RE elements row, 782
 - lanthanides row, 782
 - leaching conditions, 783
 - nitrate solutions, 782
 - organophosphorus extracting agents, 782
 - RE nitrates, 782
 - TBP extraction, 782
 - tributylphosphate (TBP), 782
 - trisolvate, 782
- Shape factors
 - bulkiness factor, 8
 - elongation factor, 8
 - surface factor, 8
- Sherardizing (thermo-diffusion galvanizing)
 - anti-corrosion treatment of metal articles, 630
 - coating steel surfaces, 630
 - compact delta layer, 630
 - diffused gamma layer, 630
 - protection against corrosion and abrasion, 630
- Sieve analysis
 - sieve shaker, 11
 - variations, 13
- Signals used in scanning electron beam instruments
 - Auger electron, 31*t*
 - backscattered plasmon, 31*t*
 - elastically backscattered electrons, 31*t*
 - inelastically backscattered electrons, 31*t*
 - secondary electrons, 31*t*
- Silver alloy powders, 835
- Silver-nickel, 836–837*t*, 852–853
- Silver powders
 - apparent density, 833
 - fibrous dendritic silver, 835, 837*f*
 - particle size, 832–833
 - production of silver powders, 832–835
- Single rotary hammer mills
 - active rotor part rotation, 914
 - by-pass pipes, 915–917
 - dynamic interaction coefficient, 913–914*t*, 917, 917*t*
 - ejection suction, 915–917
 - excess pressure, 912
 - hammers action zone, 913–914*t*, 915
 - hydraulic resistance coefficient, 915–917
 - moving rotary parts, 912
 - underpressure, 912, 915, 917
 - unpressurized receiving bin, 915
- Sintering of porous metal
 - bond growth, 326
 - melting temperature, 326
 - sintering temperature, 326
 - surface energy, 326
- Size measurement
 - Feret's diameter, 7
 - longest diameter, 7
 - Martin's diameter, 7
 - maximum horizontal intercept diameter, 7
 - perimeter diameter, 7
 - project area diameter, 7
 - two-dimensional particle size images, 7
- Sliding at impact point
 - chute angle, 54
 - constrained moving, 54
 - impact point, 54
 - suspension state, 54
- Sodium reduction method (Hunter process)
 - aluminum–vanadium master alloy, 550
 - ductile metallic titanium, 550
 - metallic titanium, 550
 - sponge fines, 550, 550*f*
 - temperature reduction, 550
 - titanium tetrachloride, 550
- Solder alloy powders, 858, 859*t*
- Sol-gel method
 - agglomeration of the nanoparticles, 306
 - CdTe nanoparticles, 306
 - glass phosphors, 306
 - layer-by-layer (LbL) self-assembly method, 306
 - semiconductor nanoparticles, 306
 - ZnSe nanoparticles, 306
- Solid–gas eutectic solidification (Gasar)
 - elongated pores, 332
 - eutectic system, 332
 - gas-reinforced, 332
 - high pressure, 332
 - hydrogen atmosphere, 332
- Solid phase reduction (production of nickel powder)
 - fluidized bed, 661
 - hydrogen atmosphere, 661
 - hydrogen current, 661
 - needle shaped, 661
 - nickel oxalate, 661
 - producer gas, 661
 - purification of nickel–cobalt solutions, 661
 - reducing agents, 661
 - roasting of sulfide materials, 661
 - sponge particle surface, 661
 - thermal decomposition, 661
- Solid phase reduction of cobalt oxide
 - binder in production of hardmetals, 673
 - cobalt carbide, 674
 - metallothermic reduction, 674
 - reduction by carbon, 674
 - reduction by hydrogen, 674
 - reduction of cobalt oxide, 673–674
 - reduction of cobalt salts, 673–674
 - reduction temperature, 673–674
 - treatment of cobalt chloride, 674
- Solid-phase reduction of metal oxides and salts
 - application of chemically reduced powders and salts, 225
 - conveyor furnaces, 219
 - drum furnaces, 219
 - feed stock and reagent-reducers, 215–218
 - kinetics and mechanism of process, 212–215
 - powder production, 218–219
 - push type furnaces, 218
 - safety engineering, 220–221
- Soluble gas atomization process
 - argon hydrogen mixture, 163
 - droplets solidify, 163
 - gas-saturated molten metal, 163
 - powder collection tank, 163
 - rapid expansion, 163
 - spherical powder, 163
 - vacuum atomization, 163
- Sources of raw material (beryllium comprising)
 - bertrandite, 800
 - beryl, 800
 - beryllium concentrates, 800
 - concentration methods, 800
 - disseminated ores, 800
 - electrolysis from beryllium fluoride, 800
 - flotation, 800
 - fluoride technique, 800
 - phenacite, 800
 - reduction of beryllium fluoride by magnesium, 800
 - selection grinding, 800
 - sulfate technique, 800
- Sources of raw material for scandium production
 - alumina production, 812, 818
 - aluminum–scandium master alloys, 811
 - Australia's mining, 819
 - bauxites, 812
 - Bayer process, 818
 - carbon dioxide pressure, 818
 - carbonisation leaching, 818
 - elevated scandium content, 818–819
 - extraction by organic solvents, 811
 - ion exchange, 811
 - iron ores, 811
 - metallic scandium, 812, 813*t*
 - metallothermic reduction, 812
 - mine waters, 811
 - precipitation of low-solubility compounds, 811
 - red mud of alumina production, 818
 - RUSAL technological process, 818
 - scandium chlorides, 812
 - scandium concentrate, 818
 - scandium fluoride, 812
 - scandium recovery, 818
 - scandium–vanadium ores, 811
 - slurry solid phase, 818
 - sterretite, 811
 - thortveitite deposits, 818–819
 - Timan bauxite deposit, 818

- trace element of rocks, 811
- Ural refinery, 818
- waste and middling of metallurgical production, 811
- Special methods of production of metal powders recovered from spent solutions
 - coaxially located anode, 250–251
 - conducting particles, 251
 - eco-cell, 250–251
 - hammering rods, 251–252
 - horizontally rotating cylinder, 250–251
 - ion-change membrane, 250–251
 - pump-cell, 251
 - rotating cylindrical layer, 251–252
- Spheroidization of tungsten powders
 - carrier gas, 701
 - plasma spheroidization of tungsten powders, 701
 - plasma temperature, 701
 - plasma torch, 701
 - radio frequency (RF) thermal plasma, 701
 - rapid quenching, 701
 - raw tungsten powder, 701
 - spherical droplets, 701
 - surface tension, 701
 - thermal plasma technique, 701
- Spinning cup granulation process, 494, 496, 538
- Spinning cup water granulation process
 - annular wall of water, 179
 - atomizing chamber, 179
 - centrifugal force, 179
 - cup wall apertures, 179
 - mobile layer of water, 179
 - nozzle plug, 179
 - overflow apertures, 179
 - rotating cup, 179
 - rotating disc, 179
 - spinning cup water granulator, 179
 - suspended granules discharge, 179
- Spinning disc atomization
 - argon atmosphere, 170*t*, 171
 - battery applications, 169
 - chiller chamber, 169
 - electronic applications, 169
 - free fall melt feeding, 169
 - helium atmosphere, 169–171
 - hollow cone melt film, 169–171
 - melt film, 169–171
 - melt flow rate, 169
 - narrow size distribution, 169
 - needle shaped powder, 169
 - prefilming nozzle, 169, 170*t*
 - pressure-centrifugal-atomizer, 169
 - roller circumferential speed, 171
 - running speed, 169
 - satellite-free, 169
 - solder powder electronic applications, 169, 170*f*
 - solder powder particle size, 169–171, 170*t*
- Spinning water atomization process (SWAP)
 - gas atomizer, 179
 - irregular shape, 544
 - non-combustive properties, 179
 - nozzle plug, 179
 - rotatable water stream, 179
- Spray drying
 - agglomerate size distribution, 178
 - antifoaming agents, 178
 - binders for agglomeration, 178
 - bulk density, 178
 - control of powder properties, 178
 - deflocculating agents, 179*t*
 - defoamers, 178
 - free-flowing agglomerates, 178
 - frothing agents, 178
 - plasticizers, 178
 - rapid evaporation, 178
 - slurry, 178, 419
 - spray-dried slurries, 178
 - spray dryer, 419, 420*f*
 - suspending agents, 178
 - wetting agents, 179*t*
- Spray forming
 - aluminum based materials, 523
 - compound materials, 523
 - copper based materials, 523
 - cylindrical billets, 523
 - flat products, 522
 - gas atomization, 521
 - impact and deposition of droplets, 521
 - integral spray-forming models, 521–522
 - lightweight metals, 523
 - metal spraying process, 521
 - moving substrate, 521–522
 - multiphase cone, 521
 - plasma spray deposition (PSD), 525
 - precipitation hardened aluminum alloy, 523
 - quasicrystalline alloys, 524
 - spray cone, 521–522
 - spray deposited materials, 524
 - spray formed rings, 522
 - spray formed tubes, 522
 - substrate, 521, 525
 - titanium superalloys, 522–523
- Spray granulation
 - binding liquid, 177
 - direct current plasma-heated fluidized bed, 177
 - fluidized bed, 177, 178*f*
 - formation of agglomerates, 177
 - granule size, 177
 - hot gaseous fluidized bed, 177
 - nanophase composite powders, 177
 - porous non-homogenous shell structure, 177
 - scalable technologies, 177
 - two-fluid spray nozzle, 177
- Spray rolling (spray strip casting)
 - atomized droplets, 526
 - direct strip-casting techniques, 526
 - inert gas atmosphere, 526
 - liquidus temperature, 526
 - roll gap, 526
 - rolling mill, 526, 526*f*
 - roll surface speed, 526
 - spray-rolled strip, 526, 526*t*
- Standards, development of
 - ASTM International, 929–931*t*
 - CIS (Commonwealth of Independent States)–GOST, 410, 426–427*t*, 765–766, 776, 778, 881
 - France, 426–427*t*
 - Germany–DIN, 426–427*t*
 - International Standards Organization (ISO), 3, 870–871, 874–875
 - ISO, Technical Committee, 870–871
 - Japan, 54
 - Metal Powder Industries Federation (MPIF), 929–931*t*
 - Russian Federation–GOST, 849*t*, 854–857
 - United Kingdom–BSI, 870
- Standard terminology of powder metallurgy. ASTM, Designation: B243–13, 271
- Standard test methods for metal powders and powder metallurgy products, 59
- Steam explosion method
 - CANOPUS method, 176, 176*f*
 - explosive formation of steam, 176
 - stream of cooled water, 176
- Storing and transportation of hazardous powders, 925–927
 - dangerous goods, 925–926
 - IATA dangerous goods regulations (DGR), 926
- Surface analysis
 - Auger electron spectroscopy (AES), 30–32
 - secondary ion mass spectroscopy (SIMS), 32–33
 - x-ray photoelectron spectroscopy (XPS), 32
- Surface area and porosity of powders
 - gas adsorption, 39–41
 - permeametry, 41–42
 - picnometry, 42–43
 - porosimetry, 43–46
- Surface area determination (by mercury)
 - mercury porosimetry, 45
 - specific pore geometry, 45
- Surface tension of mercury, 45
- Surfactants, 228–229, 248–250, 721
- Surfactants (by autoclave processing)
 - anthraquinone, 228
 - carboxyl containing surfactant, 229
 - covering, 228
 - mechanism of anti- skull formation, 229
 - organic substances, 228
 - polyacrylic salts, 228
 - powder dispersity, 228
 - skull formation, 228
- Synthesis of open-cell metal foams
 - catalysts, 336–337
 - chemical vapor deposition, 337
 - electrochemical cells, 336–337
 - open-cell mold, 336–337
 - physical vapor deposition, 337
 - PM route, 336–337
- T**
- Tantalum
 - consolidation and manufacturing of semi-products, 746–747
 - tantalum carbide, 744–747

Tantalum (*Continued*)

- tantalum compounds, 742
- tantalum metal powders, 742
- Tantalum carbide
 - grain growth inhibitor, 744–745
 - hydrate ammonium tantalate, 745
 - precursor of the tantalum carbide, 745, 746*f*
 - tantalum carbide powder, 744–745, 746*f*
 - tantalum–niobium carbide, 744–745
- Tantalum metal powders
 - electrochemical method, 744
 - electrolytic process, 742–743
 - HDH process, 742
 - molten sodium chloride, 742
 - sodium reduction, 742
- Tantalum powder producing by electrolytic process
 - anode current density, 744
 - cathode crucible, 744
 - cathode current density, 744
 - electrolyte, 744
 - potassium (sodium) chloride, 742–743
 - potassium fluorotantalate, 742–743
 - tantalum dendrites, 743–744
 - tantalum pentachloride, 744
 - tantalum pentoxide, 742–743
 - tantalum refining, 744
- Tantalum powder production by hydride–dehydride (HDH) process
 - brittle hydride, 742
 - electron beam (EB) melting, 742
 - porous structure, 744
 - sintering inhibitors, 742
 - slow cooling, 742
- Tantalum powder production by sodium reduction
 - capacitor powders, 742
 - electronic capacitor applications, 742
 - flake-shaped tantalum particles, 742
 - potassium tantalum fluoride, 742
- Tantalum refining
 - chloride–fluoride melt, 744
 - fluoride melt, 744
 - molten salt, 744, 744*f*
 - reducing electrochemically dissolved tantalum ions, 744
 - tantalum rod anode, 744
- Tap density
 - graduated glass cylinder, 52
 - tapped powder, 52
 - vibrated powder, 52
- Technique for prevention of exposure hazards
 - common demands to production area, equipment, and processes, 881–885
 - dust explosion protection systems, 887–891
 - localization of powder-gas emissions, 892–901
 - workplace exposure limits, 879–881
- Techniques of chemical analysis for powders
 - bulk analysis, 33–38
 - microanalysis, 27–30
 - surface analysis, 30–33
- Temperature rise during milling, 72
 - bulk temperature, 73

- contact temperature, 72–73
- Hertz's theory of elastic impact, 72–73
- Testing of nanopowders
 - instrumental indentation, 276–278
 - testing of nanopowder structures and chemistry, 275–276
- Testing of nanopowder structures and chemistry
 - atomic adsorption spectroscopy (AAS), 275
 - atomic force microscopy, 275
 - auger electron spectroscopy (AES), 275
 - bulk analysis, 275
 - electron probe x-ray microanalysis (EPMA), 275
 - energy dispersive spectrometry (EDS), 275
 - inductively coupled plasma atomic emission spectroscopy (ICP-AES), 275
 - magnetic force microscopy, 275
 - scanning electron microscopy (SEM), 275
 - scanning tunneling microscopy, 275
 - secondary ion mass spectroscopy (SIMS), 275
 - surface analysis, 275
 - transmission electron microscopy (TEM), 275
 - wavelength dispersive x-ray spectrometry (WDS), 275
 - X-ray powder diffraction (XRPD), 275
- Thallium
 - alkali refinement, 776
 - alloy addition, 776
 - crude thallium, 776
 - decreasing the alloy grain size, 776
 - electrolysis, 776
 - electrolyte composition, 776
 - fuel cell application, 776
 - marcasites, 776
 - pyrites, 776
 - solar application, 776
 - thallium ions, 776
 - thallium oxides, 776
 - thallium powder, 776
 - thallium sulfate, 776
 - ultra-red optics, 776
 - water treatment, 776
- Thermal properties of metallic foams
 - cell connectivity, 345
 - cell wall structures, 345
 - gaseous reducing agents, 879
 - heat conduction, 345
 - heat exchangers, 345
 - heat pipes, 345
 - heat sinks, 345
 - ligament structures, 345
 - modelling of heat transfer and thermal exchanges, 345
 - pore size distribution, 345
 - surface roughness, 345
 - tortuosity, 345
 - water atomized aluminum alloy powder, 346
- Thermodynamic peculiarities of metal chemical reduction
 - difference of oxidizer and reducer potentials, 221
 - oxidation–reduction potentials, 222–223*t*
 - oxidation–reduction reaction, 221
 - thermodynamic data, 221

- Thermophysical properties
 - aluminum bromide, 879
 - aluminum chloride, 879
 - aqueous alkali solution, 879
 - building categories, 875
 - carbon tetrachloride, 879
 - coefficient of linear thermal expansion, 875
 - combustibility and explosibility values, 879
 - combustible liquids, 879, 879*t*
 - combustion heat (enthalpy), 875
 - combustion reaction, 875
 - copper oxide, 879
 - exothermal reactions, 879
 - explosion and fire hazard, 875
 - explosion limits, 879
 - explosion-proof characteristics, 879, 879*t*
 - Guide to EU Legislation, 879
 - halogenated hydrocarbons, 879
 - heat of combustion, 875
 - heat of vaporization, 875
 - hydrogen evolution, 879
 - manufacturing areas, 875
 - methyl chloride, 879
 - minimum ignition temperature, 879
 - nitro-compounds, 879
 - rate of pressure rise, 879, 879*t*
 - silver oxide, 879
 - specific heat capacity, 875
 - thermal conductivity, 875
 - thermophysical magnitudes, 875
- Thin film technique
 - diamagnetic matrix, 304
 - electric arc evaporation, 304
 - ion deposition technology, 304
 - ion-plasma deposition, 304
 - magnetron sputtering, 304
 - metallic cathodes, 304
 - multi-layer, 304
 - nanosized quasicrystalline films, 304
 - paramagnetic matrix, 304
 - platinum filament, 304
 - quasicrystalline films, 304
- Thorium powder production
 - electrolysis of melts, 821
 - reduction of thorium dioxide by calcium, 820–821
- Tin powder
 - apparent density, 855–856*t*
 - applications, 858
 - fisher subsieve size, 855–856*t*
 - nominal composition, 855–856*t*
 - properties, 852, 855–856*t*
 - sieve analysis, 855–856*t*
 - trace elements, 855–856*t*
- Tin powder production
 - atomization, 852
 - bismuth–tin, 851–852*t*
 - close-coupled atomizer, 853*f*
 - cooling gas, 854*t*
 - cooling rate, 852
 - current density, 852–853
 - electrolysis, 852–853
 - electrolysis from double-layer cell, 851–852*t*
 - electrolyte composition, 851–852*t*

- horizontally cross-jet air atomization technique, 850
 - lead–tin, 851–852*t*
 - melt temperature, 854*t*
 - powder yield, 854*t*
 - pressure of cooling gas, 854*t*
 - tin–antimony, 851–852*t*
 - tin powder applications, 852
 - vertical melt atomization technique, 852
 - water solution electrolysis, 851–852*t*
 - Titanium alloys (applications of additive manufacturing)
 - build geometry, 387
 - build platform, 390
 - columnar microstructures, 390
 - corrosion resistance, 387
 - electron beam melting, 387–390
 - longitudinal direction, 390
 - melt pool, 387–390
 - powder bed fusion, 387–390
 - spot size, 390
 - strength-to-weight ratio, 387
 - transverse direction, 390
 - Titanium-based composite powders
 - ceramic slurry approach, 355
 - metal–ceramic composite powders, 355
 - metallic biomaterials, 355
 - metal matrix composites (MMCs), 355
 - nano-carbon materials, 355
 - rare earth oxides, 355
 - titanium alloy–hydroxyapatite, 355
 - titanium matrix composites, 355
 - Titanium powder-based materials selection
 - balance of mechanical properties, 567–568
 - desired combination of processing steps, 567–568
 - final product cost, 567–568
 - powder consolidation processing route, 567–568
 - processing step sequences, 567–568
 - Titanium powder process selection, 567
 - cost of powder per unit weight, 567
 - current cost titanium sponge, 567
 - master alloy powders, 567
 - minimizing the lead time, 567
 - powder process adaptability, 567
 - prealloyed (PA) methods, 567
 - process controllability, 567
 - Tovarov's apparatus, 41*f*
 - Trajectory effect
 - chute, 54
 - frictional drag, 54
 - pile surface, 54
 - Transition electron microscopy (TEM)
 - counting particles, 10
 - electron microscope grid, 10
 - powder sample preparation, 10
 - vacuum unit, 11
 - Transportable containers
 - by-pass tube, 452, 911
 - discharge of containers, 911–912
 - excess pressure, 911
 - explosion-risk powders, 911
 - pressurized performance, 911
 - protective atmospheres, 911
 - receiving vessel, 911, 912*f*
 - thinning zone, 911
 - Tumbling ball mills
 - large tumbling ball mills, 107
 - stainless steel balls, 73
 - Tungsten-arc inert-gas welding (TIG), 794
 - Tungsten carbide powder
 - diamond tools, 714
 - production of tungsten carbide powder, 707–709
 - properties of tungsten carbide powder, 709–712
 - tungsten carbide electrical contacts, 712–714
 - Tungsten composite materials
 - addition of molybdenum to quaternary alloy, 702–703
 - body-centered cubic (bcc) structure, 702
 - copper-coated tungsten composite, 703–704, 704*f*
 - copper–tungsten powder, 703–704, 704*f*
 - corrosion resistance, 702
 - dissolve-precipitation mechanism, 703
 - electrical contacts, 703
 - elemental powders, 701–702
 - high-voltage electric pulse consolidation, 703, 703*f*
 - infiltration sintering, 704–705, 704*f*
 - iron–nickel binder, 703
 - liquid-phase sintering, 702
 - mechanical alloying, 703
 - mechano–thermo–chemical process, 705
 - pores of the skeleton, 702
 - press-sinter method, 702
 - press-sinter-re-press process, 702
 - sol-spray drying, 703
 - thermo electroless method, 703–704
 - thorium-containing compounds, 705
 - tungsten–copper nanocomposite powder, 705
 - tungsten heavy alloys (WHAs), 701–702
 - tungsten powder infiltrated with copper alloys, 703
 - tungsten with oxide dispersions, 705
 - vacuum heat treatment, 702
 - welding electrodes, 705
 - Tungsten metal powders
 - amalgam technique, 693–694, 693*f*
 - carbonyl technique, 694, 694–695*f*
 - precipitation from gaseous phase of tungsten hexafluoride and hexachloride, 691–692, 692*f*
 - production of tungsten powder by a plasma process, 692–693, 693*f*
 - production of tungsten powder by hydrogen reduction, 9*f*, 686–690, 687–690*f*
 - properties of tungsten powders, 695–699, 696–698*t*, 697–698*f*
 - reduction by solid carbon, 690–691, 691*f*
 - Tungsten powder applications
 - non-sag tungsten wires, 699–701
 - pure tungsten powders, 699
 - spheroidization of tungsten powders, 701, 701*t*, 702*f*
 - tungsten composite materials, 701–702
 - ultrahigh purity powders, 699
 - Tungsten powder production by carbonyl technique
 - autoclave, 694
 - carbon monoxide action, 694
 - carbonyl decomposition, 694, 695*f*
 - compounds (salts), 694
 - dry synthesis from chlorides, 694
 - elevated temperatures, 694
 - high pressures, 694
 - horizontal sublimator, 694
 - metal carbonyl formation, 694
 - reducing agent, 694
 - synthesis of carbonyls, 694
 - tungsten hexachloride, 694
 - Tungsten powder production by hydrogen reduction
 - ammonium paratungstate (APT), 687
 - calcination step, 687
 - chemical vapor transport, 690
 - dissolution step, 687
 - dynamic powder layer, 689
 - hydrogen reducer, 687–688
 - purification step, 687
 - pusher furnace, 688–689, 688–689*f*
 - reduction step, 687–688
 - rotary furnaces, 687–689
 - tungsten-bearing minerals, 687
 - tungsten-bearing scrap, 686–687
 - wolframite concentrate, 686–687
- ## U
- Ultrahigh purity powders, 699
 - Ultrasonic additive manufacturing (UAM)
 - process
 - adhesively joined parts, 375
 - brazing, 375
 - diffusion bonding, 375
 - laser welding, 375
 - metallic sheet, 376
 - resistance welding, 375
 - sheet lamination process, 375
 - swelling effects, 375
 - ultrasonic consolidation, 375
 - ultrasonic vibration, 375
 - Ultrasonic gas atomization
 - capillary wave atomization model, 164
 - capillary wavelength, 163
 - cavitational phenomena, 163
 - confined ultrasonic atomizer, 164, 164*f*
 - Hartman tube principle, 164
 - HEVs ultrasonic atomization, 164
 - maximum entropy formalism, 125–126
 - pneumo-acoustic atomizers, 164
 - Sono–Tek ultrasonic nozzle, 164–165
 - ultrasonic atomization technology, 164–165
 - ultrasonic frequency, 163
 - ultrasonic nozzles, 164–165
 - Ultrasonic spray pyrolysis (USP)
 - cemented carbide scrap, 682
 - cobalt nanopowder synthesis, 682

Ultrasonic spray pyrolysis (USP) (*Continued*)
 cobalt nitrate aerosol, 682
 cobalt nitrate aqueous solutions, 682
 cobalt oxide, 681
 hydrogen reduction, 681–682
 narrow size distribution, 681–682
 non-agglomerated particles, 683
 precursor solution, 683
 silica-encapsulated metal nanoparticles, 681–682
 spherical cobalt powders, 682
 ultrafine cobalt powder, 681
 ultrasonic atomizer, 682

Uranium powder production
 electrolysis of halogen salts, 821
 hydride-dehydride process, 822
 metallic uranium, 821
 metallothermic reduction, 821
 reduction of uranium tetrachloride, 821
 reduction of uranium tetrafluoride, 821–822
 uranium hydride, 822
 uranium oxide, 821

V

Vacuum hot pressing (VHP) (beryllium powders)
 graphite dies, 804
 manufacturing commercial beryllium billets, 804
 nickel alloy dies, 804
 vacuum hotpressed billets, 804, 805*t*
 vacuum hot pressing chamber, 804

Vanadium

aluminothermic reduction process, 759
 calciothermic reduction, 759–760, 760*t*
 carbothermic reduction, 759–760, 760*t*
 content of vanadium, 758
 decomposition of vanadium halides, 759
 ductile vanadium, 758, 760
 electrolytic refining, 759–760
 magnesiothermic reduction, 760
 spark plasma sintering, 765
 tungsten based vanadium alloys, 765
 vanadium alloys, 760–762, 765
 vanadium carbides, 759, 764
 vanadium compositions, 764
 vanadium dioxide, 759
 vanadium oxides, 759
 vanadium pentoxide, 759
 vanadium powders, 759–761, 760*t*, 765, 765*f*
 vanadium refining, 760
 vanadium trioxide, 759–760

Vapor deposition in vacuum

combine production and processing, 297
 condensation of metallic vapor, 279
 crystallizer, 279
 electron beam installation, 297–298, 297*f*
 electron beam technologies (ICEBT), 297–298, 297–298*t*
 evaporating of metal, 278–279, 279*f*
 gas-phase technique, 297
 inert gas condensation process (IGS), 297
 microlaminate coating, 298
 nucleation centers, 279

prevention of oxidation, 297
 supersaturation, 279, 491
 VSMPO-AVISMA Corporation, 539

W

Waste aluminum foil recycling, 474–476, 475–476*f*
 Waste products utilization, storing, and transportation
 storing and transportation of hazardous powders, 925–927, 926*t*
 waste utilization, 924–925, 925*f*
 Waste utilization
 European Waste Catalogue, 925
 hazardous waste, 924–925
 metal machining scrap, 925
 scrap components, 924–925
 scrap for disposal, 924
 scrap for recycling, 924
 waste disposal, 924–925
 Water atomization
 powder characteristics, 134
 water atomization mechanism, 132–134
 water atomization technique, 128–132
 Water atomization mechanism
 bubble boiling conditions, 137–138
 cooling rate, 132, 137–138
 cooling time, 137–139
 droplet formation model, 133–134
 energy carrier, 132, 134*f*, 138–139, 139–140*f*
 film boiling conditions, 137–139
 film-bubble heat emission, 138
 first critical heat current density, 137–138
 Grandzol and Tallmadge, 132–133
 heat transfer, 132, 135, 137–138
 heat transfer coefficient, 135, 137–138, 139*f*
 liquid melt drop formation, 132
 liquidus temperature, 137, 139
 melt drop cooling time, 137
 melt superheat, 133
 second critical heat current density, 137–138
 spheroidization time, 137–139, 141
 steam film, 132, 137–138
 steam formation, 132
 superheated compressed steam, 132
 Ternovoy's formula, 133–134
 Water atomization technique
 annular jet, 129*f*
 annular ring nozzles, 130
 binary water cone configuration, 131–132, 131*f*
 closed V-jets, 129*f*, 132
 conical water swirl jet atomizer, 130–131, 130–131*f*
 IPMS atomizer, 132
 open V-jets, 129*f*
 Water granulation
 atomizing chamber, 179
 cup wall apertures, 179
 overflow apertures, 179
 pouring molten metals, 179
 rotating cup, 179
 spinning cup water granulation process, 179
 spinning cup water granulator, 179

spinning water atomization process, 179
 SWAP installation, 179
 water quenching, 179

Wavelength dispersive x-ray spectroscopy (WDS)

angular position of the crystal, 35
 charge carriers, 29
 crystal-monochromators, 35
 energy-dispersive spectrometer, 29
 gas-filled proportional detectors, 36
 radiation current, 35
 Workplace exposure limits
 airborne particles, 880
 American Conference of Governmental Industrial Hygienists (ACGIH), 881
 American Industrial Hygiene Association Journal, 881
 British Medical Research Council (BMRC), 881
 chemical substances (EINECS), 881
 commonwealth of Independent States (CIS) Standard, GOST 12.1.005-88, 881
 danger classes, 881
 dust concentration in the workplace atmospheres, 881
 occupational and environmental health, 881, 881*f*
 permissible exposure limit value (PEL), 881
 threshold limit value (TLV), 881
 tracheobronchial and alveolar components, 881
 workplace atmospheres, 880–881
 Wrought product forms (RE powders)
 beryllium extrusion, 806
 biaxial or triaxial deformation procedures, 806
 cross rolling at moderate temperature, 806
 crystallographic orientation, 806
 direction of metal flow, 806
 encasing beryllium billets in steel jackets, 806
 foil, 806
 hot-working technique, 806
 numerical control (CNC), 806–807
 plate, 806
 process AlBeWeld, 806
 sheet, 806, 807*t*

X

XD-process

exothermic reaction, 527
 metallic matrix material, 527
 reinforced aluminum composites, 527
 reinforcing phase, 527
 self-propagating reaction, 527
 ultrafine reinforcing particles, 527

X-ray diffraction (XRD), 27, 34, 38, 78–79, 378–381, 524

X-ray fluorescence spectroscopy (XRF)
 element-wise decomposition, 36
 excitation of atoms, 35
 fluorescent signal, 35
 secondary fluorescent emission, 35
 X-ray beam, 35
 X-ray spectrometers, 35

X-ray photoelectron spectroscopy (XPS)
 average surface chemistry, 32
 electron energy analyzer, 32
 electron multiplier, 32
 ion gun as x-ray source, 32
 pulse-counting detector, 32
 quantitative spectroscopic technique, 32
 ultrahigh vacuum conditions, 32

X-ray powder diffraction (XRPD)
 automated powder diffractometers, 34
 crystallites, 33, 35
 determination of crystallinity, 33
 high-temperature studies, 33
 lattice-parameters determinations, 33
 monochromatic x-ray beam, 35
 pattern-recognition methods, 34
 phase identification and analysis, 33
 Rietveld method, 35
 thin film characterization, 33
 Wulf-Bragg's law, 34

Y

Yield strength
 aluminum alloys, 498, 500–501*t*
 properties of AlBeMet, 809*t*, 810
 tensile properties of alloys doped by cerium, 792, 793*t*
 tensile properties of molybdenum wire, 725–726, 728*t*
 tensile properties of PM superalloys, 655, 656*t*
 titanium powders and sintered compacts, 550, 552*t*

Young–Laplace– Washburn equation, 43–44
 Young's modulus, xx, 276–278, 314, 357, 360, 504–505, 544

Z

Zinc powder, 128, 143–144, 169, 195–196, 196*t*, 357, 601–602, 615, 616*f*, 617, 619–620, 619*f*, 621*f*, 622, 623*t*, 625–630, 627*t*, 629*t*, 694. *See also* Production of zinc, cadmium, and their alloy powders

Zinc process, 631, 722

Zinc-rich composite powders
 aluminum pigment, 356–357, 356*f*
 cathodic protection properties, 355–356
 coating cathodic protection, 355–356
 epoxy zinc-rich coating, 356–357, 356*f*
 inorganic zinc-rich coating, 355–357
 lamellar aluminum, 356–357
 lamellar-type pigment, 356–357
 lamellar zinc, 357
 sacrificial pigment, 357
 zinc-rich coating, 355–357

Zirconium powder
 deoxidation and denitrating of steel, 766
 zirconium baddeleyite, 766
 zirconium dioxide, 766
 zirconium ortho-silicate, 766
 zirconium powder production, 766

Zirconium powder applications
 armor and gun steels, 766
 corrosion-resistant steels, 757
 electronics, 766

elevated temperature alloys, 789–792
 igniter in detonators, 766
 nuclear power industry, 766
 photoflashes, 766
 pyrotechnics, 766
 refractory, 766
 smokeless powder, 766
 steel production, 766

Zirconium powder production
 amalgam method, 770
 combustion synthesis of zirconium nitrides, 771
 electrolytic methods for production or refining of zirconium powders, 767
 iodide method of zirconium refining, 767
 lead zirconate titanate (PZT) ceramics, 772–773, 773*f*
 plasma-assisted reduction of zirconium tetrachloride by magnesium, 771, 771–772*f*
 reduction of zirconium dioxide by calcium or calcium hydrate, 768
 reduction of zirconium dioxide by magnesium using autoclave processing, 772, 772*f*
 reduction of zirconium fluoride (ZrF₄) by calcium or of potassium hexafluorozirconate (K₂ZrF₆) by sodium, 768
 reduction of zirconium tetrachloride by magnesium or sodium, 767–768
 zirconium powder applications, 766