

Guía paso a paso para recrear grpc-H2db desde cero

=====

1. Crear carpeta y pom.xml

```
```bash
mkdir grpc-H2db && cd grpc-H2db
cat > pom.xml <<'EOF'
pega aquí el contenido completo del pom (paso 2)
EOF
```
```

2. Sustituir pom.xml (idéntico al proyecto actual)

```
```xml
<project xmlns="http://maven.apache.org/POM/4.0.0"
 xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
 xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
 http://maven.apache.org/xsd/maven-4.0.0.xsd">

 <modelVersion>4.0.0</modelVersion>
 <groupId>com.grpc</groupId>
 <artifactId>ej5</artifactId>
 <version>1.0</version>

 <dependencies>
 <dependency>
 <groupId>com.google.protobuf</groupId>
 <artifactId>protobuf-java</artifactId>
 <version>3.22.2</version>
 </dependency>
 <dependency>
 <groupId>io.grpc</groupId>
 <artifactId>grpc-netty-shaded</artifactId>
 <version>1.54.0</version>
 </dependency>
 <dependency>
 <groupId>io.grpc</groupId>
 <artifactId>grpc-protobuf</artifactId>
 <version>1.54.0</version>
 </dependency>
 <dependency>
 <groupId>io.grpc</groupId>
```

```
<artifactId>grpc-stub</artifactId>
<version>1.54.0</version>
</dependency>
<dependency>
 <groupId>javax.annotation</groupId>
 <artifactId>javax.annotation-api</artifactId>
 <version>1.3.2</version>
</dependency>
<dependency>
 <groupId>io.reactivex.rxjava3</groupId>
 <artifactId>rxjava</artifactId>
 <version>3.1.8</version>
</dependency>
<dependency>
 <groupId>org.json</groupId>
 <artifactId>json</artifactId>
 <version>20230227</version>
</dependency>
```

```
<dependency>
 <groupId>com.h2database</groupId>
 <artifactId>h2</artifactId>
 <version>2.2.224</version>
 <scope>runtime</scope>
</dependency>
```

```
</dependencies>
```

```
<properties>
 <project.build.sourceEncoding>UTF-8</project.build.sourceEncoding>
</properties>
```

```
<build>
 <defaultGoal>clean generate-sources compile install</defaultGoal>
 <plugins>
 <plugin>
 <groupId>com.github.os72</groupId>
 <artifactId>protoc-jar-maven-plugin</artifactId>
 <version>3.6.0.1</version>
 <executions>
 <execution>
```

```

 <phase>generate-sources</phase>
 <goals>
 <goal>run</goal>
 </goals>
 <configuration>
 <includeMavenTypes>direct</includeMavenTypes>
 <inputDirectories>
 <include>src/main/resources</include>
 </inputDirectories>
 <!-- Descomentar SOLO SI TIENES macOS con arquitectura Intel (x86_64) --
>
 <protocArtifact>com.google.protobuf:protoc:3.22.2:exe:osx-
x86_64</protocArtifact>
 <outputTargets>
 <outputTarget>
 <type>java</type>
 <outputDirectory>src/main/java</outputDirectory>
 </outputTarget>
 <outputTarget>
 <type>grpc-java</type>
 <pluginArtifact>io.grpc:protoc-gen-grpc-java:1.54.0</pluginArtifact>
 <outputDirectory>src/main/java</outputDirectory>
 </outputTarget>
 </outputTargets>
 </configuration>
 </execution>
</executions>
</plugin>
<plugin>
 <groupId>org.apache.maven.plugins</groupId>
 <artifactId>maven-compiler-plugin</artifactId>
 <version>3.8.0</version>
 <configuration>
 <source>17</source>
 <target>17</target>
 </configuration>
</plugin>
</plugins>
</build>
</project>
` ``

```

### 3. Crear estructura de carpetas

```
```bash
mkdir -p src/main/resources
mkdir -p src/main/java/client
mkdir -p src/main/java/server
mkdir -p src/main/java/service
mkdir -p src/main/java/db
```
```

### 4. Definir contrato gRPC en src/main/resources/product.proto

```
```proto
syntax = "proto3";

option java_multiple_files = true;
option java_package = "com.grpc.ej5";
option java_outer_classname = "ProductProto";

service ProductService {

    // 1. UNARY: Obtener producto por ID
    rpc GetProductById (ProductIdRequest) returns (ProductResponse);

    // 2. SERVER STREAMING: Productos más baratos que un precio
    rpc StreamCheaperProducts (PriceRequest) returns (stream ProductResponse);

    // 3. CLIENT STREAMING: Insertar varios productos
    rpc InsertProducts (stream NewProductRequest) returns (InsertSummary);

    // 4. BIDIRECTIONAL STREAMING: Consultas dinámicas de precio
    rpc LivePriceQuery (stream PriceRequest) returns (stream ProductResponse);
}

message ProductIdRequest {
    int32 id = 1;
}

message PriceRequest {
    double maxPrice = 1;
}
```

```
message ProductResponse {
  int32 id = 1;
  string name = 2;
  double price = 3;
}
```

```
message NewProductRequest {
  string name = 1;
  double price = 2;
}
```

```
message InsertSummary{
  int32 insertedCount = 1;
}
```

5. Generar código Java desde el .proto

```
```bash
mvn clean compile
```
```

(Genera clases en src/main/java/com/grpc/ej5).

6. Implementar acceso H2 en src/main/java/db/H2Database.java

```
```java
package db;
```

```
import java.sql.Connection;
import java.sql.DriverManager;
```

```
public class H2Database {
```

```
private static final String URL = "jdbc:h2:mem:productos;DB_CLOSE_DELAY=-1";
private static final String USER = "sa";
private static final String PASS = "";
```

```
public static void init() {
 try (Connection conn = DriverManager.getConnection(URL, USER, PASS)) {
```

```
conn.createStatement().execute("""
 CREATE TABLE productos (
 id INT AUTO_INCREMENT PRIMARY KEY,
```

```

 name VARCHAR(100),
 price DOUBLE
);
""");

```

```

conn.createStatement().execute("""
 INSERT INTO productos (name, price) VALUES
 ('Teclado mecánico', 59.99),
 ('Ratón inalámbrico', 19.90),
 ('Auriculares gaming', 79.90),
 ('Alfombrilla XL', 10.00),
 ('Webcam HD', 29.95);
""");

```

```

System.out.println("[H2] Base de datos inicializada");

```

```

 } catch (Exception e) {
 e.printStackTrace();
 }
}

```

```

public static Connection getConnection() throws Exception {
 return DriverManager.getConnection(URL, USER, PASS);
}
}
```

```

7. Implementar servicio gRPC en src/main/java/service/ProductService.java

```

```java

```

```

package service;

```

```

import com.grpc.ej5.*;
import db.H2Database;
import io.grpc.stub.StreamObserver;

```

```

import java.sql.*;

```

```

public class ProductService extends
ProductServiceGrpc.ProductServiceImplBase {

```

```

 // 1. UNARY

```

```

@Override
public void getProductById(ProductIdRequest req,
 StreamObserver<ProductResponse> obs) {

 System.out.println("[SERVER](UNARY) Recibido ID del cliente = " + req.getId());

 try (Connection conn = H2Database.getConnection()) {

 PreparedStatement ps = conn.prepareStatement(
 "SELECT id, name, price FROM productos WHERE id = ?");
 ps.setInt(1, req.getId());

 ResultSet rs = ps.executeQuery();

 if (!rs.next()) {
 obs.onError(new RuntimeException("Producto no encontrado"));
 return;
 }

 ProductResponse resp = ProductResponse.newBuilder()
 .setId(rs.getInt("id"))
 .setName(rs.getString("name"))
 .setPrice(rs.getDouble("price"))
 .build();

 System.out.println("[SERVER](UNARY) Enviando producto → " +
 resp.getName());

 obs.onNext(resp);
 obs.onCompleted();

 } catch (Exception e) {
 obs.onError(e);
 }
}

```

## // 2. SERVER STREAMING

```

@Override
public void streamCheaperProducts(PriceRequest req,
 StreamObserver<ProductResponse> obs) {

```

```
System.out.println("[SERVER](SERVERSTREAMING) Recibido maxPrice = " +
req.getMaxPrice());
```

```
try (Connection conn = H2Database.getConnection()) {
```

```
 PreparedStatement ps = conn.prepareStatement(
 "SELECT id, name, price FROM productos WHERE price <= ?");
 ps.setDouble(1, req.getMaxPrice());
```

```
 ResultSet rs = ps.executeQuery();
```

```
 while (rs.next()) {
```

```
 ProductResponse p = ProductResponse.newBuilder()
 .setId(rs.getInt("id"))
 .setName(rs.getString("name"))
 .setPrice(rs.getDouble("price"))
 .build();
```

```
 System.out.println("[SERVER](SERVERSTREAMING) Enviando → " +
p.getName());
```

```
 obs.onNext(p);
 }
```

```
 obs.onCompleted();
```

```
} catch (Exception e) {
 obs.onError(e);
}
}
```

```
// 3. CLIENT STREAMING
```

```
@Override
```

```
public StreamObserver<NewProductRequest> insertProducts(
 StreamObserver<InsertSummary> obs) {
```

```
 return new StreamObserver<>() {
```



```

int count = 0;

@Override
public void onNext(NewProductRequest req) {
 System.out.println("[SERVER](CLIENTSTREAMING) Recibido producto → " +
req.getName());

 try (Connection conn = H2Database.getConnection()) {

 PreparedStatement ps = conn.prepareStatement(
 "INSERT INTO productos (name, price) VALUES (?, ?)");
 ps.setString(1, req.getName());
 ps.setDouble(2, req.getPrice());
 ps.executeUpdate();

 System.out.println("[SERVER](CLIENTSTREAMING) Insertado en BD");
 count++;

 } catch (Exception e) {
 obs.onError(e);
 }
}

@Override
public void onCompleted() {
 System.out.println("[SERVER](CLIENTSTREAMING) Finalizando stream →
total insertados = " + count);

 InsertSummary summary = InsertSummary.newBuilder()
 .setInsertedCount(count)
 .build();

 obs.onNext(summary);
 obs.onCompleted();
}

@Override
public void onError(Throwable t) {
 System.out.println("[SERVER](CLIENTSTREAMING) Error → " +
t.getMessage());
}

```

```
};
}
```

// 4. BIDI STREAMING

```
@Override
public StreamObserver<PriceRequest> livePriceQuery(
 StreamObserver<ProductResponse> obs) {

 return new StreamObserver<>() {

 @Override
 public void onNext(PricingRequest req) {
 System.out.println("[SERVER](BIDIRECTIONAL) Recibido maxPrice → " +
req.getMaxPrice());

 try (Connection conn = H2Database.getConnection()) {

 PreparedStatement ps = conn.prepareStatement(
 "SELECT id, name, price FROM productos WHERE price <= ?");
 ps.setDouble(1, req.getMaxPrice());

 ResultSet rs = ps.executeQuery();

 while (rs.next()) {

 ProductResponse p = ProductResponse.newBuilder()
 .setId(rs.getInt("id"))
 .setName(rs.getString("name"))
 .setPrice(rs.getDouble("price"))
 .build();

 System.out.println("[SERVER](BIDIRECTIONAL) Enviando → " +
p.getName());

 obs.onNext(p);
 }

 } catch (Exception e) {
 obs.onError(e);
 }
 }
 }
}
```

```

 }

 @Override
 public void onCompleted() {
 System.out.println("[SERVER](BIDIRECTIONAL) Cliente finalizó stream.");
 obs.onCompleted();
 }

 @Override
 public void onError(Throwable t) {
 System.out.println("[SERVER](BIDIRECTIONAL) Error → " + t.getMessage());
 }
};
}
}
...

```

8. Implementar servidor en src/main/java/server/ProductServer.java

```

```java
package server;

import db.H2Database;
import io.grpc.Server;
import io.grpc.ServerBuilder;
import service.ProductService;

public class ProductServer {

    public static void main(String[] args) throws Exception {

        H2Database.init();

        Server server = ServerBuilder
            .forPort(50051)
            .addService(new ProductService())
            .build();

        server.start();
        System.out.println("Servidor gRPC con H2 ejecutándose en puerto 50051...");

        server.awaitTermination();
    }
}

```

```
}  
}  
```\n
```

9. Implementar cliente en src/main/java/client/ProductClient.java

```
```java  
package client;  
  
import com.grpc.ej5.*;  
import io.grpc.ManagedChannel;  
import io.grpc.ManagedChannelBuilder;  
import io.grpc.stub.StreamObserver;  
  
import java.util.concurrent.CountDownLatch;  
import java.util.concurrent.TimeUnit;  
  
public class ProductClient {  
  
    private final ManagedChannel channel;  
    private final ProductServiceGrpc.ProductServiceBlockingStub blockingStub;  
    private final ProductServiceGrpc.ProductServiceStub asyncStub;  
  
    public ProductClient() {  
        channel = ManagedChannelBuilder  
            .forAddress("localhost", 50051)  
            .usePlaintext()  
            .build();  
  
        blockingStub = ProductServiceGrpc.newBlockingStub(channel);  
        asyncStub = ProductServiceGrpc.newStub(channel);  
    }  
  
    // 1. UNARY  
    public void unary() {  
  
        ProductIdRequest req = ProductIdRequest.newBuilder().setId(1).build();  
        System.out.println("[CLIENT](UNARY) Enviando ID = " + req.getId());  
  
        ProductResponse resp = blockingStub.getProductById(req);  
  
        System.out.println("[SERVER](UNARY) Recibido producto:");  
    }  
}
```

```

        System.out.println(" Nombre = " + resp.getName());
        System.out.println(" Precio = " + resp.getPrice());
    }

```

// 2. SERVER STREAMING

```

public void serverStreaming() {

    PriceRequest req = PriceRequest.newBuilder().setMaxPrice(50).build();
    System.out.println("[CLIENT](SERVERSTREAMING) Max price = " +
        req.getMaxPrice());

    System.out.println("[SERVER](SERVERSTREAMING) Productos recibidos:");

    blockingStub.streamCheaperProducts(req).forEachRemaining(
        p -> System.out.println(" → " + p.getName() + " | " + p.getPrice())
    );
}

```

// 3. CLIENT STREAMING

```

public void clientStreaming() throws Exception {

    CountdownLatch latch = new CountdownLatch(1);

    StreamObserver<InsertSummary> respObs = new StreamObserver<>() {
        public void onNext(InsertSummary s) {
            System.out.println("[SERVER](CLIENTSTREAMING) Insertados total = " +
                s.getInsertedCount());
        }
        public void onError(Throwable t) { latch.countDown(); }
        public void onCompleted() { latch.countDown(); }
    };

    StreamObserver<NewProductRequest> reqStream =
        asyncStub.insertProducts(respObs);

    // ENVÍO 1
    NewProductRequest p1 = NewProductRequest.newBuilder()
        .setName("Mesa gaming").setPrice(120).build();

```

```
        System.out.println("[CLIENT](CLIENTSTREAMING) Enviando → " +  
p1.getName() + "con precio " + p1.getPrice());  
        reqStream.onNext(p1);
```

```
    // ENVÍO 2  
    NewProductRequest p2 = NewProductRequest.newBuilder()  
        .setName("Monitor 27'").setPrice(199).build();  
    System.out.println("[CLIENT](CLIENTSTREAMING) Enviando → " +  
p2.getName() + "con precio " + p2.getPrice());  
    reqStream.onNext(p2);
```

```
    reqStream.onCompleted();  
    latch.await();  
}
```

// 4. BIDIRECTIONAL STREAMING

```
public void bidiStreaming() throws Exception {
```

```
    CountdownLatch latch = new CountdownLatch(1);
```

```
    StreamObserver<ProductResponse> respObs = new StreamObserver<>() {
```

```
        public void onNext(ProductResponse p) {  
            System.out.println("[SERVER](BIDIRECTIONAL) Producto → " + p.getName()  
+ " | " + p.getPrice());  
        }  
    }
```

```
    public void onError(Throwable t) { latch.countDown(); }
```

```
    public void onCompleted() {  
        System.out.println("[SERVER](BIDIRECTIONAL) Fin del stream");  
        latch.countDown();  
    }  
};
```

```
    StreamObserver<PriceRequest> reqStream =  
asyncStub.livePriceQuery(respObs);
```

```
    PriceRequest r1 = PriceRequest.newBuilder().setMaxPrice(20).build();
```

```

        System.out.println("[CLIENT](BIDIRECTIONAL) MaxPrice enviado = " +
r1.getMaxPrice());
        reqStream.onNext(r1);
        Thread.sleep(500);

        PriceRequest r2 = PriceRequest.newBuilder().setMaxPrice(60).build();
        System.out.println("[CLIENT] (BIDIRECTIONAL) MaxPrice enviado = " +
r2.getMaxPrice());
        reqStream.onNext(r2);
        Thread.sleep(500);

        PriceRequest r3 = PriceRequest.newBuilder().setMaxPrice(200).build();
        System.out.println("[CLIENT](BIDIRECTIONAL) MaxPrice enviado = " +
r3.getMaxPrice());
        reqStream.onNext(r3);

        reqStream.onCompleted();
        latch.await();
    }

    public void shutdown() throws InterruptedException {
        channel.shutdown().awaitTermination(2, TimeUnit.SECONDS);
    }

    public static void main(String[] args) throws Exception {
        ProductClient c = new ProductClient();
        c.unary();
        c.serverStreaming();
        c.clientStreaming();
        c.bidiStreaming();
        c.shutdown();
    }
}
```

```

## 10. Empaquetar

```

```bash
mvn clean package
```

```

## 11. Ejecutar

```
```bash
```

```
# Terminal 1: servidor
```

```
mvn exec:java -Dexec.mainClass=server.ProductServer
```

```
# Terminal 2: cliente
```

```
mvn exec:java -Dexec.mainClass=client.ProductClient
```

```
```
```

## 12. Flujo esperado

- Servidor arranca H2 en memoria con datos de ejemplo.
- Cliente realiza cuatro llamadas: unary, server-streaming, client-streaming (inserta y recibe resumen) y bidirectional-streaming (consultas dinámicas).
- Ajusta IDs o precios en el cliente para probar otros casos.