


Artificial Neural Networks (ANN)


X_1	X_2	X_3	Y
1	0	0	0
1	0	1	1
1	1	0	1
1	1	1	1
0	0	1	0
0	1	0	0
0	1	1	1
0	0	0	0



Output Y is 1 if at least two of the three inputs are equal to 1.

Artificial Neural Networks (ANN)

X_1	X_2	X_3	Y
1	0	0	0
1	0	1	1
1	1	0	1
1	1	1	1
0	0	1	0
0	1	0	0
0	1	1	1
0	0	0	0




$$Y = I(0.3X_1 + 0.3X_2 + 0.3X_3 - 0.4 > 0)$$

$$\text{where } I(z) = \begin{cases} 1 & \text{if } z \text{ is true} \\ 0 & \text{otherwise} \end{cases}$$

Artificial Neural Networks (ANN)

- Model is an assembly of inter-connected nodes and weighted links
- Output node sums up each of its input value according to the weights of its links
- Compare output node against some threshold t




Perceptron Model

$$Y = I\left(\sum_i w_i X_i - t\right) \quad \text{or}$$

$$Y = \text{sign}\left(\sum_i w_i X_i - t\right)$$

General Structure of ANN



Algorithm for learning ANN

- Initialize the weights (w_0, w_1, \dots, w_k)
- Adjust the weights in such a way that the output of ANN is consistent with class labels of training examples
 - Objective function: $E = \sum_i [Y_i - f(w_i, X_i)]^2$
 - Find the weights w_i 's that minimize the above objective function
 - ◆ e.g., backpropagation algorithm (see lecture notes)