```html
<!doctype html>
<html lang="en">
  <head>
    <!-- Required meta tags -->
    <meta charset="utf-8">
    <meta name="viewport" content="width=device-width, initial-scale=1">

    <!-- Bootstrap CSS -->
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css" rel="stylesheet" integrity="sha384-EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOmLASjC" crossorigin="anonymous">

    <title>Home Page</title>
      <style>
      body {
        background-color: #f5f5f5;
        color: #333;
        font-family: "Segoe UI", Arial, sans-serif;
      }
      h1, h2, h3 {
        color: #2e7d32; /* green accent */
      }
      .navbar {
        background-color: #263238 !important; /* deep navy */
      }
      .navbar-brand, .navbar-nav .nav-link {
        color: #ffffff !important;
      }
      .section {
        margin-top: 2rem;
        margin-bottom: 2rem;
        padding: 1rem 1.5rem;
        background: #ffffff;
        border-radius: 10px;
        box-shadow: 0px 2px 6px rgba(0,0,0,0.1);
      }
      .bio-img {
```

```
        max-width: 250px;
        border-radius: 50%;
        margin-bottom: 1.5rem;
        border: 4px solid #2e7d32;
      }
      hr {
        border-top: 2px solid #2e7d32;
        opacity: 0.6;
      }
      a {
        color: #0288d1;
        text-decoration: none;
      }
      a:hover {
        text-decoration: underline;
      }
    </style>
  </head>
  <body>
     <nav class="navbar navbar-expand-md">
      <a class="navbar-brand" href="#">BGF Analytics</a>
      <button class="navbar-toggler" type="button" data-bs-toggle="collapse" data-bs-target="#navbarNav">
        <span class="navbar-toggler-icon"></span>
      </button>
      <div class="collapse navbar-collapse" id="navbarNav">
        <ul class="navbar-nav ms-auto">
          <li class="nav-item"><a class="nav-link" href="{{ url_for('home_page')}}">Home Page</a></li>
          <li class="nav-item"><a class="nav-link" href="{{ url_for('resume')}}">Resume</a></li>
          <li class="nav-item"><a class="nav-link" href="{{ url_for('projects')}}">Projects</a></li>
          <li class="nav-item"><a class="nav-link" href="{{ url_for('game_sim')}}">Game Simulator</a></li>
          <li class="nav-item"><a class="nav-link" href="{{ url_for('XGB_sim')}}">Bracket Simulator</a
```

```
></li>
        </ul>
      </div>
    </nav>
    <h1>Christopher Colt Meyer Biography</h1>
     <div class="container mt-4">
        <div class="col-md-8">
            <p>
            This is a place holder for the body
            </p>
        </div>
     </div>
     <div class="container mt-4">
        <div class="row justify-content-center">
            <div class="col-md-8">

            </div>
        </div>
    </div>

    <!-- Optional JavaScript; choose one of the two ! -->

    <!-- Option 1: Bootstrap Bundle with Popper -->
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.bundle.min.js" integrity="sha384-MrcW6ZMFYlzcLA8Nl+NtUVF0sA7MsXsP1UyJoMp4YLEuNSfAP+JcXn/tWtIaxVXM" crossorigin="anonymous"></script>

    <!-- Option 2: Separate Popper and Bootstrap JS -->
    <!--
    <script src="https://cdn.jsdelivr.net/npm/@popperjs/core@2.9.2/dist/umd/popper.min.js" integrity="sha384-IQsoLXl5PILFhosVNubq5LC7Qb9DXgDA9i+tQ8Zj3iwWAwPtgFTxbJ8NT4GN1R8p" crossorigin="anonymous"></script>
    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/js/bootstrap.min.js" integrity="sha384-cVKIPhGWiC2Al4u+LWgxfKTRIcfu0JTxR+EQDz/
```

```
bgldoEyl4H0zUF0QKbrJ0EcQF" crossorigin="anonymous
"></script>
    -->
  </body>
```