



PROBLEM 6.54



A Fink roof truss is loaded as shown. Determine the force in members DF , DG , and EG . (Hint: First determine the force in member EK .)

SOLUTION

FBD Truss:




$$\rightarrow \Sigma F_x = 0: A_x = 0$$

$$\text{By symmetry: } A_y = O_y = 2000 \text{ lb } \uparrow$$

FBD Sections:

Forces in lb



$$\begin{aligned} \curvearrowleft \Sigma M_H = 0: & (a + 2a + 3a)(500 \text{ lb}) + 4a(250 \text{ lb}) \\ & - 4a(2000 \text{ lb}) + 2aF_{EK} = 0 \end{aligned}$$

$$F_{EK} = 2000 \text{ lb T}$$

$$\begin{aligned} \curvearrowleft \Sigma M_D = 0: & a(500 \text{ lb}) + 2a(250 \text{ lb}) - 2a(2000 \text{ lb}) + a(2000 \text{ lb}) \\ & + a\left(\frac{3}{5}F_{EG}\right) + (12 \text{ ft} - 2a)\left(\frac{4}{5}F_{EG}\right) = 0 \end{aligned}$$

$$F_{EG} = 1000 \text{ lb}$$

$$F_{EG} = 1.000 \text{ kip T} \blacktriangleleft$$

$$\uparrow \Sigma F_y = 0: \frac{4}{5}(1000 \text{ lb}) - \frac{1}{\sqrt{5}}F_{DF} + (2000 - 250 - 500 - 500) \text{ lb} = 0$$


$$F_{DF} = 1550\sqrt{5} \text{ lb}$$

$$F_{DF} = 3.47 \text{ kips C} \blacktriangleleft$$

$$\rightarrow \Sigma F_x = 0: 2000 \text{ lb} + \frac{3}{5}(1000 \text{ lb}) - \frac{2}{\sqrt{5}}(1550\sqrt{5} \text{ lb}) + F_{DG} = 0$$


$$F_{DG} = 500 \text{ lb T} \blacktriangleleft$$

PROBLEM 6.55




A roof truss is loaded as shown. Determine the force in members FH , GJ , and GI .

SOLUTION



By symmetry: $A_y = M_y = 2.45 \text{ kips} \uparrow$

$$\rightarrow \Sigma F_x = 0: A_x = 0$$



$$\left(\Sigma M_J = 6 \text{ ft}(0.3 \text{ kip}) - 12 \text{ ft}(2.35 \text{ kips}) + 7 \text{ ft} \left(\frac{4}{\sqrt{17}} F_{GI} \right) = 0 \right.$$

$$F_{GI} = 3.887 \text{ kips}$$

$$F_{GI} = 3.89 \text{ kips T} \blacktriangleleft$$

$$\left(\Sigma M_G = (6 \text{ ft}) F_{HJ} - (4 \text{ ft})(1.0 \text{ kips}) - (10 \text{ ft})(0.3 \text{ kips}) - (16 \text{ ft})(0.1 \text{ kips}) \right.$$

$$+ (16 \text{ ft})(2.45 \text{ kips}) = 0$$


$$F_{HJ} = -5.10 = 5.10 \text{ kips C}$$

By inspection:

$$F_{FH} = F_{HJ} = 5.10 \text{ kips C} \blacktriangleleft$$

$$\uparrow \Sigma F_y = 0: \frac{1}{\sqrt{17}} (3.887 \text{ kips}) + 2.45 \text{ kips} - 1.4 \text{ kips} - \frac{3}{\sqrt{13}} F_{GJ} = 0$$

$$F_{GJ} = 2.40 \text{ kips T} \blacktriangleleft$$




PROBLEM 6.56

A stadium roof truss is loaded as shown. Determine the force in members AB , AG , and FG .

SOLUTION

FBD Section:



$$\text{Note: } \widehat{BG} = \frac{8.4}{12.0}(2.7 \text{ m}) = 1.89 \text{ m}$$

$$\left(\sum M_A = 0: (2.7 \text{ m}) F_{FG} - (3.6 \text{ m})(8 \text{ kN}) - (7.8 \text{ m})(8 \text{ kN}) - (12 \text{ m})(4 \text{ kN}) = 0 \right.$$

$$F_{FG} = 51.56 \text{ kN}$$

$$F_{FG} = 51.6 \text{ kN C} \blacktriangleleft$$


$$\left(\sum M_G = 0: (1.89 \text{ m}) \left(\frac{12}{12.3} F_{AB} \right) - (4.2 \text{ m})(8 \text{ kN}) - (8.4 \text{ m})(4 \text{ kN}) = 0 \right.$$

$$F_{AB} = 36.44 \text{ kN}$$

$$F_{AB} = 36.4 \text{ kN T} \blacktriangleleft$$

$$\left(\sum M_D = 0: (4.2 \text{ m})(8 \text{ kN}) + (8.4 \text{ m})(8 \text{ kN}) - (8.4 \text{ m}) \left(\frac{3}{5} F_{AG} \right) = 0 \right.$$

$$F_{AG} = 20.0 \text{ kN T} \blacktriangleleft$$




PROBLEM 6.57

A stadium roof truss is loaded as shown. Determine the force in members AE, EF, and FJ.

SOLUTION

FBD Section:



$$\sum M_F = 0: (2.7 \text{ m}) \left(\frac{8}{\sqrt{145}} F_{AE} \right) - (3.6 \text{ m})(8 \text{ kN}) - (7.8 \text{ m})(8 \text{ kN}) - (12 \text{ m})(4 \text{ kN}) = 0$$

$$F_{AE} = \frac{17.4}{2.7} \sqrt{145} \text{ kN}$$

$$F_{AE} = 77.6 \text{ kN T} \blacktriangleleft$$


$$\rightarrow \sum F_x = 0: F_{EF} - \frac{8}{\sqrt{145}} \left(\frac{17.4}{2.7} \sqrt{145} \text{ kN} \right) = 0$$

$$F_{EF} = 51.555 \text{ kN}$$

$$F_{EF} = 51.6 \text{ kN C} \blacktriangleleft$$

$$\uparrow \sum F_y = 0: F_{FJ} - \frac{9}{\sqrt{145}} \left(\frac{17.4}{2.7} \sqrt{145} \text{ kN} \right) - (4 + 8 + 8 + 4) \text{ kN} = 0$$

$$F_{FJ} = 82.0 \text{ kN C} \blacktriangleleft$$




PROBLEM 6.58

A vaulted roof truss is loaded as shown. Determine the force in members BE , CE , and DF .

SOLUTION

FBD Truss:




$$\begin{aligned} \sum M_N = 0: & (1.2 \text{ m})(0.2 \text{ kN}) + (1.8 \text{ m})(0.5 \text{ kN}) + (2.88 \text{ m})(0.5 \text{ kN}) + (4.2 \text{ m})(1.3 \text{ kN}) \\ & + (4.8 \text{ m})(0.6 \text{ kN}) + (6.6 \text{ m})(0.7 \text{ kN}) + (8.4 \text{ m})(0.1 \text{ kN}) - (8.4 \text{ m})A_y = 0 \end{aligned}$$

$$A_y = 1.95 \text{ kN} \uparrow$$

$$\rightarrow \sum F_x = 0: A_x = 0$$

FBD Section:



$$\sum M_B = 0: (0.9 \text{ m})F_{CE} - (1.8 \text{ m})(1.95 \text{ kN} - 0.1 \text{ kN}) = 0$$

$$F_{CE} = 3.70 \text{ kN T} \blacktriangleleft$$

PROBLEM 6.58 CONTINUED

$$\left(\sum M_A = 0: (1.8 \text{ m}) \left[\left(\frac{1}{\sqrt{5}} F_{BE} \right) - .7 \text{ kN} \right] + (.9 \text{ m}) \left(\frac{2}{\sqrt{5}} F_{BE} \right) = 0 \right.$$

$$F_{BE} = 0.35\sqrt{5} \text{ kN}$$

$$F_{BE} = 783 \text{ N C} \blacktriangleleft$$


$$\rightarrow \sum F_x = 0: 3.70 \text{ kN} - \frac{2}{\sqrt{5}} (0.35\sqrt{5} \text{ kN}) - \frac{2}{\sqrt{5}} F_{BD} = 0$$

$$F_{BD} = 1.5\sqrt{5} \text{ kN} = 3.35 \text{ kN C}$$

Then by inspection of joint D : $F_{DF} = F_{BD}$

$$\text{so } F_{DF} = 3.35 \text{ kN C} \blacktriangleleft$$


PROBLEM 6.59



A vaulted roof truss is loaded as shown. Determine the force in members HJ , IJ , and GI .


SOLUTION

FBD Truss:



$$\begin{aligned} \sum M_A = 0: & (1.8 \text{ m})(0.7 \text{ kN}) + (3.6 \text{ m})(0.6 \text{ kN}) + (4.2 \text{ m})(1.3 \text{ kN}) + (5.52 \text{ m})(0.5 \text{ kN}) \\ & + (6.6 \text{ m})(0.5 \text{ kN}) + (7.2 \text{ m})(0.2 \text{ kN}) + (8.4 \text{ m})(0.1 \text{ kN}) - (8.4 \text{ m})(N_y) = 0 \\ N_y = & 2.05 \text{ kN} \uparrow \end{aligned}$$

FBD Section:



$$\sum M_J = 0: (1.8 \text{ m})(2.05 - 0.1) \text{ kN} - (0.6 \text{ m})(0.2 \text{ kN}) + (0.45 \text{ m})F_{IK} = 0$$

$$F_{IK} = 7.533 \text{ kN}$$

$$F_{IK} = 7.53 \text{ kN T}$$

PROBLEM 6.59 CONTINUED

$$\left(\sum M_I = 0: (2.88 \text{ m})(2.05 - 0.1) \text{ kN} - (1.68 \text{ m})(0.2 \text{ kN}) - (0.45 \text{ m})\left(\frac{2}{\sqrt{5}}F_{HJ}\right) - (1.08 \text{ m})\left(\frac{1}{\sqrt{5}}F_{HJ}\right) = 0 \right.$$

$$F_{HJ} = 2.3939\sqrt{5} \text{ kN}$$


$$F_{HJ} = 5.35 \text{ kN C} \blacktriangleleft$$

$$\uparrow \sum F_y = 0: -\frac{1}{\sqrt{5}}(2.3939\sqrt{5} \text{ kN}) + \frac{5}{13}F_{IJ} + 2.05 \text{ kN} - 0.5 \text{ kN} - 0.2 \text{ kN} - 0.1 \text{ kN} = 0$$

$$F_{IJ} = 2.974 \text{ kN}$$

$$F_{IJ} = 2.97 \text{ kN C} \blacktriangleleft$$


FBD Joint:



$$\rightarrow \sum F_x = 0: -F_{GI} - \frac{12}{13}(2.974 \text{ kN}) + 7.533 \text{ kN} = 0$$

$$F_{GI} = 4.788 \text{ kN}$$

$$F_{GI} = 4.79 \text{ kN T} \blacktriangleleft$$




PROBLEM 6.60

Determine the force in members AF and EJ of the truss shown when $P = Q = 2$ kips. (Hint: Use section aa .)

SOLUTION


FBD Truss:



$$\left(\sum M_A = 0: (24 \text{ ft}) K_x - (18 \text{ ft})(2 \text{ kips}) - (36 \text{ ft})(2 \text{ kips}) = 0 \right.$$

$$K_x = 4.5 \text{ kips} \rightarrow$$

FBD Section:



$$\left(\sum M_F = 0: (12 \text{ ft})(4.5 \text{ kips}) - (18 \text{ ft})(2 \text{ kips}) - (36 \text{ ft})(2 \text{ kips}) + (36 \text{ ft}) F_{EJ} = 0 \right.$$


$$F_{EJ} = 1.500 \text{ kips T} \blacktriangleleft$$

$$\left(\sum M_J = 0: (18 \text{ ft})(2 \text{ kips}) + (12 \text{ ft})(4.5 \text{ kips}) - (36 \text{ ft}) F_{AF} = 0 \right.$$

$$F_{AF} = 2.50 \text{ kips T} \blacktriangleleft$$


PROBLEM 6.61

Determine the force in members AF and EJ of the truss shown when $P = 2$ kips and $Q = 0$. (Hint: Use section aa .)



SOLUTION


FBD Truss:



$$\left(\sum M_A = 0: (24 \text{ ft}) K_x - (18 \text{ ft})(2 \text{ kips}) = 0 \right.$$

$$K_x = 1.5 \text{ kips} \rightarrow$$

FBD Section:



$$\left(\sum M_F = 0: (12 \text{ ft})(1.5 \text{ kips}) - (18 \text{ ft})(2 \text{ kips}) + (36 \text{ ft}) F_{EJ} = 0 \right.$$

$$F_{EJ} = 0.500 \text{ kip T} \blacktriangleleft$$

$$\left(\sum M_J = 0: (18 \text{ ft})(2 \text{ kips}) + (12 \text{ ft})(1.5 \text{ kips}) - (36 \text{ ft}) F_{AF} = 0 \right.$$

$$F_{AF} = 1.500 \text{ kips T} \blacktriangleleft$$