

Lab-Report

Report No: 08

Course code: ICT-3110

Course title: Operating Systems Lab

Date of Performance:

Date of Submission: 30/09/2020

Submitted by

Name: Md Humayun Kabir

ID:IT-18026

3rd year 1st semester

Session: 2017-2018

Dept. of ICT

MBSTU.

Submitted To

Nazrul Islam

Assistant Professor

Dept. of ICT

MBSTU.

Experiment No : 08

Experiment Name : Implementation of SJF Scheduling Algorithm.

Theory :

Shortest job first(SJF) is a scheduling algorithm, that is used to schedule processes in an operating system. It is a very important topic in Scheduling when compared to round-robin and FCFS Scheduling.

There are two types of SJF

Pre-emptive SJF

Non-Preemptive SJF

These algorithms schedule processes in the order in which the shortest job is done first. It has a minimum average waiting time.

There are 3 factors to consider while solving SJF, they are

1. BURST Time
2. Average waiting time
3. Average turn around time

Non-Preemptive Shortest Job First

Here is an example :

Processes Id	Burst Time	Waiting Time	Turn Around Time
4	3	0	3
1	6	3	9
3	7	9	16
2	8	16	25

Average waiting time = 7

Average turn around time = 13

T.A.T= waiting time + burst time

Working Process :

Code for non-preemptive SJF scheduling Algorithm -

```
#include<stdio.h>
int main()
{
    int bt[20],p[20],wt[20],tat[20],i,j,n,total=0,pos,temp;
    float avg_wt,avg_tat;
    printf("Enter number of processes :");
    scanf("%d",&n);

    printf("\nEnter Burst Time: ");
    for(i=0;i<n;i++)
    {
        printf("p%d:",i+1);
        scanf("%d",&bt[i]);
        p[i]=i+1;
    }

    //sorting of burst times
    for(i=0;i<n;i++)
    {
        pos=i;
        for(j=i+1;j<n;j++)
        {
            if(bt[j]<bt[pos])
                pos=j;
        }

        temp=bt[i];
        bt[i]=bt[pos];
        bt[pos]=temp;

        temp=p[i];
        p[i]=p[pos];
        p[pos]=temp;
    }

    wt[0]=0;
```

```

for(i=1;i<n;i++)
{
    wt[i]=0;
    for(j=0;j<i;j++)
        wt[i]+=bt[j];

    total+=wt[i];
}

avg_wt=(float)total/n;
total=0;

printf("\nProcess\t Burst Time \tWaiting Time\tTurnaround Time");
for(i=0;i<n;i++)
{
    tat[i]=bt[i]+wt[i];
    total+=tat[i];
    printf("\np%d\t\t %d\t\t %d\t\t%d",p[i],bt[i],wt[i],tat[i]);
}

avg_tat=(float)total/n;
printf("\n\nAverage Waiting Time=%f",avg_wt);
printf("\nAverage Turnaround Time=%f\n",avg_tat);
}

```

Output :

```

Enter number of processes :5

Enter Burst Time: p1:4
p2:3
p3:7
p4:1
p5:2

Process      Burst Time      Waiting Time      Turnaround Time
p4           1              0                1
p5           2              1                3
p2           3              3                6
p1           4              6               10
p3           7             10               17

Average Waiting Time=4.000000
Average Turnaround Time=7.400000

Process returned 0 (0x0)   execution time : 14.070 s
Press any key to continue.

```


Code for preemptive SJF Scheduling Algorithm :

```
#include <stdio.h>

int main()
{
    int arrival_time[10], burst_time[10], temp[10];
    int i, smallest, count = 0, time, limit;
    double wait_time = 0, turnaround_time = 0, end;
    float average_waiting_time, average_turnaround_time;
    printf("\nEnter the Total Number of Processes:\t");
    scanf("%d", &limit);
    printf("\nEnter Details of %d Processes\n", limit);
    for(i = 0; i < limit; i++)
    {
        printf("\nEnter Arrival Time:\t");
        scanf("%d", &arrival_time[i]);
        printf("Enter Burst Time:\t");
        scanf("%d", &burst_time[i]);
        temp[i] = burst_time[i];
    }
    burst_time[9] = 9999;
    for(time = 0; count != limit; time++)
    {
        smallest = 9;
        for(i = 0; i < limit; i++)
        {
            if(arrival_time[i] <= time && burst_time[i] < burst_time[smallest] && burst_time[i]
> 0)
            {
                smallest = i;
            }
        }
        burst_time[smallest]--;
        if(burst_time[smallest] == 0)
        {
            count++;
            end = time + 1;
            wait_time = wait_time + end - arrival_time[smallest] - temp[smallest];
            turnaround_time = turnaround_time + end - arrival_time[smallest];
        }
    }
}
```

```
}  
average_waiting_time = wait_time / limit;  
average_turnaround_time = turnaround_time / limit;  
printf("\n\nAverage Waiting Time:\t%f\n", average_waiting_time);  
printf("Average Turnaround Time:\t%f\n", average_turnaround_time);  
return 0;  
}
```

Output :



```
C:\WINDOWS\SYSTEM32\cmd.exe  
Enter the Total Number of Processes: 4  
Enter Details of 4 Processes  
Enter Arrival Time: 1  
Enter Burst Time: 4  
Enter Arrival Time: 2  
Enter Burst Time: 4  
Enter Arrival Time: 3  
Enter Burst Time: 5  
Enter Arrival Time: 4  
Enter Burst Time: 8  
  
Average Waiting Time: 4.750000  
Average Turnaround Time: 10.000000  
  
.....  
(program exited with code: 0)  
Press any key to continue . . .
```

Discussion :

This lab helps to learn non-preemptive and preemptive SJF (Smallest Job First) scheduling algorithm. We have implemented this algorithm using C language. In future we can solve any problem of this algorithm.