PRODUCT DATA SHEET

QUENCHING OIL – TECHNOFLUID Q 39 & QLP 32

Commercial / Pack Name: Q 39 & QLP 32

Product Description

- Highly efficient quenching oils formulated with selected high-quality base oils and advanced additives.
- Excellent oxidation and thermal stability, ensuring long service life of the oil.
- Low volatility minimizes oil loss at elevated operating temperatures.
- Provides uniform and controlled cooling to reduce distortion and cracking of components.
- Designed for fast and accelerated quenching applications requiring consistent metallurgical properties.

Key Performance Benefits

- Ensures rapid heat extraction for improved hardness and metallurgical consistency.
- Maintains stable viscosity over prolonged usage.
- Reduces sludge and deposit formation during operation.
- Enhances surface finish and minimizes oxidation of quenched components.
- Offers reliable performance under severe operating conditions.

Applications

- Recommended for general-purpose quenching operations in manufacturing industries.
- Suitable for quenching of: Moulds and dies, Leaf springs, Disc harrows, Automotive and agricultural components, Heat-treated ferrous components
- Widely used in heat treatment shops, forging units, and metal processing industries.

INDUSTRY PERFORMANCE CHARACTERISTICS

- Rapid and uniform heat extraction
- Consistent hardness development
- Reduced cracking and component distortion
- Excellent thermal stability at elevated operating temperatures
- Low volatility and reduced oil consumption
- Good resistance to oxidation and sludge formation
- Long service life under severe operating conditions
- Reliable metallurgical repeatability
- Fast quenching operations where controlled cooling is critical.

Typical Characteristics

Characteristics	IS 1448	Typical Figures	
		Q 39(Group I)	QLP 32(Group II)
Appearance	—-	Light yellow clear	Transparent
Density at 29.5° C	P:16	0.846	0.841
K.V at 40° C, cSt	P:25	35	29
Viscosity Index	P:56	98	104
Pour Point, °C	P:10	-6	-12
Flash Point, (COC), °C	P:69	212	218
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1b	1b