PRODUCT DATA SHEET

HYDRAULIC OIL – TECHNOFLUID HYDRAULIC OIL HVI

(ISO VG 46 ,68 & 100)

Product Description

- TECHNOFLUID Hydraulic Oil HVI is a premium high-viscosity-index hydraulic fluid formulated from selected high-quality base oils and advanced additive technology.
- Designed to deliver consistent hydraulic performance across a wide temperature range, especially in environments with significant temperature variations.
- Contains anti-wear, anti-oxidant, anti-rust, and anti-foam additives to ensure long oil life and superior system protection.
- Maintains excellent viscosity stability, ensuring smooth system response during cold start-up as well as high-temperature operation.
- Suitable for use in modern industrial and mobile hydraulic systems requiring high VI hydraulic oils.

Key Performance Benefits

- High viscosity index minimizes viscosity changes with temperature fluctuations.
- Excellent anti-wear protection reduces wear of pumps, valves, and hydraulic components.
- Superior oxidation and thermal stability limits sludge and varnish formation.
- Effective rust and corrosion protection safeguards system components.
- Good demulsibility allows rapid water separation, maintaining lubrication efficiency.
- Low foaming tendency and quick air release ensure smooth, responsive hydraulic operation.
- Enhances equipment reliability while reducing maintenance and downtime.

Applications

- Recommended for hydraulic systems operating over wide ambient temperature ranges.
- Suitable for use in:
- Mobile hydraulic equipment exposed to outdoor conditions
- Construction and earth-moving machinery
- Agricultural equipment
- Material handling and lifting systems
- Industrial hydraulic systems requiring stable performance in varying climates
- Compatible with vane, piston, and gear type hydraulic pumps.

Typical Uses

- Hydraulic systems requiring ISO VG 46,68 & 100 high VI oils.
- Equipment subjected to frequent temperature variations or cold start conditions.
- Applications demanding long oil life, stable viscosity, and reliable hydraulic response.

Performance Standards Meets or exceeds:

- DIN 51524 Part 3 (HVLP)
- IS 10522 : 1983 (Reaffirmed)
- Vickers V-104C / Denison HF-0, HF-1, HF-2 *(where applicable)*

Operating Characteristics

- Excellent low-temperature flow properties and high-temperature stability.
- Compatible with commonly used hydraulic system seals, hoses, and elastomers.
- Ensures clean, efficient, and trouble-free hydraulic system operation.

Typical Characteristics

Characteristics	IS 1448	Typical Figures		
TECHNOFLUID HYD HVI		46	68	100
Appearance	----	Clear fluid	Clear fluid	Clear fluid
Density at 15° C	P:16	0.831	0.831	0.830
K.V at 40° C, cSt	P:25	46.7	68.1	100.2
Viscosity Index	P:56	138	139	141
Pour Point, °C	P:10	-15	-15	-15
Flash Point, (COC), °C	P:69	242	242	242
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1	1	1
a) Sequence I	P:67	Nil	Nil	Nil
b) Sequence II		Nil	Nil	Nil
c) Sequence III		Nil	Nil	Nil
Foaming Characteristics /Stability				