PRODUCT DATA SHEET

INDUSTRIAL ENGINE OILS – TECHNOFLUID DIESEL ENGINE OILS

(For Generators, Pumps & Industrial Engines)

Commercial / Pack Name: 15W40 API CI4 PLUS / 15W40 API CF4 / 20W40 API CH4 / SAE 40 CF / SAE 50 CF

Product Description

- TECHNOFLUID Industrial Engine Oils are high-performance diesel engine lubricants formulated to meet the demanding requirements of stationary and mobile industrial engines.
- Manufactured from premium quality base oils and advanced additive technology to provide excellent protection under continuous and heavy-duty operating conditions
- Designed to control deposits, neutralize acidic combustion by-products, and protect engine components from wear and corrosion.
- Suitable for naturally aspirated and turbocharged diesel engines operating on high-sulphur and low-sulphur fuels.
- Available in multiple viscosity grades and performance levels to meet diverse industrial engine requirements.

Key Performance Benefits

- Excellent detergency and dispersancy keep engines clean and free from sludge.
- Superior wear protection extends life of pistons, rings, liners, and bearings.
- High Total Base Number (TBN) helps neutralize acidic combustion products.
- Good thermal and oxidation stability ensures long oil life in continuous operations.
- Reduces oil consumption and minimizes downtime.
- Protects engines against rust and corrosion during idle or standby periods.
- Ensures smooth engine operation and consistent power output.

Applications

Recommended for use in:

- Diesel generator sets (DG sets)
- Industrial diesel engines
- Water pump sets
- Air compressors driven by diesel engines
- Construction and mining equipment
- Agricultural and irrigation engines

Suitable for engines from leading OEMs, subject to recommended API performance level.

Typical Uses

- Continuous and standby power generation systems.
- Engines operating under heavy load and extended running hours.
- Industrial applications requiring reliable engine protection and long drain intervals.

Performance Grades Available

Commonly available in:

- SAE 15W-40 (API CI-4 / CH-4 / CF-4)
- SAE 20W-40
- SAE 40 / SAE 50 (Monograde, where required)

· Meets or exceeds:

- API CF-4 / CH-4 / CI-4 / CI-4 Plus

**OEM-recommended specifications for industrial diesel engines*

Operating Characteristics

- Maintains stable viscosity over prolonged engine operation.
- Compatible with commonly used engine seals and materials.
- Performs reliably in high ambient temperature and dusty operating environments.

Typical Characteristics

Characteristics	Test Method	15W-40 API CI-4 PLUS	15W-40 API CF-4	20W-40 API CH-4	SAE 40 API CF	SAE 50 API CF
Appearance	Visual	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright
Base Oil Type	—	Mineral	Mineral	Mineral	Mineral	Mineral
SAE Grade	SAE J300	15W-40	15W-40	20W-40	SAE 40	SAE 50
API Service Level	—	CI-4 Plus	CF-4	CH-4	CF	CF
Density @ 29.5°C, g/ml	ASTM D4052	0.855	0.860	0.870	0.880	0.880
Kinematic Viscosity @ 40°C, cSt	ASTM D445	110 – 135	110 – 135	140 – 165	150 – 180	220 – 260
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.5 – 16.0	14.5 – 16.0	15.5 – 17.5	14.0 – 16.0	17.5 – 19.5
Viscosity Index	ASTM D2270	≥ 130	≥ 130	≥ 115	≥ 95	≥ 95
Flash Point (COC), °C	ASTM D92	≥ 220	≥ 220	≥ 220	≥ 230	≥ 230
Pour Point, °C	ASTM D97	-21	-21	-15	-6	-6
Total Base Number (TBN), mg KOH/g	ASTM D2896	10 – 12	7 – 9	8 – 10	6 – 8	6 – 8
Sulphated Ash, % wt	ASTM D874	≤ 1.5	≤ 1.3	≤ 1.4	≤ 1.2	≤ 1.2
Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1b	1b	1b	1b	1b
Oxidation Stability	ASTM D943	Excellent	Excellent	Good	Good	Good
Wear Protection	ASTM D4172	Pass	Pass	Pass	Pass	Pass

Foaming Characteristics	ASTM D892	Pass	Pass	Pass	Pass	Pass