PRODUCT DATA SHEET

GREASE – TECHNOFLUID EP GREASE SERIES

(NLGI 000, 00, 0, 1, 2 & 3)

Commercial / Pack Name: GREASE EP (000/ 00 / 0 / 1 / 2 / 3)

Product Description

- TECHNOFLUID EP Grease Series are high-performance extreme pressure greases formulated using high-quality mineral base oils and advanced EP additive technology.
- Designed to provide superior protection to bearings and sliding surfaces operating under heavy loads, shock loads, and severe service conditions.
- Available in a wide range of NLGI grades from semi-fluid to stiff greases, making them suitable for diverse lubrication requirements.
- Offers excellent mechanical stability, load-carrying capacity, and wear protection.
- Suitable for centralized lubrication systems as well as manual greasing applications.

Key Performance Benefits

- Excellent extreme pressure and anti-wear properties protect components under heavy loads.
- High load-carrying capacity reduces bearing and surface wear.
- Good mechanical stability ensures consistent grease structure under shear.
- Effective rust and corrosion protection safeguards metal components.
- Good resistance to water washout and contamination.
- Reduces maintenance frequency and extends equipment service life.
- Wide consistency range allows use in different lubrication systems.

Applications

Recommended for lubrication of:

- Heavy-duty bearings and bushings
- Industrial gear couplings
- Construction and mining machinery

- Agricultural equipment
- Steel plants, crushers, conveyors, and rolling mills

· Suitable for use in:

- Centralized lubrication systems (NLGI 000 / 00 / 0)
- Bearings and general-purpose greasing (NLGI 1 / 2 / 3)

Typical Uses

- Equipment operating under high load, vibration, and shock conditions.
- Applications requiring EP protection and reliable lubrication.
- Systems demanding grease grades suited to seasonal temperature variations.

NLGI Grade Applications (Guidance)

- **NLGI 000 / 00**: Centralized lubrication systems, enclosed gearboxes.
- **NLGI 0**: Central lubrication and low-temperature applications.
- **NLGI 1**: Moderate-speed bearings and general lubrication.
- **NLGI 2**: Most common grade for bearings and chassis lubrication.
- **NLGI 3**: High-temperature or vertical applications requiring stiff grease.

Operating Characteristics

- Maintains consistency over wide operating temperatures.
- Compatible with commonly used bearing metals and seals.
- Performs reliably under severe service and harsh environments.

Typical Characteristics

Characteristics	Test Method	NLGI 000	NLGI 00	NLGI 0	NLGI 1	NLGI 2	NLGI 3
Appearance	Visual	Smooth, semi-fluid	Smooth, semi-fluid	Smooth	Smooth	Smooth	Smooth
Thickener Type	—	Lithium / Lithium EP	Lithium / Lithium EP	Lithium / Lithium EP	Lithium / Lithium EP	Lithium / Lithium EP	Lithium / Lithium EP
Base Oil Type	—	Mineral	Mineral	Mineral	Mineral	Mineral	Mineral
NLGI Grade	ASTM D217	000	00	0	1	2	3

Worked Penetration (60 strokes), 0.1 mm	ASTM D217	445–475	400–430	355–385	310–340	265–295	220–250
Drop Point, °C (Min)	ASTM D2265	180	180	180	185	190	190
Oil Viscosity @ 40°C, cSt	ASTM D445	150–220	150–220	150–220	150–220	150–220	150–220
Four Ball Weld Load, kg (Min)	ASTM D2596	200	200	220	220	250	250
Wear Scar Dia, mm (Max)	ASTM D2266	0.6	0.6	0.55	0.55	0.50	0.50
Copper Corrosion (24 hrs @ 100°C)	ASTM D4048	1a	1a	1a	1a	1a	1a
Water Washout @ 79°C, % loss (Max)	ASTM D1264	6	6	5	5	4	4
Rust Prevention	ASTM D1743	Pass	Pass	Pass	Pass	Pass	Pass
Operating Temperature Range, °C	—	-20 to 120	-20 to 120	-20 to 130	-20 to 130	-20 to 140	-20 to 140