



PRODUCT DATA SHEET

AUTOMOTIVE ENGINE OILS – TECHNOFLUID PCMO

(For Cars, MUVs & SUVs)

Commercial / Pack Name: PCMO (5W30 API SN / 10W40 API SN / 15W40 API CF4 / 15W40 API CI4 PLUS / 20W50 API SN)

Product Description

- TECHNOFLUID Automotive Engine Oils (PCMO – Passenger Car Motor Oils) are premium-quality lubricants formulated for modern petrol, diesel, and CNG passenger vehicles.
- Manufactured from high-quality base oils and advanced additive technology to deliver superior engine cleanliness, wear protection, and fuel efficiency.
- Designed to protect engines operating under severe conditions such as stop-and-go traffic, high temperatures, and long drain intervals.
- Suitable for naturally aspirated and turbocharged engines.
- Available in multiple viscosity grades and API performance levels to meet OEM requirements.

Key Performance Benefits

- Excellent anti-wear protection safeguards critical engine components such as pistons, rings, and camshafts.
- Superior detergency and dispersancy keep engines clean and free from sludge and deposits.
- Provides enhanced protection against oxidation and thermal degradation.
- Ensures smooth engine operation with reduced noise and vibration.
- Improves fuel economy by reducing internal friction.
- Protects engines against rust and corrosion during both operation and idle periods.
- Supports extended oil drain intervals as per OEM recommendations.

Applications

Recommended for use in:

- Passenger cars
- MUVs and SUVs
- Petrol, diesel, and CNG vehicles

Suitable for vehicles operating under:

- City traffic conditions
- Highway and long-distance driving
- High-temperature and dusty environments

Typical Uses

- Daily-driven personal vehicles.
- Vehicles requiring reliable engine protection and consistent performance.
- Modern engines demanding improved cleanliness and fuel efficiency.

Available Grades & Performance Levels

Available in common viscosity grades such as:

- **SAE 5W-30**
- **SAE 10W-30**
- **SAE 10W-40**
- **SAE 15W-40**
- **SAE 20W-50**

Meets or exceeds:

- **API SM / SN**
- **API CF / CH-4/ CI-4 PLUS (for diesel variants)**
- OEM-recommended specifications

Operating Characteristics

- Maintains stable viscosity over a wide range of temperatures.
- Compatible with modern engine seals, gaskets, and emission system components.
- Ensures reliable performance throughout the oil drain interval.

Typical Characteristics

Characteristics	Test Method	5W-30 API SN	10W-30 API SN	10W-40 API SN	15W-40 API CF-4	15W-40 API CI-4 PLUS	20W-50 API SN
Appearance	Visual	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright
Base Oil Type	—	Synthetic / Semi-Synthetic	Semi-Synthetic	Semi-Synthetic	Mineral	Mineral	Mineral
SAE Grade	SAE J300	5W-30	10W-30	10W-40	15W-40	15W-40	20W-50
API Service Level	—	SN	SN	SN	CF-4	CI-4 Plus	SN
Density @ 29.5°C, g/ml	ASTM D4052	0.845	0.860	0.860	0.860	0.855	0.880
Kinematic Viscosity @ 40°C, cSt	ASTM D445	55 – 65	65 – 75	90 – 105	110 – 135	110 – 135	160 – 190
Kinematic Viscosity @ 100°C, cSt	ASTM D445	10.0 – 11.5	10.0 – 11.5	13.5 – 15.5	14.5 – 16.0	14.5 – 16.0	17.0 – 19.0
Viscosity Index	ASTM D2270	≥ 160	≥ 150	≥ 145	≥ 130	≥ 130	≥ 120
Flash Point (COC), °C	ASTM D92	≥ 220	≥ 220	≥ 225	≥ 220	≥ 225	≥ 230
Pour Point, °C	ASTM D97	-36	-30	-27	-21	-21	-12
Total Base Number (TBN), mg KOH/g	ASTM D2896	7 – 9	7 – 9	7 – 9	7 – 9	10 – 12	7 – 9
Sulphated Ash, % wt	ASTM D874	≤ 1.2	≤ 1.2	≤ 1.2	≤ 1.3	≤ 1.5	≤ 1.2
Noack Volatility, % wt	ASTM D5800	≤ 13	≤ 13	≤ 13	≤ 15	≤ 15	≤ 15
Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1b	1b	1b	1b	1b	1b
Foaming Characteristics	ASTM D892	Pass	Pass	Pass	Pass	Pass	Pass
Oxidation Stability	ASTM D943	Excellent	Excellent	Excellent	Excellent	Excellent	Excellent

