



PRODUCT DATA SHEET

HEAT TRANSFER FLUID – TECHNOFLUID HT 32 PREMIUM

Product Description

- TECHNOFLUID HT 32 PREMIUM is a high-performance heat transfer fluid formulated from premium quality Group II base oils.
- Exhibits excellent oxidation and thermal stability, ensuring long operational life under continuous high-temperature conditions.
- Very low volatility reduces fluid loss and minimizes system fouling.
- Designed for efficient heat transfer with consistent performance over extended service intervals.
- Suitable for systems operating at bulk temperatures up to **310°C**, meeting requirements comparable to synthetic heat transfer oils.

Key Performance Benefits

- Provides efficient and uniform heat transfer for precise temperature control.
- Excellent resistance to thermal cracking and oxidation at elevated temperatures.
- Minimizes sludge, varnish, and deposit formation inside heat transfer systems.
- Low vapour pressure ensures safe operation and reduced maintenance.
- Enhances system cleanliness and extends equipment life.
- Maintains stable viscosity over a wide operating temperature range.

Applications

- Recommended for closed and open heat transfer systems.
- Suitable for use in:
 - Textile processing units
 - Plywood and laminate industries
 - Pharmaceutical manufacturing
 - Chemical processing plants

- Food processing (non-food contact systems)
- Plastic, rubber, and resin processing industries

Typical Uses

- Heat transfer systems requiring stable performance at high bulk temperatures.
- Industrial processes demanding consistent heating and cooling cycles.
- Applications where low volatility and long fluid life are critical.

Operating Characteristics

- Reliable performance in continuous and intermittent high-temperature operations.
- Compatible with standard heat transfer equipment and system materials.
- Reduces downtime and overall operating costs

Characteristics	Test Method		Typical Figures
	IS 1448 (P)	ASTM	
Appearance	--	Visual	Clear Fluid
Colour, Visual Observation	--	--	Transparent
Kinematic Viscosity, cSt(Typical) at 40°C at 100°C	P:25	D 445	30 6
Viscosity Index	P:56	D 2270	104
Auto Ignition Temp., °C		E 659	380
Fire Point, °C		D 92	252
Pour Point, °C	P:10	D 97	- 12
Flash Point, (COC), °C	P:69	D 92	210
Copper corrosion @100°C for 3 hrs	P:15	D 130	1a
Total Acidity,mg KOH/g	P:2	D 664	0.13
Boiling Range, °C	Under	D 2887	
Initial, IBP	Vacuum		352
Final, FBP	Distillation		499
Ash, % wt.	P:4	D 482	0.002
CCR, % mass	--	D 189	0.0038