



PRODUCT DATA SHEET

INDUSTRIAL GEAR OILS – TECHNOFLUID GEAR OILS (ISO VG 100, 150, 220, 320 & 460)

Commercial / Pack Name: GEAR EP 100 / 150 / 220 / 320 / 460

Product Description

- TECHNOFLUID Industrial Gear Oils are high-performance extreme pressure (EP) lubricants formulated from carefully selected high-quality base oils and advanced additive systems.
- Designed to provide superior protection to industrial gear systems operating under heavy loads, shock loads, and high temperatures.
- Offer excellent oxidation and thermal stability, ensuring long oil life and consistent performance.
- Provide effective protection against wear, rust, and corrosion of ferrous and non-ferrous components.
- Suitable for both circulation and splash lubrication systems.

Key Performance Benefits

- Excellent extreme pressure and anti-wear properties reduce gear tooth wear and micropitting.
- High load-carrying capacity ensures reliable operation under severe operating conditions.
- Superior oxidation stability minimizes sludge, varnish, and deposit formation.
- Good demulsibility allows rapid separation of water, maintaining lubrication efficiency.
- Low foaming tendency ensures uninterrupted oil film and smooth gear operation.
- Protects gears, bearings, and seals, extending equipment service life and reducing maintenance costs.

Applications

- Cement, steel, and rolling mills
- Sugar, paper, and textile industries
- Power plants and mining equipment
- Crushers, conveyors, and gear reducers
- Machine tools and industrial gearboxes
- Can also be used in plain and rolling bearings, sliding surfaces, chain drives, and couplings where EP-type oils are required.

Typical Uses

- Gear systems operating under high loads and shock conditions.
- Applications requiring reliable lubrication at operating temperatures up to 100°C (or as per system design).
- Industrial equipment demanding long drain intervals and consistent performance.

Performance Standards Meets or exceeds:

- AGMA 250.04 (EP)
- IS 8408 (EP Gear Oils)
- DIN 51517 Part 3 (CLP) (*where applicable*)

Operating Characteristics

- Maintains stable viscosity over prolonged operating periods.
- Non-corrosive to copper and bronze components.
- Compatible with commonly used gear materials, seals, and elastomers.

Typical Characteristics

Characteristics	Test Method	ISO VG 100	ISO VG 150	ISO VG 220	ISO VG 320	ISO VG 460
Appearance	Visual	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright
Colour	ASTM D1500	≤ 3.0	≤ 3.0	≤ 3.0	≤ 3.0	≤ 3.0
Base Oil Type	—	Mineral	Mineral	Mineral	Mineral	Mineral
Density @ 15°C, g/ml	ASTM D4052	0.865	0.868	0.870	0.875	0.880
Kinematic Viscosity @ 40°C, cSt	ASTM D445	100	150	220	320	460
Kinematic Viscosity @ 100°C, cSt	ASTM D445	11.0	14.5	19.0	24.5	30.5
Viscosity Index	ASTM D2270	≥ 95	≥ 95	≥ 95	≥ 95	≥ 95
Flash Point (COC), °C	ASTM D92	≥ 220	≥ 225	≥ 230	≥ 235	≥ 240
Pour Point, °C	ASTM D97	-6	-6	-6	-6	-6

Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1b	1b	1b	1b	1b
Rust Prevention	ASTM D665	Pass	Pass	Pass	Pass	Pass
Water Demulsibility @ 54°C	ASTM D1401	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0
Foaming Characteristics	ASTM D892	Pass	Pass	Pass	Pass	Pass
Oxidation Stability	ASTM D943	Excellent	Excellent	Excellent	Excellent	Excellent
Load Carrying (FZG Stage)	DIN 51354	≥ 12	≥ 12	≥ 12	≥ 12	≥ 12