



PRODUCT DATA SHEET

TECHNOFLUID GEAR LUBE EP SERIES

(ISO VG 150 / 220 / 320 / 460)

Commercial / Pack Name: GEAR LUBE EP (150 / 220 / 320 / 460)

Product Description

- TECHNOFLUID Gear Lube EP Series are **high pressure industrial gear oils** formulated using good-**quality mineral base oils** and **advanced EP additive technology**.
- Designed to provide protection against **wear, pitting, scuffing, and micropitting** under heavy load and shock load conditions.
- Exhibits good **thermal and oxidation stability**, ensuring long oil life even in severe operating environments.
- Provides reliable lubrication for enclosed industrial gearboxes and gear systems.

Key Performance Benefits

- High **pressure and load-carrying capacity**.
- Protection against **gear tooth wear and surface fatigue**.
- Good **demulsibility** ensures rapid separation from water.
- Good **rust and corrosion protection**.
- Low foaming tendency for smooth circulation.
- Long service life reduces maintenance and downtime.

Applications

Recommended for:

- Enclosed industrial gearboxes
- Spur, helical, bevel, and worm gears
- Bearings and circulating lubrication systems

Suitable for **cement, steel, sugar, power plants, mining, and heavy industries**.

Compatible with **splash and forced lubrication systems**.

Typical Characteristics

Characteristics	Test Method	ISO VG 150	ISO VG 220	ISO VG 320	ISO VG 460
Appearance	Visual	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright
Colour	ASTM D1500	≤ 4.0	≤ 4.0	≤ 4.0	≤ 4.0
Base Oil Type	—	Mineral	Mineral	Mineral	Mineral
Viscosity Grade	ISO 3448	150	220	320	460
Density @ 15°C, g/ml	ASTM D4052	0.860	0.860	0.860	0.860
Kinematic Viscosity @ 40°C, cSt	ASTM D445	150	220	320	460
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.5	19.0	24.5	30.5
Viscosity Index	ASTM D2270	≥ 95	≥ 95	≥ 95	≥ 95
Flash Point (COC), °C	ASTM D92	≥ 210	≥ 210	≥ 210	≥ 210
Pour Point, °C	ASTM D97	-6	-6	-6	-6
Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1b	1b	1b	1b
Four Ball Weld Load, kg	ASTM D2596	≥ 315	≥ 315	≥ 315	≥ 315
FZG Load Stage	DIN 51354	≥ 12	≥ 12	≥ 12	≥ 12
Rust Prevention	ASTM D665	Pass	Pass	Pass	Pass
Demulsibility @ 54°C	ASTM D1401	40/40/0	40/40/0	40/40/0	40/40/0
Foaming Characteristics	ASTM D892	Pass	Pass	Pass	Pass
Oxidation Stability	ASTM D943	Excellent	Excellent	Excellent	Excellent

