



PRODUCT DATA SHEET

TECHNOFLUID GREASE WR-2 (Water Resistant Grease)

Commercial / Pack Name: GREASE WR2

Product Description

- TECHNOFLUID WR-2 is a **high-performance water-resistant grease** formulated using **high-quality mineral base oils** and **special calcium / lithium-calcium soap thickener**.
- Designed to provide excellent lubrication and protection in **wet, humid, and water-wash environments**.
- Exhibits strong adhesion to metal surfaces, ensuring the grease remains in place even under continuous water exposure.
- Suitable for automotive, industrial, agricultural, and marine-related applications.

Key Performance Benefits

- Excellent **water resistance and wash-off protection**
- Strong **adhesion and mechanical stability**
- Good **load-carrying and anti-wear performance**
- Reliable **rust and corrosion protection**
- Stable performance under moderate temperatures
- Extended re-lubrication intervals in wet conditions

Applications

Recommended for:

- Wheel bearings
- Chassis and suspension components
- Agricultural machinery
- Construction equipment
- Water pumps and exposed bearings

Suitable for applications where **frequent water contact** is present.

Typical Characteristics

Characteristics	Test Method	Typical Figures
Appearance	Visual	Smooth, buttery
Colour	Visual	Brownish / Dark
Thickener Type	—	Calcium / Lithium-Calcium Soap
Base Oil Type	—	Mineral
NLGI Grade	ASTM D217	2
Worked Penetration (60 strokes), 0.1 mm	ASTM D217	265 – 295
Drop Point, °C (Min)	ASTM D2265	≥ 180
Base Oil Viscosity @ 40°C, cSt	ASTM D445	140 – 180
Four Ball Weld Load, kg	ASTM D2596	≥ 200
Wear Scar Dia, mm	ASTM D2266	≤ 0.55
Copper Corrosion (24 hrs @ 100°C)	ASTM D4048	1a
Water Washout @ 79°C, % loss	ASTM D1264	≤ 3
Rust Prevention	ASTM D1743	Pass
Mechanical Stability	ASTM D217	Good
Operating Temperature Range, °C	—	-10 to 120