



PRODUCT DATA SHEET

TEXTILE LUBRICANT – TECHNOFLUID KNITTING OIL

Product Description

- TECHNOFLUID Knitting Oil is a premium-quality textile lubricant specially formulated for lubrication of knitting machine components.
- Manufactured from carefully selected highly refined base oils with advanced additive technology to ensure smooth and trouble-free knitting operations.
- Provides excellent lubricity while maintaining low volatility and low misting characteristics.
- Designed to minimize yarn breakage and needle wear, ensuring consistent fabric quality.
- Easily washable from finished fabrics without staining or residue.

Key Performance Benefits

- Excellent lubricating properties reduce friction between needles, sinkers, and cams.
- Minimizes needle wear and machine downtime.
- Low volatility reduces oil consumption and oil mist formation.
- Non-staining formulation ensures clean fabric appearance.
- Excellent washability allows easy removal during fabric processing.
- Provides good oxidation stability, extending oil life during continuous operations.
- Improves machine efficiency and fabric uniformity.

Applications Recommended for lubrication of:

- Circular knitting machines
- Flat knitting machines
- Hosiery and garment knitting machines

Suitable for use with:

- Cotton, polyester, nylon, and blended yarns

Applicable in high-speed knitting operations.

Typical Uses

- Textile knitting operations requiring clean, non-staining lubrication.
- Machines operating continuously at high speeds.
- Applications demanding excellent washability and fabric cleanliness.

Operating Characteristics

- Maintains stable viscosity during prolonged machine operation.
- Compatible with commonly used textile machine materials and seals.
- Low odor and operator-friendly formulation.

Typical Characteristics

Characteristics	Test Method	Typical Figures
Appearance	Visual	Clear & Bright
Colour	ASTM D1500	≤ 1.5
Base Oil Type	—	Highly Refined Mineral
Density @ 15°C, g/ml	ASTM D4052	0.860 – 0.870
Kinematic Viscosity @ 40°C, cSt	ASTM D445	20 – 30
Kinematic Viscosity @ 100°C, cSt	ASTM D445	4.0 – 5.5
Viscosity Index	ASTM D2270	≥ 95
Flash Point (COC), °C	ASTM D92	≥ 190
Pour Point, °C	ASTM D97	-6
Volatility	ASTM D972	Low
Washability	In-house	Excellent
Staining Tendency	In-house	Non-staining
Odour	—	Mild
Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1a
Oxidation Stability	ASTM D943	Excellent
Mist Formation	In-house	Very Low

