



PRODUCT DATA SHEET

TEXTILE LUBRICANT – TECHNOFLUID WARPING OIL

Commercial / Pack Name: WARPING OIL

Product Description

- TECHNOFLUID Warping Oil is a premium-quality textile lubricant specially formulated for warping and sizing preparatory processes.
- Manufactured from highly refined base oils and advanced additives to ensure smooth yarn movement and consistent tension control.
- Designed to reduce friction between yarns and machine parts, minimizing yarn breakage during high-speed warping operations.
- Provides excellent lubricity with controlled volatility and low misting.
- Easily washable from yarn and fabric without staining or residue.

Key Performance Benefits

- Excellent lubrication ensures smooth yarn passage and uniform beam formation.
- Reduces yarn hairiness, breakage, and fly generation.
- Maintains consistent yarn tension, improving fabric quality.
- Low volatility minimizes oil consumption and mist formation.
- Non-staining and easily washable formulation ensures clean fabric appearance.
- Good oxidation stability provides reliable performance during continuous operation.
- Improves machine efficiency and reduces downtime.

Applications

Recommended for lubrication in:

- Warping machines
- Beam warping and sectional warping operations

Suitable for use with:

- Cotton, polyester, viscose, and blended yarns

Applicable in high-speed textile processing environments.

Typical Uses

- Yarn warping operations requiring smooth lubrication and uniform tension.
- Textile units focused on high productivity and reduced yarn waste.
- Applications demanding clean operation and easy washability.

Operating Characteristics

Maintains stable viscosity throughout prolonged machine operation.

Compatible with commonly used textile machinery components and seals.

Low odor and operator-friendly formulation.

Typical characteristics

Characteristics	Test Method	Typical Figures
Appearance	Visual	Clear & Bright
Colour	ASTM D1500	≤ 1.5
Base Oil Type	—	Highly Refined Mineral
Density @ 15°C, g/ml	ASTM D4052	0.860 – 0.875
Kinematic Viscosity @ 40°C, cSt	ASTM D445	25 – 40
Kinematic Viscosity @ 100°C, cSt	ASTM D445	5.0 – 7.0
Viscosity Index	ASTM D2270	≥ 95
Flash Point (COC), °C	ASTM D92	≥ 195
Pour Point, °C	ASTM D97	-6
Volatility	ASTM D972	Low
Washability	In-house	Excellent
Staining Tendency	In-house	Non-staining
Odour	—	Mild
Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1a
Oxidation Stability	ASTM D943	Excellent
Yarn Friction Reduction	In-house	Very Good

