



PRODUCT DATA SHEET

WET BRAKE OIL – TECHNOFLUID UTTO (UNIVERSAL TRACTOR TRANSMISSION OIL)

Commercial / Pack Name: UTTO (WET BRAKE OIL)

Product Description

- TECHNOFLUID Wet Brake Oil (UTTO) is a high-performance multifunctional lubricant specially formulated for use in tractors and off-highway equipment with wet brake systems.
- Designed to lubricate transmissions, final drives, differentials, hydraulic systems, and wet brakes using a single oil.
- Formulated from high-quality base oils and advanced additive technology to provide controlled friction characteristics for smooth wet brake operation.
- Effectively suppresses wet brake noise and chatter while ensuring positive brake engagement.
- Suitable for agricultural, construction, and earth-moving equipment operating under severe conditions.

Key Performance Benefits

- Excellent friction control eliminates wet brake noise and chatter.
- Superior anti-wear and extreme pressure performance protects gears, bearings, and hydraulic components.
- Provides smooth transmission performance and reliable power transfer.
- Good thermal and oxidation stability ensures long oil life.
- Effective rust and corrosion protection safeguards metal components.
- Good seal compatibility prevents leakage and seal deterioration.
- Reduces maintenance costs by allowing use of a single oil for multiple applications.

Applications Recommended for use in:

- Tractors with wet brake and clutch systems
- Tractor transmissions, differentials, and final drives
- Hydraulic systems of agricultural and off-highway equipment
- Construction and earth-moving machinery requiring UTTO

Suitable for equipment from various OEMs where UTTO-type oil is specified.

Typical Uses

- Agricultural and off-highway machinery requiring a universal transmission and hydraulic oil.
- Equipment operating under heavy loads and severe field conditions.
- Systems demanding reliable wet brake performance and gear protection.

Performance Standards

 Meets or exceeds requirements of:

- API GL-4
- ALLISON C-3 / C-4
- CASE MAT 3505 / 3525
- CATERPILLAR TO-2
- FORD ESN-M2C-134 C/D

Operating Characteristics

- Maintains stable viscosity and friction properties over wide temperature ranges.
- Compatible with commonly used seals, elastomers, and friction materials.
- Ensures clean, efficient, and trouble-free operation of tractor systems.

Typical Characteristics

Characteristics	Test Method	Typical Figures
Appearance	Visual	Clear & Bright
Colour	ASTM D1500	≤ 3.0
Base Oil Type	—	Mineral
Fluid Type	—	UTTO (Transmission / Hydraulic / Wet Brake)
Density @ 29.5°C, g/ml	ASTM D4052	0.845
Kinematic Viscosity @ 40°C, cSt	ASTM D445	55 – 65
Kinematic Viscosity @ 100°C, cSt	ASTM D445	9.0 – 10.5
Viscosity Index	ASTM D2270	≥ 140
Flash Point (COC), °C	ASTM D92	≥ 210
Pour Point, °C	ASTM D97	-23

Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1a
Wet Brake Friction Performance	OEM / In-house	Excellent (No chatter)
Anti-Wear Performance	ASTM D4172	Good
Rust Prevention	ASTM D665	Pass
Demulsibility @ 54°C	ASTM D1401	40/40/0
Foaming Characteristics	ASTM D892	Pass
Oxidation Stability	ASTM D943	Excellent
Seal Compatibility	In-house	Excellent