



PRODUCT DATA SHEET

FOOD GRADE HYDRAULIC OIL

Commercial / Pack Name: ISO VG 22 / 32 / 46 / 68 / 100

Product Description

- Premium food-grade hydraulic oils formulated from highly refined white mineral base oils and food-grade performance additives.
- Designed for hydraulic systems where incidental food contact may occur.
- Excellent oxidation stability and long service life.
- Outstanding anti-wear protection, rust prevention and corrosion resistance.
- Available in ISO VG 22, 32, 46, 68 and 100 viscosity grades.

Key Performance Benefits

- Excellent anti-wear performance for hydraulic pumps and valves.
- High oxidation and thermal stability.
- Good water separation and filterability.
- Superior rust and corrosion protection.
- Long equipment life with reduced maintenance.

Applications

- Food processing plants.
- Beverage manufacturing facilities.
- Pharmaceutical and cosmetic industries.
- Packaging and bottling equipment.
- Hydraulic systems requiring food-grade lubricants.

INDUSTRY PERFORMANCE CHARACTERISTICS

- Excellent anti-wear protection
- High oxidation stability
- Good demulsibility
- Excellent air release
- Low foaming tendency
- Long service life

Typical Characteristics

Characteristics	ISO VG 22	ISO VG 32	ISO VG 46	ISO VG 68	ISO VG 100
Appearance	Clear	Clear	Clear	Clear	Clear
Density @29.5°C	0.845	0.850	0.855	0.860	0.865
K.V @40°C cSt	22	32	46	68	100
Viscosity Index	100	100	100	100	100
Pour Point °C	-18	-18	-15	-12	-9
Flash Point (COC) °C	200	210	220	230	240

