



PRODUCT DATA SHEET

REAR AXLE OIL (JCB & OFF-HIGHWAY EQUIPMENT)

Commercial / Pack Name: Rear Axle Oil (JCB) SAE 80W / SAE 90

Product Description

- Premium rear axle oil formulated with high quality mineral base oils and advanced extreme pressure (EP) additives.
- Designed for rear axles, differentials and final drives used in JCB construction equipment and off-highway machinery.
- Provides outstanding protection under heavy shock loads and severe operating conditions.
- Excellent oxidation stability, rust and corrosion protection for extended service life.
- Suitable for equipment operating in construction, mining and earthmoving applications.

Key Performance Benefits

- Excellent extreme pressure and anti-wear performance.
- High load carrying capability for heavily loaded gears.
- Reduces gear scuffing, pitting and wear.
- Excellent thermal and oxidation stability.
- Protects against rust, corrosion and foam formation.

Applications

- JCB backhoe loaders and construction equipment.
- Rear axle assemblies and final drives.
- Differentials of earthmoving and off-highway equipment.

- Suitable where EP gear lubricants meeting API GL-5 or equipment manufacturer recommendations are specified.

INDUSTRY PERFORMANCE CHARACTERISTICS

- Outstanding EP protection
- Excellent load carrying capability
- Superior wear protection
- Excellent oxidation stability
- Extended component life

Typical Characteristics

Characteristics	SAE 80W	SAE 90
Appearance	Bright & Clear	Bright & Clear
Density @29.5°C	0.890	0.895
K.V @40°C cSt	75	180
Viscosity Index	105	95
Flash Point (COC) °C	210	220
Pour Point °C	-27	-12

