



PRODUCT DATA SHEET

TECHNOFLUID SPINDLE OIL

Commercial / Pack Name: ISO VG 2 / 5 / 10 / 12 / 22

Product Description

- Premium low-viscosity spindle oils formulated from highly refined base oils.
- Designed for high-speed textile spindles, precision bearings and light-duty machine tools.
- Excellent oxidation stability and rust protection.
- Low friction characteristics ensure smooth operation and reduced power consumption.
- Available in ISO VG 2, 5, 10, 12 and 22 grades.

Key Performance Benefits

- Excellent lubrication of high-speed bearings.
- Superior oxidation stability for long oil life.
- Excellent anti-rust and anti-corrosion protection.
- Low foaming and rapid air release.
- Minimizes wear and improves equipment efficiency.

Applications

- Textile spinning and weaving machinery.
- High-speed spindles and precision bearings.
- Machine tool spindles and light-duty circulating systems.
- General low-viscosity industrial lubrication.

INDUSTRY PERFORMANCE CHARACTERISTICS

- Excellent oxidation stability
- Low friction characteristics
- Excellent rust protection
- Low foaming tendency
- Long service life

Typical Characteristics

Characteristics	ISO VG 2	ISO VG 5	ISO VG 10	ISO VG 12	ISO VG 22
Appearance	Clear	Clear	Clear	Clear	Clear
Density @29.5°C	0.830	0.835	0.840	0.842	0.845
K.V @40°C cSt	2	5	10	12	22
Viscosity Index	100	100	100	100	100
Pour Point °C	-24	-21	-18	-18	-15
Flash Point (COC) °C	120	145	165	175	195

