



PRODUCT DATA SHEET

TECHNOFLUID TRANSMISSION CF4 SAE 30

Product Description

TECHNOFLUID Transmission CF-4 SAE 30 is a premium heavy-duty transmission and drivetrain lubricant formulated from highly refined mineral base oils and advanced additive technology. It is designed for powershift transmissions, torque converters, final drives, hydraulic systems, and wet brake applications used in construction, mining, earthmoving, and agricultural equipment. The product provides excellent wear protection, oxidation stability, friction control, and long service life under severe operating conditions.

Applications

- JCB Equipment Transmissions
- Powershift Transmissions
- Torque Converters
- Final Drives
- Off-Highway Equipment
- Construction & Mining Machinery
- Loaders, Excavators & Backhoe Loaders
- Agricultural Machinery
- Wet Brake Systems

Performance Level / Specifications Meets / Suitable for:

- API CF-4
- Allison C-4
- Caterpillar TO-2
- Suitable for applications requiring SAE 30 Transmission Fluid

Typical Technical Characteristics

Characteristics	Test Method	Typical Value
-----------------	-------------	---------------

Appearance	Visual	Clear & Bright
Colour	ASTM D1500	Red
Density @ 29.5°C (g/cm ³)	ASTM D4052	0.870 – 0.890
Kinematic Viscosity @ 40°C (cSt)	ASTM D445	80 – 100
Kinematic Viscosity @ 100°C (cSt)	ASTM D445	9 – 12
Viscosity Index	ASTM D2270	≥ 95
Flash Point (COC), °C	ASTM D92	210
Pour Point, °C	ASTM D97	≤ -6
Copper Corrosion (3h @100°C)	ASTM D130	1a
Foaming Characteristics	ASTM D892	Pass
Oxidation Stability	ASTM D943	Excellent

Key Features & Benefits

- Excellent anti-wear protection for gears and bearings
- Superior oxidation and thermal stability
- Smooth clutch and wet brake performance
- Excellent rust and corrosion protection
- High resistance to foaming
- Extended oil drain intervals
- Good seal compatibility
- Reduced transmission noise and wear