



## PRODUCT DATA SHEET

### TECHNOFLUID WHITE OIL ISO VG 12 / 32 / 100

*Commercial / Pack Name: ISO VG 12 / 32 / 100*

#### Product Description

- Highly refined, colourless, odourless and chemically stable white mineral oils manufactured from premium quality base oils.
- Excellent purity with low aromatic content and high oxidation stability.
- Provides outstanding lubricity, water-white appearance and long service life.
- Non-staining and suitable where clean lubrication is essential.
- Available in ISO VG 12, ISO VG 32 and ISO VG 100 viscosity grades.

#### Key Performance Benefits

- High oxidation resistance and thermal stability.
- Excellent colour stability and low volatility.
- Good rust protection and anti-foam characteristics.
- Safe for applications requiring clean, non-staining mineral oil.
- Consistent performance over a wide operating temperature range.

#### Applications

- Textile machinery and fibre processing.
- Pharmaceutical, cosmetic and personal care manufacturing (technical-grade applications as specified).
- Food packaging machinery and general clean lubrication applications where appropriate.
- Plastic, rubber and chemical processing.

- General industrial lubrication requiring colourless mineral oil.

## INDUSTRY PERFORMANCE CHARACTERISTICS

- High purity and water-white appearance
- Excellent oxidation stability
- Low odour and non-staining performance
- Reliable viscosity characteristics
- Long service life

## Typical Characteristics

| Characteristics    | ISO VG 12   | ISO VG 32    | ISO VG 100  |
|--------------------|-------------|--------------|-------------|
| Appearance         | Water White | Water White  | Water White |
| Density @29.5°C    | 0.805 -0.85 | 0.830 -0.845 | 0.865       |
| K.V @40°C cSt      | 11-14       | 30-32        | 95-105      |
| Viscosity Index    | 95          | 98           | 100         |
| Pour Point °C      | -9          | -9           | -6          |
| Flash Point COC °C | >160        | 210          | >250        |

