



PRODUCT DATA SHEET

TECHNOFLUID BRAKE FLUID (DOT 3 / DOT 4 / DOT 5)

Product Description

TECHNOFLUID BRAKE FLUID is a high-performance hydraulic brake fluid range developed for reliable and safe operation of automotive and hydraulic braking systems. The range is available in DOT 3, DOT 4 and DOT 5 grades to suit the requirements specified by vehicle manufacturers.

DOT 3 and DOT 4 grades are glycol-ether based brake fluids with high boiling points, excellent corrosion protection and good compatibility with brake-system seals and hoses. DOT 5 is a silicone-based brake fluid intended only for systems specifically designed for silicone brake fluid and must not be mixed with glycol-based DOT 3/DOT 4 fluids.

Typical Characteristics

Property	Test Method	DOT 3	DOT 4	DOT 5
Product Type	—	Glycol-Ether Brake Fluid	Glycol-Ether Brake Fluid	Silicone Brake Fluid
Appearance	Visual	Clear to Amber	Clear to Amber	Clear / Translucent
Density @ 20°C	ASTM D4052	1.04–1.07 g/cm ³	1.04–1.08 g/cm ³	0.96–1.00 g/cm ³
Dry Equilibrium Reflux Boiling Point	FMVSS 116 / SAE J1703 / J1704	>230°C	≥250°C	≥260°C
Wet Equilibrium Reflux Boiling Point	FMVSS 116 / SAE J1703 / J1704	>145°C	≥160°C	≥180°C
Kinematic Viscosity @ -40°C	FMVSS 116	≤1500 cSt	≤1500 cSt	≤900 cSt
Kinematic Viscosity @ 100°C	FMVSS 116	≥1.5 cSt	≥1.5 cSt	≥1.5 cSt
pH Value	FMVSS 116	7.0–11.5	7.0–11.5	7.0–11.0
Water Content	ASTM D1123 / equivalent	≤0.20%	≤0.20%	≤0.20%
Base Fluid Type	—	Glycol Ether	Glycol Ether / Borate Ester	Silicone
Performance Level	—	DOT 3 / FMVSS 116	DOT 4 / FMVSS 116	DOT 5 / FMVSS 116

Key Benefits

- - High dry and wet boiling points for reliable braking performance
- - Excellent protection against corrosion of brake-system metal components
- - Good lubrication and wear protection of hydraulic components
- - Good compatibility with brake-system seals and hoses when used as specified
- - Stable performance over a wide operating temperature range

- - Good resistance to vapor lock under demanding braking conditions
- - Available in DOT 3, DOT 4 and DOT 5 grades
- - Suitable for passenger cars, commercial vehicles and motorcycles where the specified grade is required
- - Consistent quality for dependable braking-system operation

Typical Applications

TECHNOFLUID BRAKE FLUID is recommended for use in:

- - Disc and drum brake hydraulic systems
- - Passenger cars
- - Commercial vehicles
- - Motorcycles and scooters
- - Hydraulic clutch systems where the specified brake fluid grade is approved
- - General automotive hydraulic braking applications

Handling & Storage

- - Store in clean, dry and covered conditions.
- - Keep containers tightly closed and protected from moisture.
- - Use only clean, dry equipment and containers during handling.
- - Avoid prolonged exposure to direct sunlight and excessive heat.
- - Recommended storage temperature: 5°C to 40°C.

Health & Safety

Avoid prolonged skin and eye contact. Wear appropriate protective equipment during handling. Brake fluid may damage vehicle paintwork; clean spills immediately. Refer to the latest Safety Data Sheet (SDS) before use.

Disclaimer

The information contained herein is based on current manufacturing data and is believed to be accurate. Typical values are not to be construed as product specifications and may vary slightly within normal manufacturing tolerances. Vehicle manufacturer recommendations must always be followed. DOT 5 silicone-based fluid must not be mixed with glycol-based DOT 3 or DOT 4 fluids.