



PRODUCT DATA SHEET

TECHNOFLUID FOOD GRADE GEAR OIL

Commercial / Pack Name: ISO VG 220 / 320

Product Description

- Premium food-grade gear oils formulated from highly refined white mineral base oils and food-grade performance additives.
- Designed for enclosed gear systems where incidental food contact may occur.
- Excellent load carrying capability and anti-wear performance.
- Superior oxidation stability for extended lubricant service life.
- Available in ISO VG 220 and ISO VG 320 viscosity grades.

Key Performance Benefits

- Excellent protection against gear wear and micropitting.
- Outstanding oxidation and thermal stability.
- High load carrying capacity.
- Excellent rust and corrosion protection.
- Long service life with reduced maintenance.

Applications

- Enclosed gearboxes in food and beverage processing plants.
- Bakery, dairy, beverage and meat processing equipment.
- Pharmaceutical and cosmetic manufacturing machinery.
- Food packaging and conveyor drive systems.

INDUSTRY PERFORMANCE CHARACTERISTICS

- Excellent EP and anti-wear performance
- High oxidation stability
- Excellent rust and corrosion protection
- Low foaming tendency
- Long lubricant life

Typical Characteristics

Characteristics	ISO VG 220	ISO VG 320
Appearance	Clear	Clear
Density @29.5°C	0.870	0.875
K.V @40°C cSt	220	320
Viscosity Index	95	95
Pour Point °C	-9	-6
Flash Point (COC) °C	250	260

