



PRODUCT DATA SHEET

TECHNOFLUID P 165

Product Description

TECHNOFLUID P 165 is a premium-quality Rubber Process Oil manufactured from highly refined API Group II base oils. It is specially developed for use in rubber compounding and processing operations where excellent thermal stability, high flash point, and consistent viscosity are required.

The product exhibits excellent compatibility with a wide range of elastomers and processing chemicals while providing improved filler dispersion, enhanced processability, and uniform mixing. Its high purity, low volatility, and transparent appearance make it suitable for modern rubber manufacturing processes.

Typical Characteristics

Property	Test Method	Typical Value
Product Type	—	Rubber Process Oil
Base Oil Type	—	API Group II
Appearance	Visual	Clear & Transparent
Color	Visual	Water White to Pale
Density @ 15°C	ASTM D4052	0.860 g/cm ³
Kinematic Viscosity @ 40°C	ASTM D445	120–130 cSt
Flash Point (COC)	ASTM D92	>260°C
Pour Point	ASTM D97	Below -6°C (Typical)
Sulphur Content	ASTM	Low

	D4294	
Volatility	ASTM D5800	Low
Oxidation Stability	ASTM D943	Excellent
Aromatic Content	—	Very Low
Compatibility	—	Suitable for most natural and synthetic rubber compounds

Key Benefits

- - Manufactured from premium API Group II base oils
- - Excellent processability during rubber mixing
- - Improves dispersion of fillers and additives
- - High flash point for safer plant operation
- - Excellent thermal and oxidation stability
- - Low volatility, minimizing oil loss during processing
- - Consistent viscosity for uniform batch quality
- - Clean, transparent appearance
- - Low aromatic content compared to conventional process oils
- - Suitable for modern rubber compounding operations

Typical Applications

TECHNOFLUID P-165 is recommended for use in:

- - Tyre manufacturing
- - Rubber hoses
- - Conveyor belts
- - Rubber mats
- - Footwear compounds
- - Automotive rubber components
- - Molded rubber goods
- - Extruded rubber products
- - General-purpose rubber compounding

Handling & Storage

- - Store in clean, dry and covered conditions.
- - Keep containers tightly closed.
- - Protect from moisture and contamination.

- - Avoid prolonged exposure to direct sunlight.
- - Recommended storage temperature: 5°C to 40°C.

Health & Safety

Avoid prolonged skin contact. Wear appropriate protective equipment during handling. Refer to the latest Safety Data Sheet (SDS) before use.

Disclaimer

The information contained herein is based on current manufacturing data and is believed to be accurate. Typical values are not to be construed as product specifications and may vary slightly within normal manufacturing tolerances. Users should evaluate the product's suitability for their specific application before use.