



PRODUCT DATA SHEET

4T ENGINE OILS – TECHNOFLUID FOUR-STROKE MOTORCYCLE ENGINE OILS

(20W-40 SM / SN, 15W-50 SN, 20W-50 SM, 10W-30 SM)

Commercial / Pack Name: 4T (20W40 API SM / 20W40 API SN / 15W50 API SN / 20W50 API SM / 10W30 API SM)

Product Description

- TECHNOFLUID 4T Engine Oils are premium-quality four-stroke motorcycle and scooter engine oils formulated to deliver reliable performance under varied riding and climatic conditions.
- Manufactured from high-quality base oils and advanced additive technology to ensure superior engine protection, smooth clutch operation, and long engine life.
- Designed to provide excellent lubrication to engine, gearbox, and wet clutch systems.
- Suitable for modern air-cooled and oil-cooled four-stroke two-wheelers.
- Available in multiple viscosity grades to meet different OEM and riding requirements.

Key Performance Benefits

- Excellent anti-wear protection reduces engine and gear wear.
- Superior detergency and dispersancy keep engines clean and free from deposits.
- Ensures smooth gear shifting and reliable wet clutch performance.
- Provides stable viscosity and lubrication at high operating temperatures.
- Reduces engine noise and vibration.
- Improves throttle response and riding comfort.
- Minimizes oil consumption and extends drain intervals.

Applications

Recommended for use in:

- Motorcycles and scooters with four-stroke engines
- Two-wheelers operating in city traffic as well as highway conditions

Suitable for engines requiring:

- **API SM / SN performance levels**

Compatible with wet clutch systems.

Typical Uses

- Daily commuting motorcycles and scooters.
- High-performance two-wheelers requiring superior engine protection.
- Engines operating under stop-and-go traffic and high-temperature conditions.

Available Grades & Performance Levels

- **TECHNOFLUID 4T 20W-40 – API SM / SN**
- **TECHNOFLUID 4T 15W-50 – API SN**
- **TECHNOFLUID 4T 20W-50 – API SM**
- **TECHNOFLUID 4T 10W-30 – API SM**

Operating Characteristics

- Maintains viscosity stability across a wide temperature range.
- Compatible with commonly used seals and engine materials.
- Ensures consistent performance throughout oil drain intervals.

Typical Characteristics

Characteristics	Test Method	4T 10W-30 API SM	4T 20W-40 API SM / SN	4T 20W-50 API SM	4T 15W-50 API SN
Appearance	Visual	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright
Base Oil Type	—	Mineral / Semi-Synthetic	Mineral	Mineral	Semi-Synthetic
SAE Grade	SAE J300	10W-30	20W-40	20W-50	15W-50
API Service Level	—	SM	SM / SN	SM	SN
JASO Specification	—	MA2	MA	MA	MA2
Density @ 29.5°C, g/ml	ASTM D4052	0.855	0.860	0.860	0.860

Kinematic Viscosity @ 40°C, cSt	ASTM D445	65 – 75	125 – 150	160 – 190	125 – 150
Kinematic Viscosity @ 100°C, cSt	ASTM D445	10.0 – 11.5	14.5 – 16.0	17.0 – 19.0	16.5 – 18.5
Viscosity Index	ASTM D2270	≥ 140	≥ 115	≥ 115	≥ 150
Flash Point (COC), °C	ASTM D92	≥ 210	≥ 215	≥ 220	≥ 225
Pour Point, °C	ASTM D97	-27	-15	-12	-30
Sulphated Ash, % wt	ASTM D874	≤ 1.2	≤ 1.2	≤ 1.3	≤ 1.2
Total Base Number (TBN), mg KOH/g	ASTM D2896	6 – 8	6 – 8	6 – 8	7 – 9
Wet Clutch Compatibility	JASO	Pass	Pass	Pass	Pass
Oxidation Stability	ASTM D943	Excellent	Excellent	Excellent	Excellent