



PRODUCT DATA SHEET

GREASE – TECHNOFLUID CALCIUM BASE GREASE

Commercial / Pack Name: GREASE C RED GEL / MP3 / SLR

Product Description

- TECHNOFLUID Calcium Base Grease is a high-quality, water-resistant grease formulated using refined mineral base oils and calcium soap thickener.
- Designed to provide effective lubrication and protection under wet and humid operating conditions.
- Exhibits excellent adhesion to metal surfaces, ensuring reliable lubrication even in the presence of water.
- Suitable for low to moderate speed bearings and general lubrication applications.
- Provides dependable performance in agricultural, automotive, and industrial environments.

Key Performance Benefits

- Excellent water resistance prevents wash-off in wet conditions.
- Good lubricating properties reduce friction and wear.
- Strong adhesion ensures the grease remains in place during operation.
- Effective rust and corrosion protection safeguards metal components.
- Stable structure provides consistent lubrication under varying loads.
- Helps extend bearing life and reduce maintenance frequency.

Applications

- Recommended for lubrication of: Chassis and automotive components, Agricultural machinery, Water pump bearings and Plain & rolling bearings operating at low to moderate speeds
- Particularly suitable for equipment exposed to water, moisture, or high humidity.

Typical Uses

- Agricultural and farm equipment operating in wet or muddy conditions.
- Automotive chassis lubrication.
- Industrial equipment requiring water-resistant grease.

Operating Characteristics

- Good pumpability at normal operating temperatures.
- Non-corrosive and compatible with commonly used bearing materials.

Typical Specifications

Characteristics	Test Method	CALCIUM RED GEL (Red)	MP3 (Creamish)	SLR (Dark Green)
Appearance	Visual	Smooth, gel type	Smooth	Smooth
Colour	Visual	Red	Creamish	Dark Green
Thickener Type	—	Calcium Soap	Calcium Soap	Calcium Soap
Base Oil Type	—	Mineral	Mineral	Mineral
NLGI Grade	ASTM D217	2	3	2
Worked Penetration (60 strokes), 0.1 mm	ASTM D217	265 – 295	220 – 250	265 – 295
Drop Point, °C (Min)	ASTM D2265	≥ 95	≥ 90	≥ 95
Base Oil Viscosity @ 40°C, cSt	ASTM D445	120 – 180	120 – 180	120 – 180
Four Ball Weld Load, kg (Min)	ASTM D2596	180	200	200
Wear Scar Dia, mm (Max)	ASTM D2266	0.60	0.55	0.55
Copper Corrosion (24 hrs @ 100°C)	ASTM D4048	1a	1a	1a
Water Washout @ 79°C, % loss (Max)	ASTM D1264	≤ 3	≤ 2	≤ 2
Rust Prevention	ASTM D1743	Pass	Pass	Pass
Mechanical Stability	ASTM D217	Good	Good	Good
Operating Temperature Range, °C	—	-10 to 70	-10 to 70	-10 to 70

