



PRODUCT DATA SHEET

HYDRAULIC OIL – TECHNOFLUID HYDRAULIC OIL HLP AW

(ISO VG 32, 46, 68, 100 & 150)

Product Description

- TECHNOFLUID Hydraulic Oil HLP AW is a high-performance anti-wear hydraulic fluid formulated from selected high-quality base oils and an advanced additive package.
- Designed to provide reliable lubrication and protection for hydraulic systems operating under high pressure and severe service conditions.
- Contains anti-wear, anti-oxidant, anti-rust, and anti-foam additives to ensure long oil life and system cleanliness.
- Offers excellent thermal and oxidation stability, maintaining performance even at elevated operating temperatures.
- Suitable for use in industrial and mobile hydraulic systems requiring DIN HLP-type oils.

Key Performance Benefits

- Excellent anti-wear protection minimizes wear of pumps, valves, and actuators.
- High load-carrying capacity ensures dependable operation under heavy-duty conditions.
- Superior oxidation stability reduces sludge, varnish, and deposit formation.
- Effective rust and corrosion protection for steel and non-ferrous components.
- Good demulsibility enables quick separation of water, maintaining lubrication efficiency.
- Low foaming tendency and rapid air release ensure smooth and responsive system operation.
- Helps extend equipment service life while reducing maintenance and downtime.

Applications

Recommended for high-pressure hydraulic systems in industrial and mobile equipment.

Suitable for use in:

- Hydraulic presses and machine tools
- Injection molding and plastic processing machines
- Steel plants, rolling mills, and foundries
- Construction, mining, and earth-moving equipmentS.
- Power generation and material handling systems
- Compatible with vane, piston, and gear type hydraulic pumps.

Typical Uses

- Hydraulic systems requiring ISO VG 32, 46, 68, 100, or 150 viscosity grades.
- Equipment operating continuously under high load and high temperature conditions.
- Applications demanding stable viscosity, strong oil film, and long service intervals.

Performance Standards Meets or exceeds:

- DIN 51524 Part 2 (HLP)
- IS 10522 : 1983 (Reaffirmed)
- Vickers V-104C / Denison HF-0, HF-1, HF-2

Operating Characteristics

- Maintains viscosity stability over a wide temperature range.
- Non-corrosive and compatible with commonly used hydraulic system seals and elastomers.
- Ensures clean, efficient, and reliable hydraulic system performance.

Typical characteristics

Characteristics	IS 1448	Test Result				
TECHNOFLUID HYD HLP AW		32	46	68	100	150
Appearance	----	Clear fluid	Clear fluid	Clear fluid	Clear fluid	Clear fluid
Density at 15° C	P:16	0.842	0.849	0.855	0.862	0.862
K.V at 40° C, cSt	P:25	32.6	46.7	68.1	100.2	150
Viscosity Index	P:56	115	115	115	115	117
Pour Point, °C	P:10	-12	-12	-12	-12	-10
Flash Point, (COC), °C	P:69	220	228	242	252	252
Copper Strip Corrosion Test at 100°C for 3 hrs.	P:15	1	1	1	1	1
a) Sequence I	P:67	Nil	Nil	Nil	Nil	Nil
b) Sequence II		Nil	Nil	Nil	Nil	Nil
c) Sequence III		Nil	Nil	Nil	Nil	Nil
Foaming Characteristics /Stability						

