



PRODUCT DATA SHEET

TECHNOFLUID GEAR EP 320

Premium Extreme Pressure Industrial Gear Oil

Product Description

TECHNOFLUID GEAR EP 320 is a premium quality **extreme pressure industrial gear lubricant** formulated using **highly refined base oils**, high shear stable viscosity index improver, pour point depressants, and advanced sulfur-phosphorus EP additive.

The product is designed to provide:

- Excellent load carrying capacity
- Superior micropitting protection
- High thermal and oxidation stability
- Excellent anti-wear protection
- Long oil service life
- Outstanding rust and corrosion protection

The use of **selected base oils** provides improved oxidation stability, lower sludge formation, reduced varnish formation, and better thermal stability.

Performance Level

TECHNOFLUID SYNTHETIC GEAR EP 320 meets or exceeds:

- DIN 51517 Part 3 (CLP)
- ISO 12925-1 CKD
- AGMA 9005-F16 EP
- David Brown S1.53.101
- US Steel 224
- Cincinnati Machine P-74

Key Features & Benefits

- Excellent EP and anti-wear performance
- High resistance to oxidation and thermal degradation
- Excellent load carrying capability

- Protection against scuffing and micropitting
- Excellent demulsibility and water separation
- Outstanding rust and corrosion protection
- Excellent foam suppression and air release
- Long service life under severe operating conditions

Typical Physical Properties

Property	Typical Value	Test Method
Appearance	Bright & clear	Visual
Density @ 29.5 °C	0.855 kg/L	ASTM D1298
Kinematic Viscosity @ 40 °C	290-340 cSt	ASTM D445
Kinematic Viscosity @ 100 °C	24 cSt	ASTM D445
Viscosity Index	>95	ASTM D2270
Flash Point (COC)	242–246 °C	ASTM D92
Pour Point	<-12 °C	ASTM D97
Copper Corrosion	1b	ASTM D130
FZG Load Stage	Pass 12+	DIN 51354
Foam Characteristics	Pass	ASTM D892
Demulsibility	Excellent	ASTM D1401

Applications : Suitable for Enclosed industrial gear drives, Helical gears, Spur gears, Bevel gears, Circulating systems, Heavy duty reduction gearboxes, Cement plants, Steel mills, Mining equipment & Paper mills

Recommended for systems operating under: Heavy shock loads, High torque conditions, Severe EP applications

