



PRODUCT DATA SHEET

TEXTILE LUBRICANT – TECHNOFLUID CONING OIL

Commercial / Pack Name: CONING OIL

Product Description

- TECHNOFLUID Coning Oil is a high-quality textile lubricant specially formulated for yarn winding and coning operations.
- Manufactured from carefully selected, highly refined base oils combined with advanced additives to ensure smooth yarn movement and uniform winding.
- Designed to provide excellent lubricity while maintaining low volatility and low misting characteristics.
- Helps reduce friction between yarn and machine components, preventing yarn damage and breakage.
- Easily washable from yarn and fabric without leaving stains or residues.

Key Performance Benefits

- Excellent lubrication reduces yarn tension and breakage during high-speed coning.
- Ensures uniform winding and improved package build.
- Low volatility minimizes oil consumption and oil mist formation.
- Non-staining formulation ensures clean yarn and fabric appearance.
- Superior washability allows easy removal during subsequent processing.
- Good oxidation stability ensures consistent performance during continuous operations.
- Improves machine efficiency and reduces downtime.

Applications

Recommended for lubrication in:

- Yarn coning machines
- Winding and rewinding machines
- Textile preparatory processes

Suitable for use with:

- Cotton, polyester, nylon, and blended yarns

Applicable in high-speed textile processing operations.

Typical Uses

- Yarn winding and coning operations requiring clean, uniform lubrication.
- Textile units focusing on high productivity and fabric quality.
- Applications demanding low oil carry-over and easy washability.

Operating Characteristics

Maintains stable viscosity during prolonged machine operation.

Compatible with commonly used textile machine materials and seals.

Low odor and operator-friendly formulation.

Typical Characteristics

Characteristics	Test Method	Typical Figures
Appearance	Visual	Clear & Bright
Colour	ASTM D1500	≤ 1.5
Base Oil Type	—	Highly Refined Mineral
Density @ 15°C, g/ml	ASTM D4052	0.860 – 0.870
Kinematic Viscosity @ 40°C, cSt	ASTM D445	15 – 25
Kinematic Viscosity @ 100°C, cSt	ASTM D445	3.5 – 5.0
Viscosity Index	ASTM D2270	≥ 95
Flash Point (COC), °C	ASTM D92	≥ 185
Pour Point, °C	ASTM D97	-6
Volatility	ASTM D972	Low
Washability	In-house	Excellent
Staining Tendency	In-house	Non-staining
Odour	—	Mild
Copper Corrosion (3 hrs @ 100°C)	ASTM D130	1a
Oxidation Stability	ASTM D943	Excellent
Static Charge Build-up	In-house	Very Low

